

SEALBOND EXT

ADVANCED EXTERIOR
WATERPROOFING COATING

PREMIUM WEATHER-RESISTANT FORMULA

Sealbond Ext locks out dampness while ensuring a flawless, long-lasting finish for your interior walls. Superior whiteness, strong adhesion, and enhanced coverage for a professional, beautiful interior aesthetic.



UV
RESISTANT



WATERPROOF
BARRIER



CRACK-
BRIDGING



HIGH SCRUB
RESISTANCE

1. IDEAL FOR



INTERIOR WALL SURFACES

2. FEATURES AND BENEFITS



PREVENTS SURFACE DAMPNESS

Effectively prevents dampness from appearing on walls, keeping them dry and beautiful.



3-YEAR WATERPROOFING WARRANTY

Trusted performance with a 3-year warranty for complete peace of mind.



INCREASES TOPCOAT COVERAGE BY 15%

Enhances the coverage and efficiency of your topcoat, saving time and cost.



SUPERIOR WHITENESS AND HIDING

Delivers excellent whiteness and hiding for a brighter, more uniform finish.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Acrylic Copolymer Based Primer

PHYSICAL PARAMETERS:

- Colour and appearance: White (Smooth)
- Packaging: 20 L
- Shelf life: 2 years
- Coverage: 10 – 12 sq m/L per coat at 25 microns DFT
- Finish: Aesthetic finish
- Application: Interior walls

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Finish	Visual	Smooth Matt
Colour	Visual	White
Solids by Volume	ASTM D 2697	35 – 40%
Specific Gravity	ASTM D 1475	1.25 – 1.40
pH	ASTM E 70	8.5 – 9.5
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Hard Dry	ASTM D 1640	6 – 8 hours
Recoat Time	–	4 – 6 hours
Application	–	Interior walls
Coverage	ISO 11890-1	10 – 12 sq m/L per coat

4. APPLICATION METHOD

1



PREPARE SURFACE

Ensure the interior wall is clean, dry, and free from dust or loose particles before application.

2



APPLY PRIMER

Apply Sealbond Ext evenly across the surface to ensure strong adhesion and optimal base whiteness.

3



FINISH COATING

Allow the primer to dry completely before applying your chosen topcoat to achieve an enhanced, aesthetic finish.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MSDS for Sealbond Ext for detailed information about safety measures while handling the paint, which is available on request.



Store the container with the lid tightly closed, in an upright position, in a cool, dry place.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drain or in water courses.



In the event of spills, contain spillage using sand or earth.



No added lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



Store at a cool and dry place at ambient temperatures.



RECOMMENDED FOR



- ✓ Interior residential walls
- ✓ Interior commercial building surfaces

HOW TO USE

- 1 Prepare Surface**
Ensure the interior wall is clean, dry, and free from dust or loose particles.
- 2 Apply Primer**
Apply Sealbond Ext evenly across the surface to ensure strong adhesion and base whiteness.
- 3 Finish Coating**
Allow the primer to dry completely before applying your chosen topcoat to achieve an enhanced, aesthetic finish.



UV RESISTANT



WATERPROOF
BARRIER



CRACK-BRIDGING



HIGH SCRUB
RESISTANCE



PREMIUM WEATHER-
RESISTANT FORMULA