

EXTERIOR EMULSION

Shield Emulsion

Premium Exterior Protection.
Built to **Shield**. Designed to **Last**.



AREAS OF APPLICATION



CONCRETE



PLASTER



BRICKWORK



ASBESTOS

FEATURES AND BENEFITS

- ✓ ULTRA-DURABLE ALL-WEATHER FINISH
 - ✓ HYDROPHOBIC BARRIER TECHNOLOGY
 - ✓ UV FADE RESISTANCE
 - ✓ EASY-CLEAN SURFACE
- ✓ ANTI-ALGAE & FUNGAL PROPERTIES
 - ✓ EXCELLENT ADHESION
 - ✓ CRACK RESISTANT
 - ✓ LONG-LASTING DURABILITY

PRODUCT DETAILS

- Finish: Eggshell Sheen
- Pack Sizes: 1L, 4L, 10L, 20L
- Shelf Life: 24 months from date of manufacture in original sealed containers

SPECIFICATIONS	Test Standard Used	Typical Values
Volume Solids	ASTM D2697	40 ± 2%
Specific Gravity	ASTM D1475	1.30 ± 0.05
Theoretical Spreading Rate	ISO 3233	12 – 14 sq. m/L per coat
Drying Time (Touch Dry)	ASTM D1640	30 minutes
Drying Time (Hard Dry)	ASTM D1640	4 – 6 hours
Recoating Interval	-	Min. 4 – 6 hours
Flash Point	ASTM D3278	Not Applicable (Water Based)

APPLICATION METHOD



SURFACE PREPARATION:

Ensure substrate is clean, dry, and free from contaminants. Remove loose paint, dust, and grease. Repair cracks and defects with suitable filler.



PRIMING:

Apply one coat of “COLORSOME” Wall Primer (Water Based) and allow it to dry for 4–6 hours.



APPLICATION:

Stir thoroughly before use. Apply two coats of Shield Emulsion using a brush, roller, or spray. Thin with up to 10% clean water if required for brush/roller application; 15–20% for spray application. Allow 4–6 hours between coats.

SAFETY FEATURES & PRECAUTIONS



Ensure good ventilation during application and drying.



Avoid contact with skin and eyes. In case of contact, rinse immediately with plenty of water and seek medical advice.



Keep out of reach of children.



Do not empty into drains or watercourses.



Store in a cool, dry place away from direct sunlight and heat.



Do not apply when surface temperature is below 10°C or above 40°C.



Direct sunlight and heat.



Dispose of contents/container in accordance with local regulations.

RECOMMENDED FOR



EXTERIOR WALLS



CONCRETE SURFACES



BUILDING FACADES

STORAGE PRECAUTIONS



Store in a cool, dry place away from direct sunlight and heat. Keep container tightly closed.



ALL WEATHER PROTECTION



HYDROPHOBIC BARRIER



UV FADE RESISTANT



EASY CLEAN SURFACE



ANTI ALGAE & FUNGAL



LONG LASTING DURABILITY