

Shield PU Emulsion

PREMIUM POLYURETHANE-ENHANCED COATING
SUPERIOR DURABILITY AND GLOSS

Experience superior exterior protection with Shield PU Emulsion, featuring advanced PU Serum for lasting brilliance.

This high-performance, water-based 100% acrylic emulsion is engineered with unique PU Serum and 90% higher biocide content to resist algae and moisture. Its advanced formula provides superior UV protection and dust resistance, ensuring your home stays vibrant for years under an 8-year performance warranty.



- ENHANCED WITH PU SERUM
- ANTI-ALGAL HIGH-PERFORMANCE FORMULA
- DPUR AND MOISTURE-FREE TECHNOLOGY
- LOW VOC, IGBC-COMPLIANT COMPOSITION

2. AREAS OF APPLICATION



 **EXTERIOR WALL SURFACES**
Ideal for all types of exterior walls including residential, commercial, and institutional buildings.

3. FEATURES AND BENEFITS



ENHANCED WITH PU SERUM
Advanced PU Serum technology delivers superior gloss, smoothness, and long-lasting protection.



ANTI-ALGAL HIGH-PERFORMANCE FORMULA
Contains 90% higher biocide content to effectively resist algae, fungus and microbial growth.



DPUR AND MOISTURE-FREE TECHNOLOGY
Prevents moisture penetration and provides excellent resistance against rainwater and damp conditions.



SUPERIOR UV PROTECTION
Advanced UV blockers protect exterior surfaces from harmful rays and prevent color fading.



DUST RESISTANCE
Special nano technology ensures reduced dust pick-up, keeping your walls cleaner for longer.



LOW VOC, IGBC-COMPLIANT COMPOSITION
Eco-friendly, low VOC formulation that meets IGBC green building standards.

4. PRODUCT DETAILS

- Type** : Exterior Emulsion Paint
- Finish** : Sheen
- Colour** : As per Shade Card
- Packaging** : 1 L, 4 L, 10 L, 20 L
- Shelf Life** : 3 years from date of manufacture
- Application** : Exterior walls

PHYSICAL & PERFORMANCE PARAMETERS

PARAMETER	TEST STANDARD / METHOD	TYPICAL VALUE
Appearance	Visual	Smooth, Sheen Finish
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Recoat Time	ASTM D 1640	4 – 6 hours
Washability	Internal Method	Excellent
Algal Resistance	Internal Method	Excellent
UV Resistance	Internal Method	Excellent
Coverage*	Internal Method	10 – 12 sq m/L/coat*
Application Method	-	Brush, Roller, Spray
VOC Content	ISO 11890-1	Low (IGBC Compliant)

*Coverage may vary depending on surface texture and porosity.

5. HOW TO APPLY



1. PREPARE SURFACE
Ensure the exterior surface is clean, dry, and free from loose paint, dust, or contaminants.



2. APPLY PRIMER
Apply a suitable exterior primer to ensure optimal adhesion and long-term protection.



3. PAINT APPLICATION
Apply two coats of Shield PU Emulsion evenly, allowing adequate drying time between coats for a smooth sheen finish.

6. SAFETY FEATURES & PRECAUTIONS



Read the Safety Data Sheet (SDS) carefully before use.



Store the container tightly closed in a cool, dry place away from direct sunlight and heat.



Keep out of reach of children and away from eatables.
May be harmful if swallowed. In case of ingestion, seek immediate medical attention.



Do not pour leftover paint down the drain or in water bodies.



In the event of spills, contain spillage using sand or earth.



Wear eye protection during application. In case of contact, rinse with plenty of water.
No added lead, mercury, or chromium compounds.

7. STORAGE PRECAUTIONS



Store in a cool and dry place at ambient temperatures. Protect from extreme heat, freezing, and direct sunlight.

8. RECOMMENDED FOR



- Residential buildings
- Commercial complexes
- Institutional Projects
- Renovation Projects

9. WHY CHOOSE SHIELD PU EMULSION?

- Advanced PU Serum technology
- Long-lasting beauty and protection
- Superior resistance to harsh climates
- Keeps surfaces clean and vibrant
- 8-year performance warranty*



HIGH GLOSS FINISH



WATER RESISTANT



UV RESISTANT



WASHABLE SURFACE



PU GUARD