

Shieldex Pro

PREMIUM PROTECTIVE COATING

Shieldex Pro offers premium, long-lasting exterior protection against environmental damage and structural corrosion.

This high-performance coating shields concrete structures by resisting CO₂ diffusion to prevent steel corrosion. With built-in anti-algal and UV protection, it ensures your walls remain pristine, clean, and durable for years to come.



2. AREAS OF APPLICATION



 **EXTERIOR WALLS**



 **CONCRETE STRUCTURES**

Ideal for exterior walls, concrete structures, and other exposed surfaces requiring superior protection.

FEATURES AND BENEFITS



RESISTS CO₂ DIFFUSION
Prevents carbon dioxide penetration to protect steel reinforcement from corrosion.



ANTI-ALGAL PROTECTION
Built-in technology prevents algae and fungal growth, ensuring a healthy surface.



DUST PICK-UP RESISTANCE
Special formulation reduces dirt accumulation, keeping surfaces cleaner for longer.



LEED VOC COMPLIANT
Low VOC formulation that meets green building standards for a safer environment.

3. PRODUCT DETAILS

Type	: Protective Coating
Finish	: Premium
Colour	: As per Shade Card
Packaging	: 1 L, 4 L, 10 L, 20 L
Shelf Life	: 3 years
Application	: Exterior walls; Concrete structures

PHYSICAL & PERFORMANCE PARAMETERS

PARAMETER	TEST STANDARD / METHOD	TYPICAL VALUE
Appearance	Visual	Smooth, Uniform Finish
Drying Time (Touch Dry)	ASTM D 1640	30 – 60 mins
Recoat Time	ASTM D 1640	4 – 6 hours
CO ₂ Diffusion Resistance	Internal Method	Excellent
Algal Resistance	Internal Method	Excellent
Water Resistance	Internal Method	Excellent
Application Method	–	Brush, Roller, Spray
Curing	–	Standard Industry Drying Time

4. APPLICATION METHOD



1. PREPARE SURFACE

Ensure the surface is clean, dry, and free from loose particles or contaminants.



2. APPLY COATING

Use a brush, roller, or spray equipment to apply an even coat over the prepared substrate.



3. FINAL CURE

Allow the coating to dry thoroughly in accordance with recommended environmental conditions for optimal performance.

5. SAFETY FEATURES & PRECAUTIONS



Read the Safety Data Sheet (SDS) carefully before use for safe handling and usage.



Keep out of reach of children and away from eatables.



Do not pour leftover paint down the drain or in water bodies.



Wear eye protection during application. In case of contact, rinse with plenty of water.



Store the container tightly closed in a cool, dry place away from direct sunlight and heat.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



In the event of spills, contain spillage using sand or earth.



No added lead, mercury, or chromium compounds.

6. STORAGE PRECAUTIONS



Store in a cool and dry place at ambient temperatures. Protect from extreme heat, freezing, and direct sunlight.

RECOMMENDED FOR



- ✓ Residential Buildings
- ✓ Commercial Buildings
- ✓ Infrastructure Projects
- ✓ Renovation Projects

WHY CHOOSE SHIELDX PRO?

- ✓ Advanced protective technology
- ✓ Long-lasting performance
- ✓ Weather & UV resistant
- ✓ Keeps surfaces cleaner for longer
- ✓ Value for money solution



SUPERIOR PROTECTION



ALL-WEATHER RESISTANT



HIGH DURABILITY



WATER REPELLENT