


UNDER COATS

SILICOAT PRIME

Modified acrylic, water-based alkali resistant primer-cum-sealer with silicone additives.



WATER
BASED



LEAD
FREE



SAFE &
ENVIRONMENT
FRIENDLY



WATER
BASED



LEAD
FREE



*All COLORSOME®
products contain
no added Lead,
Mercury, Arsenic
or Chromium.

1. AREAS OF APPLICATION



Cement
Plaster



Fresh
Concrete



Processed
Sand
Substrate



Mild
Moisture
Content



Interior/
Exterior
Surfaces

Ideal for a wide range of interior and exterior surfaces.

2. FEATURES AND BENEFITS

- ✓ Binder rich formula seals highly absorptive substrates
- ✓ Reduces top coat consumption
- ✓ Prevents efflorescence
- ✓ Higher subsequent top coat coverage
- ✓ Provides Excellent Sealing Property
- ✓ pH Resistance up to 12.5
- ✓ Water Permeability resistance (CRGI certified)
- ✓ Opacity and Adhesion (CRGI certified)

3. PRODUCT DETAILS



COLOR: White



FINISH: Ultra-Matte



PACK SIZES: 1 ltr, 4 ltr, 20 ltr



SHELF LIFE: 3 years in original closed containers



COVERAGE: 100–120 sq.ft./ltr (1 COAT)*

PHYSICAL PARAMETERS:

PARAMETER	TYPICAL VALUES
Surface Dry Time	30 minutes
Recoat Period	4–5 HOURS
Stability of thinned paint	Use within 24 hours
Dilution % for Brush/Roller	100% Water

4. APPLICATION METHOD



SURFACE PREPARATION

- Allow new masonry surfaces to cure completely (recommended 28 days), though product can be applied on fresh concrete.
- Ensure surface is clean, free of dirt, loose plaster, powdery residue, oil, grease, or contaminants.
- Remove algae, fungus, or moss by wire brushing and water cleaning; a generic bio-block is recommended.
- Fill holes and cracks (up to 3mm) using crack seal or a 1:3 white cement and fine sand mix.



APPLICATION

- STEP 1:** Sand the surface with emery paper 180 and wipe clean.
- STEP 2 (OPTIONAL):** Apply a generic wall putty as directed.
- STEP 3:** Apply SILICOAT PRIME by Brush / Roller.
Thinner: Water (100% dilution).
Recoat: 4–5 HOURS.
- STEP 4:** Apply top coat emulsion over the primer.

5. SAFETY FEATURES & PRECAUTIONS



Store in lid
tightly closed
while paint is
in more when
chassis
available.



Store in a cool,
dry place away
from direct
sunlight.



Keep out of
reach of children
in eatables.



Wear eye
protection and
open on death.



Do not breathe
vapor/spray of
your vansra.



Wash skin
with soap and
water.



Do not pour
down drain or
with water
courses.

POST-PAINTING CARE



Ensure proper washing
and cleaning of all
algal and fungal
growth at six-month
intervals for best
performance.

RECOMMENDED FOR



- ✓ Exterior Masonry
- ✓ Residential Homes
- ✓ Commercial Buildings
- ✓ Boundary Walls

Ideal for new and
maintenance projects.

HOW TO USE

- 1 Prepare
- 2 Sand
- 3 Prime
- 4 Top Coat



ADVANCED
UV PROTECTION



SILICON
TECHNOLOGY



DUST PROOF
TECHNOLOGY



WEATHER
RESISTANT



LONG LASTING
PERFORMANCE