

PREMIUM SILK EMULSION

Silkura

PREMIUM SILK EMULSION

An exquisite, highly washable wall finish with a smooth, luxurious sheen.



AREAS OF APPLICATION



FEATURES & BENEFITS

-  Excellent washability and stain resistance
-  Smooth and luxurious silk sheen finish
-  Low odor and low VOC formulation
-  High opacity for superior coverage
-  Provides a durable, long-lasting film

ABOUT THE PRODUCT

Silkura is a premium acrylic silk emulsion that delivers a smooth, luxurious sheen with excellent washability and stain resistance. Its low odor, eco-friendly formulation ensures a beautiful and healthy living environment.

CHEMICAL TYPE	VISCOSITY	FINISH	SHELF LIFE
Acrylic Silk Emulsion	95 - 105 KU @ 30°C	Silk Sheen	24 months from date of manufacture

TECHNICAL INFORMATION

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Finish	IS 101	Smooth Silk Sheen
Specific Gravity	ASTM D1475	1.20 - 1.24
Drying Time (Surface Dry)	IS 101 (Part 3/Sec 1)	30 mins
Recoat Time	-	Min. 4 - 6 hours
Flash Point	ASTM D93	> 60°C
Shelf Life	-	24 months from date of manufacture

APPLICATION METHOD

1 SURFACE PREPARATION



- Ensure the surface is clean, dry, and free from dust, grease, and loose material.
- Scrape off old paint and repair any cracks or imperfections with a suitable wall putty.
- Sand the surface smooth and wipe clean.
- Allow new plaster to cure for at least 4 weeks.

2 PRIMING



- Apply one coat of a suitable **COLORSOME Wall Primer** (Water Based or Solvent Based) by brush or roller.
- Allow the primer to dry completely (typically 4-6 hours).

3 APPLICATION



- Thin Silkura Premium Silk Emulsion with clean water up to a maximum of 5-10% by volume if necessary.
- Apply two coats with a high-quality brush or roller, allowing a minimum of 4-6 hours between coats.
- For best results, maintain a uniform wet edge and avoid over-application.

SAFETY FEATURES & PRECAUTIONS



Ensure adequate ventilation during application and drying.



Avoid inhalation of spray mist and contact with skin and eyes.



In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Wear suitable protective clothing, gloves, and eye/face protection.



Keep out of reach of children and away from food, drink, and animal feed.



Do not empty into drains or watercourses. Dispose of waste in accordance with local regulations.



Store the container tightly closed in a cool, dry, and well-ventilated area.



Do not over-thin or over-extend the brush.



Tint using authorized machine colourants only.



STORAGE PRECAUTIONS

Store in a cool, dry place, away from direct sunlight and heat sources. Keep the container tightly sealed when not in use.



RECOMMENDED FOR

- Interior masonry surfaces, concrete, and plaster
- Gypsum board and fiber cement panels
- Repainting over existing painted surfaces

