

UNDER COATS

Smoothfill Pro

A ready-to-use solvent-based paste filler for metallic and wooden surfaces.



**WATER
BASED**



**LEAD-FREE*
GUARANTEE**



**NO ADDED LEAD,
MERCURY,
ARSENIC OR
CHROMIUM**

*All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium from April 2008.

1. AREAS OF APPLICATION




**METALLIC
SURFACES**



**WOODEN
SURFACES**



**DENTS &
IMPERFECTIONS**



**SURFACE
LEVELING**

2. FEATURES AND BENEFITS

- ✓ Butter-like consistency; easy to apply.
- ✓ Supplied ready-to-use; thinnable if needed.
- ✓ Dries hard upon air drying.
- ✓ Easy cutting with no strain.
- ✓ Excellent for filling imperfections.
- ✓ Provides a smooth, matte finish.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

- Solvent-based
- Matt finish
- Smooth texture

PHYSICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Available Packs	-	1 kg, 2 kgs, 5 kgs, 15 kgs, 30 kgs
Shelf Life	-	2 years in original, tightly closed containers (stored away from direct sunlight & excess heat)
Coverage	-	4 - 6 Sq.Ft./Kg at a dry film thickness of 4 Mills**
Drying Time (Surface)	-	~30 minutes max
Drying Time (Recoat)	-	4 - 6 hours (at 25°C, 50% RH)*
Flash Point	IS101/1987 Part 1, Sec 6	> 30°C [> 85°F]
Specific Gravity	-	Nominal, supplied consistency
Viscosity	-	40 - 45 SEC (Supply consistency)

**Actual coverage may vary due to factors like application method and surface roughness.

4. APPLICATION METHOD



SURFACE PREPARATION:

- Ensure that the surface is free from moisture and loose matter.
- Metal and wooden surfaces should be suitably primed with respective primer and undercoats prior to application.



APPLICATION & SANDING:

Apply Smoothfill Pro using a putty knife at ready-to-use consistency. If thinned consistency is desired, use Mineral Turpentine Oil (MTO) nominal, if required. Lightly sand with sand paper 320 and wipe clean before subsequent coats.

*Recoat times are quoted for 25°C and 50% relative humidity; may vary under different conditions.

5. SAFETY FEATURES & PRECAUTIONS



Flammable product. Keep away from ignition sources.



Work in a well-ventilated place; wear overalls and gloves.



Avoid eye and skin contact; wash with plenty of clean water in case of contact.



Do not inhale or inject; seek medical attention if symptoms persist.



Store container tightly closed, upright, in a cool, dry place.



Keep out of reach of children.



May be harmful if swallowed; seek immediate medical attention.

STORAGE PRECAUTIONS



- Store container with lid tightly closed in an upright position.
- Store in a cool, dry place away from children and eatables.
- Work in a well-ventilated place.

RECOMMENDED FOR

- ✓ Filling dents and surface imperfections on metal surfaces
- ✓ Filling dents and surface imperfections on wooden surfaces
- ✓ Smoothing surfaces for undercoat applications.

HOW TO USE

- 1 Clean surface.
- 2 Sand surface.
- 3 Apply 1 coat primer.



**SMOOTH
FINISH**



**EASY TO APPLY
& SAND**



**STRONG
ADHESION**



**PREMIUM
QUALITY**