

EXTERIOR WALL FINISH

Solaris Shield

Modified acrylic, water-based paint with Silicon additives.

WATER BASED

LEAD FREE GUARANTEE



WATER BASED

LEAD FREE GUARANTEE

NO ADDED LEAD, MERCURY OR ARSENIC OR CHROMIUM

*All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION

EXTERNAL WALLS

RESIDENTIAL HOMES

COMMERCIAL BUILDINGS

BOUNDARY WALLS

Ideal for a wide range of exterior surfaces for long-lasting protection and beauty.

2. FEATURES AND BENEFITS

- ✓ Advanced UV protection; resists shade fading.
 - ✓ Advanced formula resists algae and fungi growth.
 - ✓ Withstands harsh humidity and heat.
 - ✓ Smooth modified acrylic film.
- ✓ Comprehensive 4 year performance warranty.
 - ✓ Over 1700 attractive shades available.
 - ✓ Excellent resistance to black spots.
 - ✓ Best in class film integrity and fieldwork performance.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Silicon modified acrylic dispersion.

PHYSICAL PARAMETERS:

- Colour and appearance: White (viscous pastes)
- Packaging: 20 L
- Shelf life: 2 years
- Coverage: 1.2 - 2 kg per sq. m in two coats for 1mm DFT

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Drying time (Surface dry)	IS101	30 minutes
Thinned paint stability	-	Used within 24 hours
Flash point (IS101/1987)	IS101 Part 1, Sec 6	NA
Sheen	-	Matt & Soft Sheen
Finish	Visual	Smooth
UV Resistance	-	Excellent
Lead, Mercury, Chromium	-	No added compounds

4. APPLICATION METHOD



SURFACE PREPARATION

- Ensure wall surface is clean, dry, and free of dust, grease, and fungal growth.
- Clean existing algal/fungal growth thoroughly.
- Apply generic Wall Primer and wait for it to dry.
- For smooth walls, use generic Acrylic Wall Putty, sand with Sanding Paper, and apply another coat of Wall Primer.



APPLICATION

- Thin the paint with 100% clean water.
- Apply by brush only.
- Do not apply when ambient temperature is below 10°C or likely to drop within 4 hours.
- No roller application.
- Tinted paints must be thoroughly shaken immediately after tinter addition and before use.

5. SAFETY FEATURES & PRECAUTIONS

Refer to MSDS for detailed information.

Store in a cool, dry place away from direct sunlight.


Keep out of reach of children and away from edibles.

Wear eye protection during application.

Avoid dust inhalation during sanding and preparation.

Do not breathe vapor/spray.

Wash skin with soap and water.

Do not pour leftover paint down the drain or in water or courses.

POST-PAINTING CARE

Ensure proper washing and cleaning of all algal and fungal growth at six-month intervals for best performance.

RECOMMENDED FOR



- ✓ Exterior Masonry
- ✓ Residential Homes
- ✓ Commercial Buildings
- ✓ Boundary Walls

Ideal for new and maintenance projects.

HOW TO USE

- 1 Prepare surface
- 2 Apply Primer
- 3 Apply 2 coats of product

