

PREMIUM EMULSION PAINT

STAINSHIELD EMULSION

Premium Performance Paint for
Stain Repellence & Lasting Beauty



STAIN
REPELLENT



SCRUB
RESISTANT

1. AREAS OF APPLICATION



INTERIOR
WALLS



CEILINGS



DRYWALL



MASONRY

2. FEATURES AND BENEFITS

- ✓ Stain repellent finish
- ✓ Ultra durable formula
- ✓ Washable color
- ✓ Scrub resistant
- ✓ Easy to clean
- ✓ Excellent hide

3. PRODUCT DETAILS

CHEMICAL PARAMETERS:

Acrylic Copolymer Dispersion

PHYSICAL PARAMETERS:

- Colour and appearance: White (viscous paste)
- pH (at 25 °C): 8.0 – 9.5
- Specific gravity: 1.30 – 1.40
- Shelf life: 2 years

TECHNICAL PARAMETERS:

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Gloss Level (85°)	ASTM D523	Matt (< 5 gloss units)
DFT per coat	ASTM D1186	30 – 40 microns
Coverage	–	12 – 14 sq.m/L per coat
Solid Content	ASTM D2369	58 – 62%
Drying Time (Surface dry)	ASTM D1640	30 – 60 minutes

4. APPLICATION METHOD



SURFACE PREPARATION

- **New Concrete Plaster:** should be cured for at least 28 days old and have a moisture content of less than 5 – 10%.
- Remove laitance and loose particles by mechanical methods. Dust and other details should be removed by thorough cleaning. Any fine cracks or pin holes should be filled with appropriate filler and allowed to dry.
- **Old Concrete Plaster:** damaged areas or surface irregularities should be repaired using epoxy-based mortar. All cracks and holes should be filled and leveled using suitable repair mortar and allowed to dry before application of Stainshield Emulsion.



PRIMING

- Apply a suitable acrylic wall primer as per manufacturer's recommendation.
- [Mixing ratio of Resin: Hardener: Water is 1 : 1 : 2 (by weight)] (if using a two-component primer).
- Allow primer to surface dry for 2 – 3 hours.



APPLICATION

- Stir Stainshield Emulsion well before use.
- Apply 2 coats using brush, roller or spray.
- Allow 4 – 6 hours drying time between coats.
- Thin with up to 10% clean water if required.
- Ensure uniform coverage for best results.

5. SAFETY FEATURES & PRECAUTIONS



Kindly refer to the MSDS for Stainshield Emulsion for more information on safety measures while handling the paint, which is available on request.



Store the container with the lid tightly closed in a dry place, away from direct sunlight and heat.



Keep out of reach of children and away from eatables.



May be harmful if swallowed. In case of ingestion seek immediate medical attention.



Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drain in water courses.



In the event of spills, contain spillage using sand or earth.



No added Lead, Mercury or Chromium compounds.

6. STORAGE PRECAUTIONS



- Store at a cool and dry place at ambient temperatures.
- Keep container tightly closed when not in use.

RECOMMENDED FOR

- ✓ Interior Walls
- ✓ Exterior Walls
- ✓ Ceilings
- ✓ Gypsum Boards

HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply 1 coat of primer evenly.
- 3 Apply 2 coats of Stainshield Emulsion.
- 4 Allow 4 – 6 hours between coats.



STAIN
REPELLENT



SCRUB
RESISTANT



EXCELLENT
HIDE



WASHABLE
COLOR



DURABLE
FINISH