



TerraCoat Pro

PREMIUM STONE-EFFECT FINISH

Timeless Stone Aesthetics.
Engineered to Last.

Crafted from a premium blend of selected sands, unfired clays, and natural pigments, TerraCoat Pro creates a durable, breathable barrier against the elements. Its unique formulation ensures exceptional moisture management and long-term film integrity, backed by a 10-year performance warranty.





AUTHENTIC
NATURAL STONE
AESTHETIC



ENHANCED
BREATHABILITY



SUPERIOR
ALL-WEATHER
RESISTANCE



10
10-YEAR
PERFORMANCE
WARRANTY

1. AREAS OF APPLICATION



Exterior Masonry Walls



Architectural
Cladding Finishes

2. FEATURES AND BENEFITS



AUTHENTIC NATURAL STONE AESTHETIC

Delivers a natural stone look including Granite, Sand, Flakes, and Sparkle.



ENHANCED BREATHABILITY

Allows walls to breathe while preventing moisture build-up from within.



SUPERIOR ALL-WEATHER RESISTANCE

Engineered to withstand harsh weather conditions and UV exposure.



10-YEAR PERFORMANCE WARRANTY

Backed by a 10-year warranty for worry-free, long-term performance and durability.

3. PRODUCT DETAILS

COMPOSITION

Premium blend of selected sands, unfired clays, natural pigments, additives, and resins.

PHYSICAL PROPERTIES

- **Finish:** Natural stone aesthetic (Granite Sand, Flakes, and Sparkle)
- **Packaging:** 20 L
- **Shelf Life:** 2 years
- **Application:** Exterior walls; Cladding finishes
- **Drying Time:** Touch dry in 4 – 6 hours*
- **Colours:** Available in a wide range of shades

*Under standard application conditions.

TECHNICAL SPECIFICATIONS

PARAMETER	DETAILS
Application	Exterior walls; Cladding finishes
Binder Type	Acrylic Polymer Emulsion
Drying Time	Touch dry in 4 – 6 hours*
Recoating Time	After 24 hours
Theoretical Coverage	1.5 – 2.0 kg per sq. m.**
No. of Coats	2 coats recommended
Finish	Natural stone aesthetic including Granite Sand, Flakes, and Sparkle.
Shelf Life	2 years from date of manufacture in original sealed container
Storage	Store in a cool, dry place. Protect from direct sunlight and frost.

**Coverage may vary depending on surface texture, porosity and application method.

4. APPLICATION METHOD

1



PREPARE SURFACE

Ensure the substrate is clean, dry, and free from loose debris or contaminants.

2



APPLY TEXTURE

Use a specialized applicator to achieve a uniform thickness across the wall surface.

3



CURING

Allow the coating to dry thoroughly in accordance with environmental conditions to ensure full film integrity.

5. SAFETY FEATURES & PRECAUTIONS



Read the product label and technical data sheet before use.



Wear appropriate gloves and protective clothing during application.



Keep out of reach of children and away from food and feed.



Avoid contact with eyes. In case of contact, rinse immediately with water and seek medical advice.



Do not pour leftover material down the drain or in water courses.



In case of spills, contain spillage using sand or earth.

6. STORAGE PRECAUTIONS



- Store in a cool, dry place at ambient temperatures.
- Keep container tightly closed when not in use.
- Protect from direct sunlight and extreme heat.
- Shelf life: 12 months from date of manufacture.

7. RECOMMENDED FOR



- ✓ Residential Building Facades
- ✓ Commercial Establishments
- ✓ Renovation Projects
- ✓ Decorative Exterior Walls

8. HOW TO USE

- 1 Clean the surface and remove dust, grease, and loose particles.
- 2 Apply a suitable primer/base coat.
- 3 Evenly apply the TerraCoat Pro texture using professional tools.



HIGH SCRUB
RESISTANCE



ULTRA-MATTE
FINISH



WASHABLE



ADVANCED
COLOR TECH

STRONG BASE. SUPERIOR FINISH.