

TEXTURA PRO

PREMIUM ARCHITECTURAL FINISH

Premium acrylic and dolomite-based texture for durable beauty and structural protection.

- 

HIDES SURFACE IMPERFECTIONS
- 

REINFORCES STRUCTURAL PROTECTION
- 

ALL-WEATHER DURABILITY
- 

CREATES AESTHETIC TROWEL PATTERNS



- 

LOW VOC
- 

ECO FRIENDLY
- 

DURABLE PROTECTION

2. AREAS OF APPLICATION

- 

Interior Wall Surfaces
- 

Exterior Wall Surfaces
- 

Protective & Decorative Undercoat
- 

Ideal for Textured Wall Finishes

FEATURES AND BENEFITS

- 

HIDES SURFACE IMPERFECTIONS

Effectively masks undulations, fine cracks and minor surface flaws.
- 

ALL-WEATHER DURABILITY

Withstands harsh weather conditions and maintains performance over time.
- 

REINFORCES STRUCTURAL PROTECTION

A strong, resilient formulation that adds a protective barrier to your walls.
- 


CREATIVE TROWEL PATTERNS

Provides a versatile base to create unique, trowel-based texture designs.

3. PRODUCT DETAILS


- CHEMICAL BASE:

Modified Acrylic & Dolomite Dispersion
- PHYSICAL PROPERTIES:









4. TECHNICAL SPECIFICATIONS

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Appearance	–	Off White, Viscous Paste
Material Base	–	Modified Acrylic & Dolomite
pH	ASTM E70	8.5 – 9.5
Specific Gravity	ASTM D1475	1.60 – 1.80
Drying Time (Surface Dry)	ASTM D1640	2 – 4 hours
Drying Time (Hard Dry)	ASTM D1640	24 – 48 hours
Application Temperature	–	10°C – 40°C
Coverage	–	1.0 – 1.5 kg per sq. m (as per design & surface condition)

5. APPLICATION METHOD

- 1



PREPARE SURFACE

Ensure the wall surface is clean, dry, and free from loose debris, dust or contaminants.
- 2



APPLY TEXTURE

Use a trowel to apply the material, creating your desired aesthetic pattern across the surface.
- 3



FINISH AND PROTECT

Allow the texture to dry completely before applying your preferred topcoat shade for a lasting finish.

6. SAFETY FEATURES & PRECAUTIONS

- 

Refer to the Safety Data Sheet (SDS) before use.



Keep out of reach of children and away from food & beverages.



Wear protective gloves and eye protection during application.



Ensure good ventilation during application and drying.



Do not dispose of in drains or water bodies.



In case of contact with eyes, rinse immediately with plenty of water and seek medical help.

7. STORAGE PRECAUTIONS



Store in a cool, dry place at temperatures between 5°C – 35°C.



Keep the pouch tightly sealed when not in use.

8. RECOMMENDED FOR



Residential & commercial buildings

New construction & renovation

Interior & exterior textured wall finishes

9. WHY CHOOSE TEXTURA PRO?

Premium finish with superior aesthetics

Long-lasting beauty with strong protection

Masks imperfections and enhances wall value

Ideal base for a wide range of topcoat shades

10. SCAN TO KNOW MORE

HIDES SURFACE IMPERFECTIONS

STRUCTURAL PROTECTION

ALL-WEATHER DURABILITY

CREATIVE TROWEL PATTERNS

LOW VOC & ECO FRIENDLY