



Twinshield Emulsion

Premium Interior Protective Finish.



Water Based



Lead Free

AREAS OF APPLICATION



Living Rooms



Bedrooms



Dining Areas



Hallways

FEATURES AND BENEFITS

- ✓ Double-Guard Shield against stains & moisture
- ✓ Easy Washable surface for simple cleaning
- ✓ Superior Multi-Surface Adhesion
- ✓ Smooth, even application
- ✓ Long-lasting protective finish

PRODUCT DETAILS

Parameter	Test Standard Used	Typical Values
Nature / Type	ASTM D16	Acrylic Emulsion
Finish	ASTM D523	Smooth Sheen
Drying Time (Touch Dry)	ASTM D1640	30 - 60 mins
Recoat Time	ASTM D1640	4 - 6 hours
Dilution	By Volume	40% with water
Theoretical Coverage	IS 101	12 - 14 sq. m/L/coat
Shelf Life	Manufacturer Spec	3 Years in unopened container
Storage	Manufacturer Spec	Store in cool, dry place

APPLICATION METHOD



SURFACE PREPARATION

Ensure surface is clean, dry, and free from dust, grease, and loose paint. Remove all fungus and algae with a fungicidal wash. Sand the surface smooth.



PRIMING

Apply a single coat of Wall Primer (solvent-based or better adhesion on chalky surfaces) and allow to dry for 4 - 6 hours.



APPLICATION

Thin 1 part Twinshield Emulsion with up to 0.4 parts clean water. Apply two coats using a brush or roller, allowing 4 - 6 hours between coats. Avoid heavy application.

SAFETY FEATURES & PRECAUTIONS



Ensure good ventilation during application & drying.



Wear protective gloves and eye protection.



In case of contact with eyes, rinse immediately with water.



Keep out of reach of children.



Do not empty into drains or watercourses.



Do not empty into drains or water.



Store container securely upright in a cool place.



Refer to Safety Data Sheet before use.



HOW TO USE:

- Clean surface and remove loose particles.
- Apply primer and let dry.
- Apply two coats of emulsion.



RECOMMENDED FOR

- ✓ Premium Interior Walls
- ✓ High-Traffic Residential Areas
- ✓ Hospitality and Commercial Spaces

Scan to know more



DOUBLE-GUARD SHIELD



WASHABLE SURFACE



MULTI-SURFACE ADHESION



SMOOTH APPLICATION



LONG-LASTING PROTECTION