

# TwinShield Pro

## PREMIUM PROTECTIVE EMULSION

Premium protective emulsion with Silicon Boost and Dust Proof Technology.



WATER BASED



LEAD FREE GUARANTEE



WATER  
BASED



NO ADDED LEAD,  
MERCURY OR  
CHROMIUM



LONG LASTING  
PROTECTION

\*All COLORSOME products contain no added Lead, Mercury, Arsenic or Chromium.

### 1. AREAS OF APPLICATION



MASONRY  
WALLS



EXTERIOR  
FACADES



NEW/OLD  
EXTERIOR  
SURFACES



BRICKWORK

Suitable for both new and previously painted exterior surfaces.

### 2. FEATURES & BENEFITS

- ✓ Silicon Boost for durability
- ✓ Resists dust settlement
- ✓ Comprehensive 6 Year Performance Warranty
- ✓ High abrasion resistance for low wear
- ✓ Excellent adhesion to concrete substrates
- ✓ Smooth, modified acrylic finish
- ✓ Better hiding and superior coverage
- ✓ Improved anti-algal properties
- ✓ Water-based and environmentally friendly

### 3. PRODUCT DETAILS

#### CHEMICAL PARAMETERS

- Chemical Base: Pure Acrylic Dispersion
- Solvent Type: Water-based
- Drying Time: Surface dry 30 min (at 30°C)



#### PHYSICAL PARAMETERS

| PARAMETER            | TEST STANDARD USED | TYPICAL VALUES                  |
|----------------------|--------------------|---------------------------------|
| Theoretical Coverage | In-house Method    | 60 - 70 sq.ft./ltr in two coats |
| Finishing            | Visual             | Smooth                          |
| Warranty             | Warranty Booklet   | 6 Years                         |
| Shelf Life           | —                  | 3 Years                         |
| Pack Sizes           | —                  | 1 ltr, 4 ltr, 20 ltr            |

### 4. APPLICATION METHOD



#### SURFACE PREPARATION

- Ensure surface is dry and free from dust, dirt, grease and loose particles.
- Fill all cracks with suitable filler.



#### APPLICATION STEPS

[GENERAL APPLICATION STEPS:]

- 1 Apply a compatible primer coat.
- 2 Sand lightly.
- 3 Apply two coats of TwinShield Pro with sufficient drying time between coats.



#### RECOAT & CURING

- Recoat period (at 25°C & 50% RH) is 4 - 6 hours.
- Curing time needs to be extended in high humidity, damp, or cold conditions. Allow complete 7 days curing before regular movement.

### 5. SAFETY FEATURES & PRECAUTIONS



Use personal protective equipment during application.



Avoid inhalation, eye and skin contact.



Keep out of reach of children.



Store in a cool, dry place.



Refer to MSDS for detailed information.



Do not pour leftover paint down the drain.

### 6. STORAGE PRECAUTIONS



Store in a cool, dry place away from direct sunlight.



### 7. RECOMMENDED FOR



- ✓ Masonry Walls
- ✓ Exterior Facades
- ✓ New/Old Exterior Surfaces
- ✓ Brickwork

### 8. HOW TO USE

- 1 Clean the surface and remove dust and loose particles.
- 2 Apply 1 coat of primer.
- 3 Apply 2 coats of TwinShield Pro.
- 4 Let dry for 4-6 hours before applying next coat.



STRONG  
ADHESION



ADVANCED  
ANTI-ALGAE



DUST  
RESISTANT



WEATHER  
PROTECTION



LONG LASTING  
PERFORMANCE