

UNIPRIME EXT

PREMIUM EXTERIOR PRIMER

STRONG FOUNDATION. LASTING PROTECTION.

Uniprime Ext is a high-performance exterior primer formulated to deliver superior adhesion and long-lasting protection against harsh weather conditions.

SUPERIOR ADHESION

ALKALI RESISTANT

WEATHER PROTECTION

SEALS SURFACES



SUPERIOR ADHESION  
Ensures excellent bonding of paint with the surface for a long-lasting finish.

ALKALI RESISTANT  
Protects against alkali attack and prevents peeling and flaking.

WEATHER PROTECTION  
Shields surfaces from rain, sun, humidity and pollutants.

SEALS SURFACES  
Penetrates and seals porous surfaces for a smooth base.

1. WHY CHOOSE UNIPRIME EXT?

Superior Adhesion  
Creates a strong bonding layer between the surface and topcoat for enhanced durability.

Alkali Resistant  
Resists alkali from cement and plaster, preventing efflorescence and paint deterioration.

Weather Protection  
Provides a protective barrier against moisture, UV rays and extreme weather conditions.

Seals Surfaces  
Seals pores and reduces paint absorption for uniform finish and better coverage.

2. IDEAL FOR

Exterior Walls  
Ensures strong adhesion on exterior plastered surfaces.

Concrete Surfaces  
Ideal for RCC, concrete and cementitious substrates.

Plastered Walls  
Prepares new plaster surfaces for long-lasting paint performance.

Masonry  
Suitable for brickwork, block work and other masonry surfaces.

Ideal for both new construction and repainting projects.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Water Based Acrylic Primer
- Finish : Matt
- Colour : Off White
- Viscosity : 90 - 110 KU @ 25°C
- Specific Gravity : 1.45 ± 0.05
- Solid by Volume : 40 ± 2%
- Drying Time (Touch Dry) : 30 - 60 mins
- Drying Time (Hard Dry) : 4 - 6 hrs
- Recoat Time : 4 - 6 hrs
- Coverage : 10 - 12 m²/litre/coat\*
- No. of Coats : 1 - 2 Coats
- Thinner : Clean Water
- Packaging : 1L, 4L, 10L, 20L

PERFORMANCE PROPERTIES

| PROPERTY                 | TYPICAL VALUE    |
|--------------------------|------------------|
| Adhesion (Cross Cut)     | Excellent (5B)   |
| Alkali Resistance        | Excellent        |
| Water Resistance         | Excellent        |
| Weather Resistance       | Excellent        |
| UV Resistance            | Excellent        |
| Salt Spray Resistance    | Excellent        |
| Efflorescence Resistance | Excellent        |
| Film Integrity           | Excellent        |
| Coverage                 | 10 - 12 m²/litre |

\*Coverage may vary depending on surface type, texture and application method.

4. SURFACE PREPARATION & APPLICATION GUIDE

1. SURFACE PREPARATION

- Surface must be clean, dry and free from dust, loose particles, oil, grease and laitance.
- Remove all traces of peeling paint, moss, algae and efflorescence.
- Repair cracks and holes with suitable filler and allow to dry.

2. PRIMING

- Stir well before use.
- Apply 1 - 2 coats of Uniprime Ext using brush, roller or spray.
- Ensure uniform application for best results.

3. THINNING

- Thin with clean water up to 10 - 15% (by volume).
- Do not over-thin.

4. DRYING

- Touch dry in 30 - 60 mins.
- Hard dry in 4 - 6 hrs.
- Recoat after 4 - 6 hrs.

5. TOPCOAT APPLICATION

- After priming, apply your preferred exterior emulsion or textured finish.
- For best performance, complete within 7 days of priming.

5. SAFETY FEATURES & PRECAUTIONS

Refer to the MSDS for Uniprime Ext for detailed safety information about safe handling and disposal.

Store the container with the lid tightly closed in an upright position, in a cool, dry place.


Keep out of reach of children and away from food & feed.

May be harmful if swallowed. In case of ingestion, seek immediate medical attention.

Wear eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Do not pour leftover material down the drain or in water courses.

In the event of spills, contain spillage using sand or earth.

No added Lead, Mercury or Chromium compatible.

6. STORAGE PRECAUTIONS



- Store in a cool and dry place at ambient temperatures.
- Keep containers tightly closed when not in use.
- Protect from moisture, frost and direct sunlight.
- Shelf life: 24 months from date of manufacture.

RECOMMENDED FOR



- Residential buildings
- Commercial complexes
- Renovation projects
- New construction

HOW TO USE

- 1 Prepare the surface properly.
- 2 Apply Uniprime Ext primer evenly.
- 3 Allow to dry completely.
- 4 Apply topcoat for best results and durability.

