

UNIPRIME

INTERIOR WALL PRIMER

THE PERFECT BASE FOR A FLAWLESS FINISH.

Uniprime is a versatile all-purpose primer that prepares surfaces for optimal paint adhesion and delivers a smooth, uniform finish.



ALL-PURPOSE



QUICK DRYING



EXCELLENT
ADHESION



SEALS POROUS
SURFACES



ALL-PURPOSE
Suitable for a wide range of interior and exterior surfaces.



QUICK DRYING
Fast drying formula saves time and ensures efficient application.



EXCELLENT ADHESION
Creates a strong bonding layer for long-lasting paint performance.



SEALS POROUS SURFACES
Seals pores and reduces paint absorption for better coverage and finish.

1. WHY CHOOSE UNIPRIME?



All-Purpose Primer

Designed for multiple surfaces to ensure excellent compatibility and versatile application.



Quick Drying Formula

Dries quickly to allow faster recoating and project completion.



Excellent Adhesion

Ensures strong paint adhesion and prevents peeling, blistering and flaking.



Seals Porous Surfaces

Seals pores and minimizes porosity variations for a smooth and uniform paint finish.

2. IDEAL FOR



Interior Walls

Gypsum, putty, plastered and cement walls.



Exterior Walls

Prepares exterior surfaces for superior paint performance.



Wood

Doors, windows, furniture and wooden panels.



Metal

Metal doors, railings, frames and other metal surfaces.

Ideal for both new construction and repainting projects.

3. PRODUCT DETAILS

TECHNICAL SPECIFICATIONS

- Type : Water Based Acrylic Primer
- Finish : Matt
- Colour : Off White
- Viscosity : 80 – 110 KU @ 25°C
- Solid by Volume : 40 ± 2%
- Specific Gravity : 1.40 ± 0.05
- Drying Time (Touch Dry) : 30 – 60 mins
- Drying Time (Hard Dry) : 4 – 6 hrs
- Recoat Time : 4 – 6 hrs
- Coverage : 10 – 12 m²/litre/coat*
- No. of Coats : 1 – 2 Coats
- Thinner : Clean Water
- Packaging : 1L, 4L, 10L, 20L

* Coverage may vary depending on surface type, texture and application method.

PERFORMANCE PROPERTIES

PROPERTY	TYPICAL VALUE
Adhesion (Cross Cut)	Excellent (5B)
Alkali Resistance	Excellent
Water Resistance	Excellent
Weather Resistance	Good
Recoatability	Excellent
Salt Spray Resistance	Excellent
Efflorescence Resistance	Excellent
Film Integrity	Excellent
Coverage	10 – 12 m ² /litre

4. SURFACE PREPARATION & APPLICATION GUIDE



1. SURFACE PREPARATION

- Surface must be clean, dry and free from dust, oil, grease, loose paint or rust.
- Remove all loose particles and flaking paint.
- Repair cracks and holes with suitable filler and allow to dry.



2. PRIMING

- Stir well before use.
- Apply 1 – 2 coats of Uniprime using brush, roller or spray.
- Ensure uniform application.



3. DRYING

- Touch dry in 30 – 60 mins.
- Hard dry in 4 – 6 hrs.
- Recoat after 4 – 6 hrs.



4. TOPCOAT APPLICATION

- After priming, apply your preferred emulsion or decorative paint.
- For best performance, complete within 7 days of priming.



5. CLEANING

- Clean all tools and equipment with water immediately after use.
- Do not allow primer to dry on tools.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for complete safety information.



Keep out of reach of children.



Wear protective gloves, mask and goggles during application.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Dispose of empty containers as per local regulations.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight, frost and moisture.
- Shelf life: 24 months from date of manufacture.

RECOMMENDED FOR

- Interior Walls
- Exterior Walls
- Wood
- Metal
- New Construction
- Repainting Projects

HOW TO USE

- Prepare the surface properly.
- Apply Uniprime as per recommended method.
- Allow to dry completely.
- Apply topcoat for best results and durability.



ALL-PURPOSE



QUICK DRYING



EXCELLENT ADHESION



SEALS POROUS SURFACES



STRONG FOUNDATION