

WALL ENAMEL

Valucoat

Valucoat is a premium quality, water-based enamel for beautiful interior and exterior walls.



WATER BASED
Low odor & quick drying



LEAD FREE*
No added Lead, Mercury, Arsenic or Chromium

LEAD FREE* GUARANTEE

All COLORSOME products contain no added Lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION



Interior Walls



Exterior Walls



Masonry



Plaster

Ideal for use on interior and exterior walls, masonry, plaster, concrete and other properly prepared surfaces.

2. FEATURES AND BENEFITS



ULTRA-WASHABLE & STAIN RESISTANT

Forms a tough film that resists stains and allows easy cleaning.



HIGH DURABILITY

Provides long-lasting protection against weather and wear.



EXCELLENT OPACITY & COVERAGE

High hiding power for uniform, beautiful walls.



VIBRANT COLOURS THAT LAST

Superior colour retention that resists fading.



QUICK DRYING & LOW ODOR

Dries fast with minimal odor for a pleasant painting experience.



SMOOTH, LUXURIOUS FINISH

Delivers a rich, even and elegant enamel finish.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- Parameter | Type: Acrylic Emulsion
- Solvent: Water
- Finish: Enamel (High Sheen)
- Odor: Low
- Lead, Mercury, Arsenic & Chromium Free
- Shelf Life: 24 months
- Packaging: 1 L, 4 L, 10 L, 20 L

PHYSICAL PARAMETERS

Parameter	Test Standard Used	Typical Values
Viscosity	ASTM D 562	95 – 105 KU
Gloss (at 60°)	ASTM D 523	3 – 7 units
Specific Gravity	ASTM D 1475	1.30 ± 0.05
Solid Content	ASTM D 2369	48% – 52%
Drying Time (Touch Dry)	ASTM D 1640	30 – 45 minutes
Drying Time (Hard Dry)	ASTM D 1640	4 – 6 hours
Recoat Time	ASTM D 1640	4 – 6 hours
Washability	Internal Method	> 50,000 cycles

*Results may vary depending on surface type, porosity, application method and environmental conditions.

4. APPLICATION METHOD



SURFACE PREPARATION

- Ensure surface is clean, dry and free from dust, dirt, grease, oil, loose paint or other contaminants.
- Repair cracks and imperfections with suitable wall putty and sand smooth.
- New masonry surfaces must be cured for at least 28 days.
- Allow the surface to dry completely before painting.



PRIMING

- Apply one coat of suitable primer (Acrylic Wall Primer) at the recommended coverage.
- Dilute primer as per instructions, if required.
- Allow primer to dry for 2 – 3 hours before applying top coat.



APPLICATION

- Stir Valucoat thoroughly before use.
- Dilute as per instructions (typically 20–30% with clean water).
- Apply two coats by brush, roller or spray.
- Maintain recommended coverage and allow 4 – 6 hours drying time between coats.
- For best results, apply at 27 ± 2°C and 65 ± 5% RH.
- Final cure is achieved after 7 days.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for complete safety information.



Keep out of reach of children.



Wear protective gloves, eye protection & mask.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Do not dispose of leftover paint in drains or water courses.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight and freezing.
- Shelf Life: 24 months from date of manufacture.

RECOMMENDED FOR

- ✓ Interior Walls
- ✓ Exterior Walls
- ✓ Masonry Surfaces
- ✓ Doors, Windows & Frames
- ✓ Furniture & Cabinets

HOW TO USE

- 1 Clean the surface and remove dust, grease and loose material.
- 2 Apply 1 coat of Acrylic Wall Primer and allow to dry.
- 3 Apply 2 coats of Valucoat with proper interval between coats.
- 4 Let it dry for 4 – 6 hours before applying next coat.



PREMIUM HIGH GLOSS FINISH



EXCELLENT DURABILITY



ULTRA WASHABLE



SCRUB RESISTANT



RICH COLOURS