

DECORATIVE COATINGS

ValueGloss

PREMIUM HIGH-GLOSS ENAMEL

High-performance premium enamel that delivers a mirror-like finish with exceptional durability.



-  **WATER BASED**
Low odor & quick drying
-  **LEAD FREE***
No added lead, Mercury, Arsenic or Chromium.
-  **UV RESISTANT**
Protects against fading & yellowing

*As per standard safety norms.

1. AREAS OF APPLICATION



INTERIOR SURFACES



EXTERIOR SURFACES



FURNITURE & CABINETS



WOOD & METALWORK

Ideal for application on wood, metal, plastered walls, doors, windows, and other interior & exterior surfaces.

2. FEATURES AND BENEFITS



PREMIUM HIGH-GLOSS FINISH
Delivers a mirror-like shine that enhances the beauty of surfaces.



EXCELLENT SCRUB RESISTANCE
Stands up to frequent cleaning without losing shine.



SUPERIOR DURABILITY
Formulated for long-lasting protection and performance.



LOW ODOR
Water-based formula ensures low odor and safer application.



QUICK DRYING & NON-YELLOWING
Dries fast and maintains color brightness over time.



EXCELLENT OPACITY & COVERAGE
High hiding power provides uniform coverage.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- Acrylic Co-polymer Dispersion
- Premium Quality Pigments
- Pure Water Based
- Low VOC
- Lead, Mercury, Arsenic & Chromium Free

PHYSICAL PARAMETERS

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Weight Per Liter	ASTM D 1475	1.20 - 1.30 kg
Tensile Strength	ASTM D 2370	> 1.5 MPa
Elongation	ASTM D 2370	≥ 400%
Crack Bridging Ability	AS/NZ 4548	Up to 4 mm
Ultra Gloss (60°)	ASTM C 1250	≥ 60 Gloss Units
Advanced Binding Technology	BS EN 12390 - 8	0 mm
Washability	Internal Method	> 50,000 cycles
Surface Dry Time	ASTM D 1250	30 Minutes
Recoat Time	Internal Method	4 - 6 Hours

4. APPLICATION METHOD



SURFACE PREPARATION

- Ensure the surface is clean, dry, and free from dust, grease, oil, loose particles, or flaky paint.
- Repair cracks and imperfections with a suitable wall putty and sand smooth.
- New masonry surfaces must be cured for at least 28 days.



PRIMING

- Apply 1–2 coats of a suitable wall primer or Spoxy Primer at the recommended coverage of 80–100 sq. ft. per liter.
- [Mixing ratio for Spoxy Primer: Hardener : Water = 1 : 1 : 2 (by weight)]
- Allow the primer to dry for 2–3 hours before applying the finish.



APPLICATION GUIDANCE

- Stir the paint thoroughly before use.
- Dilute 20–30% with clean water.
- Apply 2–3 coats by brush, roller, or spray.
- Allow 4–6 hours drying time between coats at 27°C and 65% RH.
- Final cure is achieved after 7 days.

5. SAFETY FEATURES & PRECAUTIONS



Refer to the MSDS for complete safety information.



Keep out of reach of children.



Wear protective gloves, eye protection & mask.



In case of contact with eyes, rinse immediately with plenty of water.



Ensure adequate ventilation during application and drying.



If swallowed, seek medical advice immediately.



Do not dispose of leftover paint in drains or water courses.

STORAGE PRECAUTIONS



- Store in a cool, dry place away from direct sunlight.
- Keep the container tightly closed when not in use.
- Protect from freezing.
- Shelf Life: 2 Years

RECOMMENDED FOR

- Interior Walls
- Exterior Surfaces
- Furniture & Cabinets
- Doors, Windows & Frames
- Wood & Metal Surfaces

HOW TO USE

- Clean the surface and remove dust, grease, and loose particles.
- Apply primer and allow it to dry.
- Apply 2–3 coats of ValueGloss with proper interval.
- Enjoy a long-lasting, high-gloss finish.

