

PREMIUM WALL FINISH

Valuemate Emulsion

Premium quality emulsion paint for a smooth, rich matte finish and long-lasting protection.



- WASHABLE
- UV RESISTANT
- SMOOTH APPLICATION
- ECO-FRIENDLY

LEAD FREE* GUARANTEE

*All COLORSOME products contain no added Lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION



INTERIOR WALLS



PLASTERED SURFACES



MASONRY & BRICKWORK



CEILINGS

Ideal for all interior walls and ceilings in residential, commercial, and institutional spaces.

2. FEATURES AND BENEFITS



EXCELLENT COVERAGE & OPACITY

Provides high hiding power and uniform coverage.



RICH MATTE FINISH

Delivers a smooth, rich matte finish that enhances interiors.



SCRUB-RESISTANT & EASY TO CLEAN

Resists stains and allows easy cleaning for a fresh look.



QUICK DRYING

Dries quickly to save time between coats.



ENVIRONMENTALLY CONSCIOUS (LOW VOC)

Low odor and safer for your home and the environment.



LONG-LASTING DURABILITY

Provides long-term protection and maintains beauty for years.

3. PRODUCT DETAILS

CHEMICAL PARAMETERS

- Acrylic Co-polymer Dispersion
- Premium Pigments
- Pure Water Based

PHYSICAL PARAMETERS

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Weight Per Liter	Generic	1.3 kg
Finish	Generic	Deep Matte
Solid Content	Generic	55%
Washability	Generic	>50,000 cycles

4. APPLICATION METHOD



SURFACE PREPARATION

- Ensure the surface is dry, clean, and free from loose particles, dust, dirt, oil, or grease.
- Treat any cracks or imperfections with suitable wall putty and sand smooth.



PRIMING

- Apply 1–2 coats of recommended wall primer at generic coverage.
- Allow to dry completely (4–6 hours) before applying the finish.



APPLICATION OF VALUEMATE EMULSION

- Stir the paint thoroughly before use.
- Dilute as specified (e.g., 20–30% with clean water).
- Apply 2–3 coats by brush, roller, or spray.
- Allow 4–6 hours drying time between coats at 27°C.
- Final cure is achieved after 7 days.

5. SAFETY FEATURES & PRECAUTIONS



Refer to MSDS for comprehensive safety information.



Keep out of reach of children.



Wear suitable protective clothing, gloves, and eye protection.



In case of contact with eyes, rinse immediately with plenty of water.



If swallowed, seek medical advice immediately.



Ensure adequate ventilation during application and drying.



Do not dispose of leftover paint in drains or water courses.

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight and frost.

HOW TO USE

- Surface preparation
- Apply primer
- Apply 1st coat of Valuemate Emulsion
- Apply 2nd coat

RECOMMENDED FOR

- Interior Walls
- Ceilings
- Residential Projects
- Commercial Projects
- Institutional Projects



RICH MATTE FINISH



EXCELLENT HIDING POWER



EASY TO CLEAN



PREMIUM QUALITY