

VEDA LUSTRE

Premium Decorative Finish, Elegant Pearlescent Sheen



**WATER
BASED**



**LOW VOC
Formulation**




**NO ADDED
LEAD, ARSENIC
OR MERCURY**



*Walls
that Reflect
Your Style*

1. AREAS OF APPLICATION



Normal Masonry
Surfaces



Interior Walls

Ideal for interiors where you desire a rich, metallic high-sheen finish with superior aesthetics and performance.

2. FEATURES AND BENEFITS

- ✓ Lime-Based sustainable formulation
- ✓ Alluring Pearl Finish with iridescent glow
- ✓ Refined surface, soft luxurious lustre
- ✓ Silicon Tactility for durability & resilience

- ✓ Superior formulation with 100+ heritage-inspired shades
- ✓ Unmatched stain resistance against various household stains
- ✓ 10-year warranty* against peeling/flaking

*Refer to warranty guide for details.

3. PRODUCT DETAILS

CHEMICAL DETAILS:

- Lime-Based Water-Based
- Low VOC

PHYSICAL PARAMETERS:

- **Colour and appearance:** White (viscous paste)
- **Packaging:** 20 L
- **Coverage:** 1.2 – 2 kg per sq. m in two coats for 1mm DFT

PHYSICAL PARAMETERS:

Parameter	Test Standard	Typical Values
Available Packs	–	1 ltr, 4 ltr
Finish	–	Pearlescent
Washability	ASTM D2486	Excellent
Coverage	–	100 – 120 Sq.ft/ltr** (2 coats)
Surface Dry Time	–	30 minutes
Thinned Paint Stability	–	Use within 24 hours
Shelf Life	–	36 months from date of mfg
Note	–	**Actual coverage may vary

4. APPLICATION METHOD



SURFACE PREPARATION

- **Fresh surface:** Allow new masonry to cure for at least 28 days and have a moisture content of less than 5 – 10%.
- Clean surface of efflorescence, paint, dust, grease and loose particles.
- Remove algae growth before application.
- Fill cracks up to 3mm with specialized filler.
- **For metal:** Remove rust by chipping, scraping, sanding to a smooth surface. Sand with 180-grit paper, followed by 320-grit paper. Apply specialized generic Masonry/Metal Primer.



PRIMING & THINNING

- Ensure surface is smooth and free from undulations.
- Application of wall primer is **mandatory**.
- Thin 1 litre VEDA LUSTRE with 300 – 350 ml of water. Mix thoroughly.
- Allow primer to dry before topcoat.



APPLICATION

- Apply 1st coat using short nap felt roller followed by foam roller.
- Allow 8 hours recoat time at 30°C and 50–60% humidity.
- Apply 2 coats of VEDA LUSTRE for best results.

Finishing Options:

- **Natural Pearl:** Short nap felt roller followed by foam roller.
- **Vintage Pearl:** Brush in a criss-cross pattern.
- **Cloudy Enigma:** Short nap felt roller, then move sponge in circles.
- Some shades may require 3 coats.

5. SAFETY FEATURES & PRECAUTIONS



Refer to the MSDS for detailed safety information.



Keep out of reach of children and pets.



Wear eye protection, hand gloves and mask during application.



In case of eye/skin contact, rinse immediately with plenty of water and seek medical advice.



Do not pour leftover paint down the drains or in open areas.



Do not apply at low temperature (below 10°C).

STORAGE PRECAUTIONS



- Store in a cool, dry place.
- Keep containers tightly closed when not in use.
- Protect from direct sunlight and extreme heat.

RECOMMENDED FOR



- ✓ New Construction



- ✓ Renovation



- ✓ Interior Walls

POST PAINTING CARE



- Immediately remove regular stains with 5% soap solution/sponge.
- Use mild detergent for tough stains like sketch pen.
- Clean dust from top to bottom with a soft cloth.



**LUXURIOUS
METALLIC FINISH**



**SUPERIOR
UV RADIATION RESISTANCE**



**EXCELLENT
DIRT PICK UP RESISTANCE**



**BRIGHTER
CLEANER SHADES**



**LONG LASTING
PERFORMANCE**