

PREMIUM ULTRA-MATTE FINISH

Velveton Ultra

A high-performance, ultra-matte paint for luxurious interior spaces.

- EXCEPTIONAL WASHABILITY
- SCRUB RESISTANT
- ULTRA-MATTE AESTHETIC
- HIGH HIDING POWER
- DURABLE FILM FORMATION



WATER
BASED



LEAD
FREE

AREAS OF APPLICATION



Retaining Walls



Terrace



Wet Areas



Parapet Walls

FEATURES AND BENEFITS

- Exceptional washability and scrub resistance
- Smooth, velvety, ultra-matte aesthetic
- Excellent color retention and fade resistance
- High hiding power and coverage
- Seamless, durable film formation
- Low odor formulation
- Resistant to efflorescence and fungal growth
- Easy application by brush, roller, or spray

PRODUCT DETAILS

- Chemical Composition: Modified Acrylic Emulsion
- VOC Level: < 30 g/L

TECHNICAL INFORMATION

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Sheen at 60°	Visual / ASTM D 523	< 5%
Touch Dry Time	ASTM D 1640	30 - 45 minutes
Recoat Time	ASTM D 1640	4 - 6 hours
Theoretical Coverage	ISO 2811-1	12 - 14 m²/L/coat
Dilution	Internal Test Method	40% by volume with clean water
Density	ASTM D 1475	1.45 ± 0.05 kg/L
pH	ASTM E 70	8.5 - 9.5

APPLICATION METHOD



SURFACE PREPARATION

Ensure surfaces are clean, dry, and free from dust, grease, and loose material. Sand the surface smooth and remove dust. Treat affected areas with appropriate solution if fungus or algae is present. Old painted surfaces must be fully abraded and cleaned.



PRIMING

Apply one coat of COLORSOME® Wall Primer (Water Based or Solvent Based as required) and allow to dry for 4-6 hours.



APPLICATION

Apply two coats of COLORSOME® Velveton Ultra, thinned with 40% water by volume. Ensure good ventilation during application. Allow 4-6 hours between coats for recoating. Do not apply in direct sunlight or extreme temperatures.

SAFETY FEATURES & PRECAUTIONS



Keep out of reach of children and away from edibles.



Wear appropriate protective gear (gloves, eye protection, mask) during handling.



Ensure good ventilation in enclosed application areas.



Avoid contact with skin and eyes; in case of contact, rinse immediately with plenty of water and seek medical advice.



Do not empty product into drains or water courses.



Store in a cool, dry place, away from direct sunlight and sources of ignition.



Refer to the Material Safety Data Sheet (MSDS) for comprehensive safety information.



Dispose of container in accordance with local regulations.

HOW TO USE

- Prepare Surface
- Apply Primer
- Apply Velveton Ultra (2 coats)



SHELF LIFE & STORAGE

12 months from date of manufacturing in unopened packaging. Store in a cool, dry, and well-ventilated area.



RECOMMENDED FOR

Suitable for Interior Walls and Ceilings

