

EXTERIOR FINISHES

Vivida Ext

Water-Based Acrylic Emulsion
Exterior Paint.



**WATER
BASED**



**LEAD FREE*
GUARANTEE**

*All COLORSOME® products contain no added Lead, Mercury, Arsenic or Chromium.

1. AREAS OF APPLICATION



NEW PLASTER



EXTERIOR
WALLS



CEMENT
MASONRY



HORIZONTAL
SURFACES
(e.g. Ledges)

Ideal for exterior surfaces, providing a beautiful and long-lasting finish with superior protection.

2. FEATURES AND BENEFITS

- ✓ Excellent Resistance to Chalking & Cracking
- ✓ Modified Acrylic Binder for Enhanced Durability
- ✓ More Economical than Cement Paint
- ✓ No Curing Required – Saves Time & Effort
- ✓ Includes 2-Year Film Integrity and Shade Fidelity Warranty
- ✓ Eco-friendly, Low VOC Formula

3. PRODUCT DETAILS

SPECIFICATIONS

- **Chemical Parameters:** Acrylic Emulsion Binder
- **Available Packs:** 1 ltr, 4 ltr
- **Finish:** Smooth, with Rich Sheen
- **Shelf Life:** 3 years from date of manufacture (in original, tightly closed containers away from direct sunlight & excessive heat)
- **Recommended For:** Exterior Wall Applications (Dry to Moderately Humid Climatic Conditions)

TECHNICAL DATA

PARAMETER	TEST STANDARD USED	TYPICAL VALUES
Adhesion Strength	ASTM D 4541	≥ 1.5 MPa
Tensile Strength	ASTM D 2370	1.5 ± 0.15 MPa
% Elongation	ASTM D 2370	380 ± 10% (Horizontal)
Solid Content	BS EN 12390 – 8	20 ± 2%
Colour of Dry Film	Visual	As per shade card
Recoating Time (Hours)	ASTM D 2370	8
Dilution % (By Volume)	-	> 5 %

4. APPLICATION METHOD



SURFACE PREPARATION

1. Plaster curing should be done for at least 28 days and have a moisture content of 10% or less.
2. Clean the surface of dirt, dust, grease, loose particles, algae, fungi and other contaminants. Remove any loose or flaking material.
3. Fill cracks (up to 3mm) with suitable exterior putty or crack filler and allow to dry. Sand smooth.
4. Repair any damaged areas and ensure proper slope and water drainage.



PRIMING

1. Apply Exterior Wall Primer as per recommended coverage of 80 – 100 Gram per square meter.
2. Dilute with clean water in the ratio 1 : 1 – 1 : 2 (Primer : Water) by weight.
3. Allow primer to dry for 2 – 3 hours before applying the top coat.



APPLICATION

1. Stir the material well with a mechanical mixer to get a homogeneous consistency.
2. Apply the first coat using a brush, roller or spray at recommended coverage for even finish.
3. Second coat: apply using a roller at recommended dilution. Allow recoating after 4 – 6 hours depending on surface temperature.
4. Ensure uniform coverage for best results.

5. SAFETY FEATURES & PRECAUTIONS



Refer to the MSDS for detailed safety information.



Wear eye protection, hand gloves and mask during application.



Keep out of reach of children and away from foodstuff.



Wear eye protection during application.



In case of eye contact, rinse with water and seek medical attention.



Do not pour leftover paint down the drain or in other courses.



No added Lead, Mercury or Chromium compounds.

POST PAINTING CARE



- Clean fungal and algal growth using a mild detergent solution and soft brush.

RECOMMENDED FOR



- ✓ Dry Climates
- ✓ Moderately Humid Climates

HOW TO USE

- 1 Clean surface and loose particles.
- 2 Apply Primer
- 3 Apply Vivida Ext



EXCELLENT
WEATHER RESISTANCE



HIGHLY
DURABLE



SUPERIOR
WATER REPELLENCY



UV
PROTECTION