

# Machine Learning Theory (CSC 482A/581A)

## Problem Set 1

Due on Friday, October 4th, 7pm

---

### Instructions:

- You must write up your solutions individually.
- You may have high-level discussions with 1 other student registered in the course. If you discuss problems with another student, include at the top of your submission: their name, V#, and the problems discussed.
- You must type up your solutions and are encouraged to use LaTeX to do this. For any problems where you only have a partial solution, be clear about any parts of your solution for which you have low confidence.
- Please be sure to submit your solutions via conneX by the due date/time indicated above. This is a hard deadline.

### Questions:

1. Let  $\mathcal{X} = \mathbb{R}^2$  and take  $\mathcal{C}$  to be the class of concentric circles  $\mathcal{C} = \{c_r : r \geq 0\}$ , where, for each nonnegative real number  $r \geq 0$ , we have  $c_r(x) = \mathbf{1}[\|x\|_2 \leq r]$ . Prove that  $\mathcal{C}$  is PAC learnable. In particular, show a PAC learning algorithm which, given a training sample of size  $n \geq \frac{\log \frac{1}{\delta}}{\varepsilon}$ , finds with probability at least  $1 - \delta$  a hypothesis  $\hat{f} \in \mathcal{C}$  for which  $R(\hat{f}) \leq \varepsilon$ .

2. Devise an efficient mistake bound learner for the concept class  $k$ -term DNF over  $\mathcal{X} = \{0, 1\}^d$ . The runtime and mistake bound of your algorithm both should be polynomial in  $d$ ; you may treat  $k$  as a constant.

3. Let  $\mathcal{X} = \{0, 1\}^d$  and consider PAC learning a finite concept class  $\mathcal{C}$ . Assume that the inputs are drawn i.i.d. from an unknown distribution  $P$  over  $\mathcal{X}$ , and the labels are generated via the rule  $Y = c(X)$  for some  $c \in \mathcal{C}$ .

Let's call this problem the "clean" problem; so, in the clean problem, the training sample consists of random examples of the form  $(X, Y)$  for  $X \sim P$  and  $Y = c(X)$ .

Next, consider the following "corrupted" problem: Each time we request a random example  $(X, Y)$ , with probability  $\alpha(X) \in [0, 1]$  the value of the label  $Y$  is flipped. Call the resulting label  $\tilde{Y}$ . Thus,

$$\tilde{Y} = \begin{cases} -Y & \text{with probability } \alpha(X) \\ Y & \text{with probability } 1 - \alpha(X) \end{cases}$$

In the corrupted problem, the examples are of the form  $(X, \tilde{Y})$ , and so the labels are noisy.

- (a) Using  $c$  and  $\alpha$ , derive an expression for the Bayes classifier for the corrupted problem.
- (b) For the remaining questions, assume that  $\alpha(x) = \frac{1}{4}$  for all  $x \in \mathcal{X}$ . What is the Bayes classifier for the corrupted problem?
- (c) What is the Bayes risk for the corrupted problem?
- (d) Let  $c_\varepsilon \in \mathcal{C}$  be a hypothesis for which  $\Pr(c_\varepsilon(X) \neq c(X)) = \varepsilon > 0$ . What is the risk (expected zero-one loss) of  $c_\varepsilon$  for the corrupted problem?
- (e) Design an algorithm for PAC learning  $\mathcal{C}$  given access only to corrupted labeled examples  $(X_1, \tilde{Y}_1), \dots, (X_n, \tilde{Y}_n)$ . That is, your algorithm should, with probability at least  $1 - \delta$ , output a concept  $\hat{f} \in \mathcal{C}$  for which  $\mathbb{E}_{X \sim P}[\hat{f}(X) \neq c(X)] \leq \varepsilon$ . Your algorithm should be statistically efficient (you should mention the sample size  $n$  required, and  $n$  should be polynomial in  $\frac{1}{\varepsilon}$  and  $\frac{1}{\delta}$ ), but it need not be computationally efficient. Please explain why your algorithm is correct.