2. Unite / Prime V3 Regression Suite Overview (IDP Login + Universal Enrollment)

Purpose

The **Prime V3 Regression Suite** serves as the next-generation automation framework for the **Unite Enhancement (UE) and modernization projects**.
It replaces the legacy Jenkins/TestNG setup (Prime V2) with a **GitLab CI/CD-driven automation pipeline**, leveraging **Maven dependency management** and **Nexus artifact repositories** for modular and scalable execution.

This suite is currently in **scheduled setup phase** and will form the baseline for **cross-platform regression automation**, covering enrollment, payments, notifications, and key API/UI workflows in **Prime Version 3**.

GitLab CI – pipeline & jobs

Item	Detail
Project	prime-test-automation
Pipeline (example)	#2397275412 — Nightly Regression
Trigger	Scheduled (nightly) on `main`
GitLab Job Stages	`prepare schedule`
Job Schedule:	Mon-Fri @ 1AM, Scheduler
Pipeline/Jobs details	1. **`prepare`** — setup / prep (passes before regression). 2. **`scheduled_regression_job`** — runs the Stage 1 V3 regression (failing pipeline typically reflects this job).
Suite name (TestNG)	V3 Stage1 Complete Regression Test Suite
Framework	Prime Version 3 (Maven, Cucumber, TestNG; `core.runner.ParallelFeatureRunner`)
Environment	Stage 1 (front office)
Build Management	Maven
Artifact Repository	Nexus

TestNG report (GitLab Pages — job artifacts)

The HTML report is published from the **scheduled regression** job's artifacts. **Only the job ID changes each run**; swap `[JOB_ID]` for the latest job from the pipeline.

Item	Value
Pattern	`https://ascensus-gs.gitlab.io/-/products/depot/qa-automation/prime-test-automation/-/jobs/[JOB_ID]/artifacts/unite/unite-universal-enrollment/target/surefire-reports/index.html`
Example (sample run)	Job #13573736461 report

How to find `[JOB_ID]`: Open the pipeline **Jobs** select **`scheduled_regression_job`** use the job ID from the URL or job page.

Regression suite entry point (automation repo)

Paths are relative to **prime-test-automation** (Windows-style as in CI scripts):

Role	Path in repo
Master suite (V3 nightly)	`bin\regression\daily\stage1-regression-master.xml`
Child 1 – Universal Enrollment	`bin\regression\daily\universal-enrollment-stage1.xml`

Child 2 – IDP Login	`bin\regression\daily\idp-login-stage1.xml`

The master suite includes the two child suites (UE, then IDP), matching `suite-files` in XML.

Planned Regression Modules

#	Module / Feature Area	Environment	Scope
1	Universal Enrollment	Stage 1	`universal-enrollment-stage1.xml` — member UE flows
2	IDP Login Flow	Stage 1	`idp-login-stage1.xml` — IDP login positive/negative flows

Combined suite at a glance

Question	Answer
What we run	Stage 1 front-office regression: **Universal Enrollment** (26 test blocks) then **IDP Login** (13 test blocks), orchestrated by the master suite.
How it is wired	`bin\regression\daily\stage1-regression-master.xml suite-files`: `universal-enrollment-stage1.xml`, then `idp-login-stage1.xml` (paths under `bin\regression\daily\` in **prime-test-automation**).
Where	Stage 1; execution via Prime V3 UE automation project (GitLab CI).
Combined reports	`reports/v3/Regression Test (Front Office) in Stage1 - IDP Login & UE.html` (+ views 2 and 3).

Latest combined report summary (from TestNG HTML)

Metric	Value
Suites in report navigator	3 (master context + **IDP Login** child + **Universal Enrollment** child)
Top banner	`3 suites, 49 failed tests`
IDP Login sub-suite	13 tests; **33 methods/TCs**
Universal Enrollment sub-suite	26 tests; **337 methods/TCs**
Totals (arithmetic)	**39** test blocks; **370** methods;