

ASTRO / SFRP — SQL execution in staging environments

1. Overview

The source document describes **SFRP DB Update** using:

- A **.SQL** file you create.
- **sudo -u astrojob** with **/astrofeedstage/qa/bin/runsqlfile.pl**.
- Different **--user** values for different database connections (examples below).

Stage 1 / Stage 2 / Stage 4 mapping

- The source document **does not** map ASTRO commands to Stage 1, 2, or 4 by name. It only shows **asts02wtrw** in the **--user** strings below. **Do not assume** stage numbers without confirmation from your lead.

2. Prerequisites

- PuTTY (or equivalent) access to the **ASTRO / SFRP feed staging** server (hostname **not** in the source document).
- Permission to run **sudo -u astrojob**
- Understanding that **updates require a SEQ_CHANGE_ID** generated as described in §4.

3. Step-by-step (simple path)

3.1 Log in with PuTTY

1. Open **PuTTY**.
2. Connect to the server your team provides for **SFRP / ASTRO** staging execution.

(Host/jump steps are not in the source document.)

3.2 Where to save SQL files

The source document states: **Save all these files to Home folder** (your Linux home directory on that server).

3.3 File naming

The source document says: **Create .SQL file** and shows examples such as **testsql7.sql**, **testca.sql**, **testil.sql**.

3.4 Formatting rules (from the source document)

1. **New line after each SQL** — same note as UNITED: "New line needed after each sql" applies to how you structure statements in the file.
2. **Blank line at end** — follow the UNITED instruction in the same source file: "one line space at the end".
3. **Semicolons** — examples use **;** after statements (e.g. **from dual;**, end of **UPDATE**).

4. Mandatory SEQ_CHANGE_ID (ASTRO / SFRP)

The source document states that **before updating anything** you need a **SEQ_CHANGE_ID**, obtained with:

```
select AST0CENTRAL.ASTRO_CENTRAL_UTILS.GENERATE_CHANGE_ID('Pkachhia_EE_Update3_OR') from dual;
```

Important

- **'Pkachhia_EE_Update3_OR'** is an **example** label from the source document. **Clarification:** The source does not define naming rules for this string. Confirm the **tag / label** format with your lead before using in production scripts.

Run the **SELECT ... GENERATE_CHANGE_ID ...** to obtain the new ID, then use that numeric value in your **UPDATE** (see example below).

4.1 Example UPDATE using SEQ_CHANGE_ID (from the source document)

The source document shows this pattern (note: **413473003** is the **example** ID from their sample — **you must replace** with the value returned from **GENERATE_CHANGE_ID** for your run):

```
UPDATE AST0CA.TS_ATC_TAX_1099R
SET CTL_REC_STAT = 'X', SEQ_CHANGE_ID = 413473003
WHERE PAYMENT_YEAR = 2024 AND CTL_REC_STAT = 'A';
```

Not stated in the source document: whether **UPDATE**, **SELECT**, and **GENERATE_CHANGE_ID** must live in the **same .sql** file or separate files. Align with your lead.

5. Commands — [runsqlfile.pl](#) (ASTRO / SFRP)

Examples **verbatim** from the source document (filenames and users):

```
sudo -u astrojob /astrofeedstage/qa/bin/runsqlfile.pl --user astqa0ca@asts02wtrw testsql7.sql --commit
```

The source also lists (as separate lines — **confirm with your lead** whether these are alternate examples or a required sequence):

```
select AST0CENTRAL.ASTRO_CENTRAL_UTILS.GENERATE_CHANGE_ID('Pkachhia_EE_Update3_OR') from dual;

sudo -u astrojob /astrofeedstage/qa/bin/runsqlfile.pl --user astqa0ca@asts02wtrw testca.sql --commit

sudo -u astrojob /astrofeedstage/qa/bin/runsqlfile.pl --user astqa0il@asts02wtrw testil.sql --commit
```

Observations from the source (not explained further there)

- **--user** uses a **space** before the connect string (`--user astqa0ca@asts02wtrw`), unlike the UNITED examples which use `--user=...`.
- Two different users appear: **astqa0ca@asts02wtrw** and **astqa0il@asts02wtrw** — use the one that matches the schema/database you are changing.

6. Troubleshooting (ASTRO / SFRP)

Symptom / topic	What to check
Missing semicolon	End each SQL statement with <code>;</code> per the examples.
Missing blank line at end of file	Add a final blank line (same source note as UNITED).
Missing <code>--commit</code>	Source examples include <code>--commit</code> .
Missing / wrong <code>SEQ_CHANGE_ID</code>	Run <code>GENERATE_CHANGE_ID</code> first; use the returned value in UPDATE, not a copied sample ID.
Wrong <code>--user</code> / schema	Match astqa0ca@asts02wtrw vs astqa0il@asts02wtrw to the correct database for your change.
Permission or ORA errors	Capture full runsqlfile.pl output; source document does not list fixes — escalate.
Cannot <code>sudo -u astrojob</code>	Escalate to infrastructure / lead.