

qTest + Jira: How Do I...?

How do I find what was tested for a feature/requirement?

Within Jira

1. Navigate to the **requirement ticket** (usually a Story or Feature type).
2. Click the **Apps** button > Select **qTest**.
3. Scroll to the **qTest: Test Execution** section:
 - Shows related **test cases** and **executed test runs**.
 - If there's no run data, it may be an older item or not fully linked yet.
4. Click on any test case or run ID to open in **qTest**.

No visible test cases may indicate unlinked or legacy requirements.

Within qTest (using Insights)

*Use **qTest Insights** for a full execution history tied to a requirement.*

1. Search for the **Jira Ticket ID** in the Requirements tab to get the qTest ID (e.g., RQ-12580).
2. Go to **Insights** from the qTest top nav (gridded icon).
3. Open **Saved Reports > Requirements Lookup**.
4. Click **FILTER >** to modify the filter:
 - Filter Column: Requirement ID
 - Comparison: =
 - Value: RQ-12580 (your ID)
 - Click **REPLACE** and confirm.
5. Find the row for your project and click the value in **Total Test Runs**.
6. Detailed test run history appears with execution status and dates.

How do I find where an escaped defect belongs?

1. Analyze the **feature context**:
 - Is it UI, API, backend?
 - Was it mobile, CSR, web?
 - Legacy flow or new microservice?
2. Search Jira using **keywords related to the failure**.
 - Sort by **Updated Date** descending.
 - Check which project/team shows up repeatedly.
3. **If you suspect a team**, file the ticket in their Jira project and notify their **PO/Scrum Master**.
4. If **no clear owner**, consult your own PO for historical ownership.
 - They may coordinate with other POs to identify the right team.

How do I backfill traceability for previous work?

Finding Old Requirements

1. Search Jira using keywords related to the feature.
2. Use filters: creation/completion dates, team names, ticket status.
3. Review ticket summaries, link back to epics, releases, or test plans.
4. Consult **Product Owners** or team leads for roadmap or ownership history.

Connecting Requirements to Test Cases

1. Search for the requirement ticket in qTest (if synced).
2. Open the **requirement** in qTest > Click **+ Add Test Case**.
3. Link existing test cases or create new ones in the **Test Design** tab.

Connecting Requirements to Defects

1. When creating or updating a defect, mention **related requirement ID** in the **Jira description**.
2. During test execution in qTest, link the defect when a test fails.
3. Over time, this builds a **reverse traceability chain** from production defect test case requirement.

How do I handle a requirement changing during a sprint?

1. Update the **requirement ticket in Jira** (or create a versioned one).
2. Sync to qTest, where the requirement is updated or duplicated.
3. Review and update **existing test cases** or create new ones.
4. Reassemble the **test suite** to reflect changes:
 - Add/Remove test cases as required.
 - Reassign runs if they are impacted.
5. Flag or **unlink old defects** no longer relevant.
6. Leave **comments in Jira/qTest** indicating changes and test coverage updates.

Related Best Practices

- Document test planning and decisions directly in Jira tickets.
- Engage BAs in test case design and review for better traceability.
- Use comments and attachments in test tickets to **log validations**.
- Favor a **consistent test case format** (Given–When–Then or tabular steps).

Tips for Teams

Action	Tool	Who	Description
Find what was tested	Jira / qTest	QA / BA	Use Jira ticket's qTest section or qTest Insights
Find escaped defect source	Jira	QA / PO	Analyze defect symptoms and trace Jira history
Backfill traceability	Jira / qTest	QA / BA	Search, sync, and link requirements to tests
Handle evolving requirements	Jira / qTest	QA / BA / PO	Update requirements, test cases, suites, and notes