

JMeter Script Setup & Execution

Environment Properties

- Only one environment setup step should be enabled for execution

Hardcoded/Local Variables

- Variables are declared in step per environment: e.g. Environment Setup - Local (Stage 1)
- Allows for easiest execution when run locally but requires every script to declare all necessary variables for each environment

Property/Remote Execution

- Variables are declared in environment properties and loaded via step: Environment Setup - Remote
- Allows for common files but running locally will require all properties are set in environment variables

Common Scripts

- Use the Include Controller to inject common scripts
- Make sure all relative references are declared using forward slash

Key File Loader

- The logic to load the key file for decryption has been extracted to this script: `idp/jmeter/authentication/decryption.jmx`

IDP Token Handling

- The logic to get an IDP token using client id/secret has been extract to this script: `idp/jmeter/authentication/authentication-client.jmx`
 - In order to obtain a token with this script, a JWT token must be generated which requires additional libraries which can be copied to the `jmeter/lib` installation from: `L:\Departments\Financial Services\UI\UI\UI-QA\nbotvinnik\Jmeter Setup\lib`
- The logic to get an IDP token using the PKCE flow has been extracted to this script: `idp/jmeter/authentication/authentication-pkce.jmx`

Credentials Handling

Encryption

- Client secrets are expected to be encrypted
- Account credentials may or may not be encrypted

Decryption

- All decryption is handled via step: Decrypt Credentials
 - Each JMeter script should setup its necessary fields
- Requires the following fields (setup as environment properties above)
 - `keyFile` - key file name for encryption/decryption
 - `encryption` - credentials are encrypted
 - Valid values - true/false
 - `keyPathByJmx` - boolean or path to key file
 - Valid value - true (use JMeter script directory to look for key file)
 - Valid value - false (use JMeter installation directory for key file)
 - Valid value - `<path to key file from JMeter script (JMX) including trailing slash>`
 - Should point to setup folder (e.g. `.././../setup/`)

Blazemeter Reporting & YAML

Local YAML

Used for local execution via Taurus with reporting to Blazemeter

- Settings
 - Proxy
 - `ssl-cert: false`

- Do not set address (for proxy)
- Modules
 - JMeter
 - Set path to local installation directory
 - Set gui based on execution preference
- Execution
 - Update concurrency/ramp-up/hold-for based on execution preference
- Scenario
 - Set script to JMX filename
- Reporting
 - Module: Blazemeter
 - Set report-name as necessary
 - Set test name as necessary (Should be unique for this JMeter script)
 - Set project as necessary (for folderization in Blazemeter)

Remote YAML

Used for remote execution on Jenkins via Taurus with reporting to Blazemeter

- Settings
 - Env
 - jkeyfilepath: <file path to setup folder on jenkins including trailing slash>
- Execution
 - Should reference property values for concurrency/ramp-up/hold-for (to be passed in)
- Scenario
 - Set script to JMX filename
- Reporting
 - Module: Blazemeter
 - Set report-name as necessary
 - Set test name as necessary (Should be unique for this JMeter script)
 - Set project as necessary (for folderization in Blazemeter)