

UNITE — SQL execution in staging environments

1. Overview

The source document describes running SQL on the **staging feed server** using **PuTTY** and **runsqlfile.pl** with a **backoff** service user.

Environments covered in the source document (UNITE)

- **Stage 1** — `uii0qa@uiis01`
- **Stage 2** — `uii0qa@uiis02`
- **Stage 4** — `uii0qa@uiis04`

2. Prerequisites

- PuTTY (or equivalent) access to the **correct staging server** for Stage 1, 2, or 4 (obtain hostname / jump host from your team; **not** in the source document).
- Permission to run the **`sudo -u backoff . . .`** command (if you cannot sudo, escalate to your lead).
- Your SQL file placed in the **Linux home path** your team uses. The source example uses **`/home/swpatil`** — replace with **your** assigned home directory if different.

3. Step-by-step (simple path)

3.1 Log in with PuTTY

1. Open **PuTTY**.
2. Connect to the **staging server** for the target stage (**Stage 1, 2, or 4**), per infrastructure instructions from your team.

(The source document does not list hostnames or bastion steps.)

3.2 Where to create / place the SQL file

Per the source document:

- Put your SQL file under the home folder — example given: **`/home/swpatil`** on the **Stage 1** server (use the same pattern for your user if your path differs).

3.3 File naming and content

run sql file invocation with this path as the last argument: **`/home/swpatil/sql`**

So in the example, the file to execute is named **`sql`** (no `.sql` extension in the example path). **Clarification:** If your team standard is something `.sql`, confirm the **exact path** you pass to `runsqlfile.pl` with your lead. **Do not guess** a different name without confirmation.

3.4 Formatting rules (from the source document)

1. **New line after each SQL statement** — the source states: *"New line needed after each sql"*.
2. **Blank line at the end of the file** — the source states: *"then one line space at the end"*.
3. **Semicolons** — the source examples use `;` at the end of SQL statements (e.g. after `from dual`);). Terminate each statement with `;` consistent with those examples.

3.5 Commands — execute SQL (UNITE)

Run the command for the **stage you are targeting** (from the source document).

Stage 1

```
sudo -u backoff /stagefeeds/qa/bin/runsqlfile.pl --user=uii0qa@uiis01 --commit /home/swpatil/sql
```

Stage 2

```
sudo -u backoff /stagefeeds/qa/bin/runsqlfile.pl --user=uii0qa@uiis02 --commit /home/swpatil/sql
```

Stage 4

```
sudo -u backoff /stagefeeds/qa/bin/runsqlfile.pl --user=uii0qa@uiis04 --commit /home/swpatil/sql
```

Notes

- Replace **`/home/swpatil/sql`** with your **actual file path** if your home directory or filename differs.
- **`--commit`** is shown in the source document on every example line — keep it unless your lead instructs otherwise.

4. Example SQL file layout (illustrative)

The source document does not include a full UNITE sample file. Structure yours to satisfy its rules: one statement per block with newlines, ; terminators, blank line at end.

-- Example shape only – replace with approved DBA/lead-provided SQL

```
UPDATE your_schema.your_table
SET your_column = 'Y'
WHERE id = 123;
```

(Blank line after last line, as required.)

5. Troubleshooting (UNITE)

Symptom / topic	What to check
Missing semicolon	Ensure each SQL statement ends with ; as in the source examples.
Missing blank line at end of file	Add one blank line after the last statement (source: <i>"one line space at the end"</i>).
Missing --commit	Source examples always include -- commit . If omitted, behavior may not match the documented path — align with your lead.
Wrong user / schema	Verify the -- user=uii0qa@uiis0x segment matches Stage 1 (uiis01) , Stage 2 (uiis02) , or Stage 4 (uiis04) per the tables above.
Wrong path to SQL file	Confirm the file exists at the path passed as the last argument (example /home/swpatil/sql).
Permission errors / ORA-***	Capture full output from runsqlfile.pl and escalate with your lead / DBA; the source document does not list ORA codes or fixes.
Cannot sudo -u backoff	Access / sudoers issue — not documented; escalate to infrastructure / lead.