


- Objective: Configure default route, static route to the router. To connect two PC's on two different networks using two routers.
- Topology: 2 PC's are connected to two different routers, through copper cross-over and routers are connected through serial DCE.



- Procedure:
  - 1) Connect two PC's to the two different routers using copper cross-over.
  - 2) Connect the routers using serial DCE.
  - 3) Open config in the PC and configure the IP address and the gateway.

4) Do the same for the other PC.

5) Open CLI in the router and configure the fastethernet connection by the following commands :-

> enable

> config terminal

> interface fastethernet 0/0

> ip address 10.0.0.2 255.0.0.0

> no shutdown

> exit

6) Repeat the steps for other router.

7) Connect the routers by the following commands:

> enable

> config terminal

> interface serial 2/0

> ip address 30.0.0.1 255.0.0.0

> no shutdown

exit


8) Repeat the steps for other router.

• Observation:

1) All PC's and routers are successfully connected

2) ~~Ping 20.0.0.10 & Ping 30.0.0.2 are unsuccessful and show destination host unreachable. This happens because they are not neighbour network with 10.0.0.1.~~

3) Ping 30.0.0.1 will be successful.



## Command Prompt



Packet Tracer PC Command Line 1.0

PC>ping 20.0.0.1

Pinging 20.0.0.1 with 32 bytes of data:

Reply from 10.0.0.2: Destination host unreachable.

Reply from 10.0.0.2: Destination host unreachable.

Reply from 10.0.0.2: Destination host unreachable.

Reply from 10.0.0.2: Destination host unreachable.

Ping statistics for 20.0.0.1:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

PC>ping 20.0.0.1

Pinging 20.0.0.1 with 32 bytes of data:

Reply from 10.0.0.2: Destination host unreachable.

Reply from 10.0.0.2: Destination host unreachable.

Reply from 10.0.0.2: Destination host unreachable.

Reply from 10.0.0.2: Destination host unreachable.

Ping statistics for 20.0.0.1:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

PC>|



## Command Prompt

```
Reply from 10.0.0.2: Destination host unreachable.  
Reply from 10.0.0.2: Destination host unreachable.  
Reply from 10.0.0.2: Destination host unreachable.
```

```
Ping statistics for 20.0.0.1:
```

```
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
```

```
PC>ping 20.0.0.1
```

```
Pinging 20.0.0.1 with 32 bytes of data:
```

```
Reply from 10.0.0.2: Destination host unreachable.  
Reply from 10.0.0.2: Destination host unreachable.  
Reply from 10.0.0.2: Destination host unreachable.  
Reply from 10.0.0.2: Destination host unreachable.
```

```
Ping statistics for 20.0.0.1:
```

```
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
```

```
PC>ping 20.0.0.2
```

```
Pinging 20.0.0.2 with 32 bytes of data:
```

```
Reply from 10.0.0.2: Destination host unreachable.  
Reply from 10.0.0.2: Destination host unreachable.  
Reply from 10.0.0.2: Destination host unreachable.  
Reply from 10.0.0.2: Destination host unreachable.
```

```
Ping statistics for 20.0.0.2:
```

```
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
```

```
PC>|
```