

A Technical Report on Core Electronic Components and Sensors for Unmanned Aerial Vehicles

NAME: ARYAN GUPTA

Abstract—This report provides a detailed technical overview of the fundamental electronic components and perceptual sensors that constitute the core of modern Unmanned Aerial Vehicles (UAVs). The working principles, primary use-cases, inherent advantages, limitations, and integration challenges are systematically analyzed for four key components: the Flight Controller (FC), Electronic Speed Controller (ESC), Global Positioning System (GPS) module, and high-level onboard computers like the NVIDIA Jetson. Furthermore, the report examines critical sensors for autonomous operation, including LiDAR, Depth Cameras, and Optical Flow sensors. Additional sensor technologies relevant to obstacle detection, such as Ultrasonic sensors, are also discussed. The objective is to offer a clear and in-depth understanding of how these individual systems function and interoperate to enable stable flight and intelligent autonomy in UAVs.

1.0 INTRODUCTION

Unmanned Aerial Vehicles (UAVs), commonly known as drones, have evolved from simple remote-controlled aircraft into sophisticated autonomous systems. This transformation is driven by advancements in microelectronics, sensor technology, and computational power. The functionality of any UAV is critically dependent on a suite of interconnected electronic components and sensors. The Flight Controller (FC) acts as the central nervous system, ensuring flight stability, while Electronic Speed Controllers (ESCs) provide the crucial link to the propulsion system. For navigation in outdoor environments, the Global Positioning System (GPS) is indispensable. The recent trend towards advanced autonomy, including tasks like real-time object detection and simultaneous localization and mapping (SLAM), has necessitated the integration of powerful onboard computers.

This report will dissect these core components and the primary sensors that grant them environmental awareness. Understanding each element's role and its associated challenges is fundamental to designing, building, and operating capable and reliable UAV systems [1].

2.0 ELECTRONIC COMPONENTS

2.1 Flight Controller (FC)

The Flight Controller is the central processing unit or the "brain" of the UAV. It is a microcontroller-based circuit board responsible for executing flight control software and maintaining stability.

- **2.1.1 Working Principle:** The FC's core function is to execute a high-frequency control loop. It continuously reads data from an integrated Inertial Measurement Unit (IMU), which contains an accelerometer and a gyroscope. This data provides the drone's current orientation (attitude) in space. The FC compares this actual state to the desired state

commanded by the pilot's radio controller or an autonomous mission planner. The difference, or error, is fed into a **Proportional-Integral-Derivative (PID) control algorithm**. The output of the PID controller is a set of corrective commands that are sent to the Electronic Speed Controllers (ESCs) to adjust the speed of each motor, thereby correcting the drone's attitude and achieving stable flight. Modern FCs also include a barometer for altitude hold and a magnetometer for heading information.

- **2.1.2 Use-Cases:**

- **Flight Stabilization:** The primary role is to keep the drone stable and level.
- **Manual/RC Control:** Interpreting signals from a radio receiver to control the drone's movement.
- **Autonomous Flight:** Executing pre-programmed flight plans, such as waypoint navigation, using data from a GPS module.
- **Failsafes:** Managing safety procedures like Return-to-Home (RTH) on signal loss.

- **2.1.3 Advantages:**

- **High-Speed Processing:** Optimized for real-time, low-latency flight calculations.
- **Integration:** Modern FCs integrate multiple sensors (IMU, barometer) and ports (UART, I2C, CAN) for connecting peripherals.
- **Robust Firmware:** Supported by mature open-source firmware like ArduPilot and Betaflight.

- **2.1.4 Limitations:**

- **Limited Computational Power:** Not designed for heavy computational tasks like computer vision or AI inference.
- **Specialized Function:** Its processing power is dedicated almost entirely to flight-critical tasks.

- **2.1.5 Integration Challenges:**

- **Vibration Damping:** The IMU on the FC is highly sensitive to vibrations from motors. Proper mechanical damping (soft mounting) is crucial for clean sensor readings.
- **Firmware Configuration:** Requires careful tuning of PID values and configuration of various parameters, which can be complex.
- **Port Management:** Limited number of UARTs (serial ports) for connecting peripherals like GPS, RC receiver, and onboard computer.

2.2 Electronic Speed Controller (ESC)

The ESC is an intermediary device that translates control signals from the FC into the appropriate power delivery for the brushless motors.

- **2.2.1 Working Principle:** An ESC is essentially a circuit that drives a three-phase brushless DC (BLDC) motor. It takes a low-voltage control signal from the FC (e.g., PWM, DShot) and a high-current DC input from the LiPo battery. Using a series of Field-Effect Transistors (FETs), the ESC rapidly switches the power flow between the three motor phases. This creates a rotating magnetic field that forces the motor's rotor to spin. The speed of this switching sequence, dictated by the FC's signal, determines the motor's Revolutions Per Minute (RPM).
- **2.2.2 Use-Cases:**
 - **Motor Speed Control:** Precisely adjusting the RPM of each motor to control thrust and torque.

- **Braking:** Some ESCs support active braking to allow for more responsive flight maneuvers.
- **Telemetry:** Advanced ESCs can send data like RPM, temperature, and current consumption back to the FC.
- **2.1.3 Advantages:**
 - **Efficiency:** Modern ESCs are highly efficient in converting battery power to motor motion.
 - **Precision:** Digital protocols like DShot provide noise-free, high-resolution control signals.
 - **Power Handling:** Available in a wide range of current ratings to match different motor and battery combinations.
- **2.1.4 Limitations:**
 - **Heat Generation:** High current flow generates significant heat, which can lead to thermal throttling or failure if not adequately cooled.
 - **Electrical Noise:** The rapid switching can introduce electromagnetic interference (EMI) that may affect other components like GPS.
- **2.1.5 Integration Challenges:**
 - **Current Rating:** Selecting an ESC with a continuous current rating higher than the motor's maximum current draw is critical to prevent overheating.
 - **Placement:** Must be placed where it can receive adequate airflow for cooling.
 - **Calibration:** For older PWM protocols, ESCs must be calibrated to the FC's throttle range.

2.3 Global Positioning System (GPS) Module

The GPS module provides absolute position data, enabling a UAV to know its location on Earth.

- **2.3.1 Working Principle:** A GPS receiver detects signals from a constellation of satellites orbiting the Earth. Each signal contains precise timing information. By calculating the time difference between when a signal is sent and when it is received, the module determines its distance from that satellite. By receiving signals from at least four satellites simultaneously, the module can calculate its 3D position (latitude, longitude, altitude) through a process called **trilateration**. Most UAV GPS modules also contain an integrated **magnetometer (compass)** to provide heading information (yaw), which is crucial for navigation.
- **2.3.2 Use-Cases:**
 - **Position Hold:** Locking the drone's geographical coordinates, allowing it to hover in place.
 - **Waypoint Navigation:** Flying along a pre-defined path of GPS coordinates.
 - **Return-to-Home (RTH):** Automatically flying back to its takeoff location.
 - **Geofencing:** Restricting the drone's operation to a specific geographical area.
- **2.3.3 Advantages:**
 - **Global Coverage:** Provides positioning data nearly anywhere on the planet's surface.
 - **Absolute Positioning:** Unlike relative sensors, it provides a fixed global reference frame.
- **2.3.4 Limitations:**

- **Signal Dependency:** Requires a clear line of sight to the sky; does not work indoors, underground, or in "urban canyons."
- **Accuracy:** Standard civilian GPS accuracy is typically within a 1-5 meter range, which can be insufficient for precision tasks.
- **Update Rate:** Typically has a low update rate (5-10 Hz), which is much slower than the drone's control loop.
- **2.3.5 Integration Challenges:**
 - **EMI Susceptibility:** The GPS receiver is highly sensitive to electromagnetic interference. It must be mounted on a mast, away from power lines, ESCs, and other sources of electrical noise.
 - **Satellite Lock:** Can take several minutes to acquire a sufficient satellite lock from a "cold start."

2.4 Onboard Computer (e.g., NVIDIA Jetson)

An onboard computer is a high-performance single-board computer (SBC) that runs a full operating system (e.g., Linux) and handles computationally intensive tasks that are beyond the capabilities of a standard FC.

- **2.4.1 Working Principle:** An onboard computer like the NVIDIA Jetson Nano or Xavier NX combines a multi-core ARM CPU with a powerful integrated Graphics Processing Unit (GPU) containing hundreds of CUDA cores. This architecture is designed for massive parallel processing, making it ideal for running modern artificial intelligence and computer vision algorithms. It interfaces with the FC (typically via a serial connection using MAVLink protocol) to send high-level commands (e.g., "move forward 2 meters") and receives state information (e.g., attitude, altitude) from the FC.
- **2.4.2 Use-Cases:**
 - **AI and Machine Learning:** Real-time object detection and classification (e.g., identifying people, vehicles).
 - **Simultaneous Localization and Mapping (SLAM):** Building a map of an unknown environment while simultaneously tracking the drone's position within it.
 - **Advanced Obstacle Avoidance:** Fusing data from multiple sensors (cameras, LiDAR) to create a 3D understanding of the environment and plan safe paths.
 - **Sensor Fusion:** Combining data from various sensors to create a more accurate and robust state estimation.
- **2.4.3 Advantages:**
 - **Massive Computational Power:** GPU acceleration enables complex, real-time data processing.
 - **Flexibility:** Runs a full Linux OS, allowing for the use of extensive software libraries (e.g., ROS, OpenCV, TensorFlow).
 - **High-Level Abstraction:** Allows developers to focus on high-level autonomy tasks without managing low-level flight dynamics.
- **2.4.4 Limitations:**
 - **Power Consumption:** Consumes significantly more power than an FC, reducing flight time.
 - **Weight and Size:** Adds considerable weight and bulk to the UAV.

- **Heat Dissipation:** Generates substantial heat, requiring active cooling solutions like fans or heatsinks.
- **2.4.5 Integration Challenges:**
 - **Power Delivery:** Requires a clean and stable power source, often from a dedicated voltage regulator (BEC).
 - **FC Communication:** Establishing a reliable, high-bandwidth communication link (e.g., MAVLink over UART) with the FC is critical.
 - **Software Complexity:** Developing, debugging, and deploying software on an embedded Linux system is significantly more complex than configuring FC firmware.

3.0 SENSORS FOR PERCEPTION AND NAVIGATION

3.1 LiDAR (Light Detection and Ranging)

LiDAR is a remote sensing method that uses light in the form of a pulsed laser to measure ranges (variable distances) to the Earth.

- **3.1.1 Working Principle:** A LiDAR unit emits thousands of laser pulses per second. These pulses bounce off objects in the environment and return to a sensor. The system measures the precise **Time of Flight (ToF)** for each pulse to return. Since the speed of light is constant, the distance to the object can be calculated as $\text{Distance} = (\text{Speed of Light} \times \text{Time of Flight}) / 2$. By mounting the laser on a rotating head (in the case of 360° LiDAR) or using an array of lasers, a 3D point cloud representing the surrounding environment is generated.
- **3.1.2 Use-Cases:**
 - **High-Precision Mapping:** Creating detailed 3D maps of terrain and structures.
 - **Robust Obstacle Avoidance:** Detecting obstacles, including thin objects like wires, with high accuracy.
 - **SLAM:** A primary sensor for LiDAR-based SLAM algorithms.
- **3.1.3 Advantages:**
 - **High Accuracy and Range:** Provides very precise distance measurements over long ranges.
 - **Lighting Immunity:** An active sensor, it works equally well in complete darkness as in bright sunlight.
 - **Direct 3D Data:** Directly provides a 3D point cloud without complex stereo reconstruction.
- **3.1.4 Limitations:**
 - **Cost and Weight:** High-performance LiDAR units are expensive and can be heavy.
 - **Environmental Susceptibility:** Performance can be degraded by atmospheric conditions like fog, rain, or dust.
 - **Surface Properties:** Can struggle with highly reflective or light-absorbent (black) surfaces.
- **3.1.5 Integration Challenges:**
 - **Data Bandwidth:** Generates a massive amount of data that requires significant processing power.
 - **Mechanical Mounting:** Spinning LiDARs have moving parts and require secure mounting with an unobstructed view.

3.2 Depth Cameras

Depth cameras are sensors that produce a per-pixel depth map of a scene, effectively adding a third dimension to a standard 2D image.

- **3.2.1 Working Principle:** There are several common types:
 - **Stereo Vision:** Uses two cameras separated by a known distance (baseline). By finding corresponding points in both images, it calculates depth through triangulation, similar to human vision.
 - **Structured Light:** Projects a known pattern of infrared light onto a scene. A camera captures the deformation of this pattern, and the distortion is used to calculate depth.
 - **Time-of-Flight (ToF):** The camera's sensor emits a pulse of infrared light and measures the time it takes for the light to bounce back to each pixel, similar to LiDAR but for a full image frame.
- **3.2.2 Use-Cases:**
 - **Indoor Navigation and Obstacle Avoidance:** Excellent for navigating complex indoor environments.
 - **3D Reconstruction:** Creating dense 3D models of objects and rooms.
 - **Gesture and Object Recognition:** Fusing depth and color data for enhanced recognition.
- **3.2.3 Advantages:**
 - **Rich Data:** Provides both visual (RGB) and depth (D) information.
 - **Cost-Effective:** Generally much cheaper than LiDAR.
 - **No Moving Parts:** Solid-state construction makes them more robust than spinning LiDARs.
- **3.2.4 Limitations:**
 - **Limited Range:** Effective range is often less than 10 meters.
 - **Sunlight Interference:** Infrared-based systems (Structured Light, ToF) can be washed out by direct sunlight.
 - **Surface Challenges:** Stereo cameras struggle with textureless surfaces like white walls, while all types can have issues with transparent or reflective objects.
- **3.2.5 Integration Challenges:**
 - **Computational Load:** Processing depth data, especially for stereo vision, is computationally intensive.
 - **USB Bandwidth:** These cameras often require a high-speed USB 3.0 connection, which can be a limitation on some onboard computers.
 - **Calibration:** Stereo cameras require precise calibration of their intrinsic and extrinsic parameters.

3.3 Optical Flow Sensors

An optical flow sensor is a specialized downward-facing camera that determines a drone's velocity relative to the ground.

- **3.3.1 Working Principle:** The sensor continuously captures low-resolution images of the ground beneath it. By comparing consecutive frames, it identifies and tracks the

movement of features (patterns, textures). The algorithm calculates a motion vector representing the direction and magnitude of pixel movement. This vector is a direct measurement of the drone's velocity over the ground (v_x, v_y). These sensors are almost always paired with a small rangefinder (ultrasonic or single-point LiDAR) to measure the distance to the ground, which is necessary to scale the pixel movement into real-world velocity (e.g., in meters/second).

- **3.3.2 Use-Cases:**

- **GPS-Denied Position Hold:** Enabling a drone to hover accurately in place indoors or when a GPS signal is unavailable.
- **Low-Altitude Flight Stability:** Providing velocity feedback to counteract drift from wind.

- **3.3.3 Advantages:**

- **Lightweight and Low Cost:** Very small, cheap, and consumes minimal power.
- **Effective GPS Replacement:** Provides crucial velocity data for stable flight in GPS-denied environments.

- **3.3.4 Limitations:**

- **Requires Texture and Light:** Does not work over uniform surfaces (e.g., calm water, white floor) or in the dark.
- **Altitude Limit:** Performance degrades with altitude, typically effective only up to 5-10 meters.
- **Relative Positioning Only:** Only provides velocity data; it cannot determine absolute position and is subject to drift over time if used for position estimation through integration.

- **3.3.5 Integration Challenges:**

- **Focal Distance:** Must be mounted at the correct height for its lens to be in focus.
- **Interface:** Connects to the FC via protocols like I2C or UART, which must be configured correctly in the firmware.

4.0 ADDITIONAL SENSORS FOR OBSTACLE DETECTION

Beyond the primary sensors, other technologies are often used, particularly for basic obstacle detection. A notable example, as suggested by resources like Oscar Liang's articles [2], is the ultrasonic sensor.

4.1 Ultrasonic Sensors (Sonar)

- **4.1.1 Working Principle:** Similar in principle to LiDAR's Time of Flight, but uses sound instead of light. The sensor emits a high-frequency sound pulse (ultrasound) and listens for the echo. By measuring the time it takes for the echo to return, and knowing the speed of sound, it calculates the distance to the nearest object in its path.
- **4.1.2 Use-Cases:**
 - **Altitude Hold (Terrain Following):** A downward-facing sonar is commonly used for precise low-altitude control.
 - **Simple Obstacle Avoidance:** Often used on consumer drones for basic detection to prevent collisions.
- **4.1.3 Advantages:**
 - **Very Low Cost:** Extremely inexpensive and simple to implement.

- **Works on Transparent Surfaces:** Can detect objects like glass that may be invisible to cameras or LiDAR.
- **4.1.4 Limitations:**
 - **Narrow Field of View:** Has a very narrow detection cone, creating significant blind spots.
 - **Short Range:** Typically limited to a range of a few meters.
 - **Surface Sensitivity:** Soft, sound-absorbing surfaces (e.g., fabric, foam) may not return a strong echo.
 - **Crosstalk:** Multiple ultrasonic sensors operating near each other can interfere.

5.0 CONCLUSION

The modern UAV is a complex system defined by the tight integration of its electronic components and sensors. The Flight Controller and ESCs form the bedrock of stable flight control, while the GPS provides the foundational capability for outdoor navigation. The inclusion of high-performance onboard computers like the NVIDIA Jetson has unlocked the potential for advanced autonomy, shifting the paradigm from pre-programmed flight to intelligent, real-time decision-making. This intelligence is fed by a suite of perception sensors. LiDAR offers unparalleled accuracy for mapping and obstacle avoidance, Depth Cameras provide rich, dense 3D data at a lower cost, and Optical Flow sensors enable stable flight when GPS is unavailable. The future of UAV development lies in the sophisticated fusion of data from these diverse sensors to create a perception system that is more robust, reliable, and capable than any single sensor could be on its own [3].

REFERENCES

- [1] R. C. Siegwart, I. R. Nourbakhsh, and D. Scaramuzza, *Introduction to Autonomous Mobile Robots*, 2nd ed. MIT Press, 2011.
- [2] O. Liang, "Choosing the Best Sensors for Drones for Obstacle Avoidance," *OscarLiang.com*, 2022. [Online]. Available: <https://oscarliang.com/sensors-drone-obstacle-avoidance/>.
- [3] S. Thrun, W. Burgard, and D. Fox, *Probabilistic Robotics*. MIT Press, 2005.