







Questions? Contact Adela Wee @ students.olin.edu

MATERIAL: Acrylic  
FINISH:

UNLESS OTHERWISE SPECIFIED:				<div></div>			
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.		PERPENDICULARITY:	 0.001" / INCH				
DIMENSIONS ARE IN INCHES.		CONCENTRICITY:	 0.002" T.I.R.				
DE-BURR AND BREAK ALL SHARP EDGES .003 MIN.		PARALLELISM:	 0.001" / INCH				
TOLERANCES ARE: X.XX = ±0.01 X.XXX = ±0.005 X.XXXX = ±0.001 ANGLES: ±0.5°		FLATNESS:	 0.001" / INCH	TITLE: 0.500" diameter spacer			
		ROUGHNESS:	125 				
NOTICE THIS DRAWING IS FOR MECH-DESIGN USE AND CAN BE REDISTRIBUTED AND REUSED AT WILL.		ENGINEER	INIT.	DATE	SIZE	DWG. NO.	REV
		DRAWN	AW	4/25/13	<b>B</b>		<b>A</b>
		CHECKED	-	-	SCALE: 1:1	DO NOT SCALE PRINT	SHEET 1 OF 1