

33.1

Copy Constructor (1)

33.1.1 Copy Constructor: ISRO-2013-75



What is the right way to declare a copy constructor of a class if the name of the class is MyClass?

- A. MyClass (constant MyClass * arg) B. MyClass (constant MyClass & arg)
C. MyClass (MyClass arg) D. MyClass (MyClass * arg)

isro2013 copy-constructor non-gatecse

Answer key

33.2

Java (1)

33.2.1 Java: ISRO CSE 2008 | Question: 43



Consider the following code segment:

```
for (int k=0; k<20; k=k+2)
{
    if (k % 3 == 1)
        system.out.print(k+ " ");
}
```

What is printed as a result of executing the code segment?

- A. 4 16 B. 4 10 16 C. 0 6 12 18 D. 1 4 7 10 13 16 19

isro2008 java

Answer key

33.3

Object Oriented Programming (7)

33.3.1 Object Oriented Programming: ISRO CSE 2009 | Question: 33



The feature in object-oriented programming that allows the same operation to be carried out differently, depending on the object, is

- A. Inheritance B. Polymorphism
C. Overfunctioning D. Overriding

isro2009 object-oriented-programming non-gatecse

Answer key

33.3.2 Object Oriented Programming: ISRO CSE 2016 | Question: 78



If a class C is derived from class B , which is derived from class A , all through public inheritance, then a class C member function can access

- A. only protected and public data of C and B B. Only protected and public data of C
C. all data of C and private data of A and B D. public and protected data of A and B and all data of C

non-gatecse object-oriented-programming isro2016

Answer key

33.3.3 Object Oriented Programming: ISRO CSE 2017 | Question: 41



What is the output of the C++ program?

```
#include <iostream>
using namespace std;

void square(int *x){
    *x = (*x)++ * (*x);
}

void square(int *x, int *y){
    *x = (*x) * --(*y);
}

int main()
{
    int number = 30;
    square(&number, &number);
    cout<<number;
    return 0;
}
```

- A. 910 B. 920 C. 870 D. 900

isro2017 object-oriented-programming

Answer key

33.3.4 Object Oriented Programming: ISRO CSE 2017 | Question: 43



Which of the following UML 2.0 diagrams capture behavioral aspects of a system?

- A. Use case diagram, Object diagram, Activity diagram and state machine diagram
B. Use case diagram, Activity diagram and state machine diagram
C. Object diagram, Communication Diagram, Timing diagram and Interaction diagram
D. Object diagram, Composite structure diagram, package diagram and Deployment diagram

isro2017 object-oriented-programming non-gatecse

Answer key

33.3.5 Object Oriented Programming: ISRO CSE 2017 | Question: 44



Which of the following is associated with objects?

- A. State B. Behavior C. Identity D. All of the above

isro2017 object-oriented-programming non-gatecse

Answer key

33.3.6 Object Oriented Programming: ISRO CSE 2018 | Question: 43



Consider the following C++ program

```
int a (int m)
{return ++m;}
int b(int&m)
{return ++m;}
int{char &m}
{return ++m;}
void main()
{
    int p = 0, q=0, r = 0;
```

```

p += a(b(p)) ;
q += b(a(q));
r += a(c(r));
cout<<p<<q << r;
}

```

Assuming the required header first are already included, the above program

- | | |
|---------------------------------|--------------|
| a. results in compilation error | b. print 123 |
| c. print 111 | d. print 322 |

isro2018 object-oriented-programming non-gatecse

Answer key 

33.3.7 Object Oriented Programming: ISRO-DEC2017-65



Which one of the following are essential features of object-oriented language?

- A. Abstraction and encapsulation
- B. Strictly-typed
- C. Type-safe property coupled with sub-type rule
- D. Polymorphism in the presence of inheritance

- | | |
|-------------------------------|--|
| A. <i>A</i> and <i>B</i> only | B. <i>A</i> , <i>D</i> and <i>B</i> only |
| C. <i>A</i> and <i>D</i> only | D. <i>A</i> , <i>C</i> and <i>D</i> only |

isrodec2017 object-oriented-programming programming-in-c is&software-engineering

Answer key 

33.4 Operator Overloading (1)

33.4.1 Operator Overloading: ISRO CSE 2017 | Question: 42



Which of the following operator(s) cannot be overloaded?

- | | |
|---|--|
| A. <i>.</i> (member Access or Dot operator) | B. <i>?:</i> (ternary or Conditional Operator) |
| C. <i>::</i> (Scope Resolution Operator) | D. All of the above |

isro2017 operator-overloading

Answer key 

33.5 Virtual Function (1)

33.5.1 Virtual Function: ISRO CSE 2008 | Question: 73



We can make a class abstract by

- A. Declaring it abstract using the virtual keyword
- B. Making at least one member function as virtual function
- C. Making at least one member function as pure virtual function
- D. Making all member function const.

isro2008 non-gatecse virtual-function

Answer key 

Answer Keys

33.1.1	B
33.3.4	B
33.5.1	C

33.2.1	B
33.3.5	D

33.3.1	B
33.3.6	A

33.3.2	D
33.3.7	C

33.3.3	C
33.4.1	D