



37.1.1 Array: UGC NET CSE | December 2014 | Part 2 | Question: 14



When an array is passed as parameter to a function, which of the following statements is correct ?

- A. The function can change values in the original array.
- B. In C, parameters are passed by value, the function cannot change the original value in the array.
- C. It results in compilation error when the function tries to access the elements in the array.
- D. Results in a run time error when the function tries to access the elements in the array.

ugcnetcse-dec2014-paper2 programming-in-c array

Answer key

37.1.2 Array: UGC NET CSE | June 2013 | Part 3 | Question: 32



Arrays in C language can have ____ with reference to memory representation.

- A. n-subscripts
- B. two-subscripts
- C. only one subscript
- D. three subscripts only

ugcnetcse-june2013-paper3 programming-in-c array

Answer key

37.2.1 Array of Pointers: UGC NET CSE | August 2016 | Part 2 | Question: 12



The following 'C' statement :

```
int * f[] ()
```

declares :

- A. A function returning a pointer to an array of integers.
- B. Array of functions returning pointers to integers.
- C. A function returning an array of pointers to integers.
- D. An illegal statement.

ugcnetcse-aug2016-paper2 programming-in-c array-of-pointers pointers

Answer key

37.3.1 Dangling Pointers: UGC NET CSE | September 2013 | Part 3 | Question: 65



Consider the following sequence of operations:

- Pointer p1 is set to point at a new heap-dynamic variable.
- Pointer p2 is assigned p1's value
- The heap dynamic variable pointed to by p1 is explicitly de-allocated but p2 is not changed by the operation

This situation leads to which of the following:

- A. p1 becomes a dangling pointer
- B. p2 becomes a dangling pointer
- C. Both p1 and p2 are now dangling pointers
- D. Neither p1 nor p2 is now a dangling pointer

ugcnetcse-sep2013-paper3 programming-in-c dangling-pointers

37.4.1 Data Types: UGC NET CSE | December 2011 | Part 2 | Question: 33

If an integer needs two bytes of storage, then the maximum value of unsigned integer is

- A. $2^{16}-1$ B. $2^{15}-1$ C. 2^{16} D. 2^{15}

ugcnetcse-dec2011-paper2 programming-in-c data-types

Answer key

37.5 Input Output Statement (1)**37.5.1 Input Output Statement: UGC NET CSE | December 2009 | Part 2 | Question: 12**

What would be the output of the following program, if run from the command line as “myprog 1 2 3” ?

```
main (int argc, char * argv[ ])
{
    int i ;

    i = argv[1] + argv[2] + argv[3] ;

    printf ("% d", i) ;

}
```

- (A) 123
(B) 6
(C) Error
(D) “123”

ugcnetcse-dec2009-paper2 programming-in-c input-output-statement

Answer key

37.6 Operator Precedence (2)**37.6.1 Operator Precedence: UGC NET CSE | December 2010 | Part 2 | Question: 12**

The value of the following expression $(13/4 * 3)$ is

- A. 5.75 B. 2.95 C. 1.4875 D. 5

ugcnetcse-dec2010-paper2 programming-in-c operator-precedence

Answer key

37.6.2 Operator Precedence: UGC NET CSE | December 2011 | Part 2 | Question: 36

$X- = Y + 1$ means

- A. $X = X - Y + 1$ B. $X = -X - Y - 1$
C. $X = -X + Y + 1$ D. $X = X - Y - 1$

ugcnetcse-dec2011-paper2 programming-in-c operator-precedence

Answer key

37.7 Operators (2)**37.7.1 Operators: UGC NET CSE | December 2012 | Part 2 | Question: 45**

What is the result of the following expression?

$(1 \& 2) + (3 \& 4)$

- A. 1 B. 3 C. 2 D. 0

ugcnetcse-dec2012-paper2 programming-in-c operators

Answer key 

37.7.2 Operators: UGC NET CSE | June 2010 | Part 2 | Question: 11



The statement print
`f(" % d", 10 ? 0 ? 5 : 1 : 12);`
will print

- A. 10 B. 0 C. 12 D. 1

ugcnetcse-june2010-paper2 programming-in-c operators

Answer key 

37.8 Parameter Passing (1)

37.8.1 Parameter Passing: UGC NET CSE | December 2012 | Part 3 | Question: 44



The Default Parameter Passing Mechanism is called as

- A. Call by Value B. Call by Reference
C. Call by Address D. Call by Name

ugcnetcse-dec2012-paper3 programming-in-c parameter-passing

Answer key 

37.9 Pointer Declaration (1)

37.9.1 Pointer Declaration: UGC NET CSE | September 2013 | Part 3 | Question: 51



Consider the following two function declarations:

`int *f()`
`int (*f)()`

Which of the following is true?

- A. Both are identical
B. The first is a correct declaration and the second is wrong
C. Both are different ways of declaring pointer to a function
D. The first declaration is a function returning a pointer to an integer and the second is a pointer to function returning integer

ugcnetcse-sep2013-paper3 programming-in-c pointer-declaration

Answer key 

37.10 Programming In C (12)

37.10.1 Programming In C: UGC NET CSE | August 2016 | Part 2 | Question: 11



Given $i = 0, j = 1, k = -1, x = 0.5, y = 0.0$

What is the output of given 'C' expression?

`x * 3 & & 3 || j | k`

- A. -1 B. 0 C. 1 D. 2

ugcnetcse-aug2016-paper2 programming-in-c

Answer key 

37.10.2 Programming In C: UGC NET CSE | December 2010 | Part 2 | Question: 11



How many of the following declarations are correct ?

`int z = 7.0;`

`double void = 0.000;`

`short array [2] = 0, 1, 2;`

`char c = "\n";`

A. None

C. Two are correct

B. One is correct

D. All four are correct

ugcnetcse-dec2010-paper2 programming-in-c

Answer key 

37.10.3 Programming In C: UGC NET CSE | December 2010 | Part 2 | Question: 13



Which one of the following will set the value of y to 5 if x has the value 3, but not otherwise ?

A. If $(x = 3)y = 5$

B. If $x == 3(y = 5)$

C. If $(x == 3); y = 5$

D. If $(x == 3)y = 5$

ugcnetcse-dec2010-paper2 programming-in-c

Answer key 

37.10.4 Programming In C: UGC NET CSE | December 2015 | Part 2 | Question: 11



Consider the following program:

```
#include<stdio.h>
main()
{
    int i, inp;
    float x, term=1, sum=0;
    scanf("%d %f", &inp, &x);
    for(i=1; i<=inp; i++)
    {
        term=term*x/i;
        sum=sum+term;
    }
    printf("Result=%f\n", sum);
}
```

The program computes the sum of which of the following series?

A. $x + x^2/2 + x^3/3 + x^4/4 + \dots$

B. $x + x^2/2! + x^3/3! + x^4/4! + \dots$

C. $1 + x^2/2 + x^3/3 + x^4/4 + \dots$

D. $1 + x^2/2! + x^3/3! + x^4/4! + \dots$

ugcnetcse-dec2015-paper2 programming-in-c

Answer key 

37.10.5 Programming In C: UGC NET CSE | December 2015 | Part 3 | Question: 43



A horn clause is

A. A clause in which no variables occur in the expression

B. A clause that has at least one negative literal

C. A disjunction of a number of literals

D. A clause that has atmost one positive literal

programming-in-c ugcnetcse-dec2015-paper3

Answer key 

37.10.6 Programming In C: UGC NET CSE | June 2007 | Part 2 | Question: 14



What is the output of the following 'C' program?

```
main()
{
    printf("%x", -1>>4);
}
```

- A. ffff B. 0fff C. 0000 D. fff0

ugcnetcse-june2007-paper2 programming-in-c

Answer key

37.10.7 Programming In C: UGC NET CSE | June 2013 | Part 3 | Question: 51



Trace the error:

```
void main()
{
    int *b, &a;
    *b=20;
    printf("%d, %d", a, *b)
}
```

- A. No error B. Logical error C. Syntax error D. Semantic error

ugcnetcse-june2013-paper3 programming-in-c

Answer key 

37.10.8 Programming In C: UGC NET CSE | October 2020 | Part 2 | Question: 9



Consider the following pseudo-code fragment, where a and b are integer variables that have been initialized:

```

/* Pre-conditions :  $(a > 1 \wedge a < b)$  */
/* Assume that overflow never occurs */
int  $x = 0$ ; int  $p = 1$ ;
while ( $p < b$ ) {
 $p = p * a$ ;
 $x = x + 1$ ;
}

```

When the while loop terminates, what will be the value of x in terms of a and b ?

- A. a^b
 B. b^a
 C. $\lfloor \log_a^b \rfloor /* \lfloor \rfloor$ means floor */
 D. $\lfloor \log_a^b \rfloor /* \lceil \rceil$ means ceil */

ugcnetcse-oct2020-paper2 programming-in-c

Answer key 

37.10.9 Programming In C: UGC NET CSE | September 2013 | Part 2 | Question: 33



What is the size of the following union? Assume that the size of int=2, size of float =4, size of char=1

```
union tag {
int a;
float b;
char c;
};
```

- A. 2 B. 4 C. 1 D. 7

Answer key **37.10.10 Programming In C: UGC NET CSE | September 2013 | Part 2 | Question: 34**

What is the output of the following program segment?

```

sum(n)
{
    if (n<1) return n;
    else return (n+sum(n-1));
}
main()
{
    printf("%d", sum(5));
}

```

A. 10

B. 16

C. 15

D. 14

Answer key **37.10.11 Programming In C: UGC NET CSE | September 2013 | Part 2 | Question: 36**

Consider the following program segment:

```

d=0;
for(i=1; i<31, ++i)
for (j=1; j < 31; ++j)
for (k=1; k < 31; ++k)
if ((i+j+k%3)==0)
d=d+1;
printf("%d", d);

```

The output will be

A. 9000

B. 3000

C. 90

D. 2700

Answer key **37.10.12 Programming In C: UGC NET CSE | September 2013 | Part 3 | Question: 53**

What is the output of the following program?

```

#include<stdio.h>
main()
{
    int a, b =0;
    static int c[10]={1, 2, 3, 4, 5, 6, 7, 8, 9, 0};
    for (a=0; a<10; ++a)
    int ((c[a]%2)==0) b+=c[a];
    printf("%d", b);
}

```

A. 15

B. 25

C. 45

D. 20

Answer key **37.11****Storage Classes In C (1)****37.11.1 Storage Classes In C: UGC NET CSE | January 2017 | Part 2 | Question: 13**

Which of the following storage classes have global visibility in C/C++?

A. Auto

B. Extern

C. Static

D. Register

37.12.1 Three Dimensional Array: UGC NET CSE | December 2015 | Part 2 | Question: 16



A three dimensional array in 'C' is declared as `int A[x][y][z]`. Here, the address of an item at the location `A[p][q][r]` can be computed as follows: (where `w` is the word length of an integer)

- A. $\&A[0][0][0] + w(y * z * q + z * p + r)$
C. $\&A[0][0][0] + w(x * y * p + z * q + r)$

- B. $\&A[0][0][0] + w(y * z * p + z * q + r)$
D. $\&A[0][0][0] + w(x * y * q + z * p + r)$

ugcnetcse-dec2015-paper2 programming-in-c three-dimensional-array

Answer Keys

37.1.1	A
37.5.1	Q-Q
37.8.1	A
37.10.4	B
37.10.9	B
37.12.1	B

37.1.2	C
37.6.1	Q-Q
37.9.1	D
37.10.5	B
37.10.10	C

37.2.1	Q-Q
37.6.2	D
37.10.1	Q-Q
37.10.6	Q-Q
37.10.11	C

37.3.1	B
37.7.1	D
37.10.2	Q-Q
37.10.7	C
37.10.12	D

37.4.1	A
37.7.2	Q-Q
37.10.3	Q-Q
37.10.8	X
37.11.1	B