

23.1.1 Computer Peripherals: ISRO CSE 2008 | Question: 44



The device which is used to connect a peripheral to bus is known as

- A. control register
- B. interface
- C. communication protocol
- D. none of these

isro2008 non-gatecse computer-peripherals

Answer key

23.1.2 Computer Peripherals: ISRO CSE 2011 | Question: 22



A system is having 8 M bytes of video memory for bit-mapped graphics with 64-bit colour. What is the maximum resolution it can support?

- A. 800×600
- B. 1024×768
- C. 1280×1024
- D. 1920×1440

isro2011 computer-peripherals

Answer key

23.1.3 Computer Peripherals: ISRO CSE 2011 | Question: 23



What is the meaning of $\overline{RD}$ signal in Intel 8151A?

- A. Read (when it is low)
- B. Read (when it is high)
- C. Write (when it is low)
- D. Read and Write (when it is high)

isro2011 non-gatecse computer-peripherals

Answer key

23.1.4 Computer Peripherals: ISRO CSE 2011 | Question: 9



What is the raw throughput of USB 2.0 technology?

- A. 480 Mbps
- B. 400 Mbps
- C. 200 Mbps
- D. 12 Mbps

isro2011 non-gatecse computer-peripherals

Answer key

23.1.5 Computer Peripherals: ISRO CSE 2017 | Question: 46



SATA is the abbreviation of

- A. Serial Advanced Technology Attachment
- B. Serial Advanced Technology Architecture
- C. Serial Advanced Technology Adapter
- D. Serial Advanced Technology Array

isro2017 computer-peripherals non-gatecse

Answer key

23.2.1 IEEE 1394: ISRO-2013-20



IEEE 1394 is related to

- A. RS – 232
- B. USB
- C. Firewire
- D. PCI

Answer Keys

23.1.1	B
23.2.1	C

23.1.2	B
--------	---

23.1.3	A
--------	---

23.1.4	A
--------	---

23.1.5	A
--------	---