High-Performance Big Data Analytics Using R

NYC Yellow Taxi Trip Records (January – June 2024)

Laboratory Assignment 8 – R Programming

Author: Swaroop Naik (@Swaroop192005)

Contents

1. Problem Statement
2. Dataset
3. Task 1 – Data Acquisition and Preparation
4. Task 2 – Transportation Data Analytics
5. Task 3 – Functional vs Vectorized vs data.table Programming
6. Task 4 – Parallel Computing (foreach + doParallel)
7. Task 5 – Performance Benchmarking and Optimization
8. Task 6 – Data Visualization (ggplot2 + leaflet)
9. Observations
10. Task 7 – Critical Analysis and Recommendation
11. Conclusion

1. Problem Statement

The New York City Taxi and Limousine Commission (NYC TLC) publishes millions of taxi-trip records every month. Each record contains pickup/drop-off timestamps and locations, passenger count, trip distance, fare, tip, tolls, payment type and the total amount charged. Processing data at this scale with conventional row-by-row R code is slow and memory hungry.

Objective: build a high-performance and scalable analytics workflow in R that

- prepares and joins ~20 million trip records with the taxi-zone lookup table using **data.table**,
- identifies travel patterns, high-demand periods, high-revenue routes, fare/distance characteristics and payment preferences,
- compares **functional programming** (`apply()` , `lapply()` , `purrr::map()`) with **vectorized** and **data.table** implementations,
- compares **sequential** and **parallel** execution (`foreach` + `doParallel`) on month-wise partitions,

- benchmarks every approach with `microbenchmark` / `system.time()` and memory measurements, and
- critically evaluates the approaches for execution time, memory, scalability and readability.

2. Dataset

Item	Description
Source	NYC TLC Trip Record Data – https://www.nyc.gov/site/tlc/about/tlc-trip-record-data.page
Trip files	Yellow Taxi Trip Records, **January – June 2024** (6 monthly Parquet files, ≈ 20 million trips)
Lookup table	Taxi Zone Lookup Table (`taxi_zone_lookup.csv` , 265 zones) + Taxi Zone shapefile (for the map)

Main attributes used:

Column	Meaning
`tpep_pickup_datetime` , `tpep_dropoff_datetime`	Pickup / drop-off date and time
`PULocationID` , `DOLocationID`	TLC taxi-zone IDs of pickup / drop-off
`passenger_count`	Number of passengers
`trip_distance`	Trip distance in miles
`payment_type`	1 = Credit card, 2 = Cash, 3 = No charge, 4 = Dispute, 0 = Flex fare / unknown
`fare_amount` , `tip_amount` , `tolls_amount` , `total_amount`	Monetary amounts in USD

Six months were chosen because they give a sufficiently large dataset (≈ 3 million rows per month) so that the performance differences between conventional, optimized, sequential and parallel implementations are clearly visible, while still fitting in the memory of a normal laptop. Change `MONTHS` in the next cell to use fewer months on a machine with less than 8 GB RAM.

2.1 Environment setup

Install (if needed) and load the packages. `TZ = "UTC"` is set so that the timestamps, which the TLC stores as New York local time without a time zone, are kept exactly as recorded.

In [1]:
```
required <- c("data.table", "arrow", "ggplot2", "foreach", "doParallel",
"microbenchmark",
              "purrr", "lubridate", "scales", "hexbin", "leaflet",
"htmlwidgets", "sf")
missing_pkgs <- required[!vapply(required, requireNamespace, logical(1),
quietly = TRUE)]
```

```
if (length(missing_pkgs) > 0) install.packages(missing_pkgs, repos =
"https://cloud.r-project.org")

Sys.setenv(TZ = "UTC")
Sys.setenv(ARROW_DEFAULT_MEMORY_POOL = "system")   # let arrow return
memory to the OS after import
suppressPackageStartupMessages({
  library(data.table)
  library(arrow)
  library(ggplot2)
  library(foreach)
  library(doParallel)
  library(microbenchmark)
  library(purrr)
  library(lubridate)
  library(scales)
})

set.seed(2024)
options(repr.plot.width = 12, repr.plot.height = 6, scipen = 999, width =
140)

MONTHS   <- sprintf("2024-%02d", 1:6)        # analysis period: Jan - Jun
2024
DATA_DIR <- "data"
OUT_DIR  <- "outputs"
FIG_DIR  <- file.path(OUT_DIR, "figures")
for (d in c(DATA_DIR, FIG_DIR)) dir.create(d, showWarnings = FALSE,
recursive = TRUE)

N_CORES <- max(1L, parallel::detectCores() - 1L)   # keep one core free
for the OS

cat("R version          :", R.version.string, "\n")
cat("data.table version :", as.character(packageVersion("data.table")),
"\n")
cat("Logical cores      :", parallel::detectCores(), "| cores used for
parallel work:", N_CORES, "\n")
cat("data.table threads :", getDTthreads(), "\n")
```

```
R version          : R version 4.6.1 (2026-06-24)
data.table version : 1.18.6.1
Logical cores      : 4 | cores used for parallel work: 3
data.table threads : 2
```

2.2 Helper functions

- `peak_mem_mb()` – peak extra memory (MB) used by R while evaluating an expression, measured with `gc()`.
- `save_plot()` – saves a ggplot to `outputs/figures/` and returns it so it is also shown in the notebook.

In [2]:
```
peak_mem_mb <- function(expr) {
  invisible(gc(reset = TRUE))
  before <- sum(gc()[, 2])                  # MB in use now
  force(expr)
  peak <- sum(gc()[, 6])                    # max MB used since reset
  round(peak - before, 1)
}
```

```
save_plot <- function(p, name, width = 11, height = 6) {
  ggsave(file.path(FIG_DIR, paste0(name, ".png")), p, width = width,
height = height, dpi = 120, bg = "white")
  p
}

theme_set(theme_minimal(base_size = 13) +
          theme(plot.title = element_text(face = "bold"), legend.position
= "bottom"))
```

2.3 Download the data

Files are downloaded once from the official TLC CloudFront location and re-used afterwards (the `data/` folder is not committed to Git).

In [3]:
```
options(timeout = 3600)
base_url   <- "https://d37ci6vzurychx.cloudfront.net"
trip_files <- file.path(DATA_DIR, sprintf("yellow_tripdata_%s.parquet",
MONTHS))

for (i in seq_along(MONTHS)) {
  if (!file.exists(trip_files[i])) {
    download.file(sprintf("%s/trip-data/yellow_tripdata_%s.parquet",
base_url, MONTHS[i]),
                  trip_files[i], mode = "wb")
  }
}
zone_file <- file.path(DATA_DIR, "taxi_zone_lookup.csv")
if (!file.exists(zone_file)) download.file(paste0(base_url,
"/misc/taxi_zone_lookup.csv"), zone_file, mode = "wb")
shape_zip <- file.path(DATA_DIR, "taxi_zones.zip")
if (!file.exists(shape_zip)) download.file(paste0(base_url,
"/misc/taxi_zones.zip"), shape_zip, mode = "wb")

data.table(file = basename(c(trip_files, zone_file, shape_zip)),
           size_MB = round(file.size(c(trip_files, zone_file, shape_zip))
/ 2^20, 1))
```

A data.table: 8 × 2

file	size_MB
<chr>	<dbl>
yellow_tripdata_2024-01.parquet	47.6
yellow_tripdata_2024-02.parquet	48.0
yellow_tripdata_2024-03.parquet	57.3
yellow_tripdata_2024-04.parquet	56.4
yellow_tripdata_2024-05.parquet	59.7
yellow_tripdata_2024-06.parquet	57.1
taxi_zone_lookup.csv	0.0
taxi_zones.zip	1.0

3. Task 1 – Data Acquisition and Preparation

3.1 Import the trip records

`arrow::open_dataset()` treats the six Parquet files as one dataset; `as.data.frame()` reads it in a single pass and `setDT()` converts the result to a `data.table` **by reference** (no extra copy).

In [4]:
```
t_import <- system.time({
  trips <- setDT(as.data.frame(open_dataset(trip_files, unify_schemas =
TRUE)))
})
cat(sprintf("Imported %s rows x %d columns in %.1f s\n",
            format(nrow(trips), big.mark = ","), ncol(trips),
t_import[["elapsed"]]))
raw_size <- object.size(trips)
cat("Memory used by raw table:", format(raw_size, units = "auto"), "\n")
```

```
Imported 20,332,093 rows x 19 columns in 22.2 s
Memory used by raw table: 2.4 Gb
```

3.2 Inspect structure, dimensions, data types and summary statistics

In [5]:
```
dim(trips)
str(trips)
```

20332093 · 19

```
Classes ‘data.table’ and 'data.frame':  20332093 obs. of  19 variables:
 $ VendorID             : int  2 1 1 1 1 1 2 1 2 2 ...
 $ tpep_pickup_datetime : POSIXct, format: "2024-01-01 00:57:55" "2024-01-01 00:03:00" "2024-01-01
00:17:06" "2024-01-01 00:36:38" ...
 $ tpep_dropoff_datetime: POSIXct, format: "2024-01-01 01:17:43" "2024-01-01 00:09:36" "2024-01-01
00:35:01" "2024-01-01 00:44:56" ...
 $ passenger_count      : int  1 1 1 1 1 1 2 0 1 1 ...
 $ trip_distance        : num  1.72 1.8 4.7 1.4 0.8 ...
 $ RatecodeID           : int  1 1 1 1 1 1 1 1 1 1 ...
 $ store_and_fwd_flag   : chr  "N" "N" "N" "N" ...
 $ PULocationID         : int  186 140 236 79 211 148 138 246 161 113 ...
 $ DOLocationID         : int  79 236 79 211 148 141 181 231 261 113 ...
 $ payment_type         : int  2 1 1 1 1 1 1 2 2 2 ...
 $ fare_amount          : num  17.7 10 23.3 10 7.9 29.6 45.7 25.4 31 3 ...
 $ extra                : num  1 3.5 3.5 3.5 3.5 3.5 6 3.5 1 1 ...
 $ mta_tax              : num  0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 ...
 $ tip_amount           : num  0 3.75 3 2 3.2 6.9 10 0 0 0 ...
 $ tolls_amount         : num  0 0 0 0 0 0 0 0 0 0 ...
 $ improvement_surcharge: num  1 1 1 1 1 1 1 1 1 1 ...
 $ total_amount         : num  22.7 18.8 31.3 17 16.1 ...
 $ congestion_surcharge : num  2.5 2.5 2.5 2.5 2.5 2.5 0 2.5 2.5 2.5 ...
 $ Airport_fee          : num  0 0 0 0 0 0 1.75 0 0 0 ...
 - attr(*, ".internal.selfref")=<pointer: 0x55da0724f480>
```

In [6]:
```
num_cols <- names(trips)[vapply(trips, is.numeric, logical(1))]
stats <- rbindlist(lapply(num_cols, function(cn) {
  x <- trips[[cn]]
  data.table(column = cn, min = min(x, na.rm = TRUE), mean = mean(x, na.rm
= TRUE),
             median = median(x, na.rm = TRUE), max = max(x, na.rm = TRUE),
missing = sum(is.na(x)))
}))
stats[, (2:5) := lapply(.SD, round, 2), .SDcols = 2:5]
stats
cat("Pickup time range:", format(range(trips$tpep_pickup_datetime)), "\n")
```

A data.table: 16 × 6

column	min	mean	median	max	missing
<chr>	<dbl>	<dbl>	<dbl>	<dbl>	<int>
VendorID	1.00	1.76	2.00	6.00	0
passenger_count	0.00	1.33	1.00	9.00	1975985
trip_distance	0.00	4.70	1.75	312722.30	0
RatecodeID	1.00	2.23	1.00	99.00	1975985
PULocationID	1.00	164.80	162.00	265.00	0
DOLocationID	1.00	163.90	162.00	265.00	0
payment_type	0.00	1.10	1.00	5.00	0
fare_amount	-1285.40	18.89	13.50	334076.32	0
extra	-7.50	1.41	1.00	65.99	0
mta_tax	-0.50	0.48	0.50	35.84	0
tip_amount	-300.00	3.27	2.60	999.99	0
tolls_amount	-117.26	0.55	0.00	1702.88	0
improvement_surcharge	-1.00	0.97	1.00	1.00	0
total_amount	-1315.97	27.44	20.64	334145.30	0
congestion_surcharge	-2.50	2.25	2.50	2.52	1975985
Airport_fee	-1.75	0.14	0.00	1.75	1975985

```
Pickup time range: 2002-12-31 16:46:07 2026-06-26 23:53:12
```

3.3 Missing, duplicate, inconsistent and invalid records

First we count missing values per column.

In [7]:
```
na_counts <- trips[, lapply(.SD, function(x) sum(is.na(x)))]
na_counts <- melt(na_counts, measure.vars = names(na_counts),
variable.name = "column", value.name = "missing")
na_counts[, pct := round(100 * missing / nrow(trips), 2)]
na_counts[missing > 0]
# Rows with missing passenger_count also miss RatecodeID /
store_and_fwd_flag and have payment_type 0
trips[is.na(passenger_count), .N, by = payment_type]
```

A data.table: 5 × 3

column	missing	pct
<fct>	<int>	<dbl>
passenger_count	1975985	9.72
RatecodeID	1975985	9.72
store_and_fwd_flag	1975985	9.72
congestion_surcharge	1975985	9.72
Airport_fee	1975985	9.72

A data.table: 1 × 2

payment_type	N
<int>	<int>
0	1975985

Cleaning rules (each step is logged):

Problem	Rule	Action
Duplicates	identical vendor, timestamps, locations, distance and amount	remove
Out-of-period records	pickup outside 1 Jan – 30 Jun 2024 (wrong meter clocks)	remove
Missing `passenger_count` / `RatecodeID`	≈ 10 % of rows (flex-fare / app trips)	**impute** passenger count with the median (1), RatecodeID with 99 = unknown
Zero passengers	inconsistent with a paid trip	impute with median (1)
Non-positive or extreme amounts	fare ≤ 0 or > 500 USD, total ≤ 0, negative tip/tolls	remove (refunds, voids, typos)
Invalid distance	distance ≤ 0 or > 100 miles	remove
Invalid duration	drop-off not after pickup or trip longer than 3 hours	remove
Impossible speed	average speed > 80 mph	remove
Invalid zone IDs	outside 1–265	remove

In [8]:
```r
# Memory-efficient cleaning: every rule only updates one logical "keep"
vector (80 MB for 20M rows)
# and the large table is subset ONCE at the end, instead of being copied
after every rule.
n_raw     <- nrow(trips)
keep      <- rep(TRUE, n_raw)
clean_log <- data.table(step = "Raw records", removed = 0L)
apply_rule <- function(step, ok) {
  ok[is.na(ok)] <- FALSE
  clean_log <<- rbind(clean_log, data.table(step = step, removed =
```

```r
sum(keep & !ok)))
  keep <<- keep & ok
}

# trip duration in minutes (vectorized, added by reference)
trips[, trip_duration_min := as.numeric(tpep_dropoff_datetime -
tpep_pickup_datetime, units = "mins")]

period_start <- as.POSIXct("2024-01-01 00:00:00", tz = "UTC")
period_end   <- as.POSIXct("2024-07-01 00:00:00", tz = "UTC")

apply_rule("Remove duplicate trips", !duplicated(trips, by = c("VendorID",
"tpep_pickup_datetime", "tpep_dropoff_datetime",

"PULocationID", "DOLocationID", "trip_distance", "total_amount")))
apply_rule("Remove pickups outside Jan-Jun 2024", trips[,
tpep_pickup_datetime >= period_start & tpep_pickup_datetime < period_end])
apply_rule("Remove invalid fare / total / tip / tolls",
           trips[, fare_amount > 0 & fare_amount <= 500 & total_amount > 0
& tip_amount >= 0 & tolls_amount >= 0])
apply_rule("Remove invalid trip distance", trips[, trip_distance > 0 &
trip_distance <= 100])
apply_rule("Remove invalid trip duration", trips[, trip_duration_min > 0 &
trip_duration_min <= 180])
apply_rule("Remove speed > 80 mph", trips[, trip_distance /
(trip_duration_min / 60) <= 80])
apply_rule("Remove invalid zone IDs", trips[, PULocationID %between% c(1L,
265L) & DOLocationID %between% c(1L, 265L)])

trips <- trips[keep]          # the only copy of the large table
rm(keep); invisible(gc())

# impute missing / zero passenger count and missing rate code (update by
reference)
n_pass_fixed <- trips[is.na(passenger_count) | passenger_count == 0, .N]
trips[is.na(passenger_count) | passenger_count == 0, passenger_count :=
1L]
trips[is.na(RatecodeID), RatecodeID := 99L]
cat("Passenger count imputed for", format(n_pass_fixed, big.mark = ","),
"rows\n")

clean_log[, rows_left := n_raw - cumsum(removed)]
clean_log[, pct_of_raw := round(100 * rows_left / n_raw, 2)]
clean_log
```

```
Passenger count imputed for 2,001,287 rows
```

A data.table: 8 × 4

step	removed	rows_left	pct_of_raw
<chr>	<int>	<int>	<dbl>
Raw records	0	20332093	100.00
Remove duplicate trips	1	20332092	100.00
Remove pickups outside Jan-Jun 2024	39	20332053	100.00
Remove invalid fare / total / tip / tolls	324323	20007730	98.40
Remove invalid trip distance	338584	19669146	96.74
Remove invalid trip duration	13090	19656056	96.68
Remove speed > 80 mph	5840	19650216	96.65
Remove invalid zone IDs	0	19650216	96.65

3.4 Convert attributes into appropriate data types

Integer codes become labelled **factors** (stored as integers + labels – memory efficient and readable).

In [9]:
```
payment_labels <- c("0" = "Flex/Unknown", "1" = "Credit card", "2" =
"Cash",
                    "3" = "No charge", "4" = "Dispute", "5" = "Unknown",
"6" = "Voided")
rate_labels <- c("1" = "Standard", "2" = "JFK", "3" = "Newark", "4" =
"Nassau/Westchester",
                 "5" = "Negotiated", "6" = "Group ride", "99" = "Unknown")

trips[, payment_type := factor(payment_labels[as.character(payment_type)],
                               levels = c("Credit card", "Cash",
"Flex/Unknown", "Dispute", "No charge", "Unknown", "Voided"))]
trips[, RatecodeID := factor(rate_labels[as.character(RatecodeID)], levels
= unique(rate_labels))]
trips[, passenger_count := as.integer(passenger_count)]
trips[, `:=`(PULocationID = as.integer(PULocationID), DOLocationID =
as.integer(DOLocationID))]
sapply(trips[, .(payment_type, RatecodeID, passenger_count, PULocationID,
trip_distance)], class)
```

payment_type: 'factor' **RatecodeID:** 'factor' **passenger_count:** 'integer' **PULocationID:** 'integer' **trip_distance:** 'numeric'

3.5 Extract temporal attributes

Hour, day of month, day of week (Monday first), month, date and a weekend flag. data.table's `hour()`, `mday()`, `wday()` and `month()` are fast vectorized C implementations.

In [10]:
```
wday_labels <- c("Mon", "Tue", "Wed", "Thu", "Fri", "Sat", "Sun")
t_time <- system.time({
  trips[, `:=`(
    pickup_date  = as.IDate(tpep_pickup_datetime),
```

```
    pickup_hour  = hour(tpep_pickup_datetime),
    pickup_day   = mday(tpep_pickup_datetime),
    pickup_wday  = factor((wday(tpep_pickup_datetime) + 5L) %% 7L + 1L,
levels = 1:7, labels = wday_labels),
    month        = factor(month(tpep_pickup_datetime), levels = 1:6,
labels = month.abb[1:6])
  )]
  trips[, is_weekend := pickup_wday %in% c("Sat", "Sun")]
  trips[, time_period := cut(pickup_hour, breaks = c(-1, 5, 9, 15, 19,
23),
                             labels = c("Early morning (0-5)", "Morning
rush (6-9)", "Midday (10-15)",
                                        "Evening rush (16-19)", "Night (20-
23)"))]
})
cat("Temporal features created in", t_time[["elapsed"]], "s\n")
head(trips[, .(tpep_pickup_datetime, pickup_date, pickup_hour, pickup_day,
pickup_wday, month, is_weekend, time_period)])
```

```
Temporal features created in 42.951 s
```

A data.table: 6 × 8

tpep_pickup_datetime	pickup_date	pickup_hour	pickup_day	pickup_wday	month	is_w
<dttm>	<IDate>	<int>	<int>	<fct>	<fct>	
2024-01-01 00:57:55	2024-01-01	0	1	Mon	Jan	
2024-01-01 00:03:00	2024-01-01	0	1	Mon	Jan	
2024-01-01 00:17:06	2024-01-01	0	1	Mon	Jan	
2024-01-01 00:36:38	2024-01-01	0	1	Mon	Jan	
2024-01-01 00:46:51	2024-01-01	0	1	Mon	Jan	
2024-01-01 00:54:08	2024-01-01	0	1	Mon	Jan	

3.6 Remove unnecessary attributes to reduce memory

Surcharges and technical flags are not needed for the analysis. Columns are dropped **by reference** (`:= NULL`), which does not copy the table.

In [11]:
```
size_before <- object.size(trips)
drop_cols <- intersect(c("VendorID", "store_and_fwd_flag", "extra",
"mta_tax", "improvement_surcharge",
                         "congestion_surcharge", "Airport_fee",
"airport_fee"), names(trips))
trips[, (drop_cols) := NULL]
size_after <- object.size(trips)
```

```
invisible(gc())
data.table(stage = c("Raw import", "After cleaning + new features", "After
dropping columns"),
           columns = c(19, ncol(trips) + length(drop_cols), ncol(trips)),
           size = c(format(raw_size, units = "MB"), format(size_before,
units = "MB"), format(size_after, units = "MB")))
```

A data.table: 3 × 3

stage	columns	size
<chr>	<dbl>	<chr>
Raw import	19	2482 Mb
After cleaning + new features	27	3073.4 Mb
After dropping columns	20	2098.9 Mb

3.7 Import the Taxi Zone Lookup Table

In [12]:
```
zones <- fread(zone_file)
setkey(zones, LocationID)
cat("Zones:", nrow(zones), "\n")
zones[, .N, by = Borough][order(-N)]
head(zones)
```

```
Zones: 265
```

A data.table: 8 × 2

Borough	N
<chr>	<int>
Queens	69
Manhattan	69
Brooklyn	61
Bronx	43
Staten Island	20
EWR	1
Unknown	1
N/A	1

A data.table: 6 × 4

LocationID	Borough	Zone	service_zone
<int>	<chr>	<chr>	<chr>
1	EWR	Newark Airport	EWR
2	Queens	Jamaica Bay	Boro Zone
3	Bronx	Allerton/Pelham Gardens	Boro Zone
4	Manhattan	Alphabet City	Yellow Zone
5	Staten Island	Arden Heights	Boro Zone
6	Staten Island	Arrochar/Fort Wadsworth	Boro Zone

3.8 Join trips with zone information

An **update join** (`X[Y, on = , := ]`) adds pickup and drop-off borough/zone to the 20 million rows by reference – no copy of the large table is created (a `merge()` would copy it twice).

In [13]:
```
t_join <- system.time({
  trips[zones, on = .(PULocationID = LocationID), `:=`(pu_borough =
i.Borough, pu_zone = i.Zone)]
  trips[zones, on = .(DOLocationID = LocationID), `:=`(do_borough =
i.Borough, do_zone = i.Zone)]
  # repeated strings -> factors to save memory
  for (col in c("pu_borough", "pu_zone", "do_borough", "do_zone"))
set(trips, j = col, value = factor(trips[[col]]))
})
cat("Two update joins on", format(nrow(trips), big.mark = ","), "rows
took", t_join[["elapsed"]], "s\n")
setkey(trips, tpep_pickup_datetime)
trips[, .(trips = .N), by = pu_borough][order(-trips)]
```

```
Two update joins on 19,650,216 rows took 16.342 s
```

A data.table: 8 × 2

pu_borough	trips
<fct>	<int>
Manhattan	17574156
Queens	1723780
Brooklyn	234405
Unknown	60625
Bronx	52261
N/A	4009
Staten Island	520
EWR	460

3.9 Final prepared dataset

In [14]:
```
str(trips)
cat(sprintf("\nFinal dataset: %s trips (%.1f %% of raw records kept), %s
in memory\n",
            format(nrow(trips), big.mark = ","), 100 * nrow(trips) /
n_raw,
            format(object.size(trips), units = "auto")))
```

```
Classes ‘data.table’ and 'data.frame':  19650216 obs. of  24 variables:
 $ tpep_pickup_datetime : POSIXct, format: "2024-01-01 00:00:00" "2024-01-01 00:00:02" "2024-01-01
00:00:03" "2024-01-01 00:00:04" ...
 $ tpep_dropoff_datetime: POSIXct, format: "2024-01-01 00:02:49" "2024-01-01 00:04:36" "2024-01-01
00:03:16" "2024-01-01 00:22:32" ...
 $ passenger_count      : int  1 2 1 1 2 1 1 1 1 1 ...
 $ trip_distance        : num  0.3 1.57 0.5 7.37 18.85 ...
 $ RatecodeID           : Factor w/ 7 levels "Standard","JFK",..: 1 1 1 1 2 4 1 1 1 1 ...
 $ PULocationID         : int  140 161 136 125 132 234 229 113 161 162 ...
 $ DOLocationID         : int  140 236 18 157 41 265 181 234 75 236 ...
 $ payment_type         : Factor w/ 7 levels "Credit card",..: 1 1 2 2 1 2 1 1 1 1 ...
 $ fare_amount          : num  4.4 8.6 5.1 33.8 70 81.4 38 16.3 12.1 14.9 ...
 $ tip_amount           : num  1.85 2.72 0 0 15.69 ...
 $ tolls_amount         : num  0 0 0 0 6.94 ...
 $ total_amount         : num  11.2 16.3 7.6 38.8 95.9 ...
 $ trip_duration_min    : num  2.82 4.57 3.22 22.47 26.65 ...
 $ pickup_date          : IDate, format: "2024-01-01" "2024-01-01" "2024-01-01" "2024-01-01" ...
 $ pickup_hour          : int  0 0 0 0 0 0 0 0 0 0 ...
 $ pickup_day           : int  1 1 1 1 1 1 1 1 1 1 ...
 $ pickup_wday          : Factor w/ 7 levels "Mon","Tue","Wed",..: 1 1 1 1 1 1 1 1 1 1 ...
 $ month                : Factor w/ 6 levels "Jan","Feb","Mar",..: 1 1 1 1 1 1 1 1 1 1 ...
 $ is_weekend           : logi  FALSE FALSE FALSE FALSE FALSE FALSE ...
 $ time_period          : Factor w/ 5 levels "Early morning (0-5)",..: 1 1 1 1 1 1 1 1 1 1 ...
 $ pu_borough           : Factor w/ 8 levels "Bronx","Brooklyn",..: 4 4 1 4 6 4 4 4 4 4 ...
 $ pu_zone              : Factor w/ 260 levels "Allerton/Pelham Gardens",..: 134 155 130 118 122 231 226
106 155 156 ...
 $ do_borough           : Factor w/ 8 levels "Bronx","Brooklyn",..: 4 4 1 6 4 5 2 4 4 4 ...
 $ do_zone              : Factor w/ 260 levels "Allerton/Pelham Gardens",..: 135 233 16 152 39 177 179
231 72 233 ...
 - attr(*, ".internal.selfref")=<pointer: 0x55da0724f480>
 - attr(*, "sorted")= chr "tpep_pickup_datetime"
Final dataset: 19,650,216 trips (96.6 % of raw records kept), 2.3 Gb in memory
```

Interpretation: after removing duplicates, out-of-period, invalid and implausible records about 97 % of the raw records remain, so the cleaning removes noise without biasing the dataset. Converting codes to factors and dropping unused columns reduces the memory footprint, and every expensive step (feature creation, imputation, joins) was done **by reference** with data.table, which avoids copying a multi-gigabyte table.

---

4. Task 2 – Transportation Data Analytics

All aggregations use data.table's `DT[i, j, by]` syntax.

4.1 Number of taxi trips by hour of day

In [15]:
```
hourly <- trips[, .(trips = .N, avg_fare = mean(fare_amount), avg_total =
mean(total_amount)), by = pickup_hour][order(pickup_hour)]
hourly[, share_pct := round(100 * trips / sum(trips), 2)]
hourly
cat("Peak hour:", hourly[which.max(trips), pickup_hour], ":00 with",
format(max(hourly$trips), big.mark = ","), "trips\n")
cat("Quietest hour:", hourly[which.min(trips), pickup_hour], ":00 with",
format(min(hourly$trips), big.mark = ","), "trips\n")
```

A data.table: 24 × 5

pickup_hour	trips	avg_fare	avg_total	share_pct
<int>	<int>	<dbl>	<dbl>	<dbl>
0	561076	19.75567	28.25432	2.86
1	363176	17.72769	25.63441	1.85
2	235892	16.58758	24.23721	1.20
3	155337	17.78036	25.60346	0.79
4	111660	23.06086	31.63272	0.57
5	120201	26.86042	36.74176	0.61
6	272913	22.64153	30.85086	1.39
7	546596	19.39535	27.13617	2.78
8	757665	18.58747	26.21087	3.86
9	829123	18.52194	26.41832	4.22
10	882863	18.79553	26.90593	4.49
11	956840	18.86350	26.90027	4.87
12	1047428	19.17166	27.27790	5.33
13	1086352	19.96273	28.29526	5.53
14	1166101	20.67340	29.22118	5.93
15	1196675	20.64434	29.16584	6.09
16	1213118	20.61005	30.96470	6.17
17	1338016	19.24176	29.19176	6.81
18	1408831	18.07551	27.78585	7.17
19	1236569	18.22104	27.97929	6.29
20	1116640	18.34523	27.28326	5.68
21	1149071	18.47963	27.30065	5.85
22	1072132	19.25034	28.00551	5.46
23	825941	20.38919	29.23294	4.20

```
Peak hour: 18 :00 with 1,408,831 trips
Quietest hour: 4 :00 with 111,660 trips
```

4.2 Taxi demand across days of the week

Because a six-month period does not contain the same number of Mondays, Tuesdays … , demand is also normalised as **average trips per day**.

In [16]:
```
dow <- trips[, .(trips = .N, days = uniqueN(pickup_date), avg_fare =
round(mean(fare_amount), 2),
                 avg_distance = round(mean(trip_distance), 2)), by =
pickup_wday][order(pickup_wday)]
dow[, avg_trips_per_day := round(trips / days)]
```

```
dow
dow_hour <- trips[, .N, by = .(is_weekend, pickup_hour)]
dow_hour[, days := ifelse(is_weekend, trips[is_weekend == TRUE,
uniqueN(pickup_date)], trips[is_weekend == FALSE, uniqueN(pickup_date)])]
dow_hour[, trips_per_day := N / days]
dcast(dow_hour, pickup_hour ~ ifelse(is_weekend, "weekend", "weekday"),
value.var = "trips_per_day")[, lapply(.SD, round)]
```

A data.table: 7 × 6

pickup_wday	trips	days	avg_fare	avg_distance	avg_trips_per_day
<fct>	<int>	<int>	<dbl>	<dbl>	<dbl>
Mon	2351136	26	20.07	3.73	90428
Tue	2755577	26	19.20	3.27	105984
Wed	2963594	26	19.19	3.20	113984
Thu	3159268	26	19.53	3.27	121510
Fri	2938155	26	19.12	3.30	113006
Sat	2993326	26	18.23	3.12	115128
Sun	2489160	26	20.07	3.77	95737

A data.table: 24 × 3

pickup_hour	weekday	weekend
<dbl>	<dbl>	<dbl>
0	1949	5918
1	923	4678
2	508	3266
3	339	2139
4	372	1218
5	709	539
6	1760	848
7	3686	1296
8	5009	2048
9	5094	3210
10	5074	4293
11	5312	5122
12	5714	5858
13	5889	6169
14	6480	6226
15	6709	6241
16	6739	6481
17	7648	6611
18	8191	6617
19	7074	6094
20	6478	5279
21	6750	5223
22	6154	5233
23	4423	4826

4.3 Monthly variation in taxi usage

In [17]:
```
monthly <- trips[, .(trips = .N, days = uniqueN(pickup_date), revenue_musd
= round(sum(total_amount) / 1e6, 2),
                     avg_fare = round(mean(fare_amount), 2), avg_distance
= round(mean(trip_distance), 2),
                     avg_duration_min = round(mean(trip_duration_min),
1)), by = month][order(month)]
monthly[, trips_per_day := round(trips / days)]
monthly[, change_vs_prev_pct := round(100 * (trips_per_day /
shift(trips_per_day) - 1), 1)]
monthly
```

A data.table: 6 × 9

month	trips	days	revenue_musd	avg_fare	avg_distance	avg_duration_min	trips_
<fct>	<int>	<int>	<dbl>	<dbl>	<dbl>	<dbl>	
Jan	2866574	31	78.33	18.48	3.29	15.0	
Feb	2898586	29	78.90	18.40	3.22	15.4	
Mar	3436527	31	95.70	19.14	3.36	16.1	
Apr	3410774	30	96.10	19.44	3.39	16.4	
May	3612954	31	104.74	20.13	3.43	17.5	
Jun	3424801	30	98.20	19.93	3.42	17.0	

4.4 Average fare and total revenue for different time periods

In [18]:
```
period_stats <- trips[, .(trips = .N, avg_fare = round(mean(fare_amount),
2), avg_total = round(mean(total_amount), 2),
                          avg_distance = round(mean(trip_distance), 2),
revenue_musd = round(sum(total_amount) / 1e6, 2)),
                       by = time_period][order(time_period)]
period_stats[, revenue_share_pct := round(100 * revenue_musd /
sum(revenue_musd), 1)]
period_stats
trips[, .(trips = .N, avg_fare = round(mean(fare_amount), 2), avg_total =
round(mean(total_amount), 2),
          revenue_musd = round(sum(total_amount) / 1e6, 2)), by = .
(day_type = ifelse(is_weekend, "Weekend", "Weekday"))]
```

A data.table: 5 × 7

time_period	trips	avg_fare	avg_total	avg_distance	revenue_musd	revenue_share_
<fct>	<int>	<dbl>	<dbl>	<dbl>	<dbl>	<dl
Early morning (0-5)	1547342	19.39	27.66	3.79	42.81	
Morning rush (6-9)	2406297	19.21	27.02	3.45	65.02	1
Midday (10-15)	6336259	19.76	28.06	3.29	177.78	3
Evening rush (16-19)	5196534	19.00	28.94	3.15	150.37	2
Night (20-23)	4163784	19.02	27.86	3.51	116.01	2

A data.table: 2 × 5

day_type	trips	avg_fare	avg_total	revenue_musd
<chr>	<int>	<dbl>	<dbl>	<dbl>
Weekday	14167730	19.40	28.46	403.17
Weekend	5482486	19.07	27.14	148.81

4.5 Most frequently travelled pickup – drop-off routes

In [19]:
```
routes <- trips[, .(trips = .N, avg_fare = mean(fare_amount), avg_distance
= mean(trip_distance),
                    revenue = sum(total_amount)), by = .(pu_zone,
do_zone)]
top_routes <- routes[order(-trips)][1:15]
top_routes[, `:=`(avg_fare = round(avg_fare, 2), avg_distance =
round(avg_distance, 2), revenue_kusd = round(revenue / 1e3))][, revenue :=
NULL]
top_routes
cat("Distinct routes observed:", format(nrow(routes), big.mark = ","),
"\n")
cat("Share of trips starting and ending in the same zone:",
    round(100 * trips[PULocationID == DOLocationID, .N] / nrow(trips), 2),
"%\n")
```

A data.table: 15 × 6

pu_zone	do_zone	trips	avg_fare	avg_distance	revenue_kusd
<fct>	<fct>	<int>	<dbl>	<dbl>	<dbl>
Upper East Side South	Upper East Side North	137973	8.87	1.06	2169
Upper East Side North	Upper East Side South	120122	9.37	1.04	1937
Upper East Side North	Upper East Side North	92602	6.87	0.64	1228
Upper East Side South	Upper East Side South	89270	7.47	0.65	1244
Midtown Center	Upper East Side South	65481	10.12	1.07	1132
Upper East Side South	Midtown Center	57371	10.36	1.06	983
Midtown Center	Upper East Side North	55540	14.14	1.94	1225
Upper West Side South	Lincoln Square East	53721	7.92	0.89	783
Lincoln Square East	Upper West Side South	53093	8.11	1.00	796
Upper East Side South	Midtown East	51072	9.56	0.99	833
Upper West Side South	Upper West Side North	50263	7.26	0.84	697
Lenox Hill West	Upper East Side North	46049	9.09	1.09	726
Upper East Side North	Midtown Center	45924	14.88	1.93	1013
JFK Airport	Times Sq/Theatre District	43128	70.40	17.99	4067
Upper West Side North	Upper West Side South	42653	7.23	0.80	584

```
Distinct routes observed: 43,932
Share of trips starting and ending in the same zone: 4.2 %
```

4.6 Highest-revenue routes (total amount collected)

In [20]:

```
top_rev_routes <- routes[order(-revenue)][1:15]
top_rev_routes[, `:=`(revenue_musd = round(revenue / 1e6, 2), avg_fare =
round(avg_fare, 2),
                      avg_distance = round(avg_distance, 1),
revenue_per_trip = round(revenue / trips, 2))][, revenue := NULL]
top_rev_routes
airport_zones <- c("JFK Airport", "LaGuardia Airport", "Newark Airport")
trips[, .(trips = .N, revenue_musd = round(sum(total_amount) / 1e6, 1)),
      by = .(airport_trip = pu_zone %in% airport_zones | do_zone %in%
airport_zones)][
```

```
      , `:=`(trip_share_pct = round(100 * trips / sum(trips), 1),
revenue_share_pct = round(100 * revenue_musd / sum(revenue_musd), 1))][]
```

A data.table: 15 × 7

pu_zone <fct>	do_zone <fct>	trips <int>	avg_fare <dbl>	avg_distance <dbl>	revenue_musd <dbl>	revenue_per_trip <dbl>
JFK Airport	Outside of NYC	35131	106.83	21.0	4.47	127.25
JFK Airport	Times Sq/Theatre District	43128	70.40	18.0	4.07	94.31
LaGuardia Airport	Times Sq/Theatre District	39937	49.53	10.3	3.12	78.20
JFK Airport	Midtown South	22726	70.29	17.3	2.17	95.59
Upper East Side South	Upper East Side North	137973	8.87	1.1	2.17	15.72
JFK Airport	Clinton East	22425	70.44	18.2	2.10	93.71
Times Sq/Theatre District	LaGuardia Airport	26450	50.12	11.3	2.01	75.99
Upper East Side North	Upper East Side South	120122	9.37	1.0	1.94	16.13
LaGuardia Airport	Midtown Center	24343	46.71	10.0	1.84	75.46
JFK Airport	Midtown Center	18362	70.33	17.7	1.76	95.59
Times Sq/Theatre District	JFK Airport	18701	70.58	17.6	1.73	92.30
JFK Airport	Midtown North	17836	70.45	18.3	1.68	94.08
JFK Airport	Murray Hill	16971	70.23	16.9	1.62	95.41
LaGuardia Airport	Outside of NYC	10549	111.95	22.3	1.50	141.87
JFK Airport	East Chelsea	15002	70.37	18.1	1.43	95.61

A data.table: 2 × 5

airport_trip <lgl>	trips <int>	revenue_musd <dbl>	trip_share_pct <dbl>	revenue_share_pct <dbl>
FALSE	17735539	402.1	90.3	72.8
TRUE	1914677	149.9	9.7	27.2

4.7 Relationship between trip distance and fare amount

In [21]:
```
cat("Pearson correlation (distance, fare)  :", round(trips[,
cor(trip_distance, fare_amount)], 3), "\n")
samp_cor <- trips[sample(.N, 1e6), .(trip_distance, fare_amount)]
cat("Spearman correlation (1M-row sample)   :", round(samp_cor[,
cor(trip_distance, fare_amount, method = "spearman")], 3), "\n")

fit <- lm(fare_amount ~ trip_distance, data = trips[RatecodeID ==
"Standard", .(fare_amount, trip_distance)][sample(.N, 1e6)])
cat(sprintf("Linear model (standard rate, 1M-row sample): fare = %.2f +
%.2f x miles, R^2 = %.3f\n",
            coef(fit)[1], coef(fit)[2], summary(fit)$r.squared))

dist_bands <- trips[, .(trips = .N, avg_fare = round(mean(fare_amount),
2), median_fare = median(fare_amount),
                        fare_per_mile = round(mean(fare_amount /
trip_distance), 2),
                        avg_duration_min = round(mean(trip_duration_min),
1)),
                    by = .(distance_band = cut(trip_distance, c(0, 1, 2,
3, 5, 10, 20, 100),
                                               labels = c("0-1", "1-2",
"2-3", "3-5", "5-10", "10-20", "20+")))][order(distance_band)]
dist_bands
```

```
Pearson correlation (distance, fare)  : 0.936
Spearman correlation (1M-row sample)   : 0.911
Linear model (standard rate, 1M-row sample): fare = 6.15 + 3.88 x miles, R^2 = 0.918
```

A data.table: 7 × 6

distance_band	trips	avg_fare	median_fare	fare_per_mile	avg_duration_min
<fct>	<int>	<dbl>	<dbl>	<dbl>	<dbl>
0-1	4541685	8.12	7.20	28.67	6.4
1-2	6435665	12.03	11.40	8.30	11.3
2-3	3143726	17.00	16.30	6.97	16.5
3-5	2261809	22.95	21.94	6.07	21.6
5-10	1730511	34.60	33.80	4.84	27.6
10-20	1350971	61.45	66.81	4.18	44.2
20+	185849	90.72	70.00	3.71	55.2

4.8 Payment methods across boroughs

In [22]:
```
pay_overall <- trips[, .(trips = .N, avg_total = round(mean(total_amount),
2)), by = payment_type][order(-trips)]
pay_overall[, share_pct := round(100 * trips / sum(trips), 2)]
pay_overall
pay_borough <- trips[!pu_borough %in% c("Unknown", "N/A"), .N, by = .
(pu_borough, payment_type)]
pay_borough[, share_pct := round(100 * N / sum(N), 1), by = pu_borough]
dcast(pay_borough[payment_type %in% c("Credit card", "Cash",
"Flex/Unknown")], pu_borough ~ payment_type, value.var = "share_pct", fill
= 0)
```

A data.table: 5 × 4

payment_type	trips	avg_total	share_pct
<fct>	<int>	<dbl>	<dbl>
Credit card	14973411	29.10	76.20
Cash	2652440	24.47	13.50
Flex/Unknown	1789762	25.30	9.11
Dispute	164196	26.73	0.84
No charge	70407	23.86	0.36

A data.table: 6 × 4

pu_borough	Credit card	Cash	Flex/Unknown
<fct>	<dbl>	<dbl>	<dbl>
Bronx	57.0	5.3	37.0
Brooklyn	50.9	5.9	42.4
EWR	86.7	8.9	0.4
Manhattan	76.5	13.2	9.2
Queens	76.8	17.9	3.2
Staten Island	11.5	34.8	49.6

4.9 Additional patterns

In [23]:
```
# (a) tipping behaviour by payment type (cash tips are not recorded by the
meter)
trips[payment_type %in% c("Credit card", "Cash"),
      .(avg_tip = round(mean(tip_amount), 2), tip_pct_of_fare = round(100
* mean(tip_amount / fare_amount), 1),
        zero_tip_pct = round(100 * mean(tip_amount == 0), 1)), by =
payment_type]

# (b) average speed by hour - congestion pattern
speed_hour <- trips[trip_duration_min >= 1, .(avg_speed_mph =
round(mean(trip_distance / (trip_duration_min / 60)), 1)), by =
pickup_hour][order(pickup_hour)]
cat("Slowest hour:", speed_hour[which.min(avg_speed_mph), pickup_hour],
":00 (", min(speed_hour$avg_speed_mph), "mph ) | fastest hour:",
    speed_hour[which.max(avg_speed_mph), pickup_hour], ":00 (",
max(speed_hour$avg_speed_mph), "mph )\n")
```

```r
# (c) passenger count distribution
trips[, .(trips = .N), by = .(passengers = pmin(passenger_count, 5L))]
[order(passengers)][, share_pct := round(100 * trips / sum(trips), 1)][]

# (d) days with the highest and lowest demand
daily <- trips[, .(trips = .N, revenue = sum(total_amount)), by =
pickup_date][order(pickup_date)]
rbind(daily[order(-trips)][1:3][, type := "busiest"], daily[order(trips)]
[1:3][, type := "quietest"])
```

A data.table: 2 × 4

payment_type	avg_tip	tip_pct_of_fare	zero_tip_pct
<fct>	<dbl>	<dbl>	<dbl>
Credit card	4.28	25.3	5.2
Cash	0.00	0.0	100.0

```
Slowest hour: 15 :00 ( 9.3 mph ) | fastest hour: 5 :00 ( 19.6 mph )
```

A data.table: 5 × 3

passengers	trips	share_pct
<int>	<int>	<dbl>
1	15825911	80.5
2	2581756	13.1
3	592529	3.0
4	341493	1.7
5	308527	1.6

A data.table: 6 × 4

pickup_date	trips	revenue	type
<IDate>	<int>	<dbl>	<chr>
2024-05-16	139761	4165499	busiest
2024-04-11	138371	3866001	busiest
2024-06-06	137626	4081325	busiest
2024-01-07	65125	1866363	quietest
2024-02-13	67097	1701203	quietest
2024-05-27	70119	2098582	quietest

Interpretation of Task 2

- **Hourly demand** follows a clear commuter/leisure cycle: demand is lowest around 4–5 AM, builds through the morning and peaks in the late afternoon / early evening (≈ 17–18 h). Average fares are highest in the early morning because those trips are longer (airport and outer-borough runs).
- **Day of week:** Thursday has the highest average trips per day, followed by Saturday, Wednesday and Friday; Monday and Sunday are the quietest (several

Monday public holidays fall in this period). The weekday/weekend hourly profile shows weekend demand shifted to late night (0–3 h).

- **Monthly:** demand rises from January to spring (March–May are the busiest), reflecting winter seasonality and tourism; June stays high.
- **Revenue by period:** the midday (≈ 32 %) and evening-rush (≈ 27 %) periods generate most of the revenue; the amount per trip is similar in all periods (≈ 27–29 USD), but early-morning trips are the longest.
- **Routes:** the most frequent routes are short trips inside Manhattan's Upper East Side; the **highest-revenue routes all involve JFK / LaGuardia airports** – airport trips are a small share of trips but a much larger share of revenue.
- **Distance vs fare:** a strong positive, almost linear relationship (correlation ≈ 0.94; under the standard rate fare ≈ 6 USD + ≈ 3.9 USD per mile, R^2 ≈ 0.92), but the **fare per mile falls** sharply with distance because of the fixed base charge and time-based charges on short congested trips.
- **Payment:** credit cards dominate (about three quarters of trips), cash is ≈ 13 %. Cash is used more in Queens than in Manhattan, while Bronx and Brooklyn pickups have a very high "flex/unknown" share (no payment type recorded). Recorded tips are almost exclusively on card payments, because cash tips are not metered.
- **Other patterns:** taxis are slowest in the afternoon (congestion) and fastest early in the morning; most trips carry a single passenger; holidays and storms produce the quietest days.

---

5. Task 3 – Functional vs Vectorized vs data.table Programming

The same analytical operations are implemented in several styles and compared with `microbenchmark` (execution time) and `peak_mem_mb()` (peak extra memory). Row-wise functional code is far too slow for 20 million rows, so a **random sample of 200,000 trips** is used for the row-level experiment and **2 million trips** for the grouping experiment.

In [24]:
```
samp_dt <- trips[sample(.N, 2e5), .(fare_amount, trip_distance,
tip_amount, total_amount, pu_borough, pickup_hour)]
samp_df <- as.data.frame(samp_dt)          # plain data.frame for the
base-R versions
big_dt  <- trips[sample(.N, 2e6), .(fare_amount, trip_distance,
tip_amount, total_amount, pu_borough, pickup_hour)]
big_df  <- as.data.frame(big_dt)
cat("Sample sizes:", nrow(samp_df), "and", nrow(big_df), "rows\n")
bench_results <- list()   # collects every benchmark for Task 5
add_bench <- function(mb, comparison, n_rows, mem = NULL) {
  s <- as.data.table(summary(mb, unit = "ms"))[, .(approach =
as.character(expr), median_ms = round(median, 3), mean_ms = round(mean,
3))]
  s[, `:=`(comparison = comparison, rows = n_rows)]
  if (!is.null(mem)) s[, peak_mem_MB := mem[approach]]
  bench_results[[comparison]] <<- s
```

```
  s[, relative := round(median_ms / min(median_ms), 1)][order(median_ms)]
}
```

```
Sample sizes: 200000 and 2000000 rows
```

5.1 Experiment A – row-level calculation (fare per mile)

Compute `fare_amount / trip_distance` for every trip.

In [25]:

```
fpm_apply  <- function(df) apply(df[, c("fare_amount", "trip_distance")],
1, function(r) r[1] / r[2])
fpm_lapply <- function(df) unlist(lapply(seq_len(nrow(df)), function(i)
df$fare_amount[i] / df$trip_distance[i]))
fpm_map    <- function(df) purrr::map2_dbl(df$fare_amount,
df$trip_distance, function(f, d) f / d)
fpm_loop   <- function(df) { out <- numeric(nrow(df)); for (i in
seq_len(nrow(df))) out[i] <- df$fare_amount[i] / df$trip_distance[i]; out
}
fpm_vector <- function(df) df$fare_amount / df$trip_distance
fpm_dt     <- function(dt) dt[, fare_amount / trip_distance]

# all implementations give the same answer
ref <- fpm_vector(samp_df)
stopifnot(all.equal(unname(fpm_apply(samp_df)), ref),
all.equal(fpm_lapply(samp_df), ref),
          all.equal(fpm_map(samp_df), ref), all.equal(fpm_loop(samp_df),
ref), all.equal(fpm_dt(samp_dt), ref))

mem_A <- c(`apply()` = peak_mem_mb(fpm_apply(samp_df)), `lapply()` =
peak_mem_mb(fpm_lapply(samp_df)),
           `purrr::map2_dbl()` = peak_mem_mb(fpm_map(samp_df)), `for loop`
= peak_mem_mb(fpm_loop(samp_df)),
           `vectorized` = peak_mem_mb(fpm_vector(samp_df)), `data.table` =
peak_mem_mb(fpm_dt(samp_dt)))

mb_A <- microbenchmark(`apply()` = fpm_apply(samp_df), `lapply()` =
fpm_lapply(samp_df),
                       `purrr::map2_dbl()` = fpm_map(samp_df), `for loop`
= fpm_loop(samp_df),
                       `vectorized` = fpm_vector(samp_df), `data.table` =
fpm_dt(samp_dt), times = 10)
add_bench(mb_A, "A: row-level fare per mile", nrow(samp_df), mem_A)
```

A data.table: 6 × 7

approach	median_ms	mean_ms	comparison	rows	peak_mem_MB	relative
<chr>	<dbl>	<dbl>	<chr>	<int>	<dbl>	<dbl>
vectorized	0.436	0.443	A: row-level fare per mile	200000	2.3	1.0
data.table	1.641	1.700	A: row-level fare per mile	200000	2.5	3.8
purrr::map2_dbl()	296.362	371.086	A: row-level fare per mile	200000	167.9	679.7
for loop	391.298	392.982	A: row-level fare per mile	200000	188.4	897.5
lapply()	682.103	683.182	A: row-level fare per mile	200000	190.7	1564.5
apply()	1286.440	1259.652	A: row-level fare per mile	200000	206.4	2950.6

5.2 Experiment B – grouped aggregation (mean total amount per borough and hour)

In [26]:
```
grp_lapply <- function(df) {
  g <- split(df$total_amount, list(df$pu_borough, df$pickup_hour), drop =
TRUE)
  unlist(lapply(g, mean))
}
grp_map    <- function(df) purrr::map_dbl(split(df$total_amount,
list(df$pu_borough, df$pickup_hour), drop = TRUE), mean)
grp_sapply <- function(df) {           # conventional: filter the data
once per group
  keys <- unique(df[, c("pu_borough", "pickup_hour")])
  sapply(seq_len(nrow(keys)), function(k)
mean(df$total_amount[df$pu_borough == keys$pu_borough[k] & df$pickup_hour
== keys$pickup_hour[k]]))
}
grp_tapply    <- function(df) tapply(df$total_amount, list(df$pu_borough,
df$pickup_hour), mean)
grp_aggregate <- function(df) aggregate(total_amount ~ pu_borough +
pickup_hour, data = df, FUN = mean)
grp_dt        <- function(dt) dt[, .(mean_total = mean(total_amount)), by
= .(pu_borough, pickup_hour)]

# check: same group means from functional and data.table versions
chk <- grp_dt(big_dt)[order(pu_borough, pickup_hour)]
stopifnot(all.equal(unname(grp_lapply(big_df)[paste(chk$pu_borough,
chk$pickup_hour, sep = ".")]), chk$mean_total))

mem_B <- c(`lapply(split())` = peak_mem_mb(grp_lapply(big_df)),
`purrr::map_dbl(split())` = peak_mem_mb(grp_map(big_df)),
           `sapply() filter per group` = peak_mem_mb(grp_sapply(big_df)),
```

```
`tapply()` = peak_mem_mb(grp_tapply(big_df)),
          `aggregate()` = peak_mem_mb(grp_aggregate(big_df)), `data.table
by` = peak_mem_mb(grp_dt(big_dt)))

mb_B <- microbenchmark(`lapply(split())` = grp_lapply(big_df),
`purrr::map_dbl(split())` = grp_map(big_df),
                       `sapply() filter per group` = grp_sapply(big_df),
`tapply()` = grp_tapply(big_df),
                       `aggregate()` = grp_aggregate(big_df), `data.table
by` = grp_dt(big_dt), times = 5)
add_bench(mb_B, "B: grouped mean by borough x hour", nrow(big_df), mem_B)
```

A data.table: 6 × 7

approach	median_ms	mean_ms	comparison	rows	peak_mem_MB	relat
<chr>	<dbl>	<dbl>	<chr>	<int>	<dbl>	<d
data.table by	47.532	46.376	B: grouped mean by borough x hour	2000000	57.6	
tapply()	81.393	81.032	B: grouped mean by borough x hour	2000000	77.7	
purrr::map_dbl(split())	252.309	257.390	B: grouped mean by borough x hour	2000000	246.4	
lapply(split())	263.114	282.736	B: grouped mean by borough x hour	2000000	248.2	
aggregate()	658.878	649.786	B: grouped mean by borough x hour	2000000	601.2	1
sapply() filter per group	11177.844	11056.943	B: grouped mean by borough x hour	2000000	3984.7	23

5.3 Experiment C – summary statistics over many columns

Here the functional approach iterates over **columns** (only a handful of iterations), not rows.

In [27]:
```
num_vars <- c("fare_amount", "trip_distance", "tip_amount",
"total_amount")
col_apply  <- function(df) apply(df[, num_vars], 2, mean)
col_lapply <- function(df) unlist(lapply(df[, num_vars], mean))
col_map    <- function(df) purrr::map_dbl(df[, num_vars], mean)
col_vector <- function(df) colMeans(df[, num_vars])
col_dt     <- function(dt) dt[, lapply(.SD, mean), .SDcols = num_vars]

stopifnot(all.equal(col_lapply(big_df), col_vector(big_df)),
```

```
all.equal(unlist(col_dt(big_dt)), col_vector(big_df)))
mem_C <- c(`apply(, 2)` = peak_mem_mb(col_apply(big_df)), `lapply()` =
peak_mem_mb(col_lapply(big_df)),
           `purrr::map_dbl()` = peak_mem_mb(col_map(big_df)), `colMeans()
vectorized` = peak_mem_mb(col_vector(big_df)),
           `data.table .SD` = peak_mem_mb(col_dt(big_dt)))
mb_C <- microbenchmark(`apply(, 2)` = col_apply(big_df), `lapply()` =
col_lapply(big_df), `purrr::map_dbl()` = col_map(big_df),
                       `colMeans() vectorized` = col_vector(big_df),
`data.table .SD` = col_dt(big_dt), times = 10)
add_bench(mb_C, "C: column means (4 columns)", nrow(big_df), mem_C)
```

A data.table: 5 × 7

approach	median_ms	mean_ms	comparison	rows	peak_mem_MB	relative
<chr>	<dbl>	<dbl>	<chr>	<int>	<dbl>	<dbl>
purrr::map_dbl()	33.899	34.101	C: column means (4 columns)	2000000	0.0	1.0
lapply()	34.022	35.994	C: column means (4 columns)	2000000	1.2	1.0
data.table .SD	34.845	35.157	C: column means (4 columns)	2000000	1.2	1.0
colMeans() vectorized	36.658	37.029	C: column means (4 columns)	2000000	61.1	1.1
apply(, 2)	89.999	91.955	C: column means (4 columns)	2000000	213.8	2.7

5.4 Comparison of code complexity and readability

In [28]:
```
data.table(
  approach      = c("apply()", "lapply() / sapply()", "purrr::map()", "for
loop", "Vectorized base R", "data.table"),
  lines_of_code = c(1, 1, 1, 3, 1, 1),
  readability   = c("Medium - matrix conversion hidden", "Medium", "High -
explicit, type-stable (map_dbl)",
                    "High for beginners, verbose", "Very high", "High once
DT[i, j, by] is learnt"),
  complexity    = c("Low", "Low", "Low", "Medium (pre-allocation needed)",
"Very low", "Low"),
  memory        = c("High - converts data.frame to matrix", "High - one R
call + list element per row",
                    "High per row, low per column", "Low", "Low - one
result vector", "Lowest - in-place, no copies"),
  large_data    = c("Unsuitable row-wise", "Unsuitable row-wise, fine over
columns/groups",
                    "Unsuitable row-wise, fine over columns/groups",
"Unsuitable", "Good", "Best (multi-threaded, by reference)")
)
```

A data.table: 6 × 6

approach	lines_of_code	readability	complexity	memory	large_data
<chr>	<dbl>	<chr>	<chr>	<chr>	<chr>
apply()	1	Medium - matrix conversion hidden	Low	High - converts data.frame to matrix	Unsuitable row-wise
lapply() / sapply()	1	Medium	Low	High - one R call + list element per row	Unsuitable row-wise, fine over columns/groups
purrr::map()	1	High - explicit, type-stable (map_dbl)	Low	High per row, low per column	Unsuitable row-wise, fine over columns/groups
for loop	3	High for beginners, verbose	Medium (pre-allocation needed)	Low	Unsuitable
Vectorized base R	1	Very high	Very low	Low - one result vector	Good
data.table	1	High once DT[i, j, by] is learnt	Low	Lowest - in-place, no copies	Best (multi-threaded, by reference)

Why the performance differs

- `apply()` first **coerces the data.frame to a matrix** (copying all values) and then calls an R function once per row – 200,000 interpreted function calls. `lapply()`, `purrr::map()` and `for` loops avoid the matrix copy but still pay the cost of one interpreted R call per element plus list allocation.
- **Vectorized** arithmetic (`df$fare / df$dist`) performs a single call into compiled C code that loops over the whole vector – typically **hundreds to thousands of times faster** than the row-wise versions.
- For **grouping**, `split()` + `lapply()` is reasonable (the loop is over groups, not rows) but `split()` copies the data into a list; the "filter per group" `sapply()` scans the full vector once per group; `aggregate()` has heavy formula/model-frame overhead. **data.table** groups with a radix-sort based algorithm in C, uses several threads (GForce optimisation for `mean()`), and allocates memory only for the result.
- When the functional loop runs over **a few columns** (Experiment C), the call overhead is negligible: `lapply()` / `map_dbl()` call the compiled `mean()` once per column and are as fast as data.table's `.SD` and even faster than `colMeans()`, because `colMeans()` and `apply(, 2)` must first convert the data.frame into a matrix (an extra copy). Functional style is the best choice there.

---

6. Task 4 – Parallel Computing with foreach + doParallel

6.1 Logical partitions

The dataset is divided into **month-wise partitions** (6 subsets of ≈ 3 million trips). Only the columns needed by the analysis are kept so that less data has to be sent to the worker processes.

In [29]:
```
rm(samp_dt, samp_df, big_dt, big_df, samp_cor, fit); invisible(gc())   # free Task 3 objects
parts <- split(trips[, .(month, pu_borough, fare_amount, total_amount, trip_distance, trip_duration_min, tip_amount)],
               by = "month", keep.by = TRUE, drop = TRUE)
data.table(month = names(parts), rows = sapply(parts, nrow), size_MB = round(sapply(parts, function(p) object.size(p)) / 2^20, 1))
```

A data.table: 6 × 3

month	rows	size_MB
<chr>	<int>	<dbl>
Jan	2866574	131.2
Feb	2898586	132.7
Mar	3436527	157.3
Apr	3410774	156.1
May	3612954	165.4
Jun	3424801	156.8

6.2 Computationally intensive operation – bootstrap analysis per month

For every month we estimate **95 % bootstrap confidence intervals** for the mean total amount, the median trip distance and the mean fare per mile (`B` resamples of ≈ 3 million rows each), plus borough-level statistics. Resampling millions of rows many times is CPU-bound and each month is independent – a good candidate for parallelism.

In [30]:
```
analyse_partition <- function(d, B = 20) {
  data.table::setDTthreads(1)              # one thread per worker -> fair sequential vs parallel comparison
  set.seed(1000 + match(as.character(d$month[1]), month.abb))  # reproducible, identical in both modes
  n <- nrow(d)
  boot <- t(vapply(seq_len(B), function(b) {
    idx <- sample.int(n, n, replace = TRUE)
    c(mean_total    = mean(d$total_amount[idx]),
      median_dist   = median(d$trip_distance[idx]),
      fare_per_mile = mean(d$fare_amount[idx] / d$trip_distance[idx]))
  }, numeric(3)))
  ci <- apply(boot, 2, quantile, probs = c(0.025, 0.975))
```

```
  data.table::data.table(
    month = as.character(d$month[1]), trips = n,
    mean_total = mean(d$total_amount), mean_total_lo = ci[1,
"mean_total"], mean_total_hi = ci[2, "mean_total"],
    median_dist = median(d$trip_distance), median_dist_lo = ci[1,
"median_dist"], median_dist_hi = ci[2, "median_dist"],
    fare_per_mile = mean(d$fare_amount / d$trip_distance),
    manhattan_share = mean(d$pu_borough == "Manhattan"))
}
B <- 20
old_threads <- getDTthreads()
```

6.3 A. Sequential processing

In [31]:
```
t_seq <- system.time(res_seq <- rbindlist(lapply(parts, analyse_partition,
B = B)))
t_seq_foreach <- system.time(res_seq_fe <- foreach(d = parts, .combine =
rbind) %do% analyse_partition(d, B = B))
setDTthreads(old_threads)
cat(sprintf("Sequential lapply()      : %.2f s\nSequential foreach %%do%%
: %.2f s\n", t_seq[["elapsed"]], t_seq_foreach[["elapsed"]]))
res_seq[, lapply(.SD, function(x) if (is.numeric(x)) round(x, 3) else x)]
```

```
Sequential lapply()      : 42.75 s
Sequential foreach %do% : 42.91 s
```

A data.table: 6 × 10

month	trips	mean_total	mean_total_lo	mean_total_hi	median_dist	median_dist_lo
<chr>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
Jan	2866574	27.326	27.291	27.341	1.70	1.70
Feb	2898586	27.221	27.202	27.257	1.72	1.71
Mar	3436527	27.848	27.819	27.861	1.80	1.80
Apr	3410774	28.175	28.143	28.191	1.81	1.81
May	3612954	28.989	28.972	29.009	1.81	1.81
Jun	3424801	28.674	28.651	28.693	1.82	1.81

6.4 B. Parallel processing with foreach + doParallel

A PSOCK cluster (works on Windows, macOS and Linux) is created with `N_CORES` workers; `foreach(... ) %dopar%` sends one monthly partition to each free worker and `rbind`s the results.

In [32]:
```
t_cluster <- system.time({
  cl <- makeCluster(N_CORES)
  registerDoParallel(cl)
  invisible(clusterEvalQ(cl, library(data.table)))
})
cat("Workers registered:", getDoParWorkers(), "| cluster start-up:",
t_cluster[["elapsed"]], "s\n")

t_par <- system.time(
  res_par <- foreach(d = parts, .combine = rbind, .packages =
"data.table") %dopar%
```

```
    analyse_partition(d, B = B)
)
cat(sprintf("Parallel foreach %%dopar%% with %d workers: %.2f s\n",
N_CORES, t_par[["elapsed"]]))
stopifnot(all.equal(res_seq, res_par, check.attributes = FALSE))   #
identical results
cat("Results identical to sequential run: TRUE\n")
```

```
Workers registered: 3 | cluster start-up: 0.461 s
Parallel foreach %dopar% with 3 workers: 19.40 s
Results identical to sequential run: TRUE
```

6.5 Speedup and scaling with the number of cores

$$\text{Speedup} = \frac{\text{Sequential execution time}}{\text{Parallel execution time}} \qquad \text{Efficiency} = \frac{\text{Speedup}}{\text{cores}}$$

In [33]:
```
stopCluster(cl)
core_grid <- unique(c(1L, 2L, seq(2L, N_CORES, by = 2L), N_CORES))
scaling <- rbindlist(lapply(core_grid, function(k) {
  cl_k <- makeCluster(k); registerDoParallel(cl_k)
  invisible(clusterEvalQ(cl_k, library(data.table)))
  el <- system.time(foreach(d = parts, .combine = rbind, .packages =
"data.table", .export = c("analyse_partition", "B")) %dopar%
                      analyse_partition(d, B = B))[["elapsed"]]
  stopCluster(cl_k)
  data.table(cores = k, parallel_s = el)
}))
scaling[, `:=`(sequential_s = t_seq[["elapsed"]], speedup =
round(t_seq[["elapsed"]] / parallel_s, 2))]
scaling[, efficiency_pct := round(100 * speedup / cores)]
scaling
speedup_main <- round(t_seq[["elapsed"]] / t_par[["elapsed"]], 2)
cat(sprintf("\nSpeedup with %d cores = %.2f s / %.2f s = %.2fx\n",
N_CORES, t_seq[["elapsed"]], t_par[["elapsed"]], speedup_main))
```

A data.table: 3 × 5

cores	parallel_s	sequential_s	speedup	efficiency_pct
<int>	<dbl>	<dbl>	<dbl>	<dbl>
1	45.822	42.752	0.93	93
2	26.139	42.752	1.64	82
3	18.575	42.752	2.30	77

```
Speedup with 3 cores = 42.75 s / 19.40 s = 2.20x
```

6.6 When parallelism does not help – a lightweight task

Computing a simple mean per month is so cheap that sending ≈ 600 MB of partitions to the workers costs far more than the computation itself.

In [34]:
```
light_task <- function(d) data.table::data.table(month =
as.character(d$month[1]), mean_fare = mean(d$fare_amount))
cl <- makeCluster(N_CORES); registerDoParallel(cl)
t_light_seq <- system.time(foreach(d = parts, .combine = rbind) %do%
light_task(d))[["elapsed"]]
t_light_par <- system.time(foreach(d = parts, .combine = rbind, .packages
```

```
= "data.table") %dopar% light_task(d))[["elapsed"]]
t_light_dt  <- system.time(trips[, .(mean_fare = mean(fare_amount)), by =
month])[["elapsed"]]
stopCluster(cl); registerDoSEQ()
light <- data.table(approach = c("Sequential foreach %do%",
sprintf("Parallel foreach %%dopar%% (%d cores)", N_CORES), "data.table by
= month (no partitions)"),
                    elapsed_s = c(t_light_seq, t_light_par, t_light_dt))
light[, speedup_vs_seq := round(t_light_seq / elapsed_s, 2)]
light
```

A data.table: 3 × 3

approach	elapsed_s	speedup_vs_seq
<chr>	<dbl>	<dbl>
Sequential foreach %do%	0.104	1.00
Parallel foreach %dopar% (3 cores)	3.505	0.03
data.table by = month (no partitions)	0.284	0.37

Discussion

- For the **CPU-intensive bootstrap**, the parallel version is clearly faster; the speedup grows with the number of cores but stays **below the ideal linear speedup** (efficiency < 100 %) because of (1) cluster start-up, (2) serialising each ≈ 100 MB partition to the worker processes, (3) only 6 partitions for N workers (load imbalance: with 3 workers the last "round" is uneven when 6 is not a multiple of the core count) and (4) memory-bandwidth contention.
- For the **lightweight task** parallel execution is *slower* than sequential: the work per partition takes milliseconds while copying the data to workers takes seconds. A single data.table grouping on the full table (which is itself multi-threaded) is faster than both.
- Therefore parallel processing pays off only when the computation per partition is large compared with the communication overhead.

---

7. Task 5 – Performance Benchmarking and Optimization

7.1 Base R vs data.table on the full dataset

Typical operations on all ≈ 20 million trips: filtering, grouped aggregation, sorting and joining. A base-R `data.frame` copy of the needed columns is used for the base-R versions.

In [35]:
```
rm(parts); invisible(gc())   # free Task 4 partitions
full_dt <- trips[, .(PULocationID, pickup_hour, month, fare_amount,
total_amount, trip_distance)]
full_df <- setDF(copy(full_dt))   # plain data.frame for the base-R
versions
```

```
zones_df <- as.data.frame(zones)
n_full <- nrow(full_df)

invisible(gc())
cat("data.table threads:", getDTthreads(), "\n")
mb_filter <- microbenchmark(
  `base R df[cond, ]`       = full_df[full_df$trip_distance > 10 &
full_df$fare_amount > 50, ],
  `base R subset()`         = subset(full_df, trip_distance > 10 &
fare_amount > 50),
  `data.table DT[cond]`     = full_dt[trip_distance > 10 & fare_amount >
50], times = 7)
add_bench(mb_filter, "D: filter long expensive trips", n_full)
```

```
data.table threads: 2
```

A data.table: 3 × 6

approach	median_ms	mean_ms	comparison	rows	relative
<chr>	<dbl>	<dbl>	<chr>	<int>	<dbl>
data.table DT[cond]	234.808	253.493	D: filter long expensive trips	19650216	1.0
base R df[cond,]	509.634	512.129	D: filter long expensive trips	19650216	2.2
base R subset()	598.870	761.438	D: filter long expensive trips	19650216	2.6

In [36]:
```
invisible(gc())
mb_group <- microbenchmark(
  `base R aggregate()`      = aggregate(total_amount ~ month +
pickup_hour, data = full_df, FUN = sum),
  `base R tapply()`         = tapply(full_df$total_amount,
list(full_df$month, full_df$pickup_hour), sum),
  `data.table by`           = full_dt[, .(revenue = sum(total_amount)), by
= .(month, pickup_hour)], times = 7)
add_bench(mb_group, "E: revenue by month x hour", n_full)
```

A data.table: 3 × 6

approach	median_ms	mean_ms	comparison	rows	relative
<chr>	<dbl>	<dbl>	<chr>	<int>	<dbl>
data.table by	485.448	479.529	E: revenue by month x hour	19650216	1.0
base R tapply()	1002.404	973.189	E: revenue by month x hour	19650216	2.1
base R aggregate()	14558.128	14449.706	E: revenue by month x hour	19650216	30.0

In [37]:
```
invisible(gc())
mb_sort <- microbenchmark(
  `base R order()`          = full_df[order(-full_df$total_amount), ],
  `data.table setorder()`   = setorder(copy(full_dt), -total_amount),
  `data.table DT[order()]`  = full_dt[order(-total_amount)], times = 5)
add_bench(mb_sort, "F: sort by total amount", n_full)
```

A data.table: 3 × 6

approach	median_ms	mean_ms	comparison	rows	relative
<chr>	<dbl>	<dbl>	<chr>	<int>	<dbl>
data.table DT[order()]	1486.233	1923.202	F: sort by total amount	19650216	1.0
data.table setorder()	2208.682	2670.401	F: sort by total amount	19650216	1.5
base R order()	7627.326	6477.517	F: sort by total amount	19650216	5.1

In [38]:
```
join_n  <- 2e6
join_df <- full_df[seq_len(join_n), ]
join_dt <- full_dt[seq_len(join_n)]
mem_join <- c(`base R merge()` = peak_mem_mb(merge(join_df, zones_df, by.x
= "PULocationID", by.y = "LocationID", all.x = TRUE)),
              `base R match()` = peak_mem_mb({j <- join_df; j$Borough <-
zones_df$Borough[match(j$PULocationID, zones_df$LocationID)]; j}),
              `data.table join` = peak_mem_mb(zones[join_dt, on = .
(LocationID = PULocationID)]),
              `data.table update join :=` = peak_mem_mb(join_dt[zones, on
= .(PULocationID = LocationID), Borough := i.Borough]))
mb_join <- microbenchmark(
  `base R merge()`          = merge(join_df, zones_df, by.x =
"PULocationID", by.y = "LocationID", all.x = TRUE),
  `base R match()`          = {j <- join_df; j$Borough <-
zones_df$Borough[match(j$PULocationID, zones_df$LocationID)]; j},
  `data.table join`         = zones[join_dt, on = .(LocationID =
PULocationID)],
  `data.table update join :=` = join_dt[zones, on = .(PULocationID =
LocationID), Borough := i.Borough], times = 3)
add_bench(mb_join, "G: join 2M trips with zones", join_n, mem_join)
```

A data.table: 4 × 7

approach	median_ms	mean_ms	comparison	rows	peak_mem_MB	relative
<chr>	<dbl>	<dbl>	<chr>	<dbl>	<dbl>	<dbl>
base R match()	22.570	23.039	G: join 2M trips with zones	2000000	30.6	1.0
data.table update join :=	118.587	119.239	G: join 2M trips with zones	2000000	76.7	5.3
data.table join	132.743	141.892	G: join 2M trips with zones	2000000	152.9	5.9
base R merge()	3114.785	3354.335	G: join 2M trips with zones	2000000	675.0	138.0

7.2 Scalability – execution time vs number of rows

The grouped aggregation (mean fare by pickup zone) is run on increasing subsets.

In [39]:
```
sizes <- c(1e5, 5e5, 1e6, 5e6, 1e7, n_full)
scal <- rbindlist(lapply(sizes, function(n) {
  df <- full_df[seq_len(n), c("PULocationID", "fare_amount")]
  dt <- full_dt[seq_len(n), .(PULocationID, fare_amount)]
  t <- summary(microbenchmark(
    `lapply(split())` = lapply(split(df$fare_amount, df$PULocationID),
mean),
    `tapply()`        = tapply(df$fare_amount, df$PULocationID, mean),
    `aggregate()`     = aggregate(fare_amount ~ PULocationID, data = df,
FUN = mean),
    `data.table by`   = dt[, mean(fare_amount), by = PULocationID], times
= 3), unit = "ms")
  data.table(rows = n, approach = as.character(t$expr), median_ms =
t$median)
}))
dcast(scal, rows ~ approach, value.var = "median_ms")[, lapply(.SD, round,
1)]
```

A data.table: 6 × 5

rows	aggregate()	data.table by	lapply(split())	tapply()
<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
100000	28.5	2.8	3.1	4.3
500000	82.3	10.3	11.3	17.4
1000000	209.4	20.8	22.9	35.6
5000000	1243.1	97.1	142.3	163.8
10000000	4687.2	719.9	275.8	348.9
19650216	10906.1	467.5	582.0	827.4

7.3 Consolidated execution-time comparison table

In [40]:
```
par_tbl <- data.table(approach = c("Sequential lapply()", "Sequential
foreach %do%", sprintf("Parallel foreach %%dopar%% (%d cores)", N_CORES)),
                      median_ms = round(1000 * c(t_seq[["elapsed"]],
t_seq_foreach[["elapsed"]], t_par[["elapsed"]]), 1),
                      comparison = "H: bootstrap per month (sequential vs
parallel)", rows = nrow(trips))
bench_all <- rbindlist(c(bench_results, list(par_tbl)), fill = TRUE)
bench_all[, relative_to_best := round(median_ms / min(median_ms), 1), by =
comparison]
bench_all <- bench_all[order(comparison, median_ms), .(comparison, rows,
approach, median_ms, relative_to_best, peak_mem_MB)]
fwrite(bench_all, file.path(OUT_DIR, "benchmark_results.csv"))
fwrite(scaling, file.path(OUT_DIR, "parallel_scaling.csv"))
rm(full_df, full_dt, join_df, join_dt); invisible(gc())
bench_all
```

A data.table: 33 × 6

comparison	rows	approach	median_ms	relative_to_best	peak_mem_MB
<chr>	<dbl>	<chr>	<dbl>	<dbl>	<dbl>
A: row-level fare per mile	200000	vectorized	0.436	1.0	2.3
A: row-level fare per mile	200000	data.table	1.641	3.8	2.5
A: row-level fare per mile	200000	purrr::map2_dbl()	296.362	679.7	167.9
A: row-level fare per mile	200000	for loop	391.298	897.5	188.4
A: row-level fare per mile	200000	lapply()	682.103	1564.5	190.7
A: row-level fare per mile	200000	apply()	1286.440	2950.6	206.4
B: grouped mean by borough x hour	2000000	data.table by	47.532	1.0	57.6
B: grouped mean by borough x hour	2000000	tapply()	81.393	1.7	77.7
B: grouped mean by borough x hour	2000000	purrr::map_dbl(split())	252.309	5.3	246.4
B: grouped mean by borough x hour	2000000	lapply(split())	263.114	5.5	248.2
B: grouped mean by borough x hour	2000000	aggregate()	658.878	13.9	601.2
B: grouped mean by borough x hour	2000000	sapply() filter per group	11177.844	235.2	3984.7
C: column means (4 columns)	2000000	purrr::map_dbl()	33.899	1.0	0.0
C: column means (4 columns)	2000000	lapply()	34.022	1.0	1.2

comparison	rows	approach	median_ms	relative_to_best	peak_mem_MB
<chr>	<dbl>	<chr>	<dbl>	<dbl>	<dbl>
C: column means (4 columns)	2000000	data.table .SD	34.845	1.0	1.2
C: column means (4 columns)	2000000	colMeans() vectorized	36.658	1.1	61.1
C: column means (4 columns)	2000000	apply(, 2)	89.999	2.7	213.8
D: filter long expensive trips	19650216	data.table DT[cond]	234.808	1.0	NA
D: filter long expensive trips	19650216	base R df[cond,]	509.634	2.2	NA
D: filter long expensive trips	19650216	base R subset()	598.870	2.6	NA
E: revenue by month x hour	19650216	data.table by	485.448	1.0	NA
E: revenue by month x hour	19650216	base R tapply()	1002.404	2.1	NA
E: revenue by month x hour	19650216	base R aggregate()	14558.128	30.0	NA
F: sort by total amount	19650216	data.table DT[order()]	1486.233	1.0	NA
F: sort by total amount	19650216	data.table setorder()	2208.682	1.5	NA
F: sort by total amount	19650216	base R order()	7627.326	5.1	NA
G: join 2M trips with zones	2000000	base R match()	22.570	1.0	30.6
G: join 2M trips with zones	2000000	data.table update join :=	118.587	5.3	76.7
G: join 2M trips with zones	2000000	data.table join	132.743	5.9	152.9

comparison	rows	approach	median_ms	relative_to_best	peak_mem_MB
<chr>	<dbl>	<chr>	<dbl>	<dbl>	<dbl>
G: join 2M trips with zones	2000000	base R merge()	3114.785	138.0	675.0
H: bootstrap per month (sequential vs parallel)	19650216	Parallel foreach %dopar% (3 cores)	19395.000	1.0	NA
H: bootstrap per month (sequential vs parallel)	19650216	Sequential lapply()	42752.000	2.2	NA
H: bootstrap per month (sequential vs parallel)	19650216	Sequential foreach %do%	42907.000	2.2	NA

In [41]:

```
# head-to-head summary for the four required comparisons
best_of <- function(cmp, pattern) bench_all[comparison == cmp &
grepl(pattern, approach), min(median_ms)]
summary_tbl <- data.table(
  comparison = c("Base R vs data.table (grouping, 20M rows)", "Base R vs
data.table (join, 2M rows)",
                 "Functional vs vectorized (row-level)", "Functional vs
data.table (grouping)", "Sequential vs parallel (bootstrap)"),
  slower_approach_ms = c(best_of("E: revenue by month x hour",
"aggregate"), best_of("G: join 2M trips with zones", "merge"),
                         best_of("A: row-level fare per mile", "lapply"),
best_of("B: grouped mean by borough x hour", "lapply"),
                         1000 * t_seq[["elapsed"]]),
  faster_approach_ms = c(best_of("E: revenue by month x hour",
"data.table"), best_of("G: join 2M trips with zones", "data.table"),
                         best_of("A: row-level fare per mile",
"vectorized"), best_of("B: grouped mean by borough x hour", "data.table"),
                         1000 * t_par[["elapsed"]]))
summary_tbl[, speedup := round(slower_approach_ms / faster_approach_ms,
1)]
summary_tbl[, (2:3) := lapply(.SD, round, 1), .SDcols = 2:3]
summary_tbl
```

A data.table: 5 × 4

comparison	slower_approach_ms	faster_approach_ms	speedup
<chr>	<dbl>	<dbl>	<dbl>
Base R vs data.table (grouping, 20M rows)	14558.1	485.4	30.0
Base R vs data.table (join, 2M rows)	3114.8	118.6	26.3
Functional vs vectorized (row-level)	682.1	0.4	1564.5
Functional vs data.table (grouping)	263.1	47.5	5.5
Sequential vs parallel (bootstrap)	42752.0	19395.0	2.2

Analysis

- **Execution time:** data.table is the fastest approach for filtering, grouping and sorting, and its joins are one to two orders of magnitude faster than `merge()`; grouped aggregation is far faster than `aggregate()`. For a *single-column lookup* the vectorized base-R `match()` is even faster than a data.table join, because it only builds one integer index – a good example that a well-chosen vectorized primitive is hard to beat, whereas data.table's join is the general tool for multi-column / many-to-many joins. For row-level arithmetic, vectorized base R and data.table are equivalent and both are thousands of times faster than `apply()` / `lapply()` / `map()`.
- **Memory:** `merge()` and `aggregate()` create several intermediate copies; data.table joins and especially the **update join** `:=` add a column in place, so the peak extra memory is only the size of the new column. `apply()` needs an extra matrix copy of the data.
- **Scalability:** all approaches grow roughly linearly with the number of rows, but with very different slopes – at 20 million rows `aggregate()` needs many seconds while `data.table` stays well below a second, so the gap widens as the data grows.
- **Programming complexity / readability:** vectorized code and data.table one-liners are both short and readable. `purrr::map_*()` is the most explicit and type-safe functional style but is slow when used per row. Parallel code adds the most complexity (cluster set-up, exporting functions/packages, seeds, cleanup) and only pays off for heavy, independent computations.


---

8. Task 6 – Data Visualization (ggplot2)

All figures are also saved as PNG files in `outputs/figures/`.


In [42]:
```
p <- ggplot(hourly, aes(pickup_hour, trips / 1e3)) +
  geom_col(fill = "#F2B705") +
  geom_line(aes(y = avg_fare * max(trips / 1e3) / max(avg_fare), colour =
```

```
"Average fare (right axis)"), linewidth = 1.1, group = 1) +
  scale_colour_manual(values = "#1F4E79", name = NULL) +
  scale_x_continuous(breaks = 0:23) +
  scale_y_continuous(labels = comma, sec.axis = sec_axis(~ . *
max(hourly$avg_fare) / max(hourly$trips / 1e3), name = "Average fare
(USD)")) +
  labs(title = "1. Number of taxi trips by hour of day", subtitle = "NYC
Yellow Taxi, Jan-Jun 2024",
       x = "Pickup hour (0-23)", y = "Number of trips (thousands)")
save_plot(p, "01_trips_by_hour")
```




Demand is lowest at 4–5 AM and peaks at 17–18 h; average fares are highest in the early morning when trips are longer.

In [43]:
```
p <- ggplot(dow, aes(pickup_wday, avg_trips_per_day / 1e3, fill =
pickup_wday %in% c("Sat", "Sun"))) +
  geom_col() +
  geom_text(aes(label = comma(avg_trips_per_day)), vjust = -0.4, size = 4)
+
  scale_fill_manual(values = c(`FALSE` = "#1F4E79", `TRUE` = "#F2B705"),
labels = c("Weekday", "Weekend"), name = NULL) +
  labs(title = "2. Taxi demand by day of week", subtitle = "Average number
of trips per calendar day",
       x = "Day of week", y = "Average trips per day (thousands)")
save_plot(p, "02_demand_by_weekday")
```




In [44]:
```
wk <- melt(dcast(dow_hour, pickup_hour ~ ifelse(is_weekend, "Weekend",
"Weekday"), value.var = "trips_per_day"),
           id.vars = "pickup_hour", variable.name = "day_type", value.name
= "trips_per_day")
p <- ggplot(wk, aes(pickup_hour, trips_per_day, colour = day_type)) +
geom_line(linewidth = 1.2) + geom_point() +
  scale_colour_manual(values = c(Weekday = "#1F4E79", Weekend =
"#E07A00"), name = "Day type") +
  scale_x_continuous(breaks = 0:23) + scale_y_continuous(labels = comma) +
  labs(title = "2b. Hourly demand profile: weekdays vs weekends", x =
"Pickup hour (0-23)", y = "Average trips per day")
save_plot(p, "02b_weekday_vs_weekend_hourly")
```



Weekdays show morning and evening commuter peaks; weekends have no morning peak but much higher late-night demand (0–3 h).


In [45]:
```
p <- ggplot(monthly, aes(month, trips_per_day / 1e3)) +
  geom_col(fill = "#1F4E79") +
  geom_text(aes(label = paste0(comma(trips_per_day), "\n(", revenue_musd,
" M USD)")), vjust = -0.2, size = 3.6) +
  scale_y_continuous(expand = expansion(mult = c(0, 0.2))) +
  labs(title = "3. Monthly taxi demand", subtitle = "Average trips per day
```

```
(labels: trips/day and monthly revenue)",
       x = "Month (2024)", y = "Average trips per day (thousands)")
save_plot(p, "03_monthly_demand")
```




January and February are the quietest months; demand peaks in spring (March–May).

In [46]:
```
fare_trend <- trips[, .(avg_fare = mean(fare_amount), avg_total =
mean(total_amount)), by = .(month, time_period)]
p <- ggplot(fare_trend, aes(month, avg_fare, colour = time_period, group =
time_period)) +
  geom_line(linewidth = 1.1) + geom_point(size = 2) +
  scale_colour_brewer(palette = "Dark2", name = "Time period") +
  labs(title = "4. Average fare trends by month and time of day", x =
"Month (2024)", y = "Average fare amount (USD)") +
  guides(colour = guide_legend(nrow = 2))
save_plot(p, "04_average_fare_trends")
```




Early-morning trips are consistently the most expensive on average; fares are stable across months.

In [47]:
```
daily[, rev_7d := frollmean(revenue, 7, align = "center")]
p <- ggplot(daily, aes(as.Date(pickup_date))) +
  geom_line(aes(y = revenue / 1e6, colour = "Daily revenue"), alpha = 0.5)
+
  geom_line(aes(y = rev_7d / 1e6, colour = "7-day moving average"),
linewidth = 1.2, na.rm = TRUE) +
  scale_colour_manual(values = c(`Daily revenue` = "grey50", `7-day moving
average` = "#C0392B"), name = NULL) +
  scale_x_date(date_breaks = "1 month", date_labels = "%b") +
  labs(title = "5. Revenue trend", subtitle = "Total amount collected per
day", x = "Date (2024)", y = "Revenue (million USD)")
save_plot(p, "05_revenue_trend")
```




Revenue shows a strong weekly cycle and dips on holidays (e.g. New Year, Memorial Day) and stormy days.

In [48]:
```
top_pu <- trips[, .N, by = pu_zone][order(-N)][1:10]
top_do <- trips[, .N, by = do_zone][order(-N)][1:10]
top_zones <- rbind(top_pu[, .(zone = pu_zone, N, type = "Pickup")],
top_do[, .(zone = do_zone, N, type = "Drop-off")])
top_zones[, zone_in_panel := reorder(paste(zone, type, sep = "___"), N)]
# sort bars separately in each panel
p <- ggplot(top_zones, aes(zone_in_panel, N / 1e3, fill = type)) +
geom_col(show.legend = FALSE) + coord_flip() +
  facet_wrap(~ factor(type, c("Pickup", "Drop-off")), scales = "free_y") +
  scale_x_discrete(labels = function(x) sub("___.*$", "", x)) +
  scale_fill_manual(values = c(Pickup = "#1F4E79", `Drop-off` =
"#E07A00")) +
  labs(title = "6-7. Top 10 pickup and drop-off zones", x = NULL, y =
"Number of trips (thousands)")
save_plot(p, "06_07_top_pickup_dropoff_zones", width = 13)
```




Midtown/Upper East Side and JFK dominate pickups; drop-offs are spread over residential Manhattan zones.

In [49]:
```
tr <- copy(top_routes[1:10])[, route := paste(pu_zone, "->", do_zone)]
p <- ggplot(tr, aes(reorder(route, trips), trips / 1e3)) + geom_col(fill =
"#2E86C1") + coord_flip() +
  geom_text(aes(label = paste0(avg_distance, " mi")), hjust = 1.1, colour
= "white", size = 3.5) +
  labs(title = "8. Most frequently travelled routes", subtitle = "Labels
show average trip distance",
       x = NULL, y = "Number of trips (thousands)")
save_plot(p, "08_top_routes", width = 12)
```




In [50]:
```
rr <- copy(top_rev_routes[1:10])[, route := paste(pu_zone, "->", do_zone)]
p <- ggplot(rr, aes(reorder(route, revenue_musd), revenue_musd)) +
geom_col(fill = "#C0392B") + coord_flip() +
  geom_text(aes(label = paste0("$", revenue_per_trip, "/trip")), hjust =
1.1, colour = "white", size = 3.5) +
  labs(title = "9. Highest-revenue routes", subtitle = "Total amount
collected; labels show revenue per trip",
       x = NULL, y = "Revenue (million USD)")
save_plot(p, "09_top_revenue_routes", width = 12)
```



Short Upper-East-Side hops are the most frequent routes, but the money is made on airport routes, which earn several times more per trip.


In [51]:
```
pb <- pay_borough[pu_borough != "EWR"]
p <- ggplot(pb, aes(pu_borough, share_pct, fill = payment_type)) +
geom_col(position = "fill") +
  scale_y_continuous(labels = percent) + scale_fill_brewer(palette =
"Set2", name = "Payment type") +
  labs(title = "10. Payment-type distribution by pickup borough", x =
"Pickup borough", y = "Share of trips")
save_plot(p, "10_payment_by_borough")
```



Credit cards dominate everywhere, but cash and flex/unknown payments are more common outside Manhattan.

In [52]:
```
hex_samp <- trips[sample(.N, 5e5)][trip_distance <= 30 & fare_amount <=
150]
p <- ggplot(hex_samp, aes(trip_distance, fare_amount)) +
  geom_hex(bins = 70) + scale_fill_viridis_c(trans = "log10", name =
"Trips (log scale)") +
  geom_smooth(method = "lm", formula = y ~ x, colour = "red", linewidth =
```

```
1) +
  labs(title = "11. Trip distance vs fare amount", subtitle = "500,000-
trip random sample; red line = linear fit",
       x = "Trip distance (miles)", y = "Fare amount (USD)")
save_plot(p, "11_distance_vs_fare")
```




Fare rises almost linearly with distance. The horizontal band at ≈ 70 USD is the JFK–Manhattan flat fare.

In [53]:


```
bp <- bench_all[comparison %in% c("A: row-level fare per mile", "B:
grouped mean by borough x hour", "E: revenue by month x hour", "G: join 2M
trips with zones")]
bp[, fast_style := grepl("data.table|vectorized", approach)]
bp[, approach_in_panel := reorder(paste(approach, comparison, sep =
"___"), median_ms)]   # sort within each panel
p <- ggplot(bp, aes(approach_in_panel, median_ms, colour = fast_style)) +
  geom_segment(aes(xend = approach_in_panel, y = 0.1, yend = median_ms),
linewidth = 1.2, show.legend = FALSE) +
  geom_point(size = 3.5, show.legend = FALSE) +
  geom_text(aes(label = ifelse(median_ms >= 10, comma(median_ms, accuracy
= 1), round(median_ms, 2))), hjust = -0.3, size = 3.4, colour = "black") +
  coord_flip() + facet_wrap(~ comparison, scales = "free_y", ncol = 2) +
  scale_x_discrete(labels = function(x) sub("___.*$", "", x)) +
  scale_y_log10(labels = comma, expand = expansion(mult = c(0, 0.25))) +
  scale_colour_manual(values = c(`FALSE` = "grey55", `TRUE` = "#27AE60"))
+
  labs(title = "12. Benchmark: execution time of different R approaches",
subtitle = "Median of repeated runs, log scale (green = vectorized /
data.table)",
       x = NULL, y = "Median execution time (ms, log scale)")
save_plot(p, "12_benchmark_comparison", width = 14, height = 8)
```



In [54]:
```
p <- ggplot(scaling, aes(cores, speedup)) +
  geom_abline(slope = 1, intercept = 0, linetype = "dashed", colour =
"grey50") +
  geom_line(colour = "#8E44AD", linewidth = 1.2) + geom_point(size = 3,
colour = "#8E44AD") +
  geom_text(aes(label = paste0(speedup, "x")), vjust = -1) +
  scale_x_continuous(breaks = scaling$cores) + expand_limits(y = 0) +
  labs(title = "13. Parallel speedup (bootstrap per month)", subtitle =
"Dashed line = ideal linear speedup",
       x = "Number of worker cores", y = "Speedup (sequential time /
parallel time)")
save_plot(p, "13_parallel_speedup", width = 9)
```



In [55]:
```
p <- ggplot(scal, aes(rows, median_ms / 1000, colour = approach)) +
geom_line(linewidth = 1.1) + geom_point(size = 2) +
  scale_x_log10(labels = label_number(scale_cut = cut_short_scale())) +
scale_y_log10() +
  scale_colour_brewer(palette = "Set1", name = NULL) +
  labs(title = "14. Scalability: grouped mean by pickup zone", x = "Number
of rows (log scale)", y = "Execution time (seconds, log scale)")
save_plot(p, "14_scalability")
```



data.table is fastest for every size and the gap widens as the number of rows grows; parallel speedup is real but sub-linear.


8.1 Optional advanced task – geographical visualizations

Zone polygons from the official TLC shapefile are used for a static choropleth (ggplot2 + sf) and an interactive **leaflet** map of the top pickup zones.

In [56]:
```
suppressPackageStartupMessages({ library(sf); library(leaflet);
library(htmlwidgets) })
shape_dir <- file.path(DATA_DIR, "taxi_zones")
if (!dir.exists(shape_dir)) unzip(shape_zip, exdir = shape_dir)
shp <- list.files(shape_dir, pattern = "\\.shp$", recursive = TRUE,
full.names = TRUE)[1]
zones_sf <- st_transform(st_make_valid(st_read(shp, quiet = TRUE)), 4326)
zone_stats <- trips[, .(pickups = .N, revenue = sum(total_amount),
avg_total = mean(total_amount)), by = .(LocationID = PULocationID)]
zones_sf <- merge(zones_sf, zone_stats, by = "LocationID", all.x = TRUE)

p <- ggplot(zones_sf) + geom_sf(aes(fill = pickups), colour = "white",
linewidth = 0.05) +
  scale_fill_viridis_c(trans = "log10", labels = comma, name = "Pickups
(log)", na.value = "grey90") +
  labs(title = "15. Pickups by taxi zone, Jan-Jun 2024") +
theme_void(base_size = 13) + theme(legend.position = "right", plot.title =
element_text(face = "bold"))
save_plot(p, "15_pickup_map", width = 9, height = 9)
```

15. Pickups by taxi zone, Jan-Jun 2024



In [57]:

```
top_sf <- zones_sf[order(-zones_sf$revenue), ][1:25, ]
cent <- suppressWarnings(st_coordinates(st_centroid(top_sf)))
top_sf$lng <- cent[, 1]; top_sf$lat <- cent[, 2]
pal <- colorNumeric("YlOrRd", domain = top_sf$avg_total)
m <- leaflet(top_sf) |>
  addProviderTiles(providers$CartoDB.Positron) |>
  addPolygons(data = zones_sf, weight = 0.4, color = "grey", fillOpacity =
0.05) |>
  addCircleMarkers(~lng, ~lat, radius = ~sqrt(pickups) / 60, color =
~pal(avg_total), fillOpacity = 0.8, stroke = FALSE,
                   label = ~sprintf("%s (%s): %s pickups, $%s M revenue,
$%.2f avg", zone, borough, comma(pickups), round(revenue / 1e6, 1),
avg_total)) |>
  addLegend("bottomright", pal = pal, values = ~avg_total, title = "Avg
total (USD)")
saveWidget(m, file.path(normalizePath(OUT_DIR),
"leaflet_top_revenue_zones.html"), selfcontained = TRUE)
m
```

The busiest and highest-revenue zones are concentrated in Midtown/Lower Manhattan, while the two airports (JFK, LaGuardia) stand out with the highest average amount per trip. Open `outputs/leaflet_top_revenue_zones.html` *for the interactive map.*

---

9. Observations

The key measured numbers from this run are collected below (they will vary slightly between machines).

In [58]:
```
bm <- function(cmp, appr) bench_all[comparison == cmp & approach == appr,
median_ms]
obs <- data.table(
  metric = c("Trips analysed (after cleaning)", "Peak pickup hour",
"Busiest weekday (avg trips/day)", "Busiest month (avg trips/day)",
             "Top revenue route", "Credit-card share of trips (%)",
"Distance-fare correlation",
             "Row-level: apply() vs vectorized (x slower)", "Grouping 2M:
lapply(split()) vs data.table (x slower)",
             "Grouping 20M: aggregate() vs data.table (x slower)", "Join
2M: merge() vs data.table (x slower)",
             sprintf("Parallel speedup with %d cores", N_CORES), "Light
task: parallel vs sequential (speedup)"),
  value = c(format(nrow(trips), big.mark = ","),
paste0(hourly[which.max(trips), pickup_hour], ":00"),
            as.character(dow[which.max(avg_trips_per_day), pickup_wday]),
as.character(monthly[which.max(trips_per_day), month]),
            top_rev_routes[1, paste(pu_zone, "->", do_zone)],
pay_overall[payment_type == "Credit card", share_pct],
```

```
            round(trips[, cor(trip_distance, fare_amount)], 3),
            round(bm("A: row-level fare per mile", "apply()") / bm("A:
row-level fare per mile", "vectorized")),
            round(bm("B: grouped mean by borough x hour",
"lapply(split())") / bm("B: grouped mean by borough x hour", "data.table
by")),
            round(bm("E: revenue by month x hour", "base R aggregate()") /
bm("E: revenue by month x hour", "data.table by")),
            round(bm("G: join 2M trips with zones", "base R merge()") /
bm("G: join 2M trips with zones", "data.table join")),
            paste0(speedup_main, "x"), paste0(light[2, speedup_vs_seq],
"x")))
obs
```

A data.table: 13 × 2

metric	value
<chr>	<chr>
Trips analysed (after cleaning)	19,650,216
Peak pickup hour	18:00
Busiest weekday (avg trips/day)	Thu
Busiest month (avg trips/day)	May
Top revenue route	JFK Airport → Outside of NYC
Credit-card share of trips (%)	76.2
Distance-fare correlation	0.936
Row-level: apply() vs vectorized (x slower)	2951
Grouping 2M: lapply(split()) vs data.table (x slower)	6
Grouping 20M: aggregate() vs data.table (x slower)	30
Join 2M: merge() vs data.table (x slower)	23
Parallel speedup with 3 cores	2.2x
Light task: parallel vs sequential (speedup)	0.03x

1. **Demand** is strongly time dependent: an evening peak around 17–18 h, a minimum at 4–5 AM, the highest per-day demand on mid-week days and the lowest on Sundays, and a spring high after the winter months.
2. **Revenue** is concentrated in the midday and evening-rush periods, while **airport routes** (JFK, LaGuardia) generate by far the highest revenue per trip and dominate the highest-revenue routes.
3. **Fare vs distance** is strongly linear, but the fare per mile is highest for very short trips.
4. **Payments:** credit cards account for about three quarters of trips; cash and unrecorded ("flex/unknown") payments are relatively more common outside Manhattan, and tips are recorded almost only for card payments.
5. **Performance:** data.table and vectorized operations were faster than functional row-wise code by orders of magnitude; data.table beat base R

`aggregate()` / `merge()` by a large factor while using less memory; parallel processing gave a real but sub-linear speedup for the heavy bootstrap and was slower for the light task.

---

10. Task 7 – Critical Analysis and Recommendation

1. Which approach provides the best execution performance? data.table for data manipulation (filter, group, sort, join) and **vectorized** code for element-wise arithmetic. In the benchmarks data.table was the fastest entry for filtering, grouping and sorting, many times faster than base R `aggregate()` and `merge()`, and vectorized arithmetic was thousands of times faster than row-wise `apply()`. The exceptions are instructive: a single-column `match()` lookup beat the data.table join, and functional `lapply()` over a few columns matched data.table – iterating over a few large units costs nothing.

2. How does data.table improve the processing of large datasets? (a) Operations are implemented in optimised, **multi-threaded C** (radix sorting and grouping, GForce for `mean` / `sum`); (b) `:=`, `set()`, `setkey()`, `setorder()` and update joins modify data **by reference**, so a 20-million-row table is never copied – visible in the much lower peak memory of the update join; (c) `fread()` / `setDT()` give fast import; (d) the concise `DT[i, j, by]` syntax combines filtering, computing and grouping in one optimised step.

3. When is functional programming preferable? When iterating over a **small number of large items** – columns, files, months, model specifications, groups – where the per-call overhead is negligible (Experiment C showed `lapply()` / `map_dbl()` as fast as `colMeans()`), and when clarity and composability matter (purrr's type-stable `map_dbl()`, pipelines, applying the same function to every partition). It is also the natural interface to parallelism (`foreach`, `parLapply`). It should not be used to loop over millions of rows.

4. When do vectorized operations provide better performance? Whenever the same operation is applied to every element of a vector/column (arithmetic, comparisons, `ifelse`, `pmin`, cumulative functions): one call into compiled code replaces millions of interpreted R calls, giving the 1000×-scale gains measured in Experiment A.

5. What performance improvement was obtained using parallel computing? For the CPU-intensive month-wise bootstrap the measured speedup is shown in the scaling table (Section 6.5) and the observations table – a clear gain that increases with the number of cores but stays below the ideal (efficiency below 100 %).

6. Does parallel computing always result in faster execution? No. The lightweight task (mean fare per month) was *slower* in parallel than sequentially, because starting workers and serialising ≈ 600 MB of partitions costs much more than the computation. Even for the heavy task, overheads (data transfer, uneven number of partitions per

worker, memory bandwidth) prevent linear speedup. A single multi-threaded data.table grouping was faster than both partitioned versions for the light task. Parallelism helps only when the computation per partition is large relative to the communication cost.

7. Trade-offs between speed, memory, readability and scalability

Approach	Speed	Memory	Readability	Scalability
`apply()` / `lapply()` / `map()` per row	very slow	high (per-call allocation, matrix copy)	good	poor
`for` loop (pre-allocated)	very slow	low	good for beginners, verbose	poor
Vectorized base R	very fast	moderate (temporary vectors)	very good	good
Base R `aggregate()` / `merge()`	slow	high (copies)	good	moderate
data.table	fastest	lowest (by reference)	good once learnt, terse syntax	excellent
foreach + doParallel	faster only for heavy tasks	high (data copied to every worker)	more complex code	good for CPU-bound, independent tasks

8. Recommendation for large-scale analytical applications Use **data.table as the core engine** (import with arrow/fread, clean, join and aggregate by reference), write element-wise logic in **vectorized** form, use **functional programming** (`lapply` / `purrr::map`) for iterating over files, columns or partitions, and add **foreach + doParallel** only for genuinely CPU-intensive, independent tasks such as bootstrapping, simulation or model fitting per partition – after checking with a benchmark that the speedup outweighs the overhead. This recommendation is directly supported by the benchmark and speedup tables obtained in this notebook.

---

11. Conclusion

An end-to-end, reproducible big-data workflow was built in R for ≈ 20 million NYC Yellow Taxi trips (January–June 2024). data.table made it possible to import, clean, enrich, join and aggregate the full dataset in seconds on a laptop with modest memory, by working in place. The analysis showed clear temporal demand patterns, the dominance of credit-card payments and the outsized revenue of airport routes. The benchmarks demonstrated that **how** R code is written matters more than the hardware: row-wise functional code was thousands of times slower than vectorized

code, base R grouping and joining were many times slower and more memory hungry than data.table, and parallel computing with foreach/doParallel delivered a useful but sub-linear speedup only for compute-heavy work. The recommended architecture is therefore data.table + vectorization at the core, functional programming for iteration over a few large units, and parallelism only where benchmarks prove it worthwhile.

In [59]:
```
sessionInfo()
```

```
R version 4.6.1 (2026-06-24)
Platform: x86_64-pc-linux-gnu
Running under: Ubuntu 24.04.5 LTS

Matrix products: default
BLAS:   /usr/lib/x86_64-linux-gnu/blas/libblas.so.3.12.0
LAPACK: /usr/lib/x86_64-linux-gnu/lapack/liblapack.so.3.12.0  LAPACK version 3.12.0

locale:
 [1] LC_CTYPE=C.UTF-8    LC_NUMERIC=C        LC_TIME=C           LC_COLLATE=C        LC_MONETARY=C
LC_MESSAGES=C
 [7] LC_PAPER=C          LC_NAME=C           LC_ADDRESS=C        LC_TELEPHONE=C      LC_MEASUREMENT=C
LC_IDENTIFICATION=C

time zone: Etc/UTC
tzcode source: system (glibc)

attached base packages:
[1] parallel  stats     graphics  grDevices utils     datasets  methods   base

other attached packages:
 [1] htmlwidgets_1.6.4    leaflet_2.2.3        sf_1.1-3             scales_1.4.0         lubridate_1.9.5
purrr_1.2.2
 [7] microbenchmark_1.5.0 doParallel_1.0.17    iterators_1.0.14     foreach_1.5.2        ggplot2_4.0.3
arrow_26.0.0
[13] data.table_1.18.6.1

loaded via a namespace (and not attached):
 [1] s2_1.1.13               generics_0.1.4          class_7.3-24            KernSmooth_2.23-27
lattice_0.23-1
 [6] digest_0.6.39           magrittr_2.0.5          evaluate_1.0.5          grid_4.6.1
timechange_0.4.0
[11] RColorBrewer_1.1-3      pbdZMQ_0.3-14           fastmap_1.2.0           jsonlite_2.0.0
e1071_1.7-17
[16] DBI_1.3.0               viridisLite_0.4.3       crosstalk_1.2.2         jquerylib_0.1.4
codetools_0.2-20
[21] cli_3.6.6               rlang_1.3.0             crayon_1.5.3            units_1.0-1
bit64_4.8.6
[26] yaml_2.3.12             base64enc_0.1-6         withr_3.0.3             repr_1.1.7
tools_4.6.1
[31] uuid_1.2-2              assertthat_0.2.1        IRdisplay_1.1           vctrs_0.7.3
R6_2.6.1
[36] proxy_0.4-29            lifecycle_1.0.5         classInt_0.4-11         leaflet.providers_3.0.0
bit_4.6.0
[41] pillar_1.11.1           hexbin_1.28.6           gtable_0.3.6            glue_1.8.1
Rcpp_1.1.2
[46] xfun_0.62               tidyselect_1.2.1        knitr_1.52              IRkernel_1.3.2
farver_2.1.2
[51] htmltools_0.5.9         rmarkdown_2.32          labeling_0.4.3          wk_0.9.5
compiler_4.6.1
[56] S7_0.2.2
```