Here are few screenshots of my Live Italian to English Translation project.

I have used images with Italian text and kept infront of my laptop. Using web cam I can detect the Italian text and translate it to English.

```
131
132
133
134
135
136
137
138
139
140
141 # i
142 pyt
143 cap
144 net
145
146 # i
147 fil
148 for
149
150 tot
151 ind = 0
152
153 #while cv2.waitKey(1) < 0:
154 #while (cap.isOpened()):
155 while (cap.isOpened() and cv2.waitKey(1) != ord('q')):
156
157
158     # read images one by one
159     hasFrame, image = cap.read()
160     #image = cv2.imread(file_names[ind])
161     #ind += 1
162
163     if not hasFrame:
164         break
165
166     # Get image shapes
167     orig = image
168     orig2 = image
```

```
:/Applied_AI/Case_Studies/
run_attention_from_image.py', wdir='D:/
ies/case_study_2/test')
oaded

:/Applied_AI/Case_Studies/
_attention_from_image.py', wdir='D:/
ies/case_study_2/test')
oaded

:/Applied_AI/Case_Studies/
_attention_from_image.py', wdir='D:/
ies/case_study_2/test')
oaded

case_study_2/test/run_attention_from_video.py', wdir='D:/
Applied_AI/Case_Studies/case_study_2/test')
Checkpoint already loaded

In [117]: runfile('D:/Applied_AI/Case_Studies/
case_study_2/test/run_attention_from_video.py', wdir='D:/
Applied_AI/Case_Studies/case_study_2/test')
Checkpoint already loaded

In [118]: runfile('D:/Applied_AI/Case_Studies/
case_study_2/test/run_attention_from_video.py', wdir='D:/
Applied_AI/Case_Studies/case_study_2/test')
Checkpoint already loaded

In [119]: runfile('D:/Applied_AI/Case_Studies/
case_study_2/test/run_attention_from_video.py', wdir='D:/
Applied_AI/Case_Studies/case_study_2/test')
Checkpoint already loaded
```

```
131
132
133
134
135
136
137
138
139
140
141 # i
142 pyt
143 cap
144 net
145
146 # i
147 fil
148 for
149
150 tot
151 ind = 0
152
153 #while cv2.waitKey(1) < 0:
154 #while (cap.isOpened()):
155 while (cap.isOpened() and cv2.waitKey(1) != ord('q')):
156
157
158     # read images one by one
159     hasFrame, image = cap.read()
160     #image = cv2.imread(file_names[ind])
161     #ind += 1
162
163     if not hasFrame:
164         break
165
166     # Get image shapes
167     orig = image
168     orig2 = image
```

```
:/Applied_AI/Case_Studies/
n_attention_from_image.py', wdir='D:/
ies/case_study_2/test')
oaded

:/Applied_AI/Case_Studies/
_attention_from_image.py', wdir='D:/
ies/case_study_2/test')
oaded

:/Applied_AI/Case_Studies/
_attention_from_image.py', wdir='D:/
ies/case_study_2/test')
oaded

case_study_2/test/run_attention_from_video.py', wdir='D:/
Applied_AI/Case_Studies/case_study_2/test')
Checkpoint already loaded

In [117]: runfile('D:/Applied_AI/Case_Studies/
case_study_2/test/run_attention_from_video.py', wdir='D:/
Applied_AI/Case_Studies/case_study_2/test')
Checkpoint already loaded

In [118]: runfile('D:/Applied_AI/Case_Studies/
case_study_2/test/run_attention_from_video.py', wdir='D:/
Applied_AI/Case_Studies/case_study_2/test')
Checkpoint already loaded

In [119]: runfile('D:/Applied_AI/Case_Studies/
case_study_2/test/run_attention_from_video.py', wdir='D:/
Applied_AI/Case_Studies/case_study_2/test')
Checkpoint already loaded
```