

SR UNIVERSITY

AI ASSISTED CODING LAB ASSIGNMENT

Name: M.Swathi

HTNO: 2503A51L12


Lab 12: Algorithms with AI Assistance – Sorting, Searching, and Optimizing Algorithms

Lab Objectives:

- Apply AI-assisted programming to implement and optimize sorting and searching algorithms.
- Compare different algorithms in terms of efficiency and use cases.
- Understand how AI tools can suggest optimized code and complexity improvements.

Task Description #1 (Sorting – Merge Sort Implementation):

Given prompt to AI:



Given program by AI:

```
merge_sort.py > _main
1  """Merge Sort implementation with tests.
2
3  This module defines a stable merge sort function `merge_sort(arr)` that returns a
4  new list sorted in ascending order.
5  """
6
7  from __future__ import annotations
8  from typing import List, TypeVar, Iterable
9  import argparse
10 import sys
11
12
13 T = TypeVar("T")
14
15
16 def merge_sort(arr: Iterable[T]) -> List[T]:
17     """Return a new list containing the elements of `arr` sorted ascending using Merge Sort.
18
19     Merge Sort is a stable, divide-and-conquer sorting algorithm. This implementation
20     is non-mutating: it does not modify the input iterable and instead returns a new list.
21
22     Time Complexity:
23     - Best:    O(n log n)
24     - Average: O(n log n)
25     - Worst:   O(n log n)
26
27     Space Complexity:
28     - O(n) additional space for the temporary arrays used during merging.
29
30     Args:
31     |     arr: An iterable of comparable elements.
32
33     Returns:
34     |     A new list containing the elements of `arr` sorted ascending.
35     """
36     return _merge_sort(arr)
```

Problems Output Debug Console Terminal Ports + v ...

```

merge_sort.py > _main
16 def merge_sort(arr: Iterable[T]) -> List[T]:
17     >>
18
19
20
21
22
23
24
25
26
27     # Convert to List to allow slicing and length operations if not already a list
28     items: List[T] = list(arr)
29
30
31
32
33
34
35
36
37
38
39
40     def _merge(left: List[T], right: List[T]) -> List[T]:
41         merged: List[T] = []
42         i = 0
43         j = 0
44         # Merge while preserving stability: when elements are equal, take from left first
45         while i < len(left) and j < len(right):
46             if left[i] <= right[j]:
47                 merged.append(left[i])
48                 i += 1
49             else:
50                 merged.append(right[j])
51                 j += 1
52         # Append any remaining elements
53         if i < len(left):
54             merged.extend(left[i:])
55         if j < len(right):
56             merged.extend(right[j:])
57         return merged
58
59     def _merge_sort(xs: List[T]) -> List[T]:
60         if len(xs) <= 1:
61             return xs
62         mid = len(xs) // 2
63         left_sorted = _merge_sort(xs[:mid])
64         right_sorted = _merge_sort(xs[mid:])
65         return _merge(left_sorted, right_sorted)
66

```

```

merge_sort.py > _main
70 def _run_tests() -> None:
71     # Basic cases
72     assert merge_sort([]) == []
73     assert merge_sort([1]) == [1]
74     assert merge_sort([1, 2, 3]) == [1, 2, 3]
75     assert merge_sort([3, 2, 1]) == [1, 2, 3]
76
77     # Duplicates and stability check: equal elements preserve relative order
78     class StableCheck:
79         def __init__(self, key: int, tag: str) -> None:
80             self.key = key
81             self.tag = tag
82
83         def __le__(self, other: "StableCheck") -> bool: # type: ignore[override]
84             return self.key <= other.key
85
86         def __repr__(self) -> str:
87             return f"({self.key},{self.tag})"
88
89     items = [StableCheck(2, "a"), StableCheck(1, "x"), StableCheck(2, "b"), StableCheck(1, "y")]
90     sorted_items = merge_sort(items)
91     # keys should be [1,1,2,2] and tags for equal keys should maintain original order (x before y, a before b)
92     assert [it.key for it in sorted_items] == [1, 1, 2, 2]
93     assert [it.tag for it in sorted_items if it.key == 1] == ["x", "y"]
94     assert [it.tag for it in sorted_items if it.key == 2] == ["a", "b"]
95
96     # Negative numbers and mixed values
97     assert merge_sort([0, -1, 5, -10, 8, 8, 3]) == [-10, -1, 0, 3, 5, 8, 8]
98
99     # Already sorted and reverse-sorted
100     assert merge_sort(list(range(20))) == list(range(20))
101     assert merge_sort(list(range(20, -1, -1))) == list(range(21))

```

```

merge_sort.py > _main
114 def _parse_tokens(tokens: List[str]) -> List[float] | List[str]:
115     # can
116     return numeric_values if all_numeric else tokens
117
118
119 def _main() -> None:
120     parser = argparse.ArgumentParser(description="Merge Sort utility")
121     parser.add_argument("values", nargs="*", help="Values to sort (space-separated). If omitted, reads a line from
122     parser.add_argument("--test", action="store_true", help="Run internal tests and exit.")
123     args = parser.parse_args()
124
125     if args.test:
126         _run_tests()
127         return
128
129     tokens: List[str]
130     if args.values:
131         tokens = args.values
132     elif not sys.stdin.isatty():
133         # Read all stdin only when data is being piped in
134         data = sys.stdin.read().strip()
135         tokens = data.split()
136     else:
137         # Interactive terminal with no args: use a default demo list
138         tokens = ["5", "2", "9", "1", "5", "6"]
139
140     parsed = _parse_tokens(tokens)
141     result = merge_sort(parsed)
142     print(" ".join(str(x) for x in result))
143
144
145 if __name__ == "__main__":
146     _main()
147

```

Output:

```

Problems Output Debug Console Terminal Ports
PS C:\Users\musta\.cursor> & C:/Users/musta/AppData/Local/Programs/Python/Python313/python.exe c:/Users/musta/.cursor/merge_sort.py
1.0 2.0 5.0 5.0 6.0 9.0
PS C:\Users\musta\.cursor>

```

Observation:

The program executed successfully and printed the sorted list in ascending order: 1.0 2.0 5.0 5.0 6.0 9.0.

This confirms that your merge_sort.py implementation is working correctly.

Task Description #2 (Searching – Binary Search with AI Optimization):

Given prompt to AI:

@Add Context 10.1%

create a binary search function that finds a target element in a sorted list
create a function `binary_search(arr, target)` returning the index of the target or -1 if not found.
Include docstrings explaining best, average, and worst-case complexities.
Test with various inputs.

Given program by AI:

```
binary_search.py > ...
1  """Binary Search implementation with tests.
2
3  This module defines a function `binary_search(arr, target)` that finds the index of
4  `target` in a sorted list `arr` or returns -1 when the `target` is not present.
5  """
6
7  from __future__ import annotations
8  from typing import List, Sequence, TypeVar, Protocol, runtime_checkable
9
10
11 @runtime_checkable
12 class SupportsRichComparison(Protocol):
13     def __lt__(self, other: "SupportsRichComparison", /) -> bool: ...
14     def __le__(self, other: "SupportsRichComparison", /) -> bool: ...
15     def __gt__(self, other: "SupportsRichComparison", /) -> bool: ...
16     def __ge__(self, other: "SupportsRichComparison", /) -> bool: ...
17     def __eq__(self, other: object, /) -> bool: ...
18
19
20 T = TypeVar("T", bound=SupportsRichComparison)
21
22
23 def binary_search(arr: Sequence[T], target: T) -> int:
24     """Return the index of `target` in sorted sequence `arr`, or -1 if not found.
25
26     The input sequence must be sorted in ascending order according to the elements' ordering.
27
28     Time Complexity:
29     - Best:    O(1)   when the middle element equals the target on the first check
30     - Average: O(log n)
31     - Worst:   O(log n)
32
33     Space Complexity:
```

binary_search.py > ...

```
23 def binary_search(arr: Sequence[T], target: T) -> int:
39
40     Returns:
41     |     The index of `target` in `arr` if present; otherwise -1.
42     |     """
43
44     left = 0
45     right = len(arr) - 1
46
47     while left <= right:
48         mid = left + (right - left) // 2
49         mid_value = arr[mid]
50
51         if mid_value == target:
52             return mid
53         if mid_value < target:
54             left = mid + 1
55         else:
56             right = mid - 1
57
58     return -1
59
60
61 def _run_tests() -> None:
62     # Empty and single-element cases
63     arr: List[int]
64     arr = []
65     target = 1
66     result = binary_search(arr, target)
67     print(f"arr={arr}, target={target} -> index={result}")
68     assert result == -1
69
70     arr = [5]
```

```

binary_search.py > _run_tests
61 def _run_tests() -> None:
62     target = 3
63     result = binary_search(arr, target)
64     print(f"arr={arr}, target={target} -> index={result}")
65     assert result == -1
66     arr = [1, 3, 5, 7, 9, 11]
67     for i, v in enumerate(arr):
68         result = binary_search(arr, v)
69         print(f"arr={arr}, target={v} -> index={result}")
70         assert result == i
71     for v in [0, 2, 4, 6, 8, 10, 12]:
72         result = binary_search(arr, v)
73         print(f"arr={arr}, target={v} -> index={result}")
74         assert result == -1
75     dup = [1, 2, 2, 2, 3, 4]
76     idx = binary_search(dup, 2)
77     print(f"arr={dup}, target=2 -> index={idx}")
78     assert idx in {1, 2, 3}
79     neg = [-10, -3, -1, 0, 2, 4]
80     res = binary_search(neg, -3)
81     print(f"arr={neg}, target=-3 -> index={res}")
82     assert res == 1
83     res = binary_search(neg, 1)
84     print(f"arr={neg}, target=1 -> index={res}")
85     assert res == -1
86     big = list(range(-1000, 1001))
87     for probe in [-1000, -500, 0, 123, 1000]:
88         res = binary_search(big, probe)
89         print(f"arr=[-1000..1000], target={probe} -> index={res}")
90         assert res == big.index(probe)
91     print("All binary search tests passed.")
92
93     res = binary_search(neg, 1)
94     print(f"arr={neg}, target=1 -> index={res}")
95     assert res == -1
96     big = list(range(-1000, 1001))
97     for probe in [-1000, -500, 0, 123, 1000]:
98         res = binary_search(big, probe)
99         print(f"arr=[-1000..1000], target={probe} -> index={res}")
100         assert res == big.index(probe)
101
102     print("All binary_search tests passed.")
103
104
105
106
107
108
109
110 if __name__ == "__main__":
111     _run_tests()
112
113

```

Output:

```
PS C:\Users\musta\.cursor> & C:/Users/musta/AppData/Local/Programs/Python/Python313/python.exe c:/Users/musta/.cursor/binary_search.py
arr=[], target=1 -> index=-1
arr=[5], target=5 -> index=0
arr=[5], target=3 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=1 -> index=0
arr=[1, 3, 5, 7, 9, 11], target=3 -> index=1
arr=[1, 3, 5, 7, 9, 11], target=5 -> index=2
arr=[1, 3, 5, 7, 9, 11], target=7 -> index=3
arr=[1, 3, 5, 7, 9, 11], target=9 -> index=4
arr=[1, 3, 5, 7, 9, 11], target=11 -> index=5
arr=[1, 3, 5, 7, 9, 11], target=0 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=2 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=4 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=6 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=8 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=11 -> index=5
arr=[1, 3, 5, 7, 9, 11], target=0 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=2 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=4 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=6 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=8 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=2 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=4 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=6 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=8 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=4 -> index=-1
arr=[1, 3, 5, 7, 9, 11], target=6 -> index=-1
```


```
arr=[1, 2, 2, 2, 3, 4], target=2 -> index=2
arr=[-10, -3, -1, 0, 2, 4], target=-3 -> index=1
arr=[-10, -3, -1, 0, 2, 4], target=1 -> index=-1
arr=[-10, -3, -1, 0, 2, 4], target=-3 -> index=1
arr=[-10, -3, -1, 0, 2, 4], target=1 -> index=-1
arr=[-10, -3, -1, 0, 2, 4], target=1 -> index=-1
arr=[-1000..1000], target=-1000 -> index=0
arr=[-1000..1000], target=-500 -> index=500
arr=[-1000..1000], target=-1000 -> index=0
arr=[-1000..1000], target=-500 -> index=500
arr=[-1000..1000], target=0 -> index=1000
arr=[-1000..1000], target=0 -> index=1000
arr=[-1000..1000], target=123 -> index=1123
arr=[-1000..1000], target=123 -> index=1123
arr=[-1000..1000], target=1000 -> index=2000
arr=[-1000..1000], target=1000 -> index=2000
All binary_search tests passed.
PS C:\Users\musta\.cursor>
```

Observation:

binary_search.py implementation is working correctly — all test cases passed, returning correct indices for both small and large datasets

Task Description #3 (Real-Time Application – Inventory Management System):

Given prompt to AI:



Given program by AI:

```
inventory_algorithms.py > _demo
1  """Simple inventory search and sorting with concise demo output.
2
3  Recommendations (for thousands of products):
4  - Search by ID: Hash map (dict) for O(1) average lookups.
5  - Search by exact name: Dict of name->list for O(1) average lookups.
6  - Sort by price/quantity: Built-in `sorted` (Timsort), O(n log n), stable.
7  """
8
9  from __future__ import annotations
10 from dataclasses import dataclass
11 from typing import Dict, List, Iterable, Optional
12
13
14 @dataclass(frozen=True)
15 class Product:
16     product_id: int
17     name: str
18     price: float
19     quantity: int
20 def index_by_id(products: Iterable[Product]) -> Dict[int, Product]:
21     return {p.product_id: p for p in products}
22
23
24 def index_by_name(products: Iterable[Product]) -> Dict[str, List[Product]]:
25     name_index: Dict[str, List[Product]] = {}
26     for p in products:
27         key = p.name.lower()
28         name_index.setdefault(key, []).append(p)
29     return name_index
30
31
32 def search_by_id(id_index: Dict[int, Product], product_id: int) -> Optional[Product]:
33     return id_index.get(product_id)
34
```

inventory_algorithms.py > _demo

```
36 def search_by_name(name_index: Dict[str, List[Product]], name: str) -> List[Product]:
37     return list(name_index.get(name.lower(), []))
38
39
40 def sort_by_price(products: Iterable[Product], ascending: bool = True) -> List[Product]:
41     return sorted(products, key=lambda p: p.price, reverse=not ascending)
42
43
44 def sort_by_quantity(products: Iterable[Product], ascending: bool = True) -> List[Product]:
45     return sorted(products, key=lambda p: p.quantity, reverse=not ascending)
46
47 def _print_recommendations_table() -> None:
48     print("Operation | Algorithm | Why")
49     print("-" * 48)
50     print("Search by ID | dict | O(1) average lookups")
51     print("Search by name | dict[name]->list | O(1) average lookups")
52     print("Sort by price | sorted (Timsort) | O(n log n), stable")
53     print("Sort by quantity | sorted (Timsort) | O(n log n), stable")
54
55
56 def _demo() -> None:
57     products = [
58         Product(101, "Apple iPhone 15", 999.0, 12),
59         Product(205, "Samsung Galaxy S23", 849.0, 7),
60         Product(309, "Google Pixel 8", 799.0, 15),
61         Product(411, "Apple AirPods Pro", 249.0, 30),
62         Product(512, "Anker Charger", 39.0, 120),
63         Product(613, "Apple Watch", 429.0, 18),
64         Product(714, "Samsung Buds", 149.0, 26),
65     ]
66
67     id_index = index_by_id(products)
68     name_index = index_by_name(products)
69
70     print("\n=== Recommendations ===")
71     _print_recommendations_table()
72     print("\n=== Search ===")
```

inventory_algorithms.py > _demo

```
56 def _demo() -> None:
57     products = [
58         Product(101, "Apple iPhone 15", 999.0, 12),
59         Product(205, "Samsung Galaxy S23", 849.0, 7),
60         Product(309, "Google Pixel 8", 799.0, 15),
61         Product(411, "Apple AirPods Pro", 249.0, 30),
62         Product(512, "Anker Charger", 39.0, 120),
63         Product(613, "Apple Watch", 429.0, 18),
64         Product(714, "Samsung Buds", 149.0, 26),
65     ]
66
67     id_index = index_by_id(products)
68     name_index = index_by_name(products)
69
70     print("\n=== Recommendations ===")
71     _print_recommendations_table()
72     print("\n=== Search ===")
73     found = search_by_id(id_index, 309)
74     print("ID 309 ->", f"{found.name} ({found.price})" if found else None)
75     print("Name 'Apple Watch' ->", [p.name for p in search_by_name(name_index, "Apple Watch")])
76     print("\n=== Sort ===")
77     print("Price asc:", [(p.name, p.price) for p in sort_by_price(products)])
78     print("Qty desc:", [(p.name, p.quantity) for p in sort_by_quantity(products, ascending=False)])
79 if __name__ == "__main__":
80     _demo()
81
82
83
```

Output:

```
PS C:\Users\musta\.cursor> & C:/Users/musta/AppData/Local/Programs/Python/Python313/python.exe c:/Users/musta/.cursor/inventory_algorithms.py

=== Recommendations ===
Operation | Algorithm | Why
-----
Search by ID | dict | O(1) average lookups
Search by name | dict[name]->list | O(1) average lookups
Sort by price | sorted (Timsort) | O(n log n), stable
Sort by quantity | sorted (Timsort) | O(n log n), stable

=== Search ===
ID 309 -> Google Pixel 8 ($799.0)
Name 'Apple Watch' -> ['Apple Watch']

=== Sort ===
Price asc: [('Anker Charger', 39.0), ('Samsung Buds', 149.0), ('Apple AirPods Pro', 249.0), ('Apple Watch', 429.0), ('Google Pixel 8', 799.0), ('Samsung Galaxy S23', 849.0), ('Apple iPhone 15', 999.0)]
Qty desc: [('Anker Charger', 120), ('Apple AirPods Pro', 30), ('Samsung Buds', 26), ('Apple Watch', 18), ('Google Pixel 8', 15), ('Apple iPhone 15', 12), ('Samsung Galaxy S23', 7)]
PS C:\Users\musta\.cursor>
```

Observation:

The program demonstrates searching and sorting items in an inventory using efficient algorithms. It quickly finds products by ID or name and lists them by price or quantity