



1a	<pre> Algorithm Run(n) count ← 0 i ← n while(i > 0) j ← 1 while(j ≤ i) for k ← 1 to n count ← count + 1 j ← j + 2 i ← floor(i / 2) return count </pre> <p>Find the worst-case asymptotic time complexity of the above algorithm in Θ-notation.</p>	06
1b	<pre> INCREMENT(A[0..k-1]) i ← 0 while i < k and A[i] = 1 A[i] ← 0 (toggles the bit) i ← i + 1 if i < k then A[i] ← 1 (toggles the bit) </pre> <p>Using "Aggregate Method", find the amortized cost of the above operation which increments a binary number A[0..k-1].</p>	06
1c	<pre> TABLE-INSERT(T, x) 1 if size[T] = 0 2 then allocate table[T] with 1 slot 3 size[T] ← 1 4 if num[T] = size[T] 5 then allocate new-table with 2 · size[T] slots 6 insert all items in table[T] into new-table 7 free table[T] 8 table[T] ← new-table 9 size[T] ← 2 · size[T] 10 insert x into table[T] 11 num[T] ← num[T] + 1 </pre> <p>Consider the given TABLE-INSERT procedure for inserting a new element x in the dynamic table T. Find the amortized cost of the given TABLE-INSERT procedure using the potential method.</p>	08

2a	Find the pattern "31415" in the text "2359023141526739921" using the Rabin-Karp method. Use radix-10 with "mod 13" for finding the hash values.	06
2b	<p>KMP-MATCHER(T, P)</p> <pre> 1 $n = T.length$ 2 $m = P.length$ 3 $\pi = \text{COMPUTE-PREFIX-FUNCTION}(P)$ 4 $q = 0$ // number of characters matched 5 for $i = 1$ to n // scan the text from left to right 6 while $q > 0$ and $P[q + 1] \neq T[i]$ 7 $q = \pi[q]$ // next character does not match 8 if $P[q + 1] == T[i]$ 9 $q = q + 1$ // next character matches 10 if $q == m$ // is all of P matched? 11 print "Pattern occurs with shift" $i - m$ 12 $q = \pi[q]$ // look for the next match</pre> <p>For the KMP-MATCHER algorithm given above, write the COMPUTE-PREFIX-FUNCTION procedure it requires.</p>	06
2c	Explain an $O(n)$ method of finding the longest common substring of two strings T_1 and T_2 of length $O(n)$ using generalized suffix trees. Use the method to find the longest common substring of $T_1 = \text{"nonsense"}$ and $T_2 = \text{"offense"}$.	08
3a	Find the integers x and y in the equation $840x + 462y = \text{gcd}(840, 462)$ using the extended Euclid's algorithm.	06
3b	Explain the procedure of generating a pair of public-private keys for a participant in the RSA public-key cryptosystem.	06
3c	Let P_A, S_A, P_B, S_B are public-key and secret-key of Alice, and public-key and secret-key of Bob, respectively. Explain with a block diagram, a procedure for: (i) Bob to send message M to Alice confidentially, (ii) Alice to send a short message M' to Bob authenticating it is her who sent the message.	08
4a	<p>What is memoization technique? Write an algorithm using memoization technique to find the binomial coefficient $C(n, k)$ in $O(nk)$ time. Use Pascal's identity given below to find the binomial coefficient.</p> <p>$C(n, k) = C(n-1, k-1) + C(n-1, k)$ for $n > k > 0$ $C(n, 0) = 1, C(n, n) = 1$ for $n \geq 0$</p>	06

4b	Using dynamic programming, find the longest common subsequence of two strings T1 = "GCCCTAGCG" and T2 = "GCGCAATG".	06
4c	Apply dynamic programming to solve the problem of fully parenthesizing for optimally multiplying a chain of n matrices. Find the optimal substructure, recursive solution and write the procedure to find the optimal value (finding an optimal solution is not necessary, just the optional value is needed).	08
5a	Convert the polynomial $A(x) = a_0 + a_1x + a_2x^2 + a_3x^3$ from the coefficient representation to the point-value representation.	06
5b	Explain the addition of two polynomials in point-value representation.	06
5c	<p>RECURSIVE-FFT(a)</p> <pre> 1 $n = a.length$ 2 if $n == 1$ 3 return a 4 $\omega_n = e^{2\pi i/n}$ 5 $\omega = 1$ 6 $a^{[0]} = (a_0, a_2, \dots, a_{n-2})$ 7 $a^{[1]} = (a_1, a_3, \dots, a_{n-1})$ 8 $y^{[0]} = \text{RECURSIVE-FFT}(a^{[0]})$ 9 $y^{[1]} = \text{RECURSIVE-FFT}(a^{[1]})$ 10 for $k = 0$ to $n/2 - 1$ 11 $y_k = y_k^{[0]} + \omega y_k^{[1]}$ 12 $y_{k+(n/2)} = y_k^{[0]} - \omega y_k^{[1]}$ 13 $\omega = \omega \omega_n$ 14 return y </pre> <p>Explain the working of the above FFT algorithm to evaluate coefficient vector a into its value vector y.</p>	08