Five-Model Comparison

Two baselines, the proposed model, the caution-aware model and an image-only model: how each was built, trained, tested and what it achieved

Working document for the project team
Repository state of 12 November 2026

Contents

1 What this document is **3**

2 How every model is tested (the same way for all five) **3**

2.1 The test . . . 3

2.2 How the weather reaches each model . . . 4

2.3 The numbers reported, and their formulas . . . 5

2.4 How energy is computed (identical for all five models) . . . 6

3 Results of all five models together **7**

4 Model 1 and model 2: the two baseline driving models (teammates) **10**

4.1 What they are . . . 10

4.2 What they see and the network . . . 10

4.3 How they were trained . . . 10

4.4 How they were tested . . . 11

4.5 Results . . . 11

4.6 What we can and cannot say . . . 11

5 Model 3: the Proposed Bird's-Eye-View Driving Model **11**

5.1 What it is . . . 11

5.2 What it sees and the network . . . 11

5.3 How it was trained . . . 11

5.4 How it was tested . . . 12

5.5 Results . . . 12

5.6 What we can and cannot say . . . 12

6 Model 4: the Caution-Study Caution-Aware Driving Model **12**

6.1 What it is . . . 12

6.2 What it sees and the network . . . 13

6.3 How it was trained . . . 13

6.4 How it was tested . . . 13
6.5 Results . . . 13
6.6 Why it differs from the proposed model in clear weather . . . 13
6.7 Longer time limit (post-hoc check) . . . 13
6.8 What we can and cannot say . . . 14

7 Model 5: the Image-Only Driving Model (front camera) 14
7.1 What it is . . . 14
7.2 What it sees and the network . . . 14
7.3 How it was trained . . . 15
7.4 How it was tested . . . 15
7.5 Results . . . 15
7.6 What we can and cannot say . . . 15

8 Reinforcement learning: what we tried (two-page record) 15

9 Which wording each result supports 17

10 Where the files are 17

1 What this document is

This document is for the people working on the project. It compares **five driving models**, one section each, with the same headings every time: what it sees, the network, how it was trained, how it was tested, how its energy is computed, what it achieved, which graph shows it, and *what we are allowed to say about it.* A shorter story of the project is in the *Director's Research Guide*; every detail, every experiment and every file is in the *Complete Technical Research Report.*

The five models in one table

All five models take the same job: drive a car from a start to a goal in the MetaDrive simulator, steering and using throttle or brake. They differ in *what they look at* and *how they were taught.* Four of them look at a small top-down picture (a "bird's-eye-view grid"); one of them looks at the raw front-camera picture.

Table 1: The five models. "Teacher" is the rule-based driver whose actions the model copies. Models 1 and 2 were built by the teammates and are on GitHub; models 3 to 5 exist only on the local machine.

	Model	What it looks at	How it was taught	Role in the comparison
1	Baseline Driving Model Trained Without Traffic	Bird's-eye-view grid, six vehicle-state numbers	Copy of 5 recorded drives, no other vehicles	Teammates' baseline (weaker)
2	Baseline Driving Model Trained With Traffic	Same	Copy of 5 recorded drives, sparse traffic	Teammates' baseline, supposedly stronger
3	Proposed Bird's-Eye-View Driving Model	Grid with the road drawn in, three vehicle-state numbers	Repeated drive-and-correct (dataset aggregation)	The strong method
4	Caution-Study Caution-Aware Driving Model	As model 3 plus one "caution" number	As model 3 but the teacher drives slower and keeps more distance when caution is high	Adaptive-behaviour candidate
5	Image-Only Driving Model (front camera)	Only the front-camera picture	Repeated drive-and-correct on camera images	The weak control: what you get without the grid

Strong against weak. Model 5 is deliberately the weakest design: no grid, no road drawing, no speed input. It shows what the other four gain from the bird's-eye-view grid. Models 1 and 2 are the teammates' starting point. Model 3 is the strong method. Model 4 asks whether the strong method can also adapt to weather.

Plain-language rule used throughout. Every model is called by its descriptive name. The code nicknames (for example `ov_split`) appear only in the file list at the end.

2 How every model is tested (the same way for all five)

2.1 The test

- **Simulator.** MetaDrive 0.4.3. A *scenario seed* (a whole number) fixes the map, the route and the starting traffic, so every model drives exactly the same 200 scenarios (seeds 5000 to 5199). These seeds were never used for training or for choosing a model.

- **Traffic.** Sparse: traffic density 0.05. **Time limit:** 800 steps of 0.1 s = 80 seconds (a 160-second check is in Section 6.7).
- **An episode ends** with exactly one of four outcomes: *success* (destination reached), *collision*, *left the road*, or *timeout*.
- **Weather conditions:** clear, fog 1.0, rain 0.6, rain 1.0 (the number is the intensity of the teammates' weather filter; 1.0 is the strongest).

2.2 How the weather reaches each model

Weather never changes the road grip or the car's physics. It only damages perception.

Models 1 to 4 (grid models)
They do not look at camera pictures in these tests. The grid is built from the simulator's list of vehicles, and *each vehicle is removed from the grid with the probability that the detector was measured to miss it* at that weather intensity. That measurement is the detector retention in Figure 1. So the weather reaches these models *indirectly*, through a measured number, not through pictures.

Model 5 (image-only)
It looks at the real camera picture, and the teammates' weather filter (fog haze, rain streaks) is applied to that picture directly. This is the strongest form of weather test, but it is applied to a different kind of input.

Honest limit

Models 1 to 4 are tested with *measured* detector retention but with an ideal detector otherwise (the grid is built from the simulator's vehicle list). The GitHub README asks that the policy never receives exact simulator positions; these tests depart from that rule, and the result says how the models behave under a measured loss of vehicles, not how a full camera system would behave.




Figure 1: Detector retention measured at different fog and rain intensities, and the probability that the driving model keeps a vehicle. In 20 scenes (seeds 1000 to 1019, traffic density 0.3, stationary car, up to three vehicles placed around it) the same camera frames were passed through the teammates' vehicle detector twice: once clean and once with the weather filter at each intensity (two random weather draws per scene). Retention is the number of vehicles found with weather divided by the number found without weather. Grey dots are single scenes, the blue line is the mean over scenes with its 95% interval, the orange dashed line is the measured retention capped at 1, which is the probability that the weather proxy keeps a vehicle in the driving model's grid. Dotted vertical lines mark the intensities used in the 200-episode weather tests.

Plain-English reading. Fog does almost nothing up to intensity 0.6, then removes vehicles quickly: about 71% are kept at 0.8 and 27% at 1.0. Rain acts earlier and harder: about half of the vehicles are kept at 0.45, 16% at 0.6 and 4% at 1.0. Values slightly above 1 in light fog mean that the detector found a few more boxes than in the clean frame; they are treated as no loss.

Research implication. The driving model never sees the weather and never sees camera images in these tests. It receives the weather only indirectly: each vehicle is removed from its bird's-eye-view grid with the probability read off this curve. The conclusions about weather therefore hold for *loss of detected vehicles at these measured rates*, from 20 scenes per point; they do not cover other perception failures.

2.3 The numbers reported, and their formulas

Let $n = 200$ be the number of episodes and k the number that ended in success.

Success rate $\hat{p} = k/n$. Collision, left-road and timeout rates are computed the same way; the four rates add up to 1.

95% interval (Wilson)
$\dfrac{\hat{p} + \frac{z^2}{2n} \pm z\sqrt{\frac{\hat{p}(1-\hat{p})}{n} + \frac{z^2}{4n^2}}}{1 + \frac{z^2}{n}}$, $z = 1.96$. It is the range of true success rates that is compatible with the 200 episodes we saw.

Paired comparison (exact McNemar test)
Two models are compared on the same seeds. Let b be the number of episodes only model A solved and c the number only model B solved. Under "no difference" each of these $b + c$ episodes is equally likely to go either way, so $p = \min\Big(1,\ 2\sum_{i=0}^{\min(b,c)} \binom{b+c}{i} 2^{-(b+c)}\Big)$. A small p means the difference is unlikely to be chance.

Mean speed Average of the car's speed over all steps of an episode (m/s), then averaged over the 200 episodes.

Route completion
Fraction of the planned route driven when the episode ended (1.0 = the destination).

Estimated energy
Same formula for every model, applied to the speed the model produced (below).

2.4 How energy is computed (identical for all five models)

MetaDrive has no electric-energy model. We therefore estimate the *mechanical work at the wheels* of a declared virtual car, using only the speed history of each episode. The model does not influence the formula; a model uses less energy only because it drives differently (mostly slower or smoother). For one step of $\Delta t = 0.1\,\mathrm{s}$ with start speed v_0 and end speed v_1 (speed assumed to change in a straight line inside the step):

$$
\begin{aligned}
W_{\text{inertia}} &= \tfrac{1}{2}\, m\,(v_1^2 - v_0^2) && \text{(change of kinetic energy)}\\
W_{\text{air}} &= k\,\Delta t\,\tfrac{1}{4}\,(v_0^3 + v_0^2 v_1 + v_0 v_1^2 + v_1^3), \quad k = \tfrac{1}{2}\rho C_d A && \text{(air drag)}\\
W_{\text{roll}} &= C_{rr}\, m\, g\, \tfrac{v_0+v_1}{2}\,\Delta t && \text{(tyre rolling resistance)}\\
W_{\text{step}} &= \max\left(0,\ W_{\text{inertia}} + W_{\text{air}} + W_{\text{roll}}\right)
\end{aligned}
$$

with air density $\rho = 1.225\,\mathrm{kg/m^3}$, drag coefficient $C_d = 0.23$, frontal area $A = 2.22\,\mathrm{m^2}$, rolling resistance $C_{rr} = 0.01$, gravity $g = 9.81\,\mathrm{m/s^2}$ and the car mass m taken from the simulator's vehicle. Then

$$
E_{\text{Wh}} = \frac{\sum_{\text{steps}} W_{\text{step}}}{3600}, \qquad D_{\text{km}} = \frac{1}{1000}\sum_{\text{steps}} \tfrac{v_0+v_1}{2}\Delta t, \qquad \text{energy per kilometre} = \frac{E_{\text{Wh}}}{D_{\text{km}}}.
$$

Braking steps count as zero (the clip at 0): there is *no regenerative braking*, so braking energy is lost, not recovered. Road slope is zero (the simulator's roads are flat). **Only differences between models are meaningful; this is not a battery measurement.** The reported value of a model is the mean over its 200 episodes of the per-episode energy per kilometre.

Table 2: Energy computation per model. The formula is the same; only the speed history differs.

Model	What determines its energy
1, 2 Baselines	Their own speed history: they hold about 8.1 m/s and brake little.
3 Proposed	Its own speed history: about 7.9 m/s; slightly more braking and accelerating than the baselines, hence slightly more energy.
4 Caution-aware	Slower in fog and rain (5.6 to 6.2 m/s), which lowers drag work strongly (drag grows with the cube of speed).
5 Image-only	Fast and erratic (about 9 m/s), with many accelerations; it uses much more energy per kilometre, but most episodes end early by leaving the road.

3 Results of all five models together

Table 3: All metrics, five models, four weather conditions, 200 episodes each (seeds 5000–5199, sparse traffic, 800-step limit). Collision, left road and timeout are shares of the episodes. Energy is the estimate of Section 2.4. "not yet evaluated" marks a run that had not finished when this document was built.

Weather	Model	Success	95% interval	Collision	Left road	Timeout	Speed (m/s)	Route completion	Energy (Wh per km)
Clear	Baseline Driving Model Trained Without Traffic	0.850	[0.794, 0.893]	0.125	0.025	0.000	8.09	0.918	85.9
	Baseline Driving Model Trained With Traffic	0.745	[0.680, 0.800]	0.120	0.135	0.000	8.07	0.883	90.7
	Proposed Bird's-Eye-View Driving Model	0.925	[0.880, 0.954]	0.060	0.010	0.005	7.87	0.939	96.2
	Caution-Study Caution-Aware Driving Model	0.890	[0.839, 0.926]	0.090	0.020	0.000	7.97	0.920	94.1
	Image-Only Driving Model (front camera)	0.130	[0.090, 0.184]	0.200	0.605	0.065	9.20	0.550	276.6
Fog (intensity 1.0)	Baseline Driving Model Trained Without Traffic	0.860	[0.805, 0.901]	0.115	0.025	0.000	8.09	0.920	85.9
	Baseline Driving Model Trained With Traffic	0.750	[0.686, 0.805]	0.120	0.130	0.000	8.07	0.886	90.5
	Proposed Bird's-Eye-View Driving Model	0.895	[0.845, 0.930]	0.085	0.020	0.000	7.92	0.933	96.5
	Caution-Study Caution-Aware Driving Model	0.895	[0.845, 0.930]	0.050	0.020	0.035	6.15	0.945	62.7
	Image-Only Driving Model (front camera)	not yet evaluated							
Rain (intensity 0.6)	Baseline Driving Model Trained Without Traffic	0.850	[0.794, 0.893]	0.125	0.025	0.000	8.09	0.918	86.0
	Baseline Driving Model Trained With Traffic	0.755	[0.691, 0.809]	0.120	0.125	0.000	8.08	0.886	90.5
	Proposed Bird's-Eye-View Driving Model	0.900	[0.851, 0.934]	0.085	0.015	0.000	7.94	0.934	94.9
	Caution-Study Caution-Aware Driving Model	0.890	[0.839, 0.926]	0.030	0.020	0.060	5.87	0.951	60.4
	Image-Only Driving Model (front camera)	not yet evaluated							
Rain (intensity 1.0)	Baseline Driving Model Trained Without Traffic	0.850	[0.794, 0.893]	0.125	0.025	0.000	8.09	0.918	85.9
	Baseline Driving Model Trained With Traffic	0.755	[0.691, 0.809]	0.120	0.125	0.000	8.08	0.886	90.5
	Proposed Bird's-Eye-View Driving Model	0.900	[0.851, 0.934]	0.095	0.005	0.000	7.95	0.932	93.0
	Caution-Study Caution-Aware Driving Model	0.820	[0.761, 0.867]	0.035	0.040	0.105	5.56	0.935	59.7
	Image-Only Driving Model (front camera)	not yet evaluated							




Figure 2: Success rate of the five models in four weather conditions. Each bar is the share of 200 episodes that reached the destination; the black line is the 95% interval. Weather becomes stronger from left to right.

Plain-English reading. The proposed model and the caution-aware model stay between 0.82 and 0.93; the two baselines stay near 0.85 and 0.75; the image-only model is far below all of them. Weather barely moves any of the four grid-based models in the tests that apply it as a measured loss of vehicles; the one clear drop is the caution-aware model in rain 1.0 at the 80-second limit, which is caused by timeouts (Section 6.7).

Research implication. The bird's-eye-view grid is what makes driving possible at this level; the training method (repeated correction) separates the proposed model from the baselines. The weather result is limited to loss of detected vehicles in sparse traffic.




Figure 3: How the episodes ended, per model and weather. Each horizontal bar is one model in one weather condition; its coloured parts add up to the 200 episodes: green = destination reached, red = collision, yellow = left the road, grey = time limit reached.

Plain-English reading. The baselines fail mainly by collisions (and, for the one trained with traffic, by leaving the road); the proposed model fails rarely and mostly by collision; the caution-aware model replaces collisions by timeouts as the weather gets stronger; the image-only model mostly leaves the road.

Research implication. Models fail in different ways, so success alone hides what to fix. Leaving the road points at steering and road understanding; collisions point at seeing and reacting to other vehicles; timeouts point at speed choice.




Figure 4: Estimated energy and mean speed of the five models. Top: estimated traction energy in watt-hours per kilometre. Bottom: mean speed in metres per second. Same four weather conditions.

Plain-English reading. Baselines and the proposed model use about 86 to 96 watt-hours per kilometre at about 8 metres per second. The caution-aware model drops to about 60 in fog and rain by driving at 5.6 to 6.2 metres per second. The image-only model is the fastest and the most energy-hungry.

Research implication. Lower energy came only from lower speed. A speed-matched comparison would be needed to say that the caution-aware model is more *efficient* and not simply slower.

Table 4: Paired comparison of every model against the image-only model on the same episodes. Positive differences favour the model named in the second column.

Weather	Model	Difference in success (model minus image-only)	Only this model succeeded	Only image-only succeeded	Exact McNemar p
Clear	Baseline Driving Model Trained Without Traffic	+0.720	144	0	< 0.0001
	Baseline Driving Model Trained With Traffic	+0.615	128	5	< 0.0001
	Proposed Bird's-Eye-View Driving Model	+0.795	159	0	< 0.0001
	Caution-Study Caution-Aware Driving Model	+0.760	152	0	< 0.0001

Table 5: Paired comparison among the four grid-based models in clear weather (200 episodes). From the technical report.

Comparison	Difference in success	Only first succeeded	Only second succeeded	Exact McNemar p
Proposed against Baseline without traffic	+0.075	—	—	0.0007
Proposed against Baseline with traffic	+0.180	—	—	< 0.0001
Caution-aware against Proposed	−0.035	3	10	0.092
Caution-aware against Baseline without traffic	+0.040	11	3	0.057
Caution-aware against Baseline with traffic	+0.145	32	3	< 0.0001

4 Model 1 and model 2: the two baseline driving models (teammates)

4.1 What they are

Two copies of the same design, trained from five demonstrations each. Model 1 was trained on drives without other vehicles; model 2 on drives with sparse traffic. Both are on GitHub (`bev_policy/checkpoints/`).

4.2 What they see and the network

A 64×64 bird's-eye-view grid (20 m wide and long: 17.5 m ahead, 2.5 m behind; cell 0.3125 m) with values for unknown, free, own car and detected vehicle, *no road drawing*, and six vehicle-state numbers (speed, route progress, sideways offset from the lane centre, heading error, curvature ahead, distance to goal). The network is the shared `BEVScalarPolicy` (110 530 adjustable numbers): three convolution layers (32, 64, 96 maps) on the grid, a small network (6→64→32) on the numbers, and a head (160→128→2) with output steering and throttle or brake, each between −1 and 1.

4.3 How they were trained

Behaviour cloning: MetaDrive's stock driving rule (Intelligent Driver Model) drives five episodes, only episodes that reach the destination are kept, and the network is fitted to the recorded actions (mean squared error, at most 60 epochs, batch 64, learning rate $3 \cdot 10^{-4}$, early stopping after 10 epochs without improvement). **Weakness:** the network sees only places the expert visited, so after a small error it has no example of how to recover.

4.4 How they were tested

As in Section 2. The weather proxy removes vehicles from the grid; the models are not given any weather input.

4.5 Results

Success 0.850 (without traffic) and 0.745 (with traffic) in clear weather, with 0.85–0.86 and 0.75–0.755 in the three weather conditions (Table 3). The one trained *with* traffic is the *worse* one: it leaves the road in 13.5% of clear episodes (the other 2.5%), collisions about 12% in both. Energy 85.9 and 90.7 watt-hours per kilometre at 8.1 m/s.

4.6 What we can and cannot say

We can say	Because
Training with traffic did not help these baselines; it was 0.105 worse in clear weather.	200 paired episodes, 0.745 against 0.850.
Both baselines are flat across the four weather conditions.	Success within 0.015 in each, in the vehicle-loss proxy.
We cannot say	**Because**
That 0.745 contradicts the README value 0.90.	The README reports 9 of 10 episodes (interval 0.596–0.982), which includes 0.745.
That the baselines are robust to real fog and rain in the camera chain.	The perception damage is measured as vehicle loss only.

5 Model 3: the Proposed Bird's-Eye-View Driving Model

5.1 What it is

The same network family as the baselines, with two changes to what it *sees* and a different way of *teaching*.

5.2 What it sees and the network

- The grid has the **road drawn in**: the route centre line (value 0.5) and the road boundaries (0.8), taken from the simulator's map in the car's frame.
- It gets **three** vehicle-state numbers (speed, route progress, distance to goal). Sideways offset, heading error and curvature are *not* given as numbers, because the drawn road already shows them.

Network: the same `BEVScalarPolicy`, 110 530 adjustable numbers.

5.3 How it was trained

Dataset aggregation: the model drives, a rule-based teacher says what it should have done at each state the model reached, and these labels are added to the training data. Six rounds (0 to 5).

Round 0: the teacher drives. Later rounds: the teacher's action is executed with probability 0.5^t, otherwise the model's. Each round: 8 episodes at each of five traffic densities (0, 0.05, 0.1, 0.2, 0.3) on training seeds 2000–2999, Gaussian action noise 0.1, retraining on all data so far (Adam, learning rate 10^{-3}, batch 128, mean squared error; 24 epochs in round 0, 8 later). The saved model is round 5, trained on 73 032 labelled steps. Teacher: the stock Intelligent Driver Model on the exact simulator state.

5.4 How it was tested

As in Section 2; no weather input; weather acts through vehicle loss only.

5.5 Results

Clear 0.925 (interval 0.880–0.954), fog 1.0 0.895, rain 0.6 0.900, rain 1.0 0.900. It is better than the baselines in clear weather by +0.075 ($p = 0.0007$) and +0.180 ($p < 0.0001$). 15 of 200 clear episodes fail; a collision-aware teacher solves 14 of those 15, which points to information that the model's grid does not contain (late, coarse view of other vehicles). Energy 93.0–96.5 watt-hours per kilometre at 7.9 m/s.

5.6 What we can and cannot say

We can say	Because
Repeated drive-and-correct training with the road drawn in beats five-demonstration cloning.	+0.075 and +0.180 on 200 paired episodes.
Loss of detected vehicles at the measured rates did not lower its success in sparse traffic.	0.895–0.925 in all four conditions; the pre-registered test of harm failed.
We cannot say	**Because**
Which of the two changes (road drawing, training method) caused the gain.	They were not separated at 200 episodes.
That it is better than its own teacher.	The collision-aware teacher scores 0.950; the difference is not significant.
That it works with a real detector and camera.	Tests used a measured loss of vehicles on top of the simulator's vehicle list.

6 Model 4: the Caution-Study Caution-Aware Driving Model

6.1 What it is

The proposed design with **one extra number**, "caution" between 0 and 1. Caution is derived from the measured detector reliability: $c = 1 - \text{retention}$ (0 in clear weather).

6.2 What it sees and the network

Same grid and three vehicle-state numbers as model 3, plus caution through a small extra branch (1→16) joined before the head (176→128→2); 112 610 adjustable numbers. *The caution value is given to the model from the known weather; the model does not sense it.*

6.3 How it was trained

Dataset aggregation as for model 3, but the **teacher also depends on caution**: at caution 0 it drives at 30 km/h with a 10 m gap; at caution 1 at 20 km/h with a 25 m gap. Five rounds of 40 episodes, 6 epochs per round, action noise 0.1, caution per episode half uniform in $[0, 1]$ and half derived from weather. The saved model is the round with the best validation result, *round 1* (35 503 labelled steps). A control with the caution input fixed at 0 was trained the same way.

6.4 How it was tested

As in Section 2, with caution computed from the weather condition (clear: 0).

6.5 Results

Success 0.890, 0.895, 0.890, 0.820 (clear, fog 1.0, rain 0.6, rain 1.0). In weather it slows to 5.6–6.2 m/s and its estimated energy falls to 59.7–62.7 watt-hours per kilometre, about 35% lower than the proposed model (93.0–96.5). Collisions fall to 3–5%, but timeouts rise to 3.5%, 6% and 10.5%.

6.6 Why it differs from the proposed model in clear weather

It is a different network, trained in a separate run on different labels, so it behaves differently even at caution 0. It solves 178 of 200 clear episodes, the proposed model 185; they disagree on 13 episodes (3 vs 10, $p = 0.092$). The control trained the same way with caution fixed at 0 scores 0.895, the same as model 4, so run-to-run differences of a few points exist at 200 episodes.

6.7 Longer time limit (post-hoc check)

Every extra failure of model 4 in weather was a timeout, so it was re-run in the three weather conditions with a 160-second limit (1600 steps; same seeds). The proposed model and the baselines had no timeouts in weather, so their results cannot change. The limit was changed *after* seeing the timeouts.

Table 6: Caution-aware model with the 80-second and the 160-second limit, next to the proposed model (80 seconds). 200 episodes each.

Weather	Model	Step limit	Success	Collision	Left road	Timeout	Speed (m/s)	Energy (Wh per km)
Fog (intensity 1.0)	Proposed Bird's-Eye-View Driving Model	800 (80 s)	0.895	0.085	0.020	0.000	7.92	96.5
	Caution-Study Caution-Aware Driving Model	800 (80 s)	0.895	0.050	0.020	0.035	6.15	62.7
	Caution-Study Caution-Aware Driving Model	1600 (160 s)	0.940	0.050	0.010	0.000	6.15	62.5
Rain (intensity 0.6)	Proposed Bird's-Eye-View Driving Model	800 (80 s)	0.900	0.085	0.015	0.000	7.94	94.9
	Caution-Study Caution-Aware Driving Model	800 (80 s)	0.890	0.030	0.020	0.060	5.87	60.4
	Caution-Study Caution-Aware Driving Model	1600 (160 s)	0.955	0.025	0.020	0.000	5.87	60.2
Rain (intensity 1.0)	Proposed Bird's-Eye-View Driving Model	800 (80 s)	0.900	0.095	0.005	0.000	7.95	93.0
	Caution-Study Caution-Aware Driving Model	800 (80 s)	0.820	0.035	0.040	0.105	5.56	59.7
	Caution-Study Caution-Aware Driving Model	1600 (160 s)	0.935	0.035	0.030	0.000	5.56	59.7

Table 7: Paired comparison of the caution-aware model at 160 seconds with the proposed model at 80 seconds.

Weather	Difference in success (caution-aware at 1600 minus proposed at 800)	Only caution-aware succeeded	Only proposed succeeded	Exact McNemar p
Fog (intensity 1.0)	+0.045	19	10	0.1360
Rain (intensity 0.6)	+0.055	20	9	0.0614
Rain (intensity 1.0)	+0.035	20	13	0.2962

At 160 seconds all timeouts disappear: 0.940, 0.955 and 0.935 in fog 1.0, rain 0.6 and rain 1.0, against 0.895, 0.900 and 0.900 for the proposed model; no difference is significant ($p = 0.136$, 0.061, 0.296).

6.8 What we can and cannot say

We can say	Because
The model shows *learned adaptive behaviour*: it slows down by itself when the caution value is high.	The control with caution fixed at 0 does not slow down; speed fell from about 8.0 to 5.6–6.2 m/s.
In fog and rain it used about 35% less estimated energy with success tied to the proposed model at a 160-second limit.	Table 6; no significant difference.
At the original 80-second limit it was significantly lower in rain 1.0 (0.820 against 0.900, $p = 0.033$) because of timeouts.	Table 3.
We cannot say	**Because**
That caution makes driving safer or more successful.	Success did not rise; weather did not hurt the proposed model in the first place.
That it is more energy-*efficient*.	It is slower; no speed-matched control exists.
That the model senses the weather.	The caution value is supplied.
That the 160-second result is pre-registered.	The limit was changed after the timeouts were seen.

7 Model 5: the Image-Only Driving Model (front camera)

7.1 What it is

A model that gets only the front-left camera picture and nothing else: no grid, no road drawing, no speed, no weather label. It is the weak control: "what happens if we skip the bird's-eye-view grid."

7.2 What it sees and the network

The camera picture is rendered at 320×240, resized to 128×96 and scaled to the range 0 to 1. Five convolution layers with batch normalisation (24, 36, 48, 64, 64 maps; kernels 5, 5, 3, 3, 3; all stride

2; output 64×3×4), then a head (768→128, dropout 0.2, 128→2, tanh). It is a different, smaller network type than models 1 to 4.

7.3 How it was trained

Behaviour cloning of the collision-aware teacher on 40 clean-weather episodes (teacher drives with action noise 0, 0.1 and 0.25, so that recoveries are in the data), followed by three dataset-aggregation rounds of 20 episodes (teacher mix 0.30, 0.20, 0.10), 37 692 labelled pictures in total; Adam, learning rate 10^{-3} then $5 \cdot 10^{-4}$, 8 epochs per fit, mild brightness jitter. Training seeds 100–199. It was trained only on clean pictures.

7.4 How it was tested

The same 200 seeds and metrics. In weather, the teammates' fog or rain filter is applied to the picture it receives (a different seed stream per episode), at the same intensities as for the other models.

7.5 Results

Clear: success 0.130 (interval 0.090 to 0.184); 60.5% of episodes end by leaving the road, 20.0% by collision, 6.5% by timeout; speed 9.20 m/s, route completion 0.55, energy 276.6 watt-hours per kilometre. The three weather runs of the image-only model had not all finished when this document was built, so its weather results are not stated here.

7.6 What we can and cannot say

We can say	Because
A camera-only model trained this way is far below the grid-based models.	0.130 against 0.745–0.925 in clear weather, paired difference to the proposed model +0.795 (159 episodes where only the proposed model succeeded, none the other way).
Its main failure is leaving the road.	60.5% of clear episodes.
We cannot say	**Because**
That cameras cannot drive.	This is one small network, 40 plus 60 teacher episodes, no road or speed input.
That weather "breaks" it, if it already fails in clear weather.	Its clear-weather success is already near the floor; see the weather sentence above for what changes.

8 Reinforcement learning: what we tried (two-page record)

Reinforcement learning is not part of the five-model comparison. It is recorded here so the team knows what was tried. In all four attempts the algorithm is proximal policy optimisation (PPO), the action is the same two numbers (steering, throttle or brake, each between −1 and 1), and the network starts from an imitation-trained model, because a random start settles at standing still.

State (what the network is given). Attempt 1: 12 numbers of simulator state (six vehicle-state values, the previous action, a 4-number weather vector). Attempts 2 to 4: the bird's-eye-view grid

and the vehicle-state numbers of the model they start from, plus (attempts 2 and 3) a weather or caution input.

Reward version 1 (attempts 1 to 3), per 0.1 s step:

$$r_t = \frac{\min(\Delta s,\, v_{cap}\Delta t)}{v_{ref}\Delta t} - 0.5\, d^2 - 5\, \psi^2 - 0.1\|a_t - a_{t-1}\|^2 - 0.002\, j^2 - 0.2\max(0, -a_t^{thr}) - 0.5\Big(\tfrac{(v-v_{cap})_+}{2}\Big)^2 - 0.2[v < 0.5] +$$

Δs distance driven, $v_{ref} = 10\,\mathrm{m/s}$, d sideways offset from the lane centre, ψ heading error, j jerk, a^{thr} throttle or brake command, v_{cap} speed cap (10 or 12 m/s), R_{end} terminal reward (+20 for success, −50 for a collision or leaving the road).

Reward version 3 (attempt 4):

$$r_t = \min\Big(\tfrac{\Delta s}{v_{ref}\Delta t}, \tfrac{v_{cap}}{v_{ref}}\Big) - 0.5d^2 - 5\psi^2 - 2\Big(1-\tfrac{\tau}{3}\Big)_+^2 - \Big(1-\tfrac{g}{6}\Big)_+^2 - 0.1\|a_t - a_{t-1}\|^2 - 0.002j^2 - 0.02E_t - 0.2[v < 0.5] + R_{end}$$

τ predicted time to collision (s), g gap to the vehicle ahead (m), E_t energy of the step (Wh); $R_{end} = +50$ for success and -100 for collision or leaving the road. The collision and gap terms use simulator truth during training only.

Table 8: The four reinforcement-learning attempts. "Validation" means the small set of episodes used during training; "test" means seeds never used for training.

Attempt	Start (initialisation)	Reward and what changed	Training (steps completed)	Testing	Result and lesson
1. Privileged teacher (runs C2, Probe C, C3)	Small network cloned from the stock driver on simulator state	Version 1, speed cap 12 (C2, Probe C) or 10 (C3), crash penalty 50; rain lowered tyre grip (later removed)	Learning rate $3 \cdot 10^{-4}$ ($5 \cdot 10^{-5}$ in C3), 512 steps per update, batch 512, 10 epochs. C2 1.5 M steps; Probe C 1 M; C3 0.3 M of 1.5 M	70 test episodes (10 clear, 10 fog, 50 rain); stock driver for reference	16 of 70 succeed (stock driver 47 of 70); all failures leave the road; reward rose while success did not. *Lesson:* a rising reward is not better driving.
2. Fine-tune the proposed model with a weather input	Proposed model; zero-initialised weather branch	Version 1, eight weather mixes with vehicle loss, density 0.1	Learning rate $5 \cdot 10^{-5}$, 256 steps per update, batch 128, clip 0.1. 120 000 of 480 000 steps	Validation on 40 episodes	0.675, 0.65, 0.675: no change. *Lesson:* a weather input cannot help a model that weather does not hurt.
3. Five reward combinations	Proposed model with zero-initialised caution input	Version 1 plus: none; energy term $-0.05E_t$; caution-dependent speed limit and crash penalty; headway term; all	As attempt 2 with 2 environments. 150 000 steps in each of five runs	Validation on 40 dense-traffic episodes	0.325–0.400 against a start of 0.350: noise. Energy did not fall. *Lesson:* 40 episodes cannot select a model; a reward cannot add missing information.
4. Reward version 3 under measured degradation	Weather-Degradation-Trained Driving Model	Version 3: adds collision-time and gap terms, no brake penalty, energy cost, $+50/-100$ terminal rewards	Learning rate 10^{-4}, 256 steps per update. 300 000 steps; the run with a weather input stopped after step 0	200 test episodes in four weather conditions	Success lower by 0.065, 0.115, 0.115, 0.095 (significant). Faster, less safe. *Lesson:* reward changes alone reduced safety; validation at 1.0 predicted nothing.

Overall: none of the four attempts beat the imitation-trained model it started from, and attempt 4 made it significantly worse. Training curves and before-and-after figures are in the technical report (reinforcement-learning section).

9 Which wording each result supports

Table 9: Claim, evidence and allowed wording.

Claim	Evidence	Allowed wording
The proposed model beats the baselines	200 paired episodes, $p = 0.0007$ and < 0.0001	"clearly better in sparse traffic in this simulator"
The grid matters	Image-only 0.130 against 0.925	"a camera-only model of this kind is far worse"
Weather does not hurt the proposed model	0.895–0.925 in every condition	"no measurable loss from vehicle loss at the measured rates in sparse traffic"; not "robust to weather"
The caution-aware model adapts	Slows down only when caution is high	"learned adaptive behaviour"; not "adaptive perception" or "senses weather"
The caution-aware model saves energy	35% lower estimate at lower speed	"lower estimated energy at lower speed"; not "more efficient"
Reinforcement learning did not help	Four attempts, one with 200 test episodes	"did not improve; once worsened"; not "cannot work"
The image-only model breaks in weather	See Model 5 results	Only what the weather sentence states

10 Where the files are

- Models: `trained_models/` (descriptive names; mapping in `trained_models/MODEL_NAME_MAPPING.md`). Models 1 and 2 are also on GitHub (`bev_policy/checkpoints/`).
- Code names (only here): model 1 `repo_bc_clear`, model 2 `repo_bc_sparse`, model 3 `ov_split`, model 4 `caut_a` (evaluated as `caut_auto`), model 5 `vcam`.
- Results: `bev_rl/adaptive/results/n200_all_weather/`, `bev_rl/adaptive/results/n200_horizon1600/`, `bev_rl/adaptive/results/vanilla_camera/`.
- Evaluation code: `bev_rl/adaptive/evaluate_n200_all_weather.py` (models 1 to 4), `bev_rl/adaptive/vanilla_camera_cnn.py` (model 5). Energy: `bev_rl/energy.py`.
- Figures and tables of this document: `report/make_five_model_comparison.py`, `report/make_detector_retention_figure.py`, `report/make_caution_longer_time_limit.py`.