

120W MOVING HEAD LIGHT 4IN1



operation instruction

Product technical parameters:

Electrical voltage: AC100V-240V.

Work rate: 180w

Frequency: 50-60Hz

Lamp bead: one 120w four-in-one COB lamp bead.

Access: 23CH

Control mode: DMX/ voice control/self-propelled

Horizontal scanning: 540 degrees

Vertical scanning: 270 degrees

Frequency flash: 1-25 times/second or random.

Display screen: LCD

address code	Addr	ADD 1	RS 12	RS 11	ADD 1	RS 12
host machine	hdnh					
reset	reset					
positive and negative	no	YES		no	YES	
automatic operation	SLnd	dnh	Auto	Sound		
X axis	PSET					
Y axis	tilt					
Acoustic sensitivity	SENS					
monitor	LED					
On/off	no	off				
passage	CHnd	CH.13				
Positive and negative display screen	disp					
temperature	TEMP					
version number	ver					
leave the factory	FACT					

Operation menu:

Menu content	First-level menu	Secondary menu	describe
DMX address	Addr	A001 ~ A512	DMX mode and address setting 001 ~ 512
Channel mode	CHAN	CH23	DMX mode and channel mode settings
Voice control mode	SOUN	SE00 ~ SE99	Voice control mode and sensitivity setting 00 ~ 99
Self-propelled mode	AUTO	S000 ~ S255	Self-propelled mode and speed setting 000 ~ 255
Manual control	MAnu	r000 ~ r255	Red linear dimming 0% ~ 100%
		g000 ~ g255	Green linear dimming 0% ~ 100%
		b000 ~ b255	Blue linear dimming 0% ~ 100%
		U000 ~ U255	White linear dimming 0% ~ 100%
		P000 ~ P255	Horizontal motion 0 ~ 540 degrees
		T000 ~ T255	Horizontal motion 0 ~ 240 degrees
Temperature information	TEMP	xxx°C	Lamp temperature display (Celsius)
display mode	dISP	ONEM	Screen after 60 seconds of departure without buttons.
		PErM	The LED display is always on
Display inversion	dSPL	NorM	Normal display
		rEVr	Display inversion
No signal setting	dmOF	bLAC	No signal returns to reset state.
		HoLd	No signal to keep the current state.
reset	rEST	no	be invalid
		yes	Perform a reset action
Dimming curve	CUrv	LINE	straight line
		SqUA	exponential curve

Channel mode:**STD 23CH Mode**

Channel	Function	Dmx Value	Description
1	Horizontal motion	0 - 255	Horizontal motion 0 ~ 540 degrees
2	Horizontal fine adjustment	0 - 255	Horizontal fine adjustment
3	vertical motion	0 - 255	Vertical motion 0 ~ 270 degrees
4	Vertical fine tuning	0 - 255	Vertical fine tuning
5	Motor speed	0 - 255	Motor speed from fastest to slowest.
6	aiming	0 - 255	Linear dimming 0 ~ 100%
7	stroboscopic	0 - 3	Closed light
		4 - 103	Regular strobe, the speed changes from slow to fast.
		104 - 107	consecrate
		108 - 207	Pulse strobe, the speed changes from slow to fast.
		208 - 212	consecrate
		213 - 225	Random strobe, slow
		226 - 238	Random strobe, medium speed
		239 - 251	Random strobe, fast
		252 - 255	consecrate
8	red	0 - 255	Red linear dimming 0 ~ 100%
9	green	0 - 255	Green linear dimming 0 ~ 100%
10	blue	0 - 255	Blue linear dimming 0 ~ 100%
11	white	0 - 255	White linear dimming 0 ~ 100%
12	colour	0	all-or-none

	temperature	1 - 255	8500K - 2800K
13	Color macro	0 - 9	all-or-none
		10 - 255	Color macro
14	Built-in program effect	0	all-or-none
		1 -- 25	Gradient effect
		26 - 51	Chasing effect
		52 - 77	Rainbow effect
		78 - 103	Gradient effect 1
		104 - 129	Gradient effect 2
		130 - 155	Gradient effect 3
		156 - 181	Gradient effect 4
		182 - 207	Gradient effect 5
		208 - 233	Gradient effect 6
		234 - 255	Gradient effect 7
15	Effect speed	0 - 255	Built-in program effect speed, from slow to fast.
16	Light strip dimming	0 - 255	Light strip dimming
17	Light strip stroboscopic	0 - 3	Lamp strip closed light
		4 - 103	The light strip flashes regularly, and the speed changes from slow to fast.
		104 - 107	Light strip opening
		108 - 207	The light flashes with pulses, and the speed changes from slow to fast.
		208 - 212	Light strip opening
		213 - 225	Random strobe of light band, slow speed
		226 - 238	Random strobe with light band, medium speed

		239 - 251	The light belt flashes randomly and quickly.
		252 - 255	Light strip opening
18	The light is reddish.	0 - 255	The light is reddish.
19	The light is green.	0 - 255	The light is green.
20	The light is blue.	0 - 255	The light is blue.
21	Lamp strip effect	0	all-or-none
		1 - 63	Effect 1
		64 - 127	Effect 2
		128 - 191	Effect 3
		192 - 255	Effect 4
22	Speed of light band effect	0 - 255	The light belt has built-in effect speed, which changes from slow to fast.
23	reset	0 - 199	Light self-propelled
		200 - 205	Stay for 5 seconds to reset
		206 - 255	No function

Routine maintenance

Cleaning and maintenance

The equipment requires daily cleaning and maintenance. The service life of the equipment depends largely on the operating environment and daily cleaning and maintenance. Before opening any cover, cut off the power supply.

Optical components should be lightly rubbed, and the coating surface is brittle and easy to scratch. Do not use destructive solvents or it will damage the plastic or coating surface. Use a soft brush, cotton paper, air cleaner or pressure blower to remove dust from fans and air holes.