Apache Virtual Host

Och samband med DNS

Note

Creating virtual host configurations on your Apache server does not magically cause DNS entries to be created for those host names. You *must* have the names in DNS, resolving to your IP address, or nobody else will be able to see your web site. You can put entries in your `hosts` file for local testing, but that will work only from the machine with those `hosts` entries.

```
# Ensure that Apache listens on port 80
Listen 80
<VirtualHost *:80>
    DocumentRoot "/www/example1"
    ServerName www.example.com

    # Other directives here
</VirtualHost>

<VirtualHost *:80>
    DocumentRoot "/www/example2"
    ServerName www.example.org

    # Other directives here
</VirtualHost>
```

The asterisks match all addresses, so the main server serves no requests. Due to the fact that the virtual host with `ServerName www.example.com` is first in the configuration file, it has the highest priority and can be seen as the *default* or *primary* server. That means that if a request is received that does not match one of the specified `ServerName` directives, it will be served by this first `<VirtualHost>`.

https://httpd.apache.org/docs/2.4/vhosts/examples.html

- ServerName är det som ska stämma med DNS och FQDN.
  - Tex www.aftonbladet.se

Lämpligt arbetssätt/metodik

1. DNS peka på webserver1
    1. websida1.domain.tld, websida2.domain.tld pekar på IP 1.2.3.10
2. Konfigurera virtual host för två websidor, websida1, websida2
3. Surfa till websida1, websida2
4. Klona eller installera server 2
    1. Kontrollera att server 2 fungererar med DNS som ovan till IP 1.2.3.20
5. Lastbalanseraren
    1. Kontrollera att lastbalanserare 1 fungererar med DNS som ovan till IP 1.2.3.30
6. 2 x Lastbalanserare
7. VRRP
8. *Certifikat TLS/SSL*

- CURL
- WGET
- NC

- NSLOOKUP
- DIG

- Alias/CNAME
- TTL ändra TTL till 0-10