

Additional Resources: Product Page | 3D Model | PCB Footprint

**date** 09/11/2024

page 1 of 5

# MODEL: CMT-0502-75-SMT-TR | DESCRIPTION: MAGNETIC BUZZER TRANSDUCER

#### **FEATURES**

- · surface mount
- · low profile
- magnetic
- externally driven





#### **SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated voltage	Vo-p		3.0		Vo-p
operating voltage		2.0		5.0	Vo-p
current consumption	at rated voltage, 4,000 Hz, ½ duty square wave			100	mA
rated frequency			4,000		Hz
sound pressure level	at 10 cm, rated voltage, 4,000 Hz, ½ duty square wave	75			dB
coil resistance		10	12	14	Ω
dimensions	5 x 5 x 2				mm
weight			0.3		g
material	LCP				
terminal	surface mount (brass)				
operating temperature		-40		85	°C
storage temperature		-40		85	°C
RoHS	yes				

### **SOLDERABILITY**


Note:

parameter	conditions/description	min	typ	max	units
reel storage	at relative humidity <60%			25	°C
reflow soldering <sup>2</sup>	see recommended reflow soldering profile			260	°C
drying conditions <sup>3</sup>	bake at 40°C for 24 hours				

2. It is recommended to reflow solder within 48 hours from opening vacuum packaging at a temperature <30°C & relative humidity <60%.

1. All specifications measured at 25±3°C, humidity at 60~70%, under 86~106 kPa pressure, unless otherwise noted.

3. When out of packaging for more than 48 hours




Top View


# **MECHANICAL DRAWING**

units: mm


tolerance: ±0.5 mm



# FREQUENCY RESPONSE CURVE




### **APPLICATION CIRCUIT**



### **PACKAGING**

units: mm

Reel Size: Ø330 mm Reel QTY: 2,000 pcs per reel Carton Size: 350 x 350 x 205 mm Carton QTY: 10,000 pcs per carton



LOT NO:

350

Additional Resources: Product Page | 3D Model | PCB Footprint

SAME SKY | MODEL: CMT-0502-75-SMT-TR | DESCRIPTION: MAGNETIC BUZZER TRANSDUCER

**date** 09/11/2024 | **page** 5 of 5

### **REVISION HISTORY**

rev.	description	date
1.0	initial release	07/23/2019
1.01	brand update	12/18/2019
1.02	logo, datasheet style update	08/05/2022
1.03	CUI Devices rebranded to Same Sky	09/11/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.