

Physics Homework

Haixuan Lin

(Fudan University department of physics)

Abstract

In order to improve my computer and English skills, please allow me to complete this physics homework in English context with \LaTeX , so as to improve my professional level. Sorry for the inconvenience!

1 Question 5-2

For satellite, according to the law of conservation of angular momentum, we have

$$3R \cdot m4v_0 = r \cdot mv_0 \quad (1)$$

So

$$r = 12R$$

2 Question 5-5

(1)

Before and after a small rocket launch, the system's orbital energy is

$$\frac{1}{2}mv_0^2 - G\frac{Mm}{R_0} = -G\frac{Mm}{2R_0} \quad (2)$$

$$\frac{1}{2}m(v_0 + \Delta v_1)^2 - G\frac{Mm}{R_0} = -G\frac{Mm}{\frac{8}{3}R_0} \quad (3)$$

So

$$\frac{\Delta v_1}{v_0} = \frac{\sqrt{5}}{2} - 1$$

(2)

In order to accomplish the same effect, Δv_2 subjects to

$$\frac{1}{2}m(v_0 + \Delta v_1)^2 = \frac{1}{2}m(v_0^2 + \Delta v_2^2) \quad (4)$$

So

$$\frac{\Delta v_2}{v_0} = \frac{1}{2}$$

3 Question 5-8

Let J be the moment of inertia of the rod, according to the law of conservation of angular momentum, we have

$$J\omega = mv_0l \quad (5)$$

The mechanical energy of the system is conserved, so

$$\frac{1}{2}J\omega^2 = (mgl + m'2l)(1 - \cos \theta) \quad (6)$$

Finally

$$J = m'l^2 + (m + m')l^2 + m'4l^2 \quad (7)$$

So

$$\theta = \arccos \left(1 - \frac{v_0^2}{2g} \frac{m^2}{(m + 6m')(m + 2m')} \right)$$

4 Question 5-9

(1)

According to the definition of barycenter, we choose the middle point of the rope and

$$x_C = \frac{m_1 \frac{-l}{2} + m_2 \frac{l}{2}}{m_1 + m_2} \quad (8)$$

The above equation takes a derivative with respect to time

$$v_C = \frac{m_1 v_1 + m_2 v_2}{m_1 + m_2} \quad (9)$$

In the system of barycenter

$$v'_1 = v_1 - v_C \quad (10)$$




Figure for 5-10

$$\omega = \frac{v'_1}{x_C + \frac{l}{2}}$$

(11) For the system on the bar, according to the impulse theorem

So

$$\begin{aligned} L &= [m_1(x_C + \frac{l}{2})^2 + m_2(\frac{l}{2} - x_C)^2]\omega \\ &= \frac{m_1 m_2}{m_1 + m_2}(v_1 + v_2)l \end{aligned} \quad 2mv_C = I \quad (14)$$

According to theorem of moment of impulse, for the system on the bar

(2)

In the system of barycenter, tension provides centripetal force

$$J\omega = I \frac{l}{2} \sin(\frac{\pi}{4} - \beta) \quad (15)$$

Because it's an elastic collision, mechanical energy is conserved

5 Question 5-10

(1)

$$\frac{1}{2}mv_0^2 = \frac{1}{2}mv_f^2 + \frac{1}{2}2mv_C^2 + \frac{1}{2}J\omega^2 \quad (16)$$

Let β subjects to

So

$$v_f = v_0 \tan \beta \quad (12)$$

And impulse I subjects to

$$I \cos \beta = mv_0 \quad (13)$$

$$\begin{aligned} v_f &= v_0 \tan \left(\frac{1}{2} \arctan \frac{51\sqrt{2} + 34}{68} \right) \\ &\approx 0.5469181607v_0 \end{aligned}$$

(2)

We can also have that

$$\omega = \frac{v_0}{\sqrt{2}l} \left[1 - \tan \left(\frac{1}{2} \arctan \frac{51\sqrt{2} + 34}{68} \right) \right]$$

$$\approx 0.320377241 \frac{v_0}{l}$$

6 Question 5-11

According to Newton's second law and kinematics

$$T = m_1g + m_1a_1 = m_2g + m_2a_2 \quad (17)$$

$$t = \sqrt{\frac{2h_1}{g}} = \sqrt{\frac{2h_2}{g}} \quad (18)$$

The solution is that

$$t = \sqrt{\frac{-2 \frac{m_1 h_1}{g} - m_2 h_2}{m_1 - m_2}}$$

7 Question 5-15

By observation, $mg < m \frac{v_0^2}{r_0} = \frac{9}{2}mg$, as a result, the object will go further and further from the centre

$$r_{min} = r_0$$

In this process, according to conservation of angular momentum and conservation of mechanical energy

$$mvr = mv_0r_0 \quad (19) \quad (2)$$

$$\frac{1}{2}m(v_0^2 - v^2) = mg(r - r_0) \quad (20)$$

So

$$r_{max} = 3r_0$$

8 Question 5-19

According to conservation of angular momentum and conservation of mechanical energy

$$2ma^2\omega_0 = 2mx^2\omega \quad (21)$$

$$\frac{1}{2}2ma^2\omega_0^2 = \frac{1}{2}2mx^2\omega^2 + 2\frac{1}{2}m \left(\frac{d}{dt}x \right)^2 \quad (22)$$

The x is the distance from the centre to the small ball. The solution can be] write as be-

low

$$\omega = \frac{\omega_0}{\omega_0^2 t^2 + 1}$$

$$\alpha = \frac{d}{dt}\omega = -\frac{2\omega_0^2 t}{(\omega_0^2 t^2 + 1)^2}$$

9 Question 5-20

(1)

According to conservation of angular momentum and conservation of mechanical energy

$$mva = mv_1L_1 \quad (23)$$

$$3mva = mv_2(4a - L_1) \quad (24)$$

$$2\frac{1}{2}mv^2 = \frac{1}{2}mv_1^2 + \frac{1}{2}mv_2^2 \quad (25)$$

So

$$L_1 = \frac{6}{\sqrt{46} \cos \left(\frac{1}{3} \arccos \left(-\frac{121}{23\sqrt{46}} \right) \right) - 1} a$$

$$\approx 1.653165286a$$

According to conservation of angular momentum and conservation of mechanical energy

$$mrv_{1n} = mav \quad (26)$$

$$m(4a - r)v_{2n} = m3av \quad (27)$$

The length of the rope is constant

$$\frac{d^2r_1}{dt^2} + \frac{d^2r_2}{dt^2} = 0 \quad (28)$$

The kinetic equations are

$$m \frac{d^2r_1}{dt^2} = m \frac{v_{1n}^2}{r} - T \quad (29)$$

$$m \frac{d^2r_2}{dt^2} = m \frac{v_{2n}^2}{r} - T \quad (30)$$

We can get the expression of T , and according to *Holder* inequation

$$\begin{aligned} T &= \frac{ma^2v^2}{2} \left(\frac{1}{r^3} + \frac{3}{(4a - r)^3} \right) \\ &\geq \frac{ma^2v^2}{2} \frac{(1 + \sqrt{3})^4}{(r + 4a - r)^3} \\ &= \frac{(1 + \sqrt{3})^4}{128} \frac{mv^2}{a} \\ &\approx 0.4352563509 \frac{mv^2}{a} \end{aligned}$$