

SLC Walkthrough for Practice Set - Week 1

- ☐ Import required libraries.
- ☐ Load data set.

Let's begin with some hands-on practice exercises:

1. Is the target variable imbalanced?

HINT:

Plot the count plot for the target variable, And see, Is the target variable imbalanced or not?

2. Build a full logistic model and calculate the odds for each variable. HINT:

- Prepare the variables before building the model.

Ex:

- ☐ Scale the numerical variables and encode the categorical variables.
- ☐ Split the dataset into train set and test set.
- Fit logit model.
- Get params, Params returns the coefficients of all the independent variables.
- take the exponential of the coefficient of a variable to calculate the odds.


3. Calculate the Specificity and Sensitivity from the confusion matrix of the full model (consider the probability threshold as 0.25).

HINT:

- Get the probability values from the trained values.
- And set the threshold as 0.25 and convert probability values into labels by below condition.

Ex: if probability_value > 0.25 then 1 else 0.

- Use confusion matrix function from sklearn.metrics and calculate specificity and sensitivity.
4. Build a logistic model on the 6 features obtained by RFE and plot the ROC curve
- HINT:
- Build the RFE feature selection model with number of features to select is 6.
 - Build the Logistic model on the 6 selected features.
 - Use ROC curve to plot scores for different thresholds. Ex: take FPR and TPR to plot the roc curve.



5. Obtain the optimal value of cut-off probability for the full model using the Youden's index.
- HINT:
- Use roc curve method to get FPR, TPR and Threshold.
 - Create a data frame with 3 columns namely FPR, TPR and Threshold.
 - Take the difference between TPR and FPR and add the difference values as a column in the data frame.

Ex: `df_name["Difference"] = df_name.TPR - df_name.FPR`

- ☐ Choose the threshold that has high difference value.

6. Consider the cut-off probability obtained from Youden's index for the full model and calculate the following measures.
 - a. f-1 score.
 - b. Accuracy.
 - c. Kappa Score.

HINT:

- Use probability cut off(threshold) value which you obtained from the question 5.
- Convert the probability values into class labels namely 0 and 1.
Ex: if probability value is greater than cut-off value then 1 else 0.
- Use sklearn metrics to find f1- score and accuracy and kappa score.

7. Identify the variables involved in multicollinearity. HINT:
Use VIF method to identify the variable.

8. Build a logistic regression model using the categorical variables and the variables obtained after calculating VIF. Also, plot the ROC curve and compute the AUC score (consider the cut-off probability as 0.6).

HINT:

- Select the features which are not correlated, we found in the VIF calculation. And also use categorical variable as well.
- Build the logit model and consider 0.6 as threshold to separate the class labels.
- Follow the question number 4 points to plot the ROC and AUC plot.

9. Consider the costs of false negatives and false positives as 2 and 0.5 respectively to obtain the optimal cut-off probability for which the total cost will be minimum.

HINT:

Multiply False negative with 2 and False positives with 0.5 for different thresholds.

Use loop to iterate the multiple thresholds, choose a threshold which has less cost.

10. Build a full logistic model using the optimal cut-off probability obtained in Q9. Also, plot the confusion matrix and ROC curve along with the AUC score.

HINT:

Convert the probability values into class label with a threshold obtained in the question 9.

Plot the confusion matrix and roc auc score using sklearn library.