

Exercise 1: Configuring a Basic Spring Application

Scenario:

Your company is developing a web application for managing a library. You need to use the Spring Framework to handle the backend operations.

Steps:

1. **Set Up a Spring Project:**
 - Create a Maven project named **LibraryManagement**.
 - Add Spring Core dependencies in the **pom.xml** file.
2. **Configure the Application Context:**
 - Create an XML configuration file named **applicationContext.xml** in the **src/main/resources** directory.
 - Define beans for **BookService** and **BookRepository** in the XML file.
3. **Define Service and Repository Classes:**
 - Create a package **com.library.service** and add a class **BookService**.
 - Create a package **com.library.repository** and add a class **BookRepository**.
4. **Run the Application:**
 - Create a main class to load the Spring context and test the configuration.

pom.xml

```
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
    http://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>

  <groupId>com.library</groupId>
  <artifactId>LibraryManagement</artifactId>
  <version>0.0.1-SNAPSHOT</version>

  <dependencies>
    <!-- Spring Core -->
    <dependency>
      <groupId>org.springframework</groupId>
      <artifactId>spring-context</artifactId>
```

```
        <version>5.3.34</version>
    </dependency>
</dependencies>
</project>
```

applicationContext.xml:

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xsi:schemaLocation="
           http://www.springframework.org/schema/beans
           http://www.springframework.org/schema/beans/spring-beans.xsd">

    <bean id="bookRepository" class="com.library.repository.BookRepository" />

    <bean id="bookService" class="com.library.service.BookService">
        <property name="bookRepository" ref="bookRepository" />
    </bean>

</beans>
```

com.library.repository

◆ **BookRepository.java**

```
package com.library.repository;
```

```
public class BookRepository {
    public void saveBook(String bookName) {
        System.out.println("Book saved: " + bookName);
    }
}
```

com.library.service

◆ **BookService.java**

```
package com.library.service;

import com.library.repository.BookRepository;

public class BookService {

    private BookRepository bookRepository;

    public void setBookRepository(BookRepository bookRepository) {
        this.bookRepository = bookRepository;
    }

    public void addBook(String bookName) {
        bookRepository.saveBook(bookName);
    }
}
```

MainApp.java:

```
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;
import com.library.service.BookService;

public class MainApp {

    public static void main(String[] args) {

        ApplicationContext context = new
        ClassPathXmlApplicationContext("applicationContext.xml");

        BookService bookService = (BookService) context.getBean("bookService");

        bookService.addBook("Spring Framework Mastery");
    }
}
```

OUTPUT:

