



Mock examination opportunity 3 (past paper)

Computer science (University of Pretoria)



Scan to open on Studocu



UNIVERSITEIT VAN PRETORIA
UNIVERSITY OF PRETORIA
YUNIBESITHI YA PRETORIA

*Faculty of EBIT/ Fakulteit van IBIT
Department of Computer Science/ Department van Rekenaarwetenskap
Program Design: Introduction / Programmeringontwerp: Inleiding
COS 110*

*Mock Exam Opportunity 3
2017/11/02*

Instructions

1. This is a mock question paper. The provided questions will not feature in the EO3.
2. The purpose of this question paper is to help you prepare for the upcoming EO3.
3. The memo to the question paper will not be provided.

Marks:

Question	Points	Score
Queues and Stacks / <i>Toue en Stapels</i>	28	
Recursion / <i>Rekursie</i>	14	
Linked lists and Recursion / <i>Geskakelde lyste en Rekursie</i>	32	
Total:	74	

Question 1 Queues and Stacks / *Toue en Stapels* (28 marks)

- 1.1 True or false: a queue is both a first in, first out, as well as a last in, last out data structure. (2)
Motive your answer. /

*Waar of vals: 'n tou is beide 'n eerste in, eerste uit, sowel as 'n laaste in, laaste uit datastruktuur.
Motiveer jou antwoord.*

True

Your motivation

- 1.2 Name one difference between a stack and a queue. / (2)
Noem een verskil tussen 'n stapel en 'n tou.

stack - grows at top insertions made at the top

queue - grows at the rear enqueues at the back

- 1.3 Will it make sense to implement a circular stack? Give a reason for your answer. / (2)
Sal dit sin maak om 'n sirkulêre stapel te implementeer? Gee 'n rede vir jou antwoord.

marks dependent on reasoning

- 1.4 Will it make sense to implement a circular queue? Give a reason for your answer. / (2)
Sal dit sin maak om 'n sirkulêre tou te implementeer? Gee 'n rede vir jou antwoord.

marks dependent on reasoning

1.5 For each of the following practical situations, indicate whether or not a queue would be an appropriate data structure, and provide an explanation for your answer. /

Vir elk van die volgende praktiese situasies, dui aan of 'n tou 'n gepaste datastruktuur sou wees of nie, en verduidelik jou antwoord.

- a) A video file is downloaded from a web server. The individual frames are downloaded in play order and are stored in a temporary buffer, until the entire video is downloaded and ready to be played. The temporary buffer is implemented as a queue. / (2)
'n Video-lêer word vanaf 'n web bediener afgelaai. Die individuele rame word in speelvolgorde afgelaai en in 'n tydelike buffer gestoor totdat die hele video afgelaai is en reg is om gespeel te word. Die buffer is as 'n tou geïmplementeer.

yes

stream movie from first frame to last frame

hence queue being FIFO it is a good option

- b) A string containing several nested pairs of brackets is checked for well-formedness. A string is well-formed if each opening bracket has a closing bracket of the same type. Furthermore, while nesting is allowed, each inner pair of brackets should be closed before its outer pair. For example, `[{}]` is well-formed, but `[{}]` is not. The string is scanned from left to right. When an opening bracket is encountered, it is enqueued to a temporary queue. When a closing bracket is encountered, an opening bracket is dequeued from the buffer, and its type is checked against the closing bracket. If both brackets' types match, the string is well-formed. / (2)
A string wat verskeie geneste hakies bevat word getoets om te bepaal of dit goed gevormd is. 'n String is goed gevorm as elke oop hakie 'n toe hakie van dieselfde tipe het. Verdermeer, alhoewel hakies genes kan wees, moet elke binneste paar toegemaak word voor sy buitenste paar. Byvoorbeeld, `[{}]` is goed-gevormd, maar `[{}]` is nie. Die string word van links na regs gelees. Elke oop hakie word in 'n tydelike tou geplaas. Wanneer 'n toe hakie gevind word, word 'n oop hakie vanuit die tou gehaal, en die oop hakie se tipe word dan vergelyk met die toe hakie s'n. As albei hakies se tipe dieselfde is, is die string goed gevorm.

No

harder to determine if well formed

easier to implement using a stack

1.6 The STL provides similar classes called `stack` and `queue`, both of which have functions called `push` and `pop`. Answer the following questions:/

Die STL verskaf soortgelyke klasse genaamd `stack` en `queue`, waarvan beide funksies genaamd `push` en `pop` het. Beantwoord die volgende vrae:

- a) Does `push` perform a different action in the `stack` class than in the `queue` class? Explain your answer. / (2)
Voer `push` 'n ander aksie in die `stack` klas uit as in die `queue` klas? Verduidelik jou antwoord.

No

It calls `push_back()` function on its inner container in both classes

- b) Does **pop** perform a different action in the **stack** class than in the **queue** class? Explain your answer. / (2)

Voer pop 'n ander aksie in die stack klas uit as in die queue klas? Verduidelik jou antwoord.

Yes

Stack elements are removed from the back of the inner container

Queue elements are removed from the front of the inner container

- 1.7 Suppose you are tasked with implementing a reverse queue in which elements are enqueued at the front and dequeued at the rear. The implementation is dynamic, and you are using the following **struct** for the nodes that are containing the elements: /

Veronderstel jy moet 'n agterstevoor tou implementeer, waar elemente aan die voorkant bygevoeg word en van die agterkant verwyder word. Die implementasie is dinamies, en jy gebruik die volgende struct vir die nodusse wat die elemente bevat:

```
struct Node {  
    char element;  
    Node *next;  
};
```

Suppose your queue class has **Node** pointers called **front** and **rear**, which point to the front and rear nodes in the queue. /

Veronderstel jou tou het Node wysers genaamd front en rear wat na die voorste en agterste nodusse in die tou wys.

- a) Implement **enqueue** with the following signature: / (3)
Implementeer enqueue met die volgende verklaring:

```
void RQueue::enqueue(char el);
```

refer tutorial memo

- b) Implement **dequeue** with the following signature (the function should return the dequeued value): /
*Implementeer **dequeue** met die volgende prototipe (die funksie moet die verwyderde element terugstuur):*

```
char RQueue::dequeue();
```

refer tutorial memo

- c) Does the different (reverse) implementation affect the behaviour of the queue from the client's perspective? Explain your answer. / *Veroorsaak die ander (agterstevoor) implementasie die gedrag van die tou vanuit die klient se perspektief? Verduidelik jou antwoord.*

No

GUI and back-end data structure are separate entities

Or

- 1.8 The STL **stack** class is a container adapter that uses another container internally. It provides a simple stack-like interface by using the functions **push_back**, **pop_back** and **back** on its internal container. The adapter can only be used on certain containers that provide those functions. You are tasked with creating a new container adapter called **StackQueue**, which uses an STL **queue** as an internal container. The class has the following simple definition: /

*Die STL stapel (**stack**) klas is 'n houer-aanpasser wat 'n ander houer intern gebruik. Dit verskaf 'n eenvoudige stapel-agtige gedrag deur die funksies **push_back**, **pop_back** en **back** op sy interne houer te roep. Die aanpasser kan slegs op sommige houters gebruik word wat wel daardie funksies verskaf. Jy word gevra om 'n nuwe houer-aanpasser genaamd **StackQueue** te skep wat 'n STL tou (**queue**) as 'n interne houer gebruik. Die klas het die volgende eenvoudige definisie:*

```
template <class T>
class QueueStack {
    queue<T, deque<T> > q;
public:
    bool empty() { return q.empty(); }
    void push(T);
    T pop();
};
```

Note that **pop**'s return type is **T**; it should return the element that is begin popped from the stack.
 / *Let wel dat **pop** se terugkeertipe **T** is; dit moet die element wat van die stapel verwyder word terugstuur.*

Assume that the **push** function is implemented as follows: /

*Aanvaar dat die **push** funksie soos volg geïmplementeer is:*

```
template <class T> void QueueStack<T>::push(T el){
    q.push(el);
```

- a) Provide an implementation for the **pop** function. You may use a temporary **queue** object if needed. / (3)

*Verskaf die implementasie vir die **pop** funksie. Jy mag 'n tydelike **queue** objek gebruik waar nodig.*

```
template <class T> T QueueStack<T>::pop();

{

    int s = q.size();
    queue> p;
    for(int i=0; i < size-1; i++)
    {
        p.push_back(q.front());
        q.pop_front();
    }

    T data = q.front();

    q.pop_front();

    int s2 = p.size()
    for(int i = 0; i { q.push_back(p.front()); p.pop_front();}return data;

}
```

Question 2 Recursion / *Rekursie* (14 marks)

- 2.1 Why would a programmer most likely not use recursion to implement a string library, but rather use iteration? / *Waarom sal 'n programmeerder waarskynlik nie rekursie gebruik om 'n string biblioteek te implementeer nie, maar eerder van iterasie gebruik maak?* (2)

String libs are bounded by ascii characters hence not suitable for recursion

- 2.2 Each of the following recursive functions has an error in the code. For each of these functions, write down what the error is, as well as how the error can be corrected. / *Elkeen van die volgende rekursiewe funksies het 'n fout in die kode. Skryf vir elkeen van die funksies neer wat die fout is en hoe die fout reggemaak kan word.*

a) `void foo(int i) {
 if (i < 1) return;
 cout << i << endl;
 foo(i);
}` (2)

error: line 4 -> foo(i);

i is not incremented;

correction: foo(--i);

b) `void printZeroToN(int n) {
 if (n < 0) return;
 cout << n- << endl;
 return printZeroToN(n);
}` (2)

error 1: order of print is N to Zero and not vice versa

or

error 2: head recursion should be used

correction

swap lines 3 & 4 and update n-1 on the new line 3

- 2.3 This question refers to the following algebraic equation: /
Hierdie vraag verwys na die volgende algebraïese vergelyking:

$$y = 1 - x + \frac{x^2}{2} - \frac{x^3}{6} + \frac{x^4}{24} + \cdots + (-1)^n \left[\frac{x^n}{n!} \right]$$

Assume that you are going to solve the algebraic equation with recursion. /
Aanvaar that jy die algebraïese funksie met rekursie gaan oplos.

- a) Write down the base case for the recursive function. / (1)
Skryf die basisgeval vir die rekursiewe funksie neer.

if(n<=1)

- b) Write down the recursive case for the recursive function. / (1)
Skryf die rekursiewe geval vir die rekursiewe funksie neer.

if(n>1)

- c) Write down a recursive function to solve the algebraic equation. Take note that the factorial in the equation should also be solved with recursion and its recursive function should be written down. The function signature of the function solving the algebraic equation is as follows: / (6)

Skryf 'n rekursiewe funksie neer om die algebraïese vergelyking op te los. Neem kennis dat die faktoriaal in die vergelyking ook met rekursie opgelos moet word, en dat die rekursiewe funksie vir die faktoriaal neergeskryf moet word. Die funksieverklaring van die funksie wat die algebraïese funksie oplos is soos volg:

```
double calculateEquation(int x, int n);

{

    if(n<=1)
        return 1;

    return pow(-1,n)*(pow(x,n)/factorial(n)) + calculateEquation(x, n-1);

}
```

```
int factorial(n)
{
    if(n<=1)
        return 1;
    else
        return n * factorial(n-1);
}
```

Question 3 Linked lists and Recursion / *Geskakelde lyste en Rekursie* (32 marks)

Consider the following linked node **struct** and dynamic queue class: /
Beskou die volgende geskakelde nodus en dinamiese tou klas:

```
template <class T>
struct Node {
    T value;
    Node<T> *next;
};

template <class T>
class Dynque
{
    protected:
        Node<T> *front;
        Node<T> *rear;
        int numItems;
    public:
        Dynque();
        Dynque(Dynque&);
        virtual ~Dynque();
        virtual void enqueue(T); // add an element to rear
        T dequeue(); // remove an element from front
        bool isEmpty();
        int getNumItems();
        void clear(); // remove all elements
        void reverse(); // reverse order of elements
};
```

3.1 Implement the copy constructor of the **Dynque** class. /

(4)

*Implementeer die kopie konstrueerder van die **Dynque** klas.*

```
template
Dynq::Dynq(Dynq &obj)
{
    node* f = obj.front;

    if(f)
    {
        while(f!=obj.rear)
        {
            enqueue(f->value);
            f = f->next;
        }
        enqueue(obj.rear->value);
    }
    else
    {
        front = rear =NULL;
    }
}
```