n. ⁊ Thumbnail

Cong. !

If you're reading . few people lucky enough to receive a nPM1100 Thumnail board from one of our represent humbnail is a giveaway board for s 100's capabilities as a small, highly efficient PMIC that requires very little board space . The nPM1100 Thumbnail features a fu. 0 PMIC and the passive components required to make it operate, with solder p he nPM1100 on a 100 mil grid. It can thus be use by soldering it to a prototyping board. It can be used for powering applic 3.0 V supply and charging lithium-ion and lithiu a USB. For instructions see the user guide below. To read more ab nload the product brief, or visit the nPM1100 product page

Download PDF **Download nPM11] (/-/media/Software-and-other-downloads/Pro -PMIC--and-EK-PB.pdf)**

Ask us about this (/About-us/Contact-Us,

Key features

- Inductor choices optimized for size
- Requires no software to operate
- 3.0 V regulated output
- USB input
- Battery charging and power delivery
- Solder pads to essential pins on nPM1100
- Solder pads on a 100 mil grid for easily integrating with prototy

↓ Downloads (/Products/Development-hardware/nPM1100-EK/_Local/nP wnloads) Overview (/Products/Development-hardware/nPM1100-EK/_Local/nPM nfotabs) Downloads (/Products/Development-hardware/nPM1100-EK/_Local/nPM1100-Thumbnail/Downloads?lang=en#infotabs)

How to use it

Connector	Description	What to conn
D_N	USB Data-	Positive and negative data l etection.
D_P	USB Data+	If unused connect D_N to grou urrent limit.
VBUS	USB p	Connect to 5 V USB power for char
VBAT	B	Positive terminal on battery.
NTC		Battery thermistor, if unused connect to groun
GND		System ground.
CHG ERR	and error indication	Connect to indicator LEDs, optional, if unused leave oper
VOUTB	egulated output	Outputs 3.0 V regulated.
VS	System voltage	Outputs battery voltage or USB voltage.

very small IC surronded by small capacitors and an inductor, with a matchstick head for scale

ed products

nPM1100 PMIC

Ultra-small form-factor Power Management IC (PMIC) for charging batteries and power delivery

The nPM1100 is a dedicated power management IC (PMIC) with dual-mode configurable buck regulator and integrated battery charger. It is designed as a complementary component to Nordic's nRF52® Series and nRF53® Series System-on-Chips (SoCs) to ensure reliable power delivery and stable operation, whilst maximizing battery life through high efficiency and low quiescent currents. It can also be used as a generic PMIC device for any other suitable application. Its extremely compact form factor makes it ideal for advanced wearables, connected medical devices, and other size constrained applications. PCB area usage can be as low as 23 mm^2.
Read more (/Products/nPM1100)

nPM1100 EK

The nPM1100 Evaluation Kit (EK) is a tool for evaluating the nPM1100 PMIC and evaluate its features for your application. The kit features switches for all selectable settings, buttons to enter and exit ship mode and connectors for batteries, USB and headers for all pins on the PMIC.
Read more (/Products/Development-hardware/nPM1100-EK)

Qua

Corporate

Modern Slavery

Investors

Investor Relations Hub

Investor Calendar

Reports and Presentations

Analyst Coverage

News & Events

PR & Media Contacts

Wireless Quarter

Latest News

Upcoming Events

Nordicsemi.com

Nordicsemi.jp

TechDocs

DevZone

Nordicsem

nRF Cloud

DevAcademy

TechWebinars

Contact U | Privacy Policy | Marketing and Cookie Use Policy | Sitemap

Copy miconductor. All rights reserved