



RENKU CHEATSHEET

Getting Started

```
$ pip install renku
```

Install with pip

```
$ brew tap swissdatasciencecenter/renku
```

```
$ brew install renku
```

Install with Homebrew

```
$ cd my_project
```

```
$ renku init
```

Starting a Renku project

```
$ cd my_project
```

```
$ renku init --force
```

Initialize Renku for an existing Git project

Running

```
$ renku run <command> [--input <in_file>...]  
  [--output <out_file>...]
```

Execute a <command> with Renku tracking inputs and outputs. Input and output files are automatically detected from the command string. With --input and/or --output: Manually specify input or output files to track

```
$ renku run <command> [--input <in_file>...]  
  --no-output
```

Run a <command> that produces no output

```
$ renku run --success-code=<n> <command>
```

Run a command and treat <n> as successful exit-code.

```
$ renku rerun <path>...
```

Recreate the file(s) <path> by rerunning the commands that created them

```
$ renku update [<path>...]
```

Update all outdated output files created by renku run. With <path>'s: Only recreate these files.

Log

```
$ renku log [--revision <rev>] [<path>...]
```

Show provenance of data created in Renku. With <path>: Show only provenance of some files. With --revision: Limit to a commit or commit range (Git syntax)

Datasets

```
$ renku dataset create my-dataset
```

Create a new dataset

```
$ renku dataset
```

List all datasets in the project

```
$ renku dataset rm my-dataset
```

Remove a dataset

```
$ renku dataset add my-dataset <url>
```

Add data from <url> to a dataset
<url> can be a local file path, an http(s) address or a Git git+http or git+ssh repository.

```
$ renku dataset add my-dataset  
  --target <path> [--relative-to <rel-path>]  
  <github-url>
```

Add only data contained in <path> from Git
With --relative-to: Trim <rel-path> from <path> locally

```
$ renku dataset ls-files
```

List all dataset files in the project

```
$ renku dataset unlink my-dataset  
  [--include <path_or_pattern>]
```

Unlink (all) files from a dataset. With --include: Specify single path or pattern of files to unlink

```
$ renku dataset import <uri>
```

Import a dataset. <uri> can be a Zenodo or Dataverse URL or DOI.

```
$ renku dataset export <dataset> <provider>
```

Export the dataset <dataset> to <provider>. Providers: Zenodo

Workflow

```
$ renku workflow create [-o <file>] <path>...
```

Create a workflow description.

```
$ renku workflow set-name <name> [<path>]
```

Set a <name> for the last workflow. With <path>: Link file to workflow.

```
$ renku workflow remove <name>
```

Remove the <name> workflow.



RENKU CHEATSHEET

Show

```
$ renku show siblings [<path>...]
```

Show sibling output files created by the same command.

```
$ renku show inputs [--revision <rev>]
```

Show all input files. With <rev>: Show at revision.

```
$ renku show outputs [--revision <rev>]
```

Show all output files. With <rev>: Show at revision.

Config

```
$ renku config [--global] <key>
```

Show Renku config value for <key>. With --global: Read from global settings.

```
$ renku config [--global] <key> <value>
```

Set Renku config <key> to <value>. With --global: Read from global settings.

Available config options:

- **registry:** Docker image registry
- **zenodo.access_token:** Token for Zenodo export

Resources

Public instance of Renku:
<https://renkulab.io/>

Github:
<https://github.com/SwissDataScienceCenter/renku>

Documentation:
<https://renku.readthedocs.io/en/latest/>

Renku-Python Documentation:
<https://renku-python.readthedocs.io/en/latest/>

SDSC:
<https://datascience.ch/>

Misc

```
$ renku rm [<path>...]
```

Remove <path>'s from a renku repository. Removes from datasets and Git.

```
$ renku mv [<path>...] <destination>
```

Move <path>'s to <destination>

```
$ renku migrate datasets
```

Migrate datasets to the current Renku version.

```
$ renku doctor
```

Check system and repository for potential problems.

```
$ renku githooks install [--force]
```

Install Renku Git hooks. With --force: Override existing hooks.

```
$ renku githooks uninstall
```

Uninstall Renku Git hooks.

```
$ renku image pull
```

Pull an existing image from the project registry

```
$ renku storage pull <path>...
```

Pull <path>'s from external storage.

```
$ renku status [--no-output]
```

Show status of the Renku repository. With --no-output: Don't show output files.