

HONDA CB750K

TORQUE SPECIFICATIONS

Chassis

Item	Thread (mm)	Nm	lb-ft
Steering stem nut	24	78-118	58-87
Steering handlebar	8	18-25	13-18
Front fork top bridge	7	9-13	7-9
Front fork cap bolt	-	20-29	15-22
Front fork bottom bridge	10	29-39	22-29
Front axle holder	8	18-25	13-18
Front axle nut	12	54-64	40-47
Front brake disc	8	26-32	20-24
Brake hose bolt	10	25-34	18-25
Front brake caliper carrier	10	29-39	22-29
Front brake caliper A	10	29-39	22-29
Rear axle	18	78-98	58-72
Final driven sprocket	12	78-98	58-72
Swing arm pivot bolt	14	54-69	40-51
Rear brake torque link	8	18-25	13-18
Rear shock absorber (Upper)	10	20-29	14-22
Rear shock absorber (Lower)	10	29-39	22-29
Engine hanger bolt (4x)	10	29-39	22-29
Engine hanger bolt (1x)	12	54-64	40-48
Foot peg	12	54-64	40-47
Gearshift pedal	6	8-12	6-9

Engine

Item	Thread (mm)	Nm	lb-ft
Cylinder head cover	6	8-12	6-9
Cam holder	6	12-16	9-12
Cylinder head	10	35-39	26-29
Cam sprocket	7	22-25	16-19
Spark plug	-	12-16	9-12
Crankcase	8	21-25	15-18
A.C. generator	12	78-98	58-72
Primary shaft	12	78-98	58-72
Mainshaft	16	37-41	28-30
Drive sprocket	10	49-53	36-39
Connecting rod nut	-	29-33	22-25
Oil filter center bolt	-	27-31	20-23
Oil pressure switch	-	15-20	11-14
Neutral switch	-	16-20	11-14
Oil drain plug	14	34-39	25-29
Oil pipe	10	30-34	22-25
Spark advancer	8	32-36	24-27
Starting clutch	8	25-29	19-22
Oil filter bolt boss	-	34-44	25-33

Standard Torque Values

Item	Thread (mm)	Nm	lb-ft
5 mm bolt, nut	5	4.5-6.0	3.5-4.5
5 mm screw	5	3.5-5.0	2.5-3.6
6 mm bolt, nut	6	8-12	6-9
6 mm screw	6	7-11	5-8
6 mm flange bolt, nut	6	10-14	7-10
8 mm bolt, nut	8	18-25	13-18
8 mm flange bolt, nut	8	24-29	17-22
10 mm bolt, nut	10	29-39	22-29
10 mm flange bolt, nut	10	29-39	22-29
12 mm bolt, nut	12	49-59	36-43