Polarization Auditing Framework for LLMs: a Toxicity Detection Study

ANONYMOUS AUTHOR(S)

Many annotation tasks, such as toxicity detection, are subjective. A text one person finds harmful may seem acceptable to another, depending partly on their demographic or ideological background. Large Language Models (LLMs) are increasingly used for such tasks as a fast, low-cost alternative to human annotation, yet when people disagree about a text, an LLM's single label sides with one perspective. Previous work asks whose perspective LLMs take by measuring which groups they agree with across entire datasets. But on most texts annotators agree, so agreeing with one group means agreeing with all and the polarized texts, where annotators divide into opposing groups, are lost in the average. We present a framework for auditing an LLM on a given dataset, focused on these texts. It finds the polarized texts, keeps those whose polarization a specific annotator characteristic, such as political views, explains, derives the position of each side and measures which side the LLM takes, with and without sociodemographic prompting. Every result comes with its uncertainty, through minimum group sizes, a chance baseline, chance-corrected agreement and bootstrap errors, so that a user can see how far to trust it, for example before using an LLM for content moderation. Because the audit is run on a dataset, a model and a prompt, it makes no general claims about any of them. The audit applies to any subjective task whose data has several individual ordinal ratings per text and annotator characteristics. We apply it to four toxicity datasets and four widely used LLMs, where it finds clear sides in some datasets and none in others, as an illustration of how the audit works.

CCS Concepts: • **Computing methodologies** → **Natural language processing**; • **Social and professional topics** → *Computing / technology policy*.

Additional Key Words and Phrases: large language models, toxicity detection, annotator disagreement, polarization, human label variation, LLM auditing, sociodemographic prompting

ACM Reference Format:

Anonymous Author(s). 2026. Polarization Auditing Framework for LLMs: a Toxicity Detection Study. In *Proceedings of ACM Conference on Fairness, Accountability, and Transparency (FAccT '27).* ACM, New York, NY, USA, 45 pages. https://doi.org/10.1145/nnnnnnn.nnnnnnn

1 Introduction

Annotation with large language models (LLMs) has become common practice for subjective tasks such as toxicity detection [13]. Yet model labels are not neutral. When annotators disagree about a text, any label sides with some of them and against others and systems built on these labels may inherit that side [16, 33]. For a given dataset, we therefore do not know whose annotators a model's labels agree with when people disagree.

Prior work finds that models favor some groups of annotators over others [1, 3]. These patterns, however, vary across datasets and setups, which is why each dataset needs its own audit. Moreover, prior work measures alignment over all texts, and on most texts annotators largely agree. There a model's label matches either all annotators or none of them, so agreement shows that the model labels like annotators in general, but not whose side it takes (Figure 1a). Even where a side can be measured, with few annotators per group it can be luck, so a result must also show how far it can be trusted.

We propose an audit framework that shows which annotator group, if any, such as liberal or conservative, a model's labels consistently follow on the polarized texts of a dataset, and how sure we can be of it. A text is polarized when its ratings split into opinion groups [9, 23]. On such a text a model's label necessarily agrees with one group and disagrees with the other (Figure 1b), so a consistent alignment across these texts shows whose side the model takes. The framework has three steps. (1) It detects the polarized texts of the dataset. (2) It retains those whose polarization an annotator characteristic accounts for [24] and checks this against chance. (3) It compares the model's labels with each




Fig. 1. LLMs as annotators on texts where people disagree. (a) When annotators agree, a model's label matches either all of them or none of them, so it reveals nothing about sides. (b) When annotators are polarized, the model's label necessarily agrees with one group and disagrees with the other.




Fig. 2. Overview of the audit framework. For a given dataset, it detects polarized texts, retains those whose polarization an annotator characteristic accounts for, and compares the labels of each LLM annotator with each group of that characteristic.

group of that characteristic, with and without the characteristic in the prompt. Each step comes with a statistical check, so that every result shows how far it can be trusted. It needs only individual ordinal ratings, annotator characteristics and several ratings per text, so it applies to any subjective task with such data (Figure 2).

We apply the framework to four toxicity datasets and four widely used LLMs, each dataset on its own, to show what an audit lets a user see. It shows which polarized texts a characteristic accounts for and whether each model follows one group's position, toxic or civil, or only leans toward one label. Where no side can be read, or an attribution cannot be told from chance, the audit points to a likely reason, for example that the groups are too small or that the model

labels almost every text the same way. Such an outcome is a result of the audit and not a failure of it. Sociodemographic prompting (SCDP), which tells the model who is labeling, shows how stable a side is, and we use it as a diagnostic and not as a mitigation. The results depend on the dataset, the model and the prompt, so they illustrate the audit and are not general claims about the models.

Our contributions are:

- An audit framework that shows whose perspective an LLM annotator reproduces on the polarized texts of a dataset, and how sure we can be.
- An application to four toxicity datasets and four LLMs, showing that the side a model takes depends on the dataset, and when no side can be read.
- Practical uses of the audit, such as checking a model before it labels or moderates content, choosing a model for a dataset or population, deciding whether it can extend or relabel a dataset, and repeating the check when it is updated.

2 Related Work

2.1 Human label variation

Human judgments frequently differ in subjective tasks such as toxicity detection, hate speech detection and sentiment analysis. Early work largely treated disagreement as annotation error and resolved it into a single label through majority voting or annotator filtering [2]. More recent work argues that this variation is a signal rather than noise [28] and that collapsing it into a single label erases minority perspectives [21, 39]. This disagreement has been linked to annotator identity and beliefs [16, 18, 34, 43, 45] and has been preserved through soft labels [11] or by modeling individual annotators [15, 21]. Other work groups together annotators who label texts in similar ways, regardless of their demographics, to find shared perspectives [4, 42]. However, sociodemographic attributes do not always account for disagreement, as models given annotators' demographics mostly learn individual behavior rather than group patterns [22]. We therefore do not assume that a characteristic accounts for disagreement, but test it for each text and keep only those where it does.

2.2 Polarization

Among the forms of disagreement discussed above, polarization is especially relevant for auditing models, because the groups hold clearly distinct views, so a model that agrees with one of them takes a concrete side. Polarization has long been studied in the social sciences, where it describes the division of people into opposing camps. It has been measured in social networks and text [12, 20, 26] and has taken several meanings [5]. In its group-based sense, polarization is more than a spread of opinions, as it requires homogeneity within groups and heterogeneity across them [9]. In annotation, this means that annotators form distinct opinion clusters instead of varying around a shared consensus [23]. Unlike general disagreement [34, 39], polarization therefore indicates that a text means something different to different groups of people. Bridging approaches such as Birdwatch instead look for content that opposing groups agree on [44]. We study the opposite, texts where no such agreement exists.

To find polarized texts, we need a polarization measure for ordinal ratings, such as van der Eijk's agreement [41], the dip test [17] or probabilistic agreement measures [6]. We use the Distance From Unimodality (DFU)[1], which correlates well with human judgments of polarization [23], agrees with mode detection in an independent comparison [20], and

[1]We use the normalized version of DFU [24] throughout and refer to it as DFU for simplicity.

best recovered every polarization pattern in our synthetic test, from consensus to minority and multi-group polarization (Appendix A). The ratings show the opinion groups but not who belongs to them. To know which groups of annotators, defined by a characteristic, form each side, we then apply A Posteriori Unimodality (AU) [24], a method that attributes a text's polarization to a specific characteristic. We take the attribution of polarization from this work. We add a chance check of the attribution, a chance-corrected measure of how models align with annotator groups on the attributed texts under different prompts, and statistical checks at each step (Section 4).

2.3 Whose perspectives do LLMs reflect?

A growing body of work asks whose views language models represent. In public opinion surveys, LLMs align more closely with some demographic groups and countries than with others [8, 31]. The same holds in annotation tasks, where models agree more with some annotator groups than others [14, 35, 36, 40], for example with Western, White, college-educated and younger annotators [32]. Beyond demographics, LLMs also have a political leaning that affects tasks such as hate speech detection [10], but measuring it with political questionnaires gives unstable results [30]. More generally, these alignment patterns vary across datasets and setups [1, 3]. Rather than measuring a model's general tendencies across all texts, we place it between concretely opposing opinions, on texts where annotator groups clearly disagree, and observe which side it falls on, since there its label is a real choice between perspectives.

2.4 LLMs as annotators and persona prompting

Because they are fast and cheap, LLMs are increasingly used to annotate data for subjective tasks, sometimes matching or outperforming crowd workers [13, 37, 38]. This raises the question of whose judgments such data represents [29]. A common answer is SCDP, which asks a model to respond as a member of a given demographic or ideological group. However, this assumes that a model knows how members of a group judge a text, although even real members of the same group often disagree [22]. In practice, the effects of SCDP depend on the model, dataset and prompt [3], and prompted models reproduce human group differences only weakly [14, 36]. We therefore do not use SCDP to make models represent groups or to mitigate bias. Instead, we use it as a diagnostic, deliberately pushing a model toward one side on polarized texts to test whether its position shifts.

3 Datasets

We present a framework that works as an audit, so it applies to any dataset that meets three requirements. To give a complete analysis, we apply it to four datasets that share one annotation task, toxicity detection. They differ in size, number of ratings per text and annotator characteristics.

First, the dataset must provide the individual labels of each annotator on an ordered scale, not only an aggregated label, since polarization is measured on the distribution of labels per text. Second, each text needs at least four labels, so that two annotator groups have at least two members each, since a single label is unimodal by definition and would make attribution trivial (Section 4.1.3). Third, it must report annotator characteristics, so that polarization can be attributed to a group. All four datasets meet these requirements (Table 1).

Attitudes. Sap et al. [34] collected toxicity ratings for posts selected for containing African American English, anti-Black language or vulgarity, and therefore likely to divide annotators. Each post was rated by about six of 173 annotators recruited on Amazon Mechanical Turk, who answered how toxic, on a scale from 1 to 5. Besides gender, race and age, annotators reported their political leaning and their traditionalism, the importance they give to traditional values.

Table 1. Overview of the datasets after preprocessing. Ratings per text are medians. Annotator counts for Attitudes and Kumar are those reported by the authors, since these datasets do not release annotator identifiers (Appendix B.1).

Dataset	Source	Texts	Annotators	Ratings/text	Scale	Demographic	Non-demographic
Attitudes [34]	Twitter	625	173	6	1–5	gender, race, age	politics, traditionalism
POPQUORN [25]	Reddit	1,500	228	8	1–5	gender, race, age	education, occupation
MHS [18]	Reddit, Twitter, YouTube	5,990	7,577	4	1–3	gender, age	politics
Kumar [19]	Twitter, Reddit, 4chan	107,620	17,280	4	1–5	gender, race, age	politics, religion

POPQUORN. Pei and Jurgens [25] collected offensiveness ratings for 1,500 Reddit comments, each rated by about eight of 262 annotators. Annotators rated how offensive each comment was, from 1 (*not offensive at all*) to 5 (*very offensive*). Besides gender, race and age, annotators reported their education and occupation.

MHS. The Measuring Hate Speech corpus [18] contains comments from Reddit, Twitter and YouTube, rated by Amazon Mechanical Turk workers. We use its hate speech item, answered as *No*, *Unclear* or *Yes*. Most comments received only one to three ratings, while 70 reference comments were rated by hundreds of annotators each, used by the corpus authors to link annotators on a common scale. We use the annotators' gender, age and political ideology.

Kumar. Kumar et al. [19] collected toxicity ratings for 107,620 comments from Twitter, Reddit and 4chan, each rated by five of 17,280 Amazon Mechanical Turk workers. Annotators answered how toxic they personally found each comment, from *not at all toxic* to *extremely toxic*. Besides gender, race and age, annotators reported their political affiliation and how important religion is to them.

Preprocessing. Preprocessing follows the same principles in every dataset, adapted to its scale and annotator categories, with details in Appendix B. First, we shift the MHS and Kumar scales, which start at 0, to start at 1, so that all scales start at 1. Following Kumar et al. [19], we then label ratings of 3 or more as toxic and lower ratings as civil. This threshold is the midpoint of the five-point scales, and it means *moderately toxic* in Kumar. In MHS, only *Yes* counts as toxic, while *Unclear* counts as civil, so a rating is toxic only when the annotator explicitly identifies hate speech. Second, we keep only texts with at least four ratings, which removes 85% of the MHS comments (39,565 to 5,990), one Attitudes text and none in POPQUORN or Kumar. Third, we merge fine-grained annotator categories into broader, commonly used groups, for example age ranges into generations [7] and political views into left, center and right. This makes groups large enough to compare, since with the original categories most texts would have at most one annotator per category, and it makes results easier to interpret. Finally, we remove ratings from annotators whose category is too rare to form a group, such as non-binary or Native American annotators, or does not define a group, such as *other*, *prefer not to say* or missing answers. This removes 3.1% (Attitudes), 4.2% (MHS), 12.9% (POPQUORN) and 16.3% (Kumar) of the remaining ratings, which is why Table 1 reports fewer ratings per text than the original datasets, and fewer annotators for POPQUORN and MHS. As a result, our analysis does not cover these small groups, which we discuss as a limitation in Section 8. Some texts are left with fewer than four ratings, and these remain in the dataset statistics but cannot be attributed.

4 Methodology

Our framework works like an audit (Figure 2). Given a dataset and a model, it asks on which texts annotators are polarized, which characteristic divides them and which side the model takes. It is applied to each dataset separately, so every result depends on the dataset, the model and the prompt. Each step comes with a check, so the framework tells not only a result but also how far it can be trusted, and each check answers a different question. The 10-text rule shows whether a group has enough texts to say anything about and the chance baseline shows whether attribution is more than chance (Section 4.1). The chance-corrected κ per group shows whether a model follows a group beyond the label it gives most, the bootstrap shows whether a result depends on which texts the dataset has, and the SCDP shows whether a side holds when the prompt changes (Section 4.2).

4.1 Detecting and attributing polarization

4.1.1 Detecting polarization. We measure the polarization of each text with DFU [23, 24], as motivated in Section 2.2. A text is not polarized when its ratings form a single peak, since annotators then share one opinion and only vary around it. It is polarized when the ratings form more than one peak, since annotators split into separate opinions. DFU measures this. It starts at the most frequent rating and moves toward both ends of the scale, recording every rise in frequency along the way (Appendix C.1). Around a single peak the frequencies only fall, so DFU is zero. A rise means another peak, and the larger it is relative to the most frequent rating, the larger DFU becomes. We keep all texts with $DFU > 0$ as polarized, since their polarization is detectable and may be attributable to annotator characteristics.

4.1.2 Attributing polarization. DFU shows that a text is polarized, but not which annotator characteristic the polarization follows. To find out, we use AU [24]. If a text is polarized overall but each group of annotators sharing a characteristic is not, that characteristic accounts for the polarization, and we say that the text is attributed to it. For example, if left-leaning annotators all rate a text as civil and right-leaning annotators all rate it as toxic, the text is polarized overall, but each group agrees within itself, so political leaning accounts for the polarization. AU works with any polarization measure. We use DFU, so a characteristic with groups G accounts for the polarization of a text if

$$\begin{cases} DFU(X) > 0, \\ DFU(X_g) = 0 \quad \forall g \in G, \end{cases}$$

where X are all ratings of the text and X_g the ratings of group g. In words, the ratings as a whole have more than one peak while those of every group have a single peak, so the groups form opposing sides. Figure 3 shows this on a synthetic text rated by eight annotators.

4.1.3 Sparsity. Attribution needs enough ratings, so we set two minimums. Each group inside a text needs at least two ratings, since a single rating always has a single peak and would make attribution trivial. A group also needs at least 10 attributed texts in a dataset, because we later compare the models with each group over these texts and a κ over fewer says too little.[2] We remove groups below 10 one by one, smallest first and test the attribution again each time, but always keep two groups, since a comparison needs two. In Attitudes, age and traditionalism stay below 10, so we keep them and mark them (Appendix D).

[2]The threshold of 10 is a round lower limit and not a derived value. It keeps some statistical weight without removing too many groups, and the later statistical tests (chance baseline, bootstrap) check each result further.




Fig. 3. AU on a synthetic text rated by eight annotators. The ratings of all annotators are polarized (left). Split by politics, each group has a single peak, so politics accounts for the polarization (middle). Split by gender, both groups remain polarized, so gender does not account for it (right). Red bars mark toxic ratings (3 or more).

4.1.4 Chance baseline. Attribution says that a characteristic splits the annotators into opposing sides, and we later read a model's alignment with a group as taking its side. We therefore first check that the groups divide the attributed texts more than chance would. A text can pass the AU test by chance, because a group with few ratings almost always has a single peak. This happens more with a dimension that has more groups, since it splits the same ratings into smaller groups. To see how often this happens, we randomly reassign the group labels among the ratings of each polarized text, keeping the group sizes, and rerun AU 1,000 times. The share of texts attributed in these shuffles is the chance rate, and attribution is more than chance when the observed rate is higher than in nearly all shuffles (Appendix F.2.5).

4.2 LLM evaluation under two prompts

Between 26% and 46% of the texts in our datasets are polarized (Section 5), a share large enough to be worth studying. A polarized text can be attributed to a characteristic, meaning that the characteristic accounts for its polarization, and this tells us who the opposing sides are (Figure 1b). We evaluate the LLMs on these attributed texts because annotators hold opposing opinions on them, so whatever label a model gives, it usually agrees with one side and disagrees with the other. If the model keeps agreeing with the same group across texts, we see an alignment. This is what the framework tells a user before they rely on a model's labels, and what overall agreement cannot show.

4.2.1 Position per side. On an attributed text, each group has a single peak, which is the group's opinion of the text. We label it toxic or civil by the majority label of the group's ratings, or by their mean when the labels are split evenly. Each group thus takes one position on a text, toxic or civil. Where the groups differ, as with civil for left and toxic for right in Figure 3.[3] In the alignment study, a model can therefore show one of two patterns. Its labels may match a group's positions whichever they are, or it may systematically follow one pole, labeling most texts toxic or most civil, and match a group only by chance. Cohen's κ corrects for this chance agreement, so we use it to measure alignment (Section 4.2) and we also study how often the model labels these texts toxic (Section 5.1).

[3] On some attributed texts, both groups fall on the same side of the toxic threshold, for example with peaks at 3 and 5. This is most frequent in POPQUORN (Appendix D.3). Such texts have no poles. A model then matches both groups or neither, so these texts favor no side and only make groups look more alike. We include them.

4.2.2 Models. We evaluate four LLMs, ChatGPT, DeepSeek, Gemini and Mistral, but the setup works with any number of models. Each model rates a text from 1 to 5, and we turn the rating into a toxic or civil label with a threshold of 3 (Section 3). We compare these labels with the labels of the groups and not the ratings, since a group's position on a text is a label and the datasets use different scales. The threshold is our choice and a user of the framework can set another one. For MHS it is a lower bar than the annotators' explicit Yes (Appendix B.1). We keep the ratings to compare the models with each other (Appendix G.1).

We use two prompts, one for each text. The default prompt asks the model only to annotate each text and it shows the side the model takes on its own. The SCDP tells the model to label one text as a member of each group of the characteristic that accounts for its polarization, in a single request. For example, if gender accounts for a text, the model labels it as a man and as a woman, and not as a millennial or a Gen Z member. We use it as a diagnostic and not as a way to remove bias, to see how inherent the alignment is. If it persists under this prompt it may be structural to the model and if it changes it may be sensitive to the prompt. Both are only possibilities, since the SCDP acts as a diagnostic test. To verify that our results do not depend on the wording, we also rerun the default prompt with rephrased versions on a subset of the attributed texts (Appendix E.4). Appendix E gives all prompts and the model versions and settings.

4.2.3 Measuring alignment. To see whether a model aligns with an annotator group, we compare, on each attributed text, the label the model gives with the position the group takes on that text, toxic or civil. For this we need a measure of agreement that removes the part expected by chance, so that a model is not credited for labeling nearly every text the same way. This measure is Cohen's κ. A higher κ means more alignment, a κ near zero means agreement no better than chance and a negative κ means systematic disagreement. We compute κ for each group separately and not for all annotators together, because a single κ mixes the groups. For example, a model that matches left-leaning annotators on every text and right-leaning annotators on none still agrees with about half of all annotators, which looks like moderate agreement (Appendix F.2.6). Under the SCDP, we also track how κ with each group changes from the default prompt. When a model gives the same label to all texts of a group, κ is zero, since it then does not follow the group beyond chance. Correlations apply to ratings, not labels, so we use Spearman's only to compare models with each other (Appendix G.1).

4.2.4 Uncertainty. Each κ rests on a small number of texts, often about 10, so we measure how much it depends on them with a bootstrap. This way, a result that comes from the luck of the sample is not mistaken for a finding. For each characteristic, we resample its attributed texts 1000 times with replacement, recompute each κ and each gap between two groups on every resample, and report κ with its standard error (Appendix F.1). A κ or a gap is clear when it keeps its sign in nearly all resamples, because then the result does not depend on which texts we draw. We mark clear κ values in bold and list clear gaps.

5 Results

An audit asks whose side a model takes on the texts where people disagree. We first measure how much of each dataset is polarized and attributed to a characteristic, and whether the attributed texts are more than chance (Table 2 and Appendix F.2.5). We then measure the alignment between the model and each group (Section 5.1), and compare it with the model's agreement with all annotators pooled, since pooling hides which side the model takes. Finally, we test whether the alignment holds when the model is told who is labeling (Section 5.2). In an exploratory step, the framework also compares how the models rate the same texts and how consistent they are with each other (Appendix G.1).




Fig. 4. DFU of each text per dataset after preprocessing. Texts with $DFU = 0$ are unimodal, all others are polarized.

Detecting polarization. The share of polarized texts is 45.4% in Attitudes, 45.7% in POPQUORN, 42.3% in Kumar and 25.6% in MHS (Figure 4), so every dataset has many contested texts for the audit to work on. We do not compare these shares across datasets, since polarization depends on the number of ratings per text (Appendix C.2), on the rating scale, annotator metadata and on the kind of texts each dataset collects. MHS has the fewest, partly because on its three-point scale two peaks can form only when *Unclear* is rarer than both *No* and *Yes*.

Attributing polarization. Attribution requires at least four ratings (Section 3), which most polarized texts have. Of these, a minority is attributed to a characteristic, from 7.2% in MHS to 22.5% in POPQUORN (Table 2, *all attributed*). No single characteristic accounts for more than about 13% of its testable texts (the polarized texts with at least two groups of at least two ratings), from 2.3% (gender in POPQUORN) to 12.9% (occupation in POPQUORN). Most polarization is therefore not explained by one characteristic, and may follow a combination of characteristics, unreported characteristics, or individual differences. The attributed texts are those on which a model can be shown to side with one group, so they are the ones we evaluate.

Attribution against chance. Attribution rates should be read against chance (Section 4.1.4). In Attitudes, POPQUORN and MHS, no characteristic is attributed clearly more often than under shuffled group labels, so we cannot tell its attributed texts from texts that pass the AU test at random. In Kumar, the observed rate exceeds the chance rate for race, religion, gender and politics, by 3.7, 2.0, 0.6 and 0.5 points, but for politics only narrowly (Appendix F.2.5). Attribution is therefore beyond chance for these characteristics in Kumar and not shown to be in the other datasets. This concerns the texts and not the model, since whether the model follows a group is tested separately by the bootstrap of κ (Section 5.1).

5.1 Default alignment

This section asks which side each model takes by default. We use Kumar as a worked example of the audit and give the other datasets in Appendix F.2. Kumar has far more attributed texts than the other datasets, so to save resources we evaluate it on the smallest sample that gives every group 10 texts, 65 attributions in all (Appendix E.3).

For each characteristic, we take the labels that each LLM gives to the attributed texts under the default prompt. We then compare them with the position of each group on the same texts, taken from the attribution stage (Section 4.1),

Table 2. Attribution of polarization per characteristic.Testable texts are polarized texts with at least two groups of at least two ratings. Attr. is the number of attributed texts and % is their share of the testable texts. D and N mark demographic and non-demographic characteristics. *Pooled* sums the characteristics of a type, and *all attributed* counts each text attributed to at least one characteristic once, among polarized texts with at least four ratings. † Fewer than 10 attributed texts.

Attitudes

Characteristic	Type	Testable	Attr.	%
gender	D	164	10	6.1
race	D	239	14	5.9
age†	D	97	6	6.2
politics	N	144	12	8.3
traditionalism†	N	154	9	5.8
pooled	D	500	30	6.0
	N	298	21	7.0
all attributed		262	41	15.6

MHS

Characteristic	Type	Testable	Attr.	%
gender	D	529	43	8.1
age	D	305	30	9.8
politics	N	336	32	9.5
pooled	D	834	73	8.8
	N	336	32	9.5
all attributed		1,316	95	7.2

POPQUORN

Characteristic	Type	Testable	Attr.	%
gender	D	615	14	2.3
race	D	204	13	6.4
age	D	583	55	9.4
education	N	591	47	8.0
occupation	N	418	54	12.9
pooled	D	1,402	82	5.8
	N	1,009	101	10.0
all attributed		684	154	22.5

Kumar

Characteristic	Type	Testable	Attr.	%
gender	D	19,436	1,224	6.3
race	D	5,727	667	11.6
age	D	11,400	1,038	9.1
politics	N	15,584	1,924	12.3
religion	N	15,940	1,237	7.8
pooled	D	36,563	2,929	8.0
	N	31,524	3,161	10.0
all attributed		38,171	5,209	13.6

Table 3. Cohen's κ between each LLM and the groups per characteristic on the polarized Kumar texts attributed to it, with the default prompt. Each group has 10 attributed texts. Values in parentheses are bootstrap standard errors (Section 4.2). Bold marks values that are clearly different from zero (Appendix F.1). D = demographic, N = non-demographic. † The model gave the same label to every text, so κ is 0 by definition. For gender, the two groups take opposite sides on every text, so their κ values are opposite.

	Gender (D)		Race (D)			Age (D)		
Model	Female	Male	Asian	Black	White	Gen X+	Gen Z	millennial
ChatGPT	0.40 (0.29)	−0.40 (0.27)	0.60 (0.28)	0.41 (0.33)	−0.36 (0.19)	−0.32 (0.16)	0.60 (0.28)	−0.30 (0.26)
DeepSeek	0.40 (0.29)	−0.40 (0.27)	0.60 (0.28)	0.29 (0.26)	−0.32 (0.16)	0.00† (0.00)	0.20 (0.29)	0.05 (0.31)
Gemini	**1.00** (0.04)	**−1.00** (0.18)	0.20 (0.29)	0.20 (0.20)	−0.36 (0.19)	0.29 (0.21)	0.20 (0.29)	0.09 (0.12)
Mistral	0.60 (0.27)	−0.60 (0.25)	0.20 (0.29)	−0.15 (0.11)	0.00 (0.25)	0.00 (0.26)	**0.80** (0.21)	−0.03 (0.24)

	Politics (N)			Religion (N)	
Model	conservative	independent	liberal	high	not high
ChatGPT	−0.09 (0.28)	−0.07 (0.23)	**1.00** (0.10)	−0.19 (0.15)	0.29 (0.20)
DeepSeek	0.07 (0.26)	−0.40 (0.21)	0.78 (0.25)	−0.19 (0.15)	0.29 (0.20)
Gemini	−0.09 (0.28)	−0.07 (0.23)	**1.00** (0.10)	−0.20 (0.17)	0.40 (0.24)
Mistral	0.05 (0.30)	−0.07 (0.23)	**0.80** (0.21)	−0.18 (0.13)	0.19 (0.16)

using Cohen's κ and its bootstrap standard error (Section 4.2). A higher κ with one group than with another means that the model aligns more with that group and this gap is clear only if it persists in almost all resamples.

In Kumar, the models side with liberal annotators (Table 3). Their agreement with the liberal group is high (κ up to 1.00), while it is near or below zero for conservative and independent annotators. As defined in Section 4.2, a higher κ with one group than with another means that the model aligns more with that group. Gemini, for example, aligns more with female than with male annotators, and ChatGPT and Mistral align more with Gen Z than with Gen X+. Of the 44 gaps between groups, 13 are clear (Appendix F.2.4 lists them). These gaps are not independent, since the models' labels are correlated and groups share texts, so we read them as leads to test on larger samples and not as 13 separate findings.

In order to see whether the models follow one group or one of the poles, we compare their labels with the two poles of the texts where the groups split (Section 4.2). On the 46 such texts in Kumar, the models label 48% to 63% toxic, and none differs clearly from 50%, so we find no lean toward either pole. Instead, their labels follow one group's position at both poles. Gemini matches women on all 10 gender texts, whether women find the text toxic or civil. On the politics texts, the models match liberal annotators on 67% to 100% of the texts at either pole (4 texts where they hold the toxic position, 3 the civil one) and conservative annotators on only 33% to 67% (6 texts and 3). Appendix F.2.7 gives the poles for all datasets.

Pooling the annotators would have given one κ for the characteristic instead of one per group (Section 4.2). On the 15 Kumar texts attributed to political leaning, ChatGPT and Gemini reach a κ of 0.47 with the majority label of all annotators, which suggests agreement with the annotators. The three groups show that it is not shared, since κ is 1.00 with liberal annotators and -0.09 and -0.07 with conservative and independent ones. Appendix F.2.6 gives the pooled κ for all datasets.

Compared with Kumar, the audit found clear gaps in POPQUORN, where the models differ most across occupations, and none in Attitudes and MHS (Appendix F.2). In POPQUORN, however, the attribution rates are close to chance (Appendix F.2.5), so the gaps describe the attributed texts, and we cannot say that occupation divides the annotators more than chance would. A missing side does not mean the model is neutral. In Attitudes, the groups are too small for any difference to appear. In MHS, the models label almost every text toxic (94% to 98% of the texts where the groups split), which may partly reflect the lower threshold for models (Section 4.2) and so track no group.

5.2 Prompting with the group

The last step of the framework asks how stable the alignments are (Figure 2). The bootstrap shows how much an alignment depends on the sample of texts, and the SCDP shows how much it depends on the prompt.[4] We compare the labels the model gives as each group with the position of the same group, for example a woman persona with women. If the alignment changes from the default one, the side depends more on the prompt, and if it does not, the side may come from the model.

Table 4 gives, for the Kumar dataset, the agreement of each model with each annotator group under the default prompt and the SCDP. Most alignments are stable, and the only clear change is Gemini's on gender, which is one finding because its two values mirror each other. Gemini agreed fully with women and disagreed fully with men by default (κ of 1.00 and -1.00), and with the SCDP these fall to 0.20 and -0.20. Gemini gives the same labels to the woman and the man persona, so this change comes from the format of the prompt and not from who is labeling. It weakens the side but does not switch it. Among the political groups, liberal annotators have the highest κ for all four models under both prompts. For Gemini and DeepSeek the gap to the other groups stays clear, so their side holds even when the model labels as another group. For ChatGPT and Mistral, κ for liberal annotators falls (from 1.00 to 0.35 and from 0.80 to 0.44), but with 10 texts per group these drops are not clear, so we cannot say whether their side is as stable. This is what the stability step is for. It separates the models whose side a user can rely on across prompts from those for which the default audit alone is a less certain guide.

The other datasets show the same signal. If the models followed the prompt, labeling as a woman, for example, should raise the agreement with women. Across the four datasets the agreement rises in 70 of 176 cases and falls in 77, and only 3 changes are clear (Appendix F.3). Clear gaps between groups are also somewhat fewer, 19 of the 148 with

[4] This differs from the prompt sensitivity check in Appendix E.4, which rewords the same instruction and finds small changes in the labels. Here we change what the model is told, namely who is labeling.

Table 4. Cohen's kappa between each LLM and the groups of each characteristic in Kumar, with the default prompt and with the SCDP. Each cell shows the default value, then the SCDP value, with their bootstrap standard errors below in the same order, and each group has 10 attributed texts. Bold marks a change that is clear, meaning that the bootstrap range of the change excludes zero (Appendix F.1). D = demographic, N = non-demographic characteristic. Under the default prompt the two groups of a two-group characteristic have opposite kappas, because the model gives one label to both. This does not hold with the SCDP, where each group has its own prompt. The standard error of each change is in Table 28.

	Gender (D)		Race (D)			Age (D)		
Model	Female	Male	Asian	Black	White	Gen X+	Gen Z	Millennial
ChatGPT	0.40 / 0.40 (0.29 / 0.29)	−0.40 / −0.40 (0.27 / 0.27)	0.60 / 0.40 (0.28 / 0.30)	0.41 / 0.09 (0.33 / 0.12)	−0.36 / 0.21 (0.19 / 0.32)	−0.32 / 0.21 (0.16 / 0.32)	0.60 / 0.60 (0.28 / 0.27)	−0.30 / 0.09 (0.26 / 0.11)
DeepSeek	0.40 / 0.40 (0.29 / 0.29)	−0.40 / −0.40 (0.27 / 0.27)	0.60 / 0.20 (0.28 / 0.31)	0.29 / 0.05 (0.26 / 0.08)	−0.32 / 0.38 (0.16 / 0.36)	0.00 / 0.55 (0.00 / 0.29)	0.20 / 0.40 (0.29 / 0.30)	0.05 / 0.09 (0.31 / 0.11)
Gemini	**1.00** / **0.20** (0.04 / 0.28)	**−1.00** / **−0.20** (0.18 / 0.27)	0.20 / 0.40 (0.29 / 0.30)	0.20 / 0.14 (0.20 / 0.16)	−0.36 / −0.25 (0.19 / 0.14)	0.29 / −0.25 (0.21 / 0.14)	0.20 / 0.80 (0.29 / 0.21)	0.09 / 0.07 (0.12 / 0.27)
Mistral	0.60 / 0.20 (0.27 / 0.30)	−0.60 / −0.40 (0.25 / 0.21)	0.20 / 0.00 (0.29 / 0.25)	−0.15 / −0.11 (0.11 / 0.09)	0.00 / −0.13 (0.25 / 0.22)	0.00 / −0.18 (0.26 / 0.21)	0.80 / 0.20 (0.21 / 0.20)	−0.03 / −0.21 (0.24 / 0.20)

	Politics (N)			Religion (N)	
Model	conservative	independent	liberal	high	not high
ChatGPT	−0.09 / −0.09 (0.28 / 0.28)	−0.07 / 0.29 (0.23 / 0.21)	1.00 / 0.35 (0.10 / 0.31)	−0.19 / −0.21 (0.15 / 0.20)	0.29 / 0.62 (0.20 / 0.39)
DeepSeek	0.07 / −0.20 (0.26 / 0.27)	−0.40 / −0.07 (0.21 / 0.23)	0.78 / 0.78 (0.25 / 0.25)	−0.19 / −0.20 (0.15 / 0.17)	0.29 / 0.62 (0.20 / 0.39)
Gemini	−0.09 / −0.30 (0.28 / 0.26)	−0.07 / −0.40 (0.23 / 0.21)	1.00 / 1.00 (0.10 / 0.10)	−0.20 / −0.21 (0.17 / 0.20)	0.40 / 0.74 (0.24 / 0.31)
Mistral	0.05 / −0.32 (0.30 / 0.16)	−0.07 / 0.00 (0.23 / 0.00)	0.80 / 0.44 (0.21 / 0.23)	−0.18 / −0.15 (0.13 / 0.11)	0.19 / −0.15 (0.16 / 0.11)

the SCDP against 26 with the default prompt, which fits the larger standard errors that come with groups of about 10 texts. For these models and datasets, we therefore find at most a weak sign that the alignments follow prompts of this kind (Appendix F.3). Since the groups are small, small changes may go unseen, so a user can read the sides as stable but not as fixed.

6 Discussion

Using LLMs as annotators is becoming common, including for subjective tasks such as toxicity, yet when annotators disagree about a text, any label a model gives takes a side. Overall agreement does not show which one, since it is dominated by the many texts that annotators agree on and agreement with all annotators pooled together can look like agreement even when the model follows only one group. The framework is an audit that tells, for a given model and dataset, which annotator group (for example liberal or conservative) the model's labels align with on the polarized texts, and how sure we can be of it. It does so by comparing the model with each group on those texts, under the default prompt and under SCDP, which tells the model which group it labels as.

The framework offers a user a way to see how far to trust each result, which is what an audit or a moderation decision needs, and where a result cannot be trusted, it says so. It is run on one dataset and one model at a time, so it makes no claim beyond them. A group enters only with at least 10 texts attributed to a characteristic. The alignment between the model and each group is corrected for chance and not pooled across groups, so that following one group is not mistaken for agreement with everyone. The results are then tested in three ways. The bootstrap shows how much each result depends on the sample of texts, and a comparison with shuffled group labels shows whether attribution is more than chance. SCDP shows whether a side holds when the model is told who is labeling, and a side that depends on the prompt is a less certain guide.

On four toxicity datasets, the framework reveals that the side a model takes depends on the dataset. In Kumar, the four models follow the liberal group and for Gemini, also women. In Attitudes they follow no group, since the groups are too small and in MHS none either, since they label 94% to 98% of the texts where the groups split toxic. The framework also exposes what the usual measures would have hidden. For political leaning in Kumar, ChatGPT and Gemini reach a κ of 0.47 with the pooled label, but 1.00 with liberal annotators and slightly below zero with the others. It marks where a result is weaker than it looks, since in Attitudes, POPQUORN and MHS the attributed texts cannot be told from chance, while in Kumar several characteristics exceed chance, though politics only narrowly. It shows that the sides are mostly stable, since under SCDP the alignment with a group differs clearly from the default in only 3 of 176 cases. The results also depend on the settings of the framework, such as the label threshold of 3, the 10-text rule and the unimodality test, so other settings may change which texts are attributed and which side a model takes.

The practical question is simple. Before relying on an LLM to label subjective content, does it take a consistent side and, if so, whose? A team that wants to use one for moderation, to extend a dataset or to choose a model for a given population can run the audit on its own annotated data and get one of three answers. If the model follows a group, the team knows which annotators its labels favor and which they would leave out, and can decide whether that is acceptable. If no side can be read because the groups are too small, more annotators are needed. If no side can be read because the model gives almost the same label to every text, another model is needed. Since hosted models change, the check is worth repeating when the model is updated. The audit does not decide which perspective is correct, and a model that follows a group does not represent that group.

7 Conclusion

A model that labels subjective data may carry a bias from its training, and the dataset one from its annotators. Where people disagree, a label cannot match everyone, so the model has to take a side. Agreement over all texts hides which side, since most texts are ones people agree on, and pooling all annotators into one group hides it too. Our framework therefore compares the model's labels with each subgroup on the polarized texts that a characteristic accounts for, under the default prompt and under SCDP, so that we can say whose side the model took. Because the audit is run on one model, one dataset and one prompt, every result is tied to all three.

Applying it, we found clear sides in some datasets and none in others. Where there was none, the audit implied why, either because the groups were too small or because the models labeled almost every text the same way. We read these results as illustrations and not as general claims. What makes them usable is that every result comes with its own statistical checks, which show how far it can be trusted. The audit is therefore a check to run on a given model and dataset before using its labels, for example for moderation or dataset creation, to see whose side the labels take and how sure we can be.

8 Limitations

Data. The audit needs several individual ratings per text and annotator characteristics, so it applies only where such data exist. Our four datasets are in English and, to our knowledge, were annotated mostly by US-based crowdworkers, and all concern toxicity. Only a minority of the polarized texts are attributed to a characteristic, so the audit covers a part of the polarized texts of each dataset and not all of them.

Method. The criterion requires a group's ratings to be exactly unimodal, which is too strict for dense data, where many annotators rate each text. It affects MHS, where none of the 70 comments with hundreds of ratings can be

attributed, and it could make datasets with many raters per text, such as DICES, unusable. At the other end, the test needs several ratings per text, and each group needs at least two, so datasets with few ratings per text cannot be audited either. We study one characteristic at a time and not their combinations. In three of the four datasets, attribution rates are close to chance (Appendix F.2.5), so some attributed texts may not be real splits. And even a real split shows that a characteristic fits the disagreement, not that it causes it. To save resources, Kumar is evaluated on a minimal sample of 65 attributions, and we did not test other samples. Turning ratings into a binary label at 3 and taking the majority as a group's position loses information.

Models. We audit four models, one version each, gpt-4o-mini, deepseek-chat, gemini-2.5-flash and open-mistral-7b. Two are closed models and two have open weights, but we queried all of them through hosted APIs. We chose mostly smaller versions to save resources, and bigger models may take different sides. Hosted models are also updated over time, so the same name can return different labels later. Our results describe these versions at the time we queried them, in October 2026, and the audit has to be repeated when a model changes.

9 Future Work

Several characteristics together. Most polarized texts are not attributed to any single characteristic, and annotators may differ along several dimensions at once. AU can test combined groups, such as age together with political leaning, so some of these texts may be attributed that way. Future work should test how characteristics interact, which would also show whether one stands in for another, and whether groups defined by several of them take different sides.

More and different data. The framework should be tested on more data. Datasets with many ratings per text, such as MHS, need a tolerance in the unimodality test, since the exact criterion is too strict for them, and they would also give larger groups. Our groups have 10 to 55 texts, which makes our clear gaps leads and not firm findings, and larger samples would show which of them hold. Other tasks, languages and annotator populations would show how far the sides we find depend on the dataset. Our datasets cover toxicity in English with mostly US-based annotators.

Classifiers. The audit needs only a model's labels, so it applies to trained classifiers as well as to LLMs. Classifiers should be built and evaluated on the polarized texts that the audit retains, since these are the texts where a label takes a side. Future work can audit such classifiers on the same datasets and test whether the side of an LLM carries over to a classifier trained on its labels.

10 Ethical Considerations

The audit describes whose perspective a model reproduces on contested texts, not which perspective is correct, and it should not be used to decide that. A model that agrees with a group on a dataset does not represent that group, and our results should not be used to replace annotators with models or to speak for a group. The characteristics we use come from the datasets, and the groups they define are broad, so they hide differences within a group. We use only public datasets and report results by group, never by annotator, and we collected no new data on people. We used the SCDP as a diagnostic and not as a way to simulate groups, since a persona prompt can flatten the group it describes.

References

[1] Shayan Alipour, Indira Sen, Mattia Samory, and Tanu Mitra. 2025. Robustness and Confounders in the Demographic Alignment of LLMs with Human Perceptions of Offensiveness. In *Findings of the Association for Computational Linguistics: ACL 2025*, Wanxiang Che, Joyce Nabende, Ekaterina Shutova,

and Mohammad Taher Pilehvar (Eds.). Association for Computational Linguistics, Vienna, Austria, 22025–22047. doi:10.18653/v1/2025.findings-acl.1136

[2] Ron Artstein and Massimo Poesio. 2008. Inter-Coder Agreement for Computational Linguistics. *Computational Linguistics* 34, 4 (12 2008), 555–596. arXiv:https://direct.mit.edu/coli/article-pdf/34/4/555/1808947/coli.07-034-r2.pdf doi:10.1162/coli.07-034-R2

[3] Tilman Beck, Hendrik Schuff, Anne Lauscher, and Iryna Gurevych. 2024. Sensitivity, Performance, Robustness: Deconstructing the Effect of Sociodemographic Prompting. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, Yvette Graham and Matthew Purver (Eds.). Association for Computational Linguistics, St. Julian's, Malta, 2589–2615. doi:10.18653/v1/2024.eacl-long.159

[4] Tadesse Destaw Belay, Ibrahim Said Ahmad, Idris Abdulmumin, Abinew Ali Ayele, Alexander Gelbukh, Eusebio Ricárdez-Vázquez, Olga Kolesnikova, Shamsuddeen Hassan Muhammad, and Seid Muhie Yimam. 2026. Beyond Majority Voting: Agreement-Based Clustering to Model Annotator Perspectives in Subjective NLP Tasks. arXiv:2605.09955 [cs.CL] https://arxiv.org/abs/2605.09955

[5] Aaron Bramson, Patrick Grim, Daniel Singer, William Berger, Graham Sack, Steven Fisher, Carissa Flocken, and Bennett Holman. 2022. Understanding Polarization: Meanings, Measures, and Model Evaluation. *Philosophy of Science* 84 (01 2022), 115–159. doi:10.1086/688938

[6] Alessandro Checco, Kevin Roitero, Eddy Maddalena, Stefano Mizzaro, and Gianluca Demartini. 2017. Let's Agree to Disagree: Fixing Agreement Measures for Crowdsourcing. *Proceedings of the AAAI Conference on Human Computation and Crowdsourcing* 5, 1 (Sep. 2017), 11–20. doi:10.1609/hcomp.v5i1.13306

[7] Michael Dimock. 2019. Defining Generations: Where Millennials End and Generation Z Begins. Pew Research Center. https://www.pewresearch.org/short-reads/2019/01/17/where-millennials-end-and-generation-z-begins/

[8] Esin Durmus, Karina Nguyen, Thomas I. Liao, Nicholas Schiefer, Amanda Askell, Anton Bakhtin, Carol Chen, Zac Hatfield-Dodds, Danny Hernandez, Nicholas Joseph, Liane Lovitt, Sam McCandlish, Orowa Sikder, Alex Tamkin, Janel Thamkul, Jared Kaplan, Jack Clark, and Deep Ganguli. 2024. Towards Measuring the Representation of Subjective Global Opinions in Language Models. arXiv:2306.16388 [cs.CL] https://arxiv.org/abs/2306.16388

[9] Joan-María Esteban and Debraj Ray. 1994. On the Measurement of Polarization. *Econometrica* 62, 4 (1994), 819–851. http://www.jstor.org/stable/2951734

[10] Shangbin Feng, Chan Young Park, Yuhan Liu, and Yulia Tsvetkov. 2023. From Pretraining Data to Language Models to Downstream Tasks: Tracking the Trails of Political Biases Leading to Unfair NLP Models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (Eds.). Association for Computational Linguistics, Toronto, Canada, 11737–11762. doi:10.18653/v1/2023.acl-long.656

[11] Tommaso Fornaciari, Alexandra Uma, Silviu Paun, Barbara Plank, Dirk Hovy, and Massimo Poesio. 2021. Beyond Black & White: Leveraging Annotator Disagreement via Soft-Label Multi-Task Learning. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, Kristina Toutanova, Anna Rumshisky, Luke Zettlemoyer, Dilek Hakkani-Tur, Iz Beltagy, Steven Bethard, Ryan Cotterell, Tanmoy Chakraborty, and Yichao Zhou (Eds.). Association for Computational Linguistics, Online, 2591–2597. doi:10.18653/v1/2021.naacl-main.204

[12] Kiran Garimella and Ingmar Weber. 2017. A Long-Term Analysis of Polarization on Twitter. arXiv:1703.02769 [cs.SI] https://arxiv.org/abs/1703.02769

[13] Fabrizio Gilardi, Meysam Alizadeh, and Maël Kubli. 2023. ChatGPT Outperforms Crowd Workers for Text-Annotation Tasks. *Proceedings of the National Academy of Sciences* 120, 30 (2023), e2305016120. doi:10.1073/pnas.2305016120

[14] Tommaso Giorgi, Lorenzo Cima, Tiziano Fagni, Marco Avvenuti, and Stefano Cresci. 2025. Human and LLM Biases in Hate Speech Annotations: A Socio-Demographic Analysis of Annotators and Targets. *Proceedings of the International AAAI Conference on Web and Social Media* 19 (2025), 653–670. doi:10.1609/icwsm.v19i1.35837

[15] Preni Golazizian, Alireza Salkhordeh Ziabari, Ali Omrani, and Morteza Dehghani. 2024. Cost-Efficient Subjective Task Annotation and Modeling through Few-Shot Annotator Adaptation. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (Eds.). Association for Computational Linguistics, Miami, Florida, USA, 3474–3491. doi:10.18653/v1/2024.findings-emnlp.199

[16] Nitesh Goyal, Ian Kivlichan, Rachel Rosen, and Lucy Vasserman. 2022. Is Your Toxicity My Toxicity? Exploring the Impact of Rater Identity on Toxicity Annotation. arXiv:2205.00501 [cs.HC] https://arxiv.org/abs/2205.00501

[17] J. A. Hartigan and P. M. Hartigan. 1985. The Dip Test of Unimodality. *The Annals of Statistics* 13, 1 (1985), 70 – 84. doi:10.1214/aos/1176346577

[18] Chris J. Kennedy, Geoff Bacon, Alexander Sahn, and Claudia von Vacano. 2020. Constructing interval variables via faceted Rasch measurement and multitask deep learning: a hate speech application. arXiv:2009.10277 [cs.CL] https://arxiv.org/abs/2009.10277

[19] Deepak Kumar, Patrick Gage Kelley, Sunny Consolvo, Joshua Mason, Elie Bursztein, Zakir Durumeric, Kurt Thomas, and Michael Bailey. 2021. Designing Toxic Content Classification for a Diversity of Perspectives. arXiv:2106.04511 [cs.SI] https://arxiv.org/abs/2106.04511

[20] Edoardo Di Martino, Matteo Cinelli, Roy Cerqueti, and Walter Quattrociocchi. 2025. Quantifying Polarization: A Comparative Study of Measures and Methods. arXiv:2501.07473 [cs.CY] https://arxiv.org/abs/2501.07473

[21] Aida Mostafazadeh Davani, Mark Díaz, and Vinodkumar Prabhakaran. 2022. Dealing with Disagreements: Looking Beyond the Majority Vote in Subjective Annotations. *Transactions of the Association for Computational Linguistics* 10 (2022), 92–110. doi:10.1162/tacl_a_00449

[22] Matthias Orlikowski, Jiaxin Pei, Paul Röttger, Philipp Cimiano, David Jurgens, and Dirk Hovy. 2025. Beyond Demographics: Fine-tuning Large Language Models to Predict Individuals' Subjective Text Perceptions. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (Eds.). Association for Computational Linguistics, Vienna, Austria, 2092–2111. doi:10.18653/v1/2025.acl-long.104

[23] John Pavlopoulos and Aristidis Likas. 2023. Distance from Unimodality for the Assessment of Opinion Polarization. *Cognitive Computation* 15, 2 (2023), 731–738. doi:10.1007/s12559-022-10088-2

[24] John Pavlopoulos and Aristidis Likas. 2024. Polarized Opinion Detection Improves the Detection of Toxic Language. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, Yvette Graham and Matthew Purver (Eds.). Association for Computational Linguistics, St. Julian's, Malta, 1946–1958. doi:10.18653/v1/2024.eacl-long.117

[25] Jiaxin Pei and David Jurgens. 2023. When Do Annotator Demographics Matter? Measuring the Influence of Annotator Demographics with the POPQUORN Dataset. arXiv:2306.06826 [cs.CL] https://arxiv.org/abs/2306.06826

[26] Catarina Pereira, Raquel da Silva, and Catarina Rosa. 2025. How to Measure Political Polarization in Text-as-Data? A Scoping Review of Computational Social Science Approaches. *Journal of Information Technology & Politics* 22, 2 (2025), 172–185. doi:10.1080/19331681.2024.2318404

[27] Roland Pfister, Katharina A. Schwarz, Markus Janczyk, Rick Dale, and Jonathan B. Freeman. 2013. Good things peak in pairs: a note on the bimodality coefficient. *Frontiers in Psychology* 4 (2013), 700. doi:10.3389/fpsyg.2013.00700

[28] Barbara Plank. 2022. The "Problem" of Human Label Variation: On Ground Truth in Data, Modeling and Evaluation. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang (Eds.). Association for Computational Linguistics, Abu Dhabi, United Arab Emirates, 10671–10682. doi:10.18653/v1/2022.emnlp-main.731

[29] Luca Rossi, Katherine Harrison, and Irina Shklovski. 2024. The Problems of LLM-generated Data in Social Science Research. *Sociologica* 18, 2 (Jan. 2024), 145–168. doi:10.6092/issn.1971-8853/19576

[30] Paul Röttger, Valentin Hofmann, Valentina Pyatkin, Musashi Hinck, Hannah Rose Kirk, Hinrich Schütze, and Dirk Hovy. 2024. Political Compass or Spinning Arrow? Towards More Meaningful Evaluations for Values and Opinions in Large Language Models. arXiv:2402.16786 [cs.CL] https://arxiv.org/abs/2402.16786

[31] Shibani Santurkar, Esin Durmus, Faisal Ladhak, Cinoo Lee, Percy Liang, and Tatsunori Hashimoto. 2023. Whose Opinions Do Language Models Reflect? arXiv:2303.17548 [cs.CL] https://arxiv.org/abs/2303.17548

[32] Sebastin Santy, Jenny Liang, Ronan Le Bras, Katharina Reinecke, and Maarten Sap. 2023. NLPositionality: Characterizing Design Biases of Datasets and Models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (Eds.). Association for Computational Linguistics, Toronto, Canada, 9080–9102. doi:10.18653/v1/2023.acl-long.505

[33] Maarten Sap, Dallas Card, Saadia Gabriel, Yejin Choi, and Noah A. Smith. 2019. The Risk of Racial Bias in Hate Speech Detection. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, Anna Korhonen, David Traum, and Lluís Màrquez (Eds.). Association for Computational Linguistics, Florence, Italy, 1668–1678. doi:10.18653/v1/P19-1163

[34] Maarten Sap, Swabha Swayamdipta, Laura Vianna, Xuhui Zhou, Yejin Choi, and Noah A. Smith. 2022. Annotators with Attitudes: How Annotator Beliefs And Identities Bias Toxic Language Detection. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, Marine Carpuat, Marie-Catherine de Marneffe, and Ivan Vladimir Meza Ruiz (Eds.). Association for Computational Linguistics, Seattle, United States, 5884–5906. doi:10.18653/v1/2022.naacl-main.431

[35] Johannes Schäfer, Aidan Combs, Christopher Bagdon, Jiahui Li, Nadine Probol, Lynn Greschner, Sean Papay, Yarik Menchaca Resendiz, Aswathy Velutharambath, Amelie Wuehrl, Sabine Weber, and Roman Klinger. 2025. Which Demographics do LLMs Default to During Annotation?. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (Eds.). Association for Computational Linguistics, Vienna, Austria, 17331–17348. doi:10.18653/v1/2025.acl-long.848

[36] Huaman Sun, Minje Choi, Jiaxin Pei, and David Jurgens. 2025. Sociodemographic Prompting is Not Yet an Effective Approach for Simulating Subjective Judgments with LLMs. arXiv:2311.09730 [cs.CL] https://arxiv.org/abs/2311.09730

[37] Zhen Tan, Dawei Li, Song Wang, Alimohammad Beigi, Bohan Jiang, Amrita Bhattacharjee, Mansooreh Karami, Jundong Li, Lu Cheng, and Huan Liu. 2024. Large Language Models for Data Annotation and Synthesis: A Survey. arXiv:2402.13446 [cs.CL] https://arxiv.org/abs/2402.13446

[38] Petter Törnberg. 2023. ChatGPT-4 Outperforms Experts and Crowd Workers in Annotating Political Twitter Messages with Zero-Shot Learning. arXiv:2304.06588 [cs.CL] https://arxiv.org/abs/2304.06588

[39] Alexandra Uma, Tommaso Fornaciari, Dirk Hovy, Silviu Paun, Barbara Plank, and Massimo Poesio. 2021. Learning from Disagreement: A Survey. *Journal of Artificial Intelligence Research* 72 (12 2021), 1385–1470. doi:10.1613/jair.1.12752

[40] Alessandra Urbinati, Mirko Lai, Simona Frenda, and Marco Antonio Stranisci. 2025. Are you sure? Measuring models bias in content moderation through uncertainty. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (Eds.). Association for Computational Linguistics, Suzhou, China, 18061–18076. doi:10.18653/v1/2025.findings-emnlp.980

[41] Cees van der Eijk. 2001. Measuring Agreement in Ordered Rating Scales. *Quality and Quantity* 35, 3 (2001), 325–341. doi:10.1023/A:1010374114305

[42] Nikolas Vitsakis, Amit Parekh, and Ioannis Konstas. 2024. Voices in a Crowd: Searching for Clusters of Unique Perspectives. arXiv:2407.14259 [cs.CL] https://arxiv.org/abs/2407.14259

[43] Ruyuan Wan, Jaehyung Kim, and Dongyeop Kang. 2023. Everyone's Voice Matters: Quantifying Annotation Disagreement Using Demographic Information. arXiv:2301.05036 [cs.CL] https://arxiv.org/abs/2301.05036

[44] Stefan Wojcik, Sophie Hilgard, Nick Judd, Delia Mocanu, Stephen Ragain, M. B. Fallin Hunzaker, Keith Coleman, and Jay Baxter. 2022. Birdwatch: Crowd Wisdom and Bridging Algorithms can Inform Understanding and Reduce the Spread of Misinformation. arXiv:2210.15723 [cs.SI] https://arxiv.org/abs/2210.15723

[45] Yinuo Xu and David Jurgens. 2026. Beyond Consensus: Perspectivist Modeling and Evaluation of Annotator Disagreement in NLP. arXiv:2601.09065 [cs.CL] https://arxiv.org/abs/2601.09065

Acronyms

AU A Posteriori Unimodality
DFU Distance From Unimodality
LLM large language model
SCDP sociodemographic prompting

A Choice of DFU

To attribute polarization to a characteristic, we first need to measure it. We measure it once for all annotators of a text, to decide whether the text is polarized, and again within each group, to check whether the polarization disappears. The measure should therefore reflect unimodality in opinions when annotators share a single view and multimodality whenever they split into opposing groups, even when one group is a minority. We illustrate how six metrics meet these requirements on five synthetic distributions.

Synthetic distributions. To test whether a metric meets these requirements, we need distributions whose structure we know in advance. A simple way to obtain them is to build a small synthetic set that covers the cases a metric should tell apart (Figure 5). Each distribution has 13 to 17 annotators on a five-point scale. Two show consensus, either around the midpoint (symmetric unimodal) or at one end (skewed unimodal). Three show polarization, with two equal opposing groups (balanced bimodal), a majority opposed by a smaller group (imbalanced bimodal), or three separate groups (trimodal).




Fig. 5. Synthetic annotation distributions. Ratings range from 1 (civil) to 5 (toxic).

- **DFU** [23]. It starts at the most common rating in a distribution and moves toward both ends of the scale, recording the largest rise in frequency it meets. It is zero when the distribution only decreases from its peak (unimodal) and positive when a second peak appears. It detects any second peak, but its values are hard to compare across texts.
- **nDFU** [24]. It divides DFU by the frequency of the most common rating. It ranges from 0 (unimodal) to 1 (a second peak as high as the first). It is comparable across texts, but, like DFU, it can be affected by single ratings when annotations are few.

- **Van der Eijk's** A [41]. It splits the distribution into layers of occupied ratings and scores how concentrated each layer is. It ranges from 1 (full agreement) through 0 (uniform) to −1 (split between the extremes). It distinguishes polarization from agreement, but has no value marking the absence of polarization, and a large majority can outweigh a smaller opposing group.
- **Agreement (Agr.)**. It computes the probability that two randomly chosen annotators give the same rating. Higher values mean more consensus. It is simple, but it ignores whether disagreeing annotators form groups.
- **Balance (Bal.)**. It compares the number of ratings below and above the midpoint of the scale. It ranges from 0 (all on one side) to 1 (equal on both sides). It shows whether both ends are represented, but ignores the shape of the distribution.
- **BC** [27]. It combines the skewness and kurtosis of the ratings. Values above 0.555 suggest two peaks. It is a common shape statistic, but it looks for at most two peaks and is influenced by skewness.

Table 5. Polarization metrics on the distributions of Figure 5. For A, negative values indicate polarization. For BC, values above 0.555 suggest bimodality.

Distribution	DFU	nDFU	A	Agr.	Bal.	BC
Sym. Uni.	0.00	0.00	+0.64	0.24	1.00	0.27
Skew. Uni.	0.00	0.00	+0.64	0.29	0.14	0.45
Bal. Bi.	0.25	0.67	−0.71	0.27	1.00	0.62
Imbal. Bi.	0.15	0.29	+0.37	0.32	0.62	0.65
Trimodal	0.33	1.00	−0.28	0.29	1.00	0.46

Results. Table 5 shows that nDFU handles all five cases correctly. It is zero for both unimodal distributions and ranks the polarized ones by structure: trimodal (1.00), whose groups are as large as the mode, then balanced (0.67) and imbalanced bimodal (0.29), whose minority is smaller. DFU gives the same ranking on a compressed scale (0.15 to 0.33), which separates cases less clearly and is harder to compare across texts.

Each alternative fails on at least one case. Van der Eijk's A, the strongest, handles the unimodal and balanced cases correctly. However, it scores the imbalanced case as agreement (+0.37), as the majority outweighs the minority, and rates the trimodal case as less polarized than the balanced one. BC separates unimodal from bimodal distributions but misses the trimodal one (0.46) and inflated by skewness, ranks the imbalanced case above the balanced. Agreement barely varies (0.24 to 0.32) and Balance gives its maximum to consensus and opposing groups alike.

These examples are illustrative, but nDFU is the only metric that separates unimodal from polarized distributions in every case, ranks the latter by structure, and is comparable across texts. We therefore use it throughout this work.

B Datasets

This appendix complements Section 3. Appendix B.1 details each preprocessing step and Appendix B.2 reports additional statistics on the cleaned datasets. These statistics describe only the annotators of each dataset, after our preprocessing. They do not describe any real population or the groups these annotators belong to.

B.1 Preprocessing details

Effect of preprocessing. Table 6 reports the number of ratings, texts and annotators before and after preprocessing. The minimum of four ratings per text is applied first, and excluded categories are removed afterwards. Attitudes and Kumar

do not release annotator identifiers, so their annotators cannot be counted in the data, and we report the numbers given by their authors.

Table 6. Ratings, texts and annotators at each preprocessing step. Attitudes and Kumar do not release annotator identifiers, so their raw annotator counts are those reported by the authors and clean counts cannot be computed.

	Ratings			Texts		Annotators	
Dataset	Raw	≥4 ratings	Clean	Raw	Clean	Raw	Clean
Attitudes	3,463	3,460	3,354	626	625	173	–
POPQUORN	13,036	13,036	11,352	1,500	1,500	262	228
MHS	135,556	67,121	64,323	39,565	5,990	7,912	7,577
Kumar	538,100	538,100	450,160	107,620	107,620	17,280	–

Rating scales. Table 7 lists, for each dataset, the rating column we use, its original values and the analyzed scale. MHS and Kumar are shifted by one so that all scales start at 1, which changes neither the order of the ratings nor their polarization. Binarizing individual ratings with a threshold is common practice, although the threshold varies across studies [16, 24]. We follow Kumar et al. [19], who consider a rating of *moderately toxic* or higher as toxic, and label ratings of 3 or more as toxic and lower ratings as civil. On the five-point scales, 3 is the midpoint. On the three-point MHS scale, only *Yes* counts as toxic, while *Unclear* counts as civil, so MHS labels a rating as toxic only when an annotator explicitly identifies hate speech. The models rate MHS texts on the same five-point scale as the other datasets, so for them a toxic label means a rating of at least the midpoint, while for annotators it means an explicit *Yes*.

Table 7. Rating scales. MHS and Kumar are shifted by one so that all scales start at 1.

Dataset	Column	Original values	Analyzed	Toxic
Attitudes	`toyou`	1–5	1–5	≥ 3
POPQUORN	`offensiveness`	1 (not offensive at all) to 5 (very offensive)	1–5	≥ 3
MHS	`hatespeech`	0 (No), 1 (Unclear), 2 (Yes)	1–3	3 (Yes)
Kumar	`toxic_score`	0 (not at all toxic) to 4 (extremely toxic)	1–5	≥ 3 (moderately toxic or more)

Group mappings. Table 8 shows how the original annotator categories are merged into groups, and which categories are excluded.

Excluded categories. We exclude two kinds of annotator categories. The first are categories with too few annotators to form a group with at least two members on the same text, such as non-binary annotators (in all four datasets) or Hispanic and Native American annotators (in Attitudes, POPQUORN and Kumar). In Kumar, this also includes annotators who selected more than one race, since each combination is too rare to form a group. Keeping these categories would add groups that can almost never be compared. The second are answers that do not describe a shared characteristic, such as *other*, *prefer not to say*, *no opinion* or missing values. Annotators who gave these answers do not form a meaningful group, even when there are many of them. In both cases, all ratings of the annotator are removed, even when their other characteristics are kept. Groups that pass this step but appear in too few attributed texts are removed later, as part of the attribution analysis (Appendix D).

Table 8. Group mappings. Excluded categories are listed in the last column.

Dataset	Characteristic	Groups (original categories)	Excluded
Attitudes	gender	man, woman	non-binary, missing
	race	Black, White	Hispanic, Native American, Middle Eastern, other, missing
	age	gen z (18–24), millennial (25–44), gen x+ (45 and older)	missing
	politics	left (−1, −0.5), center (0), right (0.5, 1)	–
	traditionalism	high (4–5), not high (1–3)	–
POPQUORN	gender	man, woman	non-binary
	race	White, Black or African American, Asian	Arab American, Native American, Hispanic or Latino
	age	gen z (18–24), millennial (25–44), gen x+ (45 and older)	–
	education	high school diploma, college degree, graduate degree	less than high school, other
	occupation	employed, self-employed, unemployed, student, retired, homemaker	other, prefer not to disclose
MHS	gender	male, female	non-binary, self-describe, prefer not to say
	age	gen z (18–24), millennial (25–44), gen x+ (45–81)	missing
	politics	liberal (extremely liberal, liberal, slightly liberal), neutral, conservative (slightly conservative, conservative, extremely conservative)	no opinion, missing
Kumar	gender	male, female	non-binary, unknown
	race	White, Black or African American, Asian	Hispanic, American Indian or Alaska Native, Native Hawaiian or Pacific Islander, multiple races, other, prefer not to say, missing
	age	gen z (under 25), millennial (25–44), gen x+ (45 and older)	prefer not to say
	politics	liberal, independent, conservative	other, prefer not to say
	religion	very important, less important (somewhat, not too, not important)	prefer not to say

Data quality checks. We ran two checks on the two datasets with annotator identifiers (POPQUORN and MHS). First, we checked that each annotator reports the same characteristics on every text they rated, so that their ratings belong to a single group. Second, we checked that no annotator rated the same text twice, so that no opinion is counted twice in a text's distribution. Both checks passed in both datasets.

B.2 Additional statistics

This section describes the four datasets after preprocessing. All numbers refer to the cleaned ratings and to all texts, before any polarization or attribution analysis.

Rating distributions. Figure 6 shows the share of each rating. In POPQUORN, MHS and Kumar, about half of the ratings are the lowest value, and between 26.4% and 42.4% count as toxic (Table 9). The higher share in MHS comes mostly from its reference comments, as explained below. Attitudes is different. Its distribution is U-shaped, with 31.1%

Table 9. Statistics after preprocessing. Ratings per text are given as minimum, median and maximum. Toxic is the share of ratings of 3 or more.

Dataset	Ratings	Ratings per text	Texts with fewer than 4	Toxic	Words per text
Attitudes	3,354	2 / 6 / 11	41 (6.6%)	54.0%	20
POPQUORN	11,352	3 / 8 / 10	2 (0.1%)	26.4%	24
MHS	64,323	2 / 4 / 777	919 (15.3%)	42.4%	20
Kumar	450,160	1 / 4 / 5	20,660 (19.2%)	29.7%	15

of the ratings at 1 and 29.2% at 5, and 54.0% count as toxic. This fits its design, since its posts were selected to divide annotators [34]. MHS is nearly binary, as only 5.2% of its ratings are *Unclear*.




Fig. 6. Share of each rating per dataset after preprocessing. MHS uses a three-point scale (1 = *No*, 2 = *Unclear*, 3 = *Yes*).

MHS reference comments. In MHS, 70 comments were rated by hundreds of annotators each (234 to 777 ratings), so that the corpus authors could place all annotators on a common scale [18]. All other comments have 2 to 6 ratings. These 70 comments account for 41,442 of the 64,323 ratings (64.4%), so they dominate the rating-level statistics of MHS. Without them, 66.1% of the ratings are *No* and 27.1% are *Yes*, which is close to POPQUORN and Kumar. On the 70 comments alone, 50.8% of the ratings are *Yes*. We keep them in the audit. Of the 70, 54 are polarized, but with hundreds of ratings every one of them has a group that is not exactly unimodal, so none is attributed and none is labeled by the models. They still count among the testable texts, which lowers the attribution rate of MHS in Table 2 from 7.5% to 7.2%.

Texts with fewer than four ratings. As explained in Section 3, a text needs at least four ratings to be attributed. Removing the ratings of excluded annotators leaves some texts below this minimum (Table 9). Kumar is affected most.

Each of its texts has only five ratings, so losing two annotators is enough to drop below four. As a result, 20,660 Kumar texts (19.2%) cannot be attributed.

Annotator groups. are unbalanced (Table 10). Most ratings come from White annotators and, except in POPQUORN, from millennials. Gen z is almost absent in Attitudes, with 4 of 3,354 ratings. Left-leaning annotators give the most ratings in all three datasets that report politics. Among the other characteristics, most Attitudes ratings come from annotators high in traditionalism (62.3%), and about a third of Kumar ratings come from annotators for whom religion is very important (32.4%). In POPQUORN, about half of the ratings come from college-educated (48.8%) and employed (51.3%) annotators, while homemakers give only 4.4%.

Table 10. Share of ratings per annotator group after preprocessing (%). Attitudes reports gender, race, age, politics and traditionalism. POPQUORN reports gender, race, age, education and occupation. MHS reports gender, age and politics. Kumar reports gender, race, age, politics and religion. A dash marks a characteristic that the dataset does not report or that we do not use.

Characteristic	Groups	Attitudes	POPQUORN	MHS	Kumar
Demographic					
Gender	man / woman	56.4 / 43.6	48.7 / 51.3	43.3 / 56.7	47.8 / 52.2
Race	White / Black / Asian	66.3 / 33.7 / –	78.6 / 13.5 / 7.9	–	79.9 / 13.7 / 6.4
Age	gen z / millennial / gen x+	0.1 / 75.8 / 24.1	11.8 / 41.2 / 46.9	8.6 / 66.7 / 24.7	10.3 / 64.9 / 24.7
Non-demographic					
Politics	left / center / right	51.9 / 13.7 / 34.4	–	55.7 / 17.8 / 26.5	42.8 / 27.8 / 29.4
Traditionalism	high / not high	62.3 / 37.7	–	–	–
Religion	very / less important	–	–	–	32.4 / 67.6
Education	high school / college / graduate	–	30.3 / 48.8 / 21.0	–	–
Occupation	employed / self-employed / retired	–	51.3 / 14.0 / 11.9	–	–
	unemployed / student / homemaker	–	11.0 / 7.5 / 4.4	–	–

Toxic ratings per group. Figure 7 shows the share of toxic ratings per group. Across all texts, most differences between groups are small. Gender groups in all datasets, and political and age groups in MHS, differ by at most 6 points. The largest differences concern race and religion. Black annotators label more ratings as toxic than White annotators, by 8.1 points in Attitudes, 11.0 in POPQUORN and 17.1 in Kumar. In Kumar, annotators for whom religion is very important label 39.4% of their ratings as toxic, against 25.0% for the others. These are averages over all texts, so they do not show on which texts groups disagree. Small average differences can hide strong disagreement on single texts, which is why we attribute polarization text by text (Section 4).

C Distance From Unimodality

This appendix complements Section 4.1 and the detection of polarization in Section 5. Appendix C.1 gives the formal definition of DFU with an example, and Appendix C.2 describes its distribution in the four datasets after preprocessing.




Fig. 7. Share of ratings called toxic per annotator group, by characteristic and dataset, after preprocessing. A rating is toxic if it is 3 or more (*Yes* in MHS).

C.1 Computing DFU

Let $f_1, \ldots, f_K$ be the relative frequencies of the ratings $1, \ldots, K$ of a text, and m its most frequent rating. DFU [23] moves from m toward both ends of the scale and records each rise in frequency:

$$d_i = \begin{cases} f_i - f_{i-1} & m < i \leq K, \\ f_i - f_{i+1} & 1 \leq i < m, \\ 0 & i = m, \end{cases} \tag{1}$$

A unimodal distribution only falls away from its peak, so all $d_i \leq 0$ and DFU is zero. We use the normalized version [24], which divides DFU by f_m. It ranges from 0 to 1 and reaches 1 when another peak is as high as the main one, with no ratings between them.

For example, the synthetic text of Figure 3 has the frequencies $(3, 1, 0, 2, 2)/8$. Its peak is at rating 1. Moving right, frequency rises from rating 3 to rating 4 by $2/8$, so DFU is 0.25, and normalized by $f_1 = 3/8$ it is 0.67.

C.2 DFU in the datasets

Table 11 summarizes the polarized texts per dataset, and Figure 4 in Section 5 shows the DFU of all texts. Figure 8 focuses on the polarized texts. In all datasets, most of them have a DFU of 0.5 or less, meaning that the second opinion group is at most half the size of the main one. A second group as large as the main one ($DFU = 1$) is rare in POPQUORN, at about 3% of the polarized texts, and more frequent in Attitudes, MHS and Kumar, at about 14% to 22%.

Table 11. Polarized texts per dataset after preprocessing. A text is polarized when $DFU > 0$.

Dataset	Texts	Polarized texts	Mean DFU of polarized texts
Attitudes	625	284 (45.4%)	0.47
POPQUORN	1,500	686 (45.7%)	0.35
MHS	5,990	1,532 (25.6%)	0.50
Kumar	107,620	45,503 (42.3%)	0.53




Fig. 8. Cumulative share of polarized texts by their DFU, per dataset. A point at (x, y) means that a share y of the polarized texts has a DFU of at most x.

Number of ratings. DFU values cluster at a few points, such as 1/3, 1/2 and 1, because most texts have few ratings. Figure 9 shows how the number of ratings affects DFU. In most datasets, texts with more ratings are polarized more often, since more annotators give a second opinion group more chances to appear. In Kumar, for example, 28.6% of the texts with two ratings are polarized, against 45.7% of those with five. At the same time, the DFU of polarized texts falls, because with few ratings one or two annotators can form a peak as high as the main one. In Kumar, it falls from 1.00 for two ratings to 0.45 for five. The 70 MHS reference comments show the other extreme. With hundreds of ratings each, 77.1% of them are polarized, but their mean DFU is only 0.14, since even a small minority forms a second peak. For this reason, we use DFU only to decide whether a text is polarized, and we do not compare its values across texts or datasets.




Fig. 9. Share of polarized texts (left) and mean DFU of the polarized texts (right) by the number of ratings per text. The group of 11 or more ratings contains only the 70 MHS reference comments.

D Attribution of polarization

This appendix complements the attribution step of Section 4.1 and its results in Section 5. Appendix D.1 details the procedure and why most polarized texts are not attributed, Appendix D.2 the groups kept and removed, Appendix D.3 the positions the groups hold, and Appendix D.4 gives examples.

D.1 Procedure and outcome

For each dataset and characteristic, we split the ratings of every polarized text by group and keep groups with at least two ratings on the text. A text is attributed to the characteristic if at least two groups remain and each of them has $DFU = 0$. We then remove the group that appears in the fewest attributed texts if it appears in fewer than 10, recompute the attribution without it as a group, and repeat until no such group is left. Its ratings still count for the polarization of a text, but no longer form a group in the comparison. The procedure stops early when only two groups remain, or when every remaining group is below 10, since no group is then a better one to remove. The first happens for traditionalism in Attitudes and the second for age, which we keep and mark.

A group's position is toxic if most of its ratings are toxic, and civil if most are civil. Sometimes a group has as many toxic as civil ratings, for example two ratings of 2 and two of 3. In that case, we use its mean rating instead, which gives toxic if the mean is 3 or more and civil otherwise. This happens rarely, for 10.8% of the group positions in Attitudes, 4.8% in POPQUORN, 0.5% in MHS and 2.4% in Kumar.

Figure 10 shows why most polarized texts are not attributed. In Attitudes and POPQUORN, the main reason is usually that at least one group remains polarized, so annotators who share the characteristic still disagree. In MHS and Kumar, the main reason is that too few groups have at least two ratings on the text, since most texts there have only four ratings. The same holds for small groups elsewhere, such as age in Attitudes and race in POPQUORN.




Fig. 10. Outcome of the attribution test per characteristic and dataset. A text is not polarized, has too few groups with at least two ratings, has a group that is not unimodal, or is attributed (AU).

D.2 Groups

Figure 11 shows in how many attributed texts each group takes part. The 10-text rule removed five groups, center in Attitudes politics (9 texts), Asian (8), gen z (7) and homemaker (3) in POPQUORN, and gen z in MHS (5). No group was removed in Kumar. In Attitudes, age and traditionalism stay below 10 texts. Traditionalism has only two groups, and in age all three groups are below 10, so no group is a better one to remove. Gen z in age appears in no attributed text, so it takes part in no result.

D.3 Positions of the groups

Figure 12 shows, for each characteristic, how often the groups of an attributed text hold different positions. In most characteristics, they do so in most texts. All groups hold the same position more often in a few characteristics, most clearly in POPQUORN, where all groups are civil on about 60% of the texts attributed to age and occupation, and in Kumar politics, where they are civil on about a third. On these texts, the groups differ only in how strongly they rate the text, not in its label. As explained in Section 4.2, such texts do not favor any side in the model evaluation, but they make differences between groups smaller.

Figure 13 shows the share of toxic ratings per group on the attributed texts. On these texts, the groups often take clearly different sides. Black annotators rate most of them as toxic in Attitudes, POPQUORN and Kumar, while White




Fig. 11. Attributed texts per group. The dashed line marks the minimum of 10 texts. Gray groups were removed, and orange groups were kept below the minimum because removing them would leave fewer than two groups.

annotators do so much less often. Similar gaps appear for religion in Kumar and for politics, where right-leaning annotators rate more texts as toxic than left-leaning ones in all three datasets that report it. Unlike the small differences over all texts (Appendix B.2), these gaps show that on attributed texts the groups hold clearly separate views.

Overlap between characteristics. Most attributed texts follow only one characteristic, 80.5% in Attitudes, 83.1% in POPQUORN, 90.5% in MHS and 84.7% in Kumar. The others follow two or more, most often politics and religion in Kumar (152 texts) and age and occupation in POPQUORN (9 texts).

D.4 Examples

Table 12 shows examples of attributed texts on which the groups hold different positions, one demographic and one non-demographic characteristic per dataset where a suitable text exists. For Attitudes and MHS, we show only one example, because most candidates contain slurs or target a group. Ratings are those of the two groups compared.




Fig. 12. Positions of the groups on attributed texts, per characteristic and dataset. The groups either hold different positions, or all hold the toxic or all the civil position.

Table 12. Examples of attributed texts on which the groups hold different positions. *Content warning: texts may be offensive.*

Dataset	Characteristic	Text	Ratings (position)	DFU
Attitudes	gender	"boy i've never been in a fight before but i fr just wanted to start one w some hartshorne kids at subway"	man 3, 3, 3, 4 (toxic) woman 1, 1 (civil)	0.67
POPQUORN	gender	"You need to stop talking"	man 3, 4, 4 (toxic) woman 1, 2, 2 (civil)	0.50
	education	"And the anthem protesters aren't breaking any laws. They are hurting certain peoples feelings. That's it."	college 1, 1, 1, 1, 1, 2 (civil) high school 4, 4 (toxic)	0.40
MHS	politics	"Just hit all of irans military"	conservative 1, 1 (civil) liberal 3, 3 (toxic)	1.00
Kumar	gender	"Yup..I'm still upset at that movie."	woman 1, 1, 1 (civil) man 5, 5 (toxic)	0.67
	politics	"Let them believe what they want."	conservative 5, 5 (toxic) liberal 1, 1 (civil)	0.67

E Models and prompts

This appendix complements Section 4.2. It lists the models and their settings, the exact prompts, the sample used for Kumar, and the prompt sensitivity ablation.

E.1 Models

Table 13 lists the four models. All are queried through their providers' APIs with temperature 0, so that repeated queries give the same labels as far as the provider allows, and with no system prompt or seed. All labels were collected on 27 October 2026. The providers return no version string, so a model is identified by the name we sent. The label is




Fig. 13. Share of toxic ratings per group on the attributed texts of each characteristic.

computed from the score, with 3 or more as toxic, and a label written by the model is ignored. A reply that could not be read would be asked again, up to three attempts in all, and none failed. Gemini was run with its thinking budget set to 0.

E.2 Prompts

The prompts below are given with "comment" as the word for a text. In practice, we use the word of each dataset, "tweet" for Attitudes, "text" for POPQUORN and "comment" for MHS and Kumar. The default prompt and its rewordings

Table 13. Models and settings. Max tokens is the output limit for the default prompt and its rewordings, and for the SCDP.

Model	Provider	Model id	Temperature	Max tokens
ChatGPT	OpenAI	`gpt-4o-mini`	0.0	256 / 200
DeepSeek	DeepSeek	`deepseek-chat`	0.0	256 / 200
Gemini	Google	`gemini-2.5-flash`	0.0	512 / 200
Mistral	Mistral AI	`open-mistral-7b`	0.0	256 / 200

send ten numbered texts per call. The SCDP sends one text per call and asks for a rating as each group of the attributed characteristic, listed in a random order with a fixed seed. Every prompt asks for a rating from 1 to 5 and a label that follows from it, with 1 or 2 as civil and 3 to 5 as toxic.

Default prompt.

```
Analyze the following comments for toxicity.
Return ONLY the score (1-5) and label (toxic/civil) for each comment in this format:
score=<1-5>, label=<toxic/civil>

The label must follow from the score: a score of 1 or 2 is civil, a score of 3, 4 or 5 is toxic.

Comments:
<numbered list of texts>
```

SCDP. (example for gender).

```
Analyze the following comment for toxicity.
Rate it separately as each of the people below, who differ in their gender: for each one, answer as a
    person from that gender group would.
Return ONLY valid JSON, with the gender groups written exactly as below, in this format:
{
  "Man": {"score": <1-5>, "label": "<toxic/civil>"},
  "Woman": {"score": <1-5>, "label": "<toxic/civil>"}
}

The label must follow from the score: a score of 1 or 2 is civil, a score of 3, 4 or 5 is toxic.

Gender groups:
- "Man"
- "Woman"

Comment:
<the text>
```

Rewording 1.

```
Here is a numbered list of comments. Rate how toxic each comment is on a scale from 1 to 5, and give each
    one a label, toxic or civil.
Label a comment civil if its score is 1 or 2, and toxic if its score is 3 or higher.
```

```
Reply with exactly one line per comment, in this format and nothing else:
score=<1-5>, label=<toxic/civil>

Comments:
<numbered list of texts>
```

Rewording 2.

```
Below are comments, numbered. For every comment, answer how toxic it is from 1 to 5 and whether it is toxic
      or civil.
Reply with one line per comment and nothing else, written as:
score=<1-5>, label=<toxic/civil>
Remember: a score of 1 or 2 means civil, and a score of 3, 4 or 5 means toxic.

Comments:
<numbered list of texts>
```

E.3 Kumar sample

Kumar has 6,090 attributions (5,209 texts), far more than the other three datasets together (339). Sending all of them to the models would take far more resources than needed to show how the framework works, and a user who wants to audit a model on Kumar can run the full set. We therefore use the smallest sample in which every group appears at least 10 times, the minimum that the framework asks for, which is 65 attributions (the other datasets have 51, 105 and 183). The sample is drawn separately for each characteristic. Within each pair of groups, such as Black and White, we draw texts at random without replacement, with a fixed seed. This gives 10 texts each for gender and religion, and 15 each for race, age and politics, with 5 per pair of groups, so 65 distinct texts in total.

The sample is deliberately not proportional. It guarantees that every group appears at least 10 times, so groups that are rare among the attributed texts, such as Asian and gen z annotators, are over-represented (Figure 14). It therefore serves only the model evaluation, and all statistics on attribution use the full set of attributed texts.

E.4 Prompt sensitivity

To check that our results do not depend on the wording of the default prompt, we rerun it with the two rewordings of Appendix E.2 on all 41 attributed texts of Attitudes and a random subset of 50 in each other dataset. For each model, we compare the labels and scores of the default prompt with those of each rewording. We report the share of identical labels and the weighted κ of the scores, which counts a difference of one point as less severe than a larger one. As a reference, we also compare different models under the same prompt.

Overall, the labels a model gives depend much more on which model it is than on how the prompt is worded, so differences between models in Section 5 are unlikely to come from the wording of the default prompt. Table 14 shows that models are largely stable across wordings. Between 86.0% and 97.0% of the labels stay the same, and the weighted κ of a model with itself under another wording ranges from 0.81 to 0.88 in Attitudes, POPQUORN and Kumar. This is clearly higher than the agreement between different models under the same prompt, from 0.49 to 0.70. In these three datasets, changing the wording therefore matters much less than changing the model. MHS is the exception. There, the wording effect (0.63 to 0.65) is about as large as the differences between models. The models label almost all MHS




Fig. 14. Share of each group among the attributed Kumar texts (all) and in the sample given to the models.

texts as toxic, so even a few changed scores weigh heavily. For the same reason, Cohen's κ of the labels is low in MHS despite 96.5% to 97.0% identical labels, since agreement by chance is already high. The second rewording also raises scores slightly in MHS and Kumar, by 0.14 and 0.09 points on average.

Table 14. Prompt sensitivity of the default prompt. Same label is the share of identical labels, pooled over the four models. Weighted κ compares the scores of each model with itself under a rewording (R1, R2), averaged over models. Between models compares different models under the default prompt.

		Same label (%)		Weighted κ, same model		Weighted κ
Dataset	Texts	R1	R2	R1	R2	between models
Attitudes	41	92.7	92.7	0.87	0.85	0.49
POPQUORN	50	87.0	92.5	0.85	0.88	0.68
MHS	50	96.5	97.0	0.63	0.65	0.66
Kumar	50	87.0	86.0	0.83	0.81	0.70

F Complementary results

This appendix completes the results of Section 5. It shows what the audit finds in the datasets that the main text leaves out and lists the comparisons behind the claims we make there. We cover the default prompt, the SCDP, and the comparison between models.

Table 15. Cohen's κ between each LLM and the groups of each characteristic on the polarized Attitudes texts attributed to it, with the default prompt. Values in parentheses are bootstrap standard errors from 10,000 resamples of the texts. No value is bold because none is clearly different from zero (Appendix F.1). D = demographic, N = non-demographic. † The model gave the same label to every text, so κ is 0 by definition. ‡ Fewer than 10 attributed texts. For gender, the two groups take opposite sides on every text, so their κ values are opposite. Share of texts the models label toxic, on average over groups: ChatGPT 72.7%, DeepSeek 78.2%, Gemini 85.2%, Mistral 86.3%.

	Gender (D)		Race (D)		Age (D)	
Model	man	woman	black	white	Gen X+‡	millennial‡
Texts	10	10	14	14	6	6
ChatGPT	−0.40 (0.21)	0.40 (0.24)	−0.26 (0.13)	0.21 (0.22)	−0.80 (0.30)	0.25 (0.39)
DeepSeek	0.00† (0.00)	0.00† (0.00)	−0.24 (0.12)	0.11 (0.20)	−0.20 (0.33)	0.25 (0.39)
Gemini	0.00† (0.00)	0.00† (0.00)	−0.21 (0.11)	0.26 (0.16)	−0.20 (0.32)	1.00 (0.29)
Mistral	0.20 (0.20)	−0.20 (0.17)	0.42 (0.35)	−0.07 (0.16)	−0.36 (0.29)	0.57 (0.39)

	Politics (N)		Traditionalism (N)	
Model	left	right	high‡	not high‡
Texts	12	12	9	9
ChatGPT	0.40 (0.29)	0.00 (0.27)	0.18 (0.32)	−0.42 (0.21)
DeepSeek	0.40 (0.29)	0.00 (0.27)	0.18 (0.32)	−0.42 (0.21)
Gemini	0.31 (0.26)	0.31 (0.26)	−0.20 (0.15)	0.27 (0.25)
Mistral	0.57 (0.28)	−0.29 (0.15)	−0.20 (0.15)	0.27 (0.25)

F.1 Bootstrap

Each κ may rest on a small number of texts, often about 10, and κ is not a mean, so no formula tells how much it would change with other texts. We therefore resample the attributed texts of each characteristic 1000 times with replacement, with a fixed seed, and recompute every κ, every gap between two groups and every change between prompts on each resample. We can trust the comparisons because all of these values come from the same resamples, so a gap or a change is computed on the same texts as the values it compares. We report the standard deviation of the resampled values as the standard error, not the standard error of the mean. A κ, a gap or a change is clear when the 2.5th to 97.5th percentile of its resampled values excludes zero, and the tables mark such values in bold or list them. In Kumar, the resampled texts are those of the 65-attribution sample (Appendix E.3), so the results do not include the choice of that sample, and they are not corrected for the number of comparisons, so we read clear gaps as leads. We do this to show how far each result depends on the texts we have, without assuming a distribution.

F.2 Default alignment

Section 5.1 gives the agreement of each model with each annotator group for Kumar. Here we give the other three datasets in the same format (Tables 15, 16 and 17). We also list every gap between two groups that is clear (Table 18 in Appendix F.2.4), so that the reader can check which gaps support the claims in the main text. Under the default prompt, a model gives the same label to every text of a group in 12 of 176 model-group cells (Attitudes 4 of 40, MHS 7 of 28, Kumar 1 of 52, POPQUORN 0 of 56). There κ is set to 0 and marked with a dagger.

F.2.1 Attitudes. Table 15 gives the agreement of each model with the annotator groups of Attitudes, in the format of Table 3. Its groups have 6 to 14 attributed texts, and age and traditionalism rest on fewer than 10 (‡).

In contrast to Kumar, the audit finds nothing certain in Attitudes. No gap between two groups is clear and no κ is clear, so the framework tells a user that these data cannot say whose side the models take. Some patterns are visible but uncertain. ChatGPT, DeepSeek and Gemini agree more with white than with black annotators (about 0.1 to 0.3 against

Table 16. Cohen's κ between each LLM and the groups of each characteristic on the polarized POPQUORN texts attributed to it, with the default prompt. Values in parentheses are bootstrap standard errors from 10,000 resamples of the texts. Bold marks values that are clearly different from zero (Appendix F.1). D = demographic, N = non-demographic. Black stands for Black or African American, College for college degree, Graduate for graduate degree, and High school for high school diploma or equivalent. Share of texts the models label toxic, on average over groups: ChatGPT 47.5%, DeepSeek 37.4%, Gemini 45.7%, Mistral 66.1%.

	Gender (D)		Race (D)		Age (D)	
Model	Man	Woman	Black	White	Gen X+	millennial
Texts	14	14	13	13	55	55
ChatGPT	0.04 (0.24)	0.16 (0.25)	0.27 (0.18)	−0.15 (0.13)	0.12 (0.12)	**0.19** (0.09)
DeepSeek	−0.14 (0.25)	0.29 (0.26)	0.15 (0.12)	−0.14 (0.11)	0.20 (0.14)	0.07 (0.12)
Gemini	−0.14 (0.25)	0.29 (0.26)	0.16 (0.27)	0.07 (0.08)	0.15 (0.14)	0.22 (0.12)
Mistral	−0.23 (0.20)	0.34 (0.18)	0.16 (0.27)	0.07 (0.08)	0.17 (0.11)	−0.02 (0.08)

	Education (N)			Occupation (N)				
Model	College	Graduate	High school	Employed	Retired	Self-employed	Student	Unemployed
Texts	44	17	38	52	11	28	11	10
ChatGPT	0.22 (0.15)	0.07 (0.24)	0.20 (0.17)	**0.30** (0.12)	1.00 (0.21)	0.19 (0.12)	−0.22 (0.25)	0.09 (0.12)
DeepSeek	0.17 (0.15)	0.33 (0.21)	0.13 (0.17)	**0.41** (0.13)	0.79 (0.25)	0.21 (0.14)	−0.52 (0.21)	0.29 (0.26)
Gemini	0.28 (0.15)	−0.34 (0.21)	0.29 (0.16)	**0.48** (0.12)	1.00 (0.21)	0.16 (0.11)	−0.52 (0.20)	0.14 (0.16)
Mistral	**0.28** (0.11)	−0.07 (0.24)	0.13 (0.11)	**0.26** (0.09)	0.35 (0.21)	0.12 (0.09)	0.03 (0.24)	0.02 (0.05)

−0.2 to −0.3), and ChatGPT, DeepSeek and Mistral agree more with left-leaning than with right-leaning annotators (up to 0.57 for Mistral), but these values are not clear. DeepSeek and Gemini gave the same label to every gender text, so κ is zero there. The models label 73% to 86% of the texts toxic on average, which also limits what κ can show.

F.2.2 POPQUORN. Table 16 gives the agreement of each model with the annotator groups of POPQUORN, in the format of Table 3. Unlike Attitudes, some gaps here are clear and almost all involve occupation.

Of the 64 gaps between groups, 13 are clear, 11 involving occupation and two involving education. Nine of the occupation gaps involve students, who have a lower κ than retired, employed, self-employed and unemployed annotators (for ChatGPT, DeepSeek and Gemini, κ from −0.22 to −0.52). The other two compare employed with self-employed (Gemini) and unemployed annotators (Mistral), and the two education gaps are Gemini's, which agrees less with graduate than with college and high school annotators. For all four models, the κ with employed annotators is clear (0.26 to 0.48). As in Kumar, the clearest gaps involve non-demographic characteristics, occupation here and political leaning there. We do not read this as a general difference between the two kinds of characteristics, which remains an open question (Appendix F.2.5). The models label 37% to 66% of the texts toxic on average.

F.2.3 MHS. Table 17 gives the agreement of each model with the annotator groups of MHS, in the same format. As in Attitudes, the audit finds no side here, and the reason is visible in the data.

No κ is clear (they run from −0.12 to 0.20), and no gap between groups is clear. The groups differ in how often they call a text toxic, from 23% of the texts for neutral annotators to 73% for Gen X+. The models, however, label between 92% and 98% of the texts toxic (92.0% for ChatGPT, 97.7% for DeepSeek, 97.1% for Gemini, 96.6% for Mistral), so they cannot follow any group's position. In 7 of the 28 comparisons the model gave the same label to every text, so κ is zero there.

F.2.4 Clear gaps between groups. Table 18 lists the 26 gaps between groups of one characteristic that are clear under the default prompt. All of them are in Kumar (13) and POPQUORN (13) and none in Attitudes or MHS. For each pair we show the group with the higher κ first, so the gap is positive, with its standard error. Group sizes are in parentheses. Out of 148 gaps, 26 are clear. We do not compare this count with the number expected by chance, because the gaps are

Table 17. Cohen's κ between each LLM and the groups of each characteristic on the polarized MHS texts attributed to it, with the default prompt. Values in parentheses are bootstrap standard errors from 10,000 resamples of the texts. No value is bold because none is clearly different from zero (Appendix F.1). D = demographic, N = non-demographic. † The model gave the same label to every text, so κ is 0 by definition. Share of texts the models label toxic, on average over groups: ChatGPT 92.0%, DeepSeek 97.7%, Gemini 97.1%, Mistral 96.6%.

	Gender (D)		Age (D)		Politics (N)		
Model	female	male	Gen X+	millennial	conservative	liberal	neutral
Texts	43	43	30	30	22	29	13
ChatGPT	0.07 (0.14)	−0.03 (0.07)	−0.12 (0.07)	0.05 (0.04)	−0.09 (0.08)	0.10 (0.07)	0.05 (0.06)
DeepSeek	0.06 (0.11)	−0.03 (0.05)	−0.06 (0.05)	0.02 (0.03)	0.00† (0.00)	0.00† (0.00)	0.00† (0.00)
Gemini	0.20 (0.13)	−0.10 (0.07)	0.00† (0.00)	0.00† (0.00)	0.00† (0.00)	0.05 (0.05)	0.05 (0.06)
Mistral	0.06 (0.11)	−0.03 (0.05)	−0.06 (0.06)	0.02 (0.03)	−0.09 (0.08)	0.05 (0.05)	0.00† (0.00)

not independent, since the models' labels are correlated (Appendix G.1), groups of a characteristic share texts, and some gaps are identical across models, for example ChatGPT and Gemini for Kumar politics. Each gap also rests on groups of 10 to 55 texts and is not corrected for the number of comparisons, so we read it as a lead. Kumar's gaps mostly involve political leaning, where Liberal annotators have the higher κ in all six. In POPQUORN, 9 of the 13 gaps involve students.

Table 18. Gaps between groups that are clear under the default prompt, meaning that the bootstrap range of the gap excludes zero (Appendix F.1). The gap is the difference in κ between the first and second group, with its bootstrap standard error in parentheses. Group sizes (texts) are in parentheses.

Dataset	Characteristic	Model	Higher κ	Lower κ	Gap (SE)
Kumar	Age	ChatGPT	Gen Z (10)	Gen X+ (10)	0.92 (0.31)
Kumar	Age	ChatGPT	Gen Z (10)	Millennial (10)	0.90 (0.39)
Kumar	Age	Mistral	Gen Z (10)	Gen X+ (10)	0.80 (0.30)
Kumar	Age	Mistral	Gen Z (10)	Millennial (10)	0.83 (0.34)
Kumar	Gender	Gemini	Female (10)	Male (10)	2.00 (0.19)
Kumar	Politics	ChatGPT	Liberal (10)	Conservative (10)	1.09 (0.31)
Kumar	Politics	ChatGPT	Liberal (10)	Independent (10)	1.07 (0.25)
Kumar	Politics	DeepSeek	Liberal (10)	Independent (10)	1.18 (0.32)
Kumar	Politics	Gemini	Liberal (10)	Conservative (10)	1.09 (0.31)
Kumar	Politics	Gemini	Liberal (10)	Independent (10)	1.07 (0.25)
Kumar	Politics	Mistral	Liberal (10)	Independent (10)	0.87 (0.31)
Kumar	Race	ChatGPT	Asian (10)	White (10)	0.96 (0.38)
Kumar	Race	DeepSeek	Asian (10)	White (10)	0.92 (0.36)
POPQUORN	Education	Gemini	College (44)	Graduate (17)	0.63 (0.28)
POPQUORN	Education	Gemini	High school (38)	Graduate (17)	0.63 (0.28)
POPQUORN	Occupation	ChatGPT	Retired (11)	Student (11)	1.22 (0.33)
POPQUORN	Occupation	DeepSeek	Employed (52)	Student (11)	0.93 (0.24)
POPQUORN	Occupation	DeepSeek	Retired (11)	Student (11)	1.31 (0.33)
POPQUORN	Occupation	DeepSeek	Self-employed (28)	Student (11)	0.73 (0.25)
POPQUORN	Occupation	DeepSeek	Unemployed (10)	Student (11)	0.80 (0.34)
POPQUORN	Occupation	Gemini	Employed (52)	Self-employed (28)	0.32 (0.14)
POPQUORN	Occupation	Gemini	Employed (52)	Student (11)	1.00 (0.24)
POPQUORN	Occupation	Gemini	Retired (11)	Student (11)	1.52 (0.29)
POPQUORN	Occupation	Gemini	Self-employed (28)	Student (11)	0.68 (0.23)
POPQUORN	Occupation	Gemini	Unemployed (10)	Student (11)	0.66 (0.26)
POPQUORN	Occupation	Mistral	Employed (52)	Unemployed (10)	0.24 (0.11)

Table 19. Observed and chance attribution rates in percent. D and N mark demographic and non-demographic characteristics, and the groups are those retained by the 10-text rule. Chance is the mean over 1,000 shuffles. Excess is observed minus chance in points, computed from unrounded values. p is the share of shuffles with at least as many attributed texts as observed.

Dataset	Characteristic	Type	Groups	Testable	Observed	Chance	Excess	p
Attitudes	Gender	D	2	164	6.1	4.0	+2.1	0.112
	Race	D	2	239	5.9	4.8	+1.0	0.262
	Age	D	3	97	6.2	4.2	+1.9	0.227
	Politics	N	2	144	8.3	7.0	+1.3	0.279
	Traditionalism	N	2	154	5.8	3.8	+2.0	0.114
POPQUORN	Gender	D	2	615	2.3	2.6	−0.3	0.754
	Race	D	2	204	6.4	4.5	+1.9	0.129
	Age	D	2	583	9.4	8.5	+1.0	0.130
	Education	N	3	591	8.0	6.4	+1.6	0.059
	Occupation	N	5	418	12.9	12.6	+0.3	0.449
MHS	Gender	D	2	529	8.1	8.4	−0.2	0.624
	Age	D	2	305	9.8	7.8	+2.0	0.081
	Politics	N	3	336	9.5	8.9	+0.6	0.366
Kumar	Gender	D	2	19,436	6.3	5.7	+0.6	0.001
	Race	D	3	5,727	11.6	8.0	+3.7	0.001
	Age	D	3	11,400	9.1	8.7	+0.4	0.072
	Politics	N	3	15,584	12.3	11.8	+0.5	0.015
	Religion	N	2	15,940	7.8	5.8	+2.0	0.001

F.2.5 Chance baseline. A text can pass the AU test by chance, and more easily when a characteristic has more groups, since two ratings form a single peak whenever they are equal or adjacent. We use the polarized texts with at least four ratings that can be tested for the characteristic. On each of them, we shuffle the group labels among the ratings of the retained groups, which keeps the ratings and the group sizes, and rerun AU with the same rules, without applying the 10-text rule again. We repeat this 1,000 times for each characteristic, shuffling each one independently with a fixed seed, and take the mean share of attributed texts as the chance rate. The p-value is one-sided. It is the share of shuffles with at least as many attributed texts as observed, counting the observed attribution as one of them. It is not corrected for the 18 characteristics tested.

Table 19 shows that the observed rate exceeds the chance rate by at most 3.7 points. The excess is clear only in Kumar gender, race, politics and religion ($p < 0.05$), and in the other three datasets no characteristic differs clearly from chance. We therefore read the attributed texts there as texts that pass the AU test, not as texts that the characteristic is shown to account for. Chance rates grow with the number of groups, with a Spearman correlation of 0.57 between the two over the 18 characteristics. The raw gap in attribution rate between non-demographic and demographic characteristics, 0.8 to 4.2 points across the four datasets, falls to 0.0 to 0.5 points once chance is subtracted, and the difference is not clear in any of the four datasets, so we do not compare the two kinds of characteristics.

F.2.6 Pooled Agreement. The pooled label of a text is the majority label of all its ratings after preprocessing: toxic if most ratings are 3 or more (in MHS, only a 3 is toxic) and civil otherwise. On an exact tie we use the mean rating, toxic if it is 3 or more. It uses no group and no characteristic. We compute it on the same attributed texts as the group κ values, with the default prompt, so both are comparable.

On a polarized text the groups disagree, so the pooled label follows the larger group. A pooled κ therefore measures agreement with the larger group on each text and not with any group. For example, take ten texts where liberals and conservatives disagree, liberals are the larger group on seven, and a model always sides with liberals. Its κ is 1.00 with liberals and −1.00 with conservatives, but 0.40 with the pooled label. If conservatives were the larger group on those seven texts, the pooled κ would be −0.40 and the model would not have changed.

Table 20. Pooled Cohen's κ of each LLM with the default prompt, followed in brackets by the lowest and highest κ with the groups of the characteristic (Table 3 and Appendix F.2). Kumar uses the 65-attribution sample. † The model gave the same label to every text, so κ is 0 by definition. In MHS age and politics the pooled label is civil on every text, so the pooled κ is 0 by construction.

Dataset	Characteristic	ChatGPT	DeepSeek	Gemini	Mistral
Attitudes	Gender	0.21 [−0.40, 0.40]	0.00† [0.00, 0.00]	0.00† [0.00, 0.00]	0.41 [−0.20, 0.20]
	Race	0.38 [−0.26, 0.21]	0.51 [−0.24, 0.11]	0.66 [−0.21, 0.26]	0.10 [−0.07, 0.42]
	Age	−0.20 [−0.80, 0.25]	−0.20 [−0.20, 0.25]	0.40 [−0.20, 1.00]	0.18 [−0.36, 0.57]
	Politics	0.56 [0.00, 0.40]	0.56 [0.00, 0.40]	0.43 [0.31, 0.31]	0.25 [−0.29, 0.57]
	Traditionalism	0.18 [−0.42, 0.18]	0.18 [−0.42, 0.18]	−0.20 [−0.20, 0.27]	−0.20 [−0.20, 0.27]
POPQUORN	Gender	0.59 [0.04, 0.16]	0.43 [−0.14, 0.29]	0.43 [−0.14, 0.29]	0.02 [−0.23, 0.34]
	Race	0.03 [−0.15, 0.27]	0.16 [−0.14, 0.15]	0.15 [0.07, 0.16]	0.15 [0.07, 0.16]
	Age	0.19 [0.12, 0.19]	0.24 [0.07, 0.20]	0.20 [0.15, 0.22]	0.06 [−0.02, 0.17]
	Education	−0.02 [0.07, 0.22]	0.01 [0.13, 0.33]	0.22 [−0.34, 0.29]	0.05 [−0.07, 0.28]
	Occupation	0.22 [−0.22, 1.00]	0.20 [−0.52, 0.79]	0.23 [−0.52, 1.00]	0.15 [0.02, 0.35]
MHS	Gender	0.01 [−0.03, 0.07]	0.00 [−0.03, 0.06]	0.00 [−0.10, 0.20]	0.00 [−0.03, 0.06]
	Age	0.00 [−0.12, 0.05]	0.00 [−0.06, 0.02]	0.00† [0.00, 0.00]	0.00 [−0.06, 0.02]
	Politics	0.00 [−0.09, 0.10]	0.00† [0.00, 0.00]	0.00 [0.00, 0.05]	0.00 [−0.09, 0.05]
Kumar	Gender	−0.25 [−0.40, 0.40]	−0.25 [−0.40, 0.40]	0.00 [−1.00, 1.00]	−0.40 [−0.60, 0.60]
	Race	0.36 [−0.36, 0.60]	0.44 [−0.32, 0.60]	−0.06 [−0.36, 0.20]	0.22 [−0.15, 0.20]
	Age	0.31 [−0.32, 0.60]	0.44 [0.00, 0.20]	0.23 [0.09, 0.29]	0.39 [−0.03, 0.80]
	Politics	0.47 [−0.09, 1.00]	0.17 [−0.40, 0.78]	0.47 [−0.09, 1.00]	0.36 [−0.07, 0.80]
	Religion	0.23 [−0.19, 0.29]	0.23 [−0.19, 0.29]	0.00 [−0.20, 0.40]	0.44 [−0.18, 0.19]

Table 21. Share of the attributed texts where the groups split that each LLM labels toxic with the default prompt, in percent, with the bootstrap standard error from 10,000 resamples of the texts in parentheses. Each text is counted once per dataset. Kumar uses the 65-attribution sample.

Dataset	Split texts	ChatGPT	DeepSeek	Gemini	Mistral
Attitudes	32	75 (8)	84 (6)	84 (6)	81 (7)
POPQUORN	76	59 (6)	49 (6)	55 (6)	75 (5)
MHS	94	94 (2)	98 (1)	98 (1)	97 (2)
Kumar	46	52 (7)	48 (7)	57 (7)	63 (7)

Table 20 shows the pooled κ next to the lowest and highest group κ of each characteristic. The pooled κ lies strictly between them in 45 of 72 cases, and in the others it lies above, below or at one of them. It can exceed every group: in Attitudes race, the pooled κ of ChatGPT, DeepSeek and Gemini (0.38, 0.51 and 0.66) is higher than that of both groups (at most 0.26). In 8 of 72 cases the pooled $|\kappa|$ is below 0.2 while the groups differ by at least 0.5 (four in Kumar, three in Attitudes and one in POPQUORN), as for Gemini on Kumar gender, where the pooled κ is 0.00 and the groups are at 1.00 and −1.00. Pooled κ also ranks models differently from the groups: in Kumar politics it is 0.36 for Mistral and 0.17 for DeepSeek, although both agree with liberal annotators to the same degree (κ of 0.80 and 0.78). Pooling can therefore give apparent agreement, but it does not always do so, which is why the audit reads each group.

The pooled label is less certain than the group labels. It is decided by the mean on 11 of 41 attributed Attitudes texts, 21 of 154 in POPQUORN and 15 of 65 in Kumar (5 of the 10 in Kumar gender). In MHS it is decided by the mean on 91 of 95 texts, so we do not read the MHS values.

F.2.7 Alignment with the Poles. The poles of a text are the toxic and the civil position of the groups on it (Section 4.2). We use the attributed texts where the groups split and the labels of the default prompt, and a model matches the toxic pole when it labels the text toxic. Table 21 gives the share of these texts that each model labels toxic. In Kumar and POPQUORN the shares are close to half for most models (48% to 63% and 49% to 75%), so the models do not lean toward a pole. In Attitudes and MHS they are high (75% to 84% and 94% to 98%), so the models sit at the toxic pole whichever group holds it, which is why no group stands out in these two datasets.

Table 22. Share of Kumar texts, in percent, on which each LLM matches a group's position, by whether the group holds the toxic or the civil pole. Groups with at least three texts at each pole are shown. n is the number of texts. GPT = ChatGPT, DS = DeepSeek, Gem = Gemini, Mis = Mistral. Independent annotators are left out because they hold the toxic pole on one text only.

		Group at the toxic pole					Group at the civil pole				
Characteristic	Group	n	GPT	DS	Gem	Mis	n	GPT	DS	Gem	Mis
Gender	Female	5	60	60	100	80	5	80	80	100	80
	Male	5	20	20	0	20	5	40	40	0	20
Politics	Conservative	6	50	50	50	67	3	33	67	33	33
	Liberal	4	100	75	100	100	3	100	100	100	67

Table 22 shows that in Kumar the labels follow a group at both poles. Gemini matches women on all 5 texts where they hold the toxic pole and on all 5 where they hold the civil pole, and matches men on none of either. The models match liberal annotators on 67% to 100% of their texts at either pole and conservative annotators on 33% to 67%. Independent annotators hold the toxic pole on only one text and the civil pole on five, and the models match their position on none of these six texts. In MHS, the groups with at least five texts at each pole are matched on 85% to 100% of their toxic-pole texts and on only 0% to 15% of their civil-pole texts, which is a lean toward the toxic pole and not the following of a group. Each cell in Table 22 rests on three to six texts, so we read it as a pattern and not as an estimate.

F.3 Alignment with Sociodemographic Prompting

Section 5.2 compares the default prompt with the SCDP for Kumar. Here we give the alignment with the SCDP for all four datasets in the format of Appendix F.2 (Tables 23, 24, 25 and 26). We then list the gaps between groups that are clear with the SCDP (Table 27) and the changes from the default prompt that are clear (Table 28). Finally, we ask whether a model agrees more with a group when it labels as that group than when it labels as another one (Table 29). With the SCDP, a model gives the same label to every text of a group in 24 of 176 model-group cells (Attitudes 10 of 40, MHS 13 of 28, Kumar 1 of 52, POPQUORN 0 of 56), against 12 under the default. There κ is set to 0 and marked with a dagger.

F.3.1 Attitudes. Table 23 gives the alignment with the SCDP in Attitudes. One κ is clear, ChatGPT for white annotators (0.36). Two gaps between groups are clear, both between Black and white annotators, for ChatGPT and Gemini, with white annotators higher (−0.26 against 0.36 and −0.24 against 0.26, groups of 14 texts). The default prompt shows no clear gap in Attitudes, so this is the only case in the dataset where the prompt reveals a gap. The left side is again above the right side for all four models, but these values are not clear. The models label 77% to 83% of the texts toxic, and in 10 of 40 model-group cells they give one label to every text, against 4 by default.

F.3.2 POPQUORN. Table 24 gives the alignment with the SCDP in POPQUORN. Ten κ values are clear, among them employed annotators for all four models. Twelve gaps between groups are clear (13 by default). Nine of them involve students, who have a lower κ than retired, employed and self-employed annotators, and two more are between employed and unemployed annotators. The education gaps of the default prompt are no longer clear. One new gap appears, for ChatGPT between women and men, but the labels of the two personas are identical (κ of 1.00 between them), so the gap reflects the model's labels and not the persona. The models label between 39% and 72% of the texts toxic, and no model gives one label to every text.

F.3.3 MHS. Table 25 gives the alignment with the SCDP in MHS. As with the default prompt, no κ is clear (they run from −0.10 to 0.35) and no gap between groups is clear. The models label between 96% and 99% of the texts toxic, and

Table 23. Cohen's κ between each LLM and the groups of each characteristic on the polarized Attitudes texts attributed to it, with the SCDP. Each group is compared with the labels the model gave as a member of that group, and n is the number of attributed texts in which it is compared. Values in parentheses are bootstrap standard errors from 10,000 resamples of the attributed texts. No κ is clearly different from zero (Appendix F.1). D = demographic, N = non-demographic. † The model gave the same label to every text, so κ is 0 by definition. ‡ The characteristic has fewer than 10 attributed texts. Toxic (%) is the share of texts the model labeled toxic (rating of 3 or more), averaged over the groups.

	Gender (D)		Race (D)		Age (D)‡	
Model	man	woman	black	white	gen x+	millennial
n	10	10	14	14	6	6
ChatGPT	0.00† (0.00)	0.20 (0.20)	−0.26 (0.13)	0.36 (0.18)	0.18 (0.22)	−0.29 (0.20)
DeepSeek	−0.20 (0.27)	0.20 (0.28)	−0.21 (0.11)	0.11 (0.20)	0.18 (0.22)	0.00† (0.00)
Gemini	0.20 (0.20)	0.00 (0.25)	−0.24 (0.12)	0.26 (0.16)	0.18 (0.22)	0.25 (0.39)
Mistral	0.00† (0.00)	0.00† (0.00)	−0.17 (0.09)	0.00† (0.00)	0.18 (0.22)	0.00† (0.00)

	Politics (N)		Traditionalism (N)‡		
Model	left	right	high	not high	Toxic (%)
n	12	12	9	9	
ChatGPT	0.40 (0.29)	0.12 (0.28)	0.00† (0.00)	−0.54 (0.27)	77%
DeepSeek	0.57 (0.28)	0.33 (0.26)	0.00† (0.00)	−0.42 (0.21)	78%
Gemini	0.57 (0.28)	0.25 (0.29)	0.00† (0.00)	−0.15 (0.30)	79%
Mistral	0.62 (0.26)	0.40 (0.29)	0.00† (0.00)	−0.05 (0.26)	83%

Table 24. Cohen's κ between each LLM and the groups of each characteristic on the polarized POPQUORN texts attributed to it, with the SCDP. Each group is compared with the labels the model gave as a member of that group, and n is the number of attributed texts in which it is compared. Values in parentheses are bootstrap standard errors from 10,000 resamples of the attributed texts. Bold marks a κ that is clearly different from zero (Appendix F.1). D = demographic, N = non-demographic. Black stands for Black or African American, College for college degree, Graduate for graduate degree, and High school for high school diploma or equivalent. Toxic (%) is the share of texts the model labeled toxic (rating of 3 or more), averaged over the groups.

	Gender (D)		Race (D)		Age (D)	
Model	Man	Woman	Black	White	gen x+	millennial
n	14	14	13	13	55	55
ChatGPT	−0.43 (0.22)	**0.57** (0.22)	0.20 (0.15)	−0.14 (0.11)	0.02 (0.13)	0.08 (0.10)
DeepSeek	0.14 (0.25)	0.00 (0.26)	0.10 (0.10)	−0.13 (0.10)	0.17 (0.13)	0.15 (0.08)
Gemini	−0.24 (0.23)	0.44 (0.23)	0.20 (0.15)	−0.15 (0.12)	**0.28** (0.13)	0.09 (0.11)
Mistral	0.17 (0.13)	0.11 (0.12)	0.26 (0.31)	0.05 (0.06)	0.06 (0.07)	0.00 (0.06)

	Education (N)			Occupation (N)					
Model	College	Graduate	High school	Employed	Retired	Self-employed	Student	Unemployed	Toxic (%)
n	44	17	38	52	11	28	11	10	
ChatGPT	**0.40** (0.15)	0.11 (0.22)	0.10 (0.17)	**0.29** (0.11)	1.00 (0.21)	0.14 (0.10)	−0.22 (0.25)	0.14 (0.16)	43%
DeepSeek	0.17 (0.15)	0.23 (0.20)	0.06 (0.16)	**0.35** (0.13)	0.38 (0.31)	0.05 (0.14)	−0.45 (0.19)	−0.20 (0.18)	39%
Gemini	**0.36** (0.15)	0.11 (0.22)	0.23 (0.17)	**0.42** (0.11)	0.74 (0.33)	0.19 (0.13)	−0.52 (0.20)	0.14 (0.16)	42%
Mistral	**0.23** (0.10)	−0.12 (0.23)	**0.26** (0.12)	**0.20** (0.07)	0.79 (0.25)	0.07 (0.06)	−0.29 (0.25)	0.02 (0.05)	72%

in 13 of 28 model-group cells they give one label to every text, against 7 by default, so the SCDP makes them more constant. The largest value is for conservative annotators with DeepSeek and Gemini (0.35), but it is not clear.

F.3.4 Kumar. Table 26 gives the alignment with the SCDP in Kumar alone, in the format of Table 3. Two κ values are clear, both for Gemini, for Gen Z annotators (0.80) and for liberal annotators (1.00). Five gaps between groups are clear (13 by default). For Gemini, Gen Z annotators are above Gen X+ annotators, and for both Gemini and DeepSeek liberal annotators are above conservative and independent annotators. For ChatGPT and Mistral the liberal gaps are no longer clear. The models label between 36% and 75% of the texts toxic, Mistral the most, and only one cell (Mistral for independent annotators) has one label for every text.

Table 25. Cohen's κ between each LLM and the groups of each characteristic on the polarized MHS texts attributed to it, with the SCDP. Each group is compared with the labels the model gave as a member of that group, and n is the number of attributed texts in which it is compared. Values in parentheses are bootstrap standard errors from 10,000 resamples of the attributed texts. No κ is clearly different from zero (Appendix F.1). D = demographic, N = non-demographic. † The model gave the same label to every text, so κ is 0 by definition. Toxic (%) is the share of texts the model labeled toxic (rating of 3 or more), averaged over the groups.

	Gender (D)		Age (D)		Politics (N)			
Model	female	male	gen x+	millennial	conservative	liberal	neutral	Toxic (%)
n	43	43	30	30	22	29	13	
ChatGPT	0.00† (0.00)	0.00† (0.00)	−0.06 (0.05)	0.02 (0.03)	0.00† (0.00)	0.00† (0.00)	0.00† (0.00)	99%
DeepSeek	0.20 (0.13)	−0.08 (0.07)	−0.06 (0.05)	0.02 (0.03)	0.35 (0.21)	0.05 (0.05)	0.00† (0.00)	96%
Gemini	0.20 (0.13)	−0.10 (0.07)	0.00† (0.00)	0.00† (0.00)	0.35 (0.21)	0.05 (0.05)	0.00† (0.00)	97%
Mistral	0.10 (0.10)	0.00† (0.00)	0.00† (0.00)	0.00† (0.00)	0.19 (0.17)	−0.02 (0.09)	0.00† (0.00)	98%

Table 26. Cohen's κ between each LLM and the groups of each characteristic on the polarized Kumar texts attributed to it, with the SCDP. Each group has 10 attributed texts and is compared with the labels the model gave as a member of that group. Values in parentheses are bootstrap standard errors from 10,000 resamples of the attributed texts. Bold marks a κ that is clearly different from zero (Appendix F.1). D = demographic, N = non-demographic. † The model gave the same label to every text, so κ is 0 by definition. Toxic (%) is the share of texts the model labeled toxic (rating of 3 or more), averaged over the groups.

	Gender (D)		Race (D)			Age (D)		
Model	Female	Male	Asian	Black	White	Gen X+	Gen Z	Millennial
ChatGPT	0.40 (0.29)	−0.40 (0.27)	0.40 (0.30)	0.09 (0.12)	0.21 (0.32)	0.21 (0.32)	0.60 (0.27)	0.09 (0.11)
DeepSeek	0.40 (0.29)	−0.40 (0.27)	0.20 (0.31)	0.05 (0.08)	0.38 (0.36)	0.55 (0.29)	0.40 (0.30)	0.09 (0.11)
Gemini	0.20 (0.28)	−0.20 (0.27)	0.40 (0.30)	0.14 (0.16)	−0.25 (0.14)	−0.25 (0.14)	**0.80** (0.21)	0.07 (0.27)
Mistral	0.20 (0.30)	−0.40 (0.21)	0.00 (0.25)	−0.11 (0.09)	−0.13 (0.22)	−0.18 (0.21)	0.20 (0.20)	−0.21 (0.20)

	Politics (N)			Religion (N)		
Model	conservative	independent	liberal	high	not high	Toxic (%)
ChatGPT	−0.09 (0.28)	0.29 (0.21)	0.35 (0.31)	−0.21 (0.20)	0.62 (0.39)	42%
DeepSeek	−0.20 (0.27)	−0.07 (0.23)	0.78 (0.25)	−0.20 (0.17)	0.62 (0.39)	43%
Gemini	−0.30 (0.26)	−0.40 (0.21)	**1.00** (0.10)	−0.21 (0.20)	0.74 (0.31)	36%
Mistral	−0.32 (0.16)	0.00† (0.00)	0.44 (0.23)	−0.15 (0.11)	−0.15 (0.11)	75%

F.3.5 Clear gaps and changes. Table 27 lists the 19 gaps between groups that are clear with the SCDP, in the same format as Table 18 (Attitudes 2, Kumar 5, POPQUORN 12 and MHS 0). The two Attitudes gaps appear only with the SCDP. Table 28 lists the 3 of 176 changes in κ from the default to the SCDP that are clear. Two of them are the two groups of Kumar gender for Gemini, whose man and woman personas give identical labels (κ of 1.00 between them), so these changes come from the SCDP format and not from the persona. The third is for graduate-degree annotators in POPQUORN, where Gemini's κ rises from −0.34 to 0.11.

Table 27. Gaps between groups that are clear with the SCDP, meaning that the bootstrap range of the gap excludes zero (Appendix F.1). The gap is the difference in κ between the first and second group, with its bootstrap standard error in parentheses. Group sizes (texts) are in parentheses.

Dataset	Characteristic	Model	Higher κ	Lower κ	Gap (SE)
Attitudes	Race	ChatGPT	White (14)	Black (14)	0.62 (0.27)
Attitudes	Race	Gemini	White (14)	Black (14)	0.50 (0.23)
Kumar	Age	Gemini	Gen Z (10)	Gen X+ (10)	1.05 (0.27)
Kumar	Politics	DeepSeek	Liberal (10)	Conservative (10)	0.98 (0.33)
Kumar	Politics	DeepSeek	Liberal (10)	Independent (10)	0.85 (0.34)
Kumar	Politics	Gemini	Liberal (10)	Conservative (10)	1.30 (0.29)
Kumar	Politics	Gemini	Liberal (10)	Independent (10)	1.40 (0.23)

Table 28. Changes in κ from the default to the SCDP that are clear, meaning that the bootstrap range of the change excludes zero (Appendix F.1). The change is κ with the SCDP minus κ by default, with its bootstrap standard error in parentheses. The other 173 changes are not clear.

Dataset	Model	Group (n)	Default	SCDP	Change (SE)
POPQUORN	Gemini	Graduate degree (17)	−0.34	0.11	0.45 (0.21)
Kumar	Gemini	Female (10)	1.00	0.20	−0.80 (0.29)
Kumar	Gemini	Male (10)	−1.00	−0.20	0.80 (0.31)

Dataset	Characteristic	Model	Higher κ	Lower κ	Gap (SE)
POPQUORN	Gender	ChatGPT	Woman (14)	Man (14)	1.00 (0.39)
POPQUORN	Occupation	ChatGPT	Retired (11)	Student (11)	1.22 (0.33)
POPQUORN	Occupation	DeepSeek	Employed (52)	Student (11)	0.81 (0.23)
POPQUORN	Occupation	DeepSeek	Employed (52)	Unemployed (10)	0.55 (0.19)
POPQUORN	Occupation	DeepSeek	Retired (11)	Student (11)	0.83 (0.36)
POPQUORN	Occupation	Gemini	Employed (52)	Student (11)	0.94 (0.24)
POPQUORN	Occupation	Gemini	Retired (11)	Student (11)	1.26 (0.39)
POPQUORN	Occupation	Gemini	Self-employed (28)	Student (11)	0.70 (0.24)
POPQUORN	Occupation	Gemini	Unemployed (10)	Student (11)	0.66 (0.26)
POPQUORN	Occupation	Mistral	Employed (52)	Student (11)	0.49 (0.25)
POPQUORN	Occupation	Mistral	Employed (52)	Unemployed (10)	0.17 (0.08)
POPQUORN	Occupation	Mistral	Retired (11)	Student (11)	1.09 (0.35)

F.3.6 Labeling as a group. Table 29 asks, for each group, whether the model agrees more with it when it labels as that group than when it labels as another group. Across the 272 comparisons, labeling as the group gives the higher κ in 131 (48%), the lower in 83 (31%) and the same in 58 (21%). The pattern is weak and differs by characteristic. It is strongest for age in Kumar (19 of 24) and education in POPQUORN (16 of 24), and reversed for traditionalism in Attitudes (7 of 8 lower). Ties dominate for gender in POPQUORN and Kumar and in MHS, where the model gives the same labels under every persona. For gender in POPQUORN and Kumar, three of the four models have a κ of 1.00 between the man and woman personas.

G Model Results

Besides the alignment with groups, we describe how the four models behave on the attributed texts, to help read the audit.

G.1 Model Comparison

The audit measures each model against the annotators, but a user also wants to know how the models compare with each other. We therefore compare how the four models rate and label the same texts, in each dataset separately (Figure 15). This step is exploratory. It does not change the audit, and it shows whether the models are consistent enough to be treated alike.

We compare the ratings with the Spearman correlation. The ratings are ordinal, so we do not assume that the distance between two rating values is the same everywhere, as the Pearson correlation does. Spearman uses only the order of the ratings. This also means that a model that rates everything higher than another, but in the same order, still correlates strongly with it. We compare the labels (a rating of 3 or more is toxic) with Cohen's κ, the same measure we use against

Table 29. For each group, whether a model agrees more with it when it labels as that group than when it labels as another group. Counts are over comparisons pooled across the four models. Mean κ is the average agreement with the group when the model labels as that group and when it labels as the other groups.

Dataset	Characteristic	Comp.	Higher	Tie	Lower	Mean κ as group	Mean κ as other
Attitudes	Gender	8	4	4	0	0.05	−0.05
	Race	8	3	0	5	−0.02	0.03
	Age	8	3	1	4	0.09	0.25
	Politics	8	5	0	3	0.41	0.29
	Traditionalism	8	1	0	7	−0.14	0.21
POPQUORN	Gender	8	1	6	1	0.10	0.10
	Race	8	2	6	0	0.05	0.04
	Age	8	4	0	4	0.11	0.10
	Education	24	16	0	8	0.18	0.07
	Occupation	56	31	4	21	0.16	0.17
MHS	Gender	8	4	4	0	0.04	0.01
	Age	8	0	8	0	−0.01	−0.01
	politics	24	11	12	1	0.08	−0.03
Kumar	Gender	8	0	6	2	−0.03	0.03
	Race	24	12	1	11	0.11	0.15
	Age	24	19	0	5	0.20	−0.14
	Politics	24	11	4	9	0.12	0.10
	Religion	8	4	2	2	0.13	0.10




Fig. 15. Agreement between the four LLMs on the same texts, for each dataset. Top: Spearman correlation between ratings. Bottom: Cohen's κ between labels. n is the number of texts.

the annotator groups. κ removes the agreement expected by chance, which matters when a model labels almost every text toxic, as in MHS, where plain agreement would look high without showing any shared judgment.

Spearman correlations between ratings run from 0.31 to 0.89 and are highest in Kumar and lowest in Attitudes. ChatGPT, DeepSeek and Gemini form a cluster in Attitudes (0.67 to 0.78) and in MHS (0.75 to 0.77), and in both Mistral stays apart (0.31 to 0.43 and 0.58 to 0.59). In POPQUORN all four models are close (0.66 to 0.79), and in Kumar ChatGPT and DeepSeek are the closest pair (0.89), with Mistral nearest to ChatGPT (0.80). For a user, this shows which models




Fig. 16. Scores (1 to 5) that each LLM gives under the default prompt to the same 355 distinct attributed texts (41 Attitudes, 154 POPQUORN, 95 MHS and 65 Kumar). Bars show the percentage of the 355 texts that receive each score.

order the texts of a dataset alike. Models in the same cluster are likely to be ordering the texts in much the same way, whereas a model outside the cluster, such as Mistral in Attitudes and MHS, needs its own audit.

Cohen's κ between labels is lower, from 0.14 to 0.78, because two models can order the texts alike and still disagree on where toxic begins. In Attitudes and POPQUORN, ChatGPT, DeepSeek and Gemini again form a cluster (κ of 0.34 to 0.59 and 0.60 to 0.67) and Mistral is apart (0.14 to 0.36 and 0.43 to 0.46). In MHS no cluster appears, with κ from 0.31 to 0.58 even though the models label 92% to 98% of the texts toxic, so their raw agreement says little. In Kumar the picture changes, since ChatGPT is the center (0.69 to 0.78) and Mistral joins it. For a user, the labels matter more than the ratings, because the audit works on labels. The clusters show which models are likely to share a side on a dataset and which are not, so a side found for one model cannot be assumed for a model outside its cluster. Models in one cluster also add little independent information if a user combines them as annotators.

G.2 Rating and Label Distributions

The audit compares labels, so how often a model says toxic matters. Figure 16 shows the scores each model gives under the default prompt, and Figure 17 the share of toxic and civil labels that follow from them.

The models use the scale differently. ChatGPT avoids the ends (11% of its scores are 1 and 14% are 5), while DeepSeek and Gemini spread their scores almost evenly over the five values. Mistral is the exception, with 46% of its scores at 5. As labels, this gives 63% toxic for ChatGPT and Gemini, 58% for DeepSeek and 74% for Mistral, so all four models label most of these texts toxic, Mistral the most.




Fig. 17. Share of civil and toxic labels that each LLM gives to the same 355 texts (a score of 3 or more is toxic).

This matters for reading κ. A model that labels most texts toxic leaves little room to follow a group that calls many of them civil, and one that labels almost all texts toxic follows no group, as in MHS (Appendix F.2). The shares here are pooled over the four datasets, so they hide differences between them.