

CareLoop — Database Structure & Schema

Supabase / PostgreSQL schema reference • Compiled from supplied query outputs

Scope: This document organizes the table columns, primary keys, foreign keys, CHECK constraints, and indexes present in the supplied output. It does not infer constraints or relationships that were not shown.

1. Schema overview

Table	Column count	Primary key (from Query 2)
action_dependencies	2	action_id, depends_on_action_id
audit_log	8	id
care_actions	16	id
care_journeys	6	id
department_slots	5	id
notifications	7	id
patients	9	id

2. Table definitions

action_dependencies

Column	Data type	Nullable	Default
action_id	uuid	NO	null
depends_on_action_id	uuid	NO	null

audit_log

Column	Data type	Nullable	Default
id	uuid	NO	gen_random_uuid()
journey_id	uuid	YES	null
action_id	uuid	YES	null
ts	timestamp with time zone	YES	now()
actor	text	YES	null
event	text	NO	null
reason	text	YES	null
meta	jsonb	YES	null

care_actions

Column	Data type	Nullable	Default
id	uuid	NO	gen_random_uuid()
journey_id	uuid	YES	null
type	text	YES	null
description	text	YES	null
category	text	YES	null
confidence	numeric	YES	null
department	text	YES	null
deadline_at	timestamp with time zone	YES	null
state	text	YES	'CREATED'::text
retry_count	integer	YES	0
scheduled_slot	text	YES	null
result_text	text	YES	null
drop_risk	numeric	YES	0
meta	jsonb	YES	null
created_at	timestamp with time zone	YES	now()
updated_at	timestamp with time zone	YES	now()

care_journeys

Column	Data type	Nullable	Default
id	uuid	NO	gen_random_uuid()
patient_id	uuid	YES	null
note_text	text	YES	null
status	text	YES	'ACTIVE'::text
created_at	timestamp with time zone	YES	now()
updated_at	timestamp with time zone	YES	now()

department_slots

Column	Data type	Nullable	Default
id	uuid	NO	gen_random_uuid()
department	text	YES	null
slot_time	timestamp with time zone	YES	null

Column	Data type	Nullable	Default
is_booked	boolean	YES	false
booked_by_action_id	uuid	YES	null

notifications

Column	Data type	Nullable	Default
id	uuid	NO	gen_random_uuid()
journey_id	uuid	YES	null
recipient_type	text	YES	null
message	text	YES	null
status	text	YES	'SENT':text
meta	jsonb	YES	null
created_at	timestamp with time zone	YES	now()

patients

Column	Data type	Nullable	Default
id	uuid	NO	gen_random_uuid()
name	text	NO	null
age	integer	YES	null
sex	text	YES	null
phone	text	YES	null
email	text	YES	null
caregiver_phone	text	YES	null
caregiver_email	text	YES	null
created_at	timestamp with time zone	YES	now()

3. Primary keys

Table	Column	Constraint name
action_dependencies	action_id	action_dependencies_pkey
action_dependencies	depends_on_action_id	action_dependencies_pkey
audit_log	id	audit_log_pkey
care_actions	id	care_actions_pkey
care_journeys	id	care_journeys_pkey
department_slots	id	department_slots_pkey
notifications	id	notifications_pkey
patients	id	patients_pkey

4. Foreign keys

Table	Column	Referenced table	Referenced column	Delete rule
action_dependencies	action_id	care_actions	id	CASCADE
action_dependencies	depends_on_action_id	care_actions	id	CASCADE
audit_log	action_id	care_actions	id	SET NULL
audit_log	journey_id	care_journeys	id	CASCADE
care_actions	journey_id	care_journeys	id	CASCADE
care_journeys	patient_id	patients	id	CASCADE
department_slots	booked_by_action_id	care_actions	id	SET NULL
notifications	journey_id	care_journeys	id	CASCADE

5. CHECK constraints

Table	Constraint name	Check clause
action_dependencies	2200_17661_1_not_null	action_id IS NOT NULL
action_dependencies	2200_17661_2_not_null	depends_on_action_id IS NOT NULL
audit_log	2200_17676_1_not_null	id IS NOT NULL
audit_log	2200_17676_6_not_null	event IS NOT NULL
audit_log	audit_log_actor_check	(actor = ANY (ARRAY[AGENT::text, 'Doctor'::text, 'Coordinator'::text, 'Patient'::text, 'Department'::text, 'SYSTEM'::text]))
care_actions	2200_17636_1_not_null	id IS NOT NULL

Table	Constraint name	Check clause
care_actions	care_actions_category_check	(category = ANY (ARRAY['Explicit':text, 'Inferred':text, 'Conditional':text]))
care_actions	care_actions_confidence_check	((confidence >= (0)::numeric) AND (confidence <= (1)::numeric))
care_actions	care_actions_department_check	(department = ANY (ARRAY['Lab':text, 'Cardiology':text, 'Pharmacy':text, 'Clinic':text, 'Emergency':text]))
care_actions	care_actions_drop_risk_check	((drop_risk >= (0)::numeric) AND (drop_risk <= (1)::numeric))
care_actions	care_actions_state_check	(state = ANY (ARRAY['CREATED':text, 'VALIDATED':text, 'HELD':text, 'REJECTED':text, 'ASSIGNED':text, 'BLOCKED':text, 'SCHEDULED':text, 'IN_PROGRESS':text, 'COMPLETED':text, 'VERIFIED':text, 'OVERDUE':text, 'ESCALATED':text]))
care_actions	care_actions_type_check	(type = ANY (ARRAY['TEST':text, 'REFERRAL':text, 'MEDICATION':text, 'FOLLOWUP':text, 'REVIEW':text]))
care_journeys	2200_17619_1_not_null	id IS NOT NULL
care_journeys	care_journeys_status_check	(status = ANY (ARRAY['ACTIVE':text, 'CLOSED':text]))
department_slots	2200_17713_1_not_null	id IS NOT NULL
department_slots	department_slots_department_check	(department = ANY (ARRAY['Lab':text, 'Cardiology':text, 'Pharmacy':text, 'Clinic':text, 'Emergency':text]))
notifications	2200_17696_1_not_null	id IS NOT NULL
notifications	notifications_recipient_type_check	(recipient_type = ANY (ARRAY['Patient':text, 'Department':text, 'Coordinator':text, 'Doctor':text, 'Caregiver':text]))
notifications	notifications_status_check	(status = ANY (ARRAY['SENT':text, 'READ':text, 'FAILED':text]))
patients	2200_17610_1_not_null	id IS NOT NULL
patients	2200_17610_2_not_null	name IS NOT NULL

6. Indexes

Table	Index name	Index definition
tablename	indexname	indexdef
action_dependencies	action_dependencies_pkey	CREATE UNIQUE INDEX action_dependencies_pkey ON public.action_dependencies USING btree (action_id, depends_on_action_id)
audit_log	audit_log_pkey	CREATE UNIQUE INDEX audit_log_pkey ON public.audit_log USING btree (id)
audit_log	idx_audit_log_journey_id	CREATE INDEX idx_audit_log_journey_id ON public.audit_log USING btree (journey_id)
audit_log	idx_audit_log_ts	CREATE INDEX idx_audit_log_ts ON public.audit_log USING btree (ts DESC)
care_actions	care_actions_pkey	CREATE UNIQUE INDEX care_actions_pkey ON public.care_actions USING btree (id)
care_actions	idx_care_actions_journey_id	CREATE INDEX idx_care_actions_journey_id ON public.care_actions USING btree (journey_id)
care_actions	idx_care_actions_state	CREATE INDEX idx_care_actions_state ON public.care_actions USING btree (state)
care_journeys	care_journeys_pkey	CREATE UNIQUE INDEX care_journeys_pkey ON public.care_journeys USING btree (id)
department_slots	department_slots_pkey	CREATE UNIQUE INDEX department_slots_pkey ON public.department_slots USING btree (id)
department_slots	idx_department_slots_dept_booked	CREATE INDEX idx_department_slots_dept_booked ON public.department_slots USING btree (department, is_booked)

Table	Index name	Index definition
notifications	idx_notifications_journey_id	CREATE INDEX idx_notifications_journey_id ON public.notifications USING btree (journey_id)
notifications	notifications_pkey	CREATE UNIQUE INDEX notifications_pkey ON public.notifications USING btree (id)
patients	patients_pkey	CREATE UNIQUE INDEX patients_pkey ON public.patients USING btree (id)

Notes for repository use

- This is a schema reference generated from query output, not a migration or executable SQL script.
- Defaults, nullability, constraint names, delete rules, and index definitions are reproduced from the supplied results.
- Review this document against the live Supabase database before treating it as the canonical production schema.